



 innovation



products catalog '66



PLAINTIFF'S
EXHIBIT


P-1134

0557288

TOWOLDMON0041022



innovation . . . MOVING AHEAD TO SERVE YOU



product

. . . in the products you depend on — and for the new ideas to fill your growing needs. If it isn't listed in this catalog, ask for it anyway.

technological

. . . Where top-notch scientists and engineers supply the thrust to keep Monsanto moving ahead. We invite your inquiries on chemical compounds, plastics, resins, fibers, and petroleum products.

manufacturing

. . . through the ingenuity and efficiency that keeps top-quality products coming to you at the lowest cost.

marketing

. . . to continually make it both desirable and easy for you to do business with Monsanto. We know to meet our marketing objectives, we must help you fulfill yours.

expansion

. . . through multistage growth, Monsanto assures you of steady dependable deliveries. Expansion today is geared to serve your needs tomorrow.

administrative

0557289

. . . to keep our product quality a part of your success pattern — Monsanto men and women move ahead to serve you.

Monsanto products are sold through the following divisions:

Agriculture Division
Chemstrand Company Division
Hydrocarbons and Polymer Division
Inorganic Chemicals Division
International Division
Organic Chemicals Division
Packaging Division
Plastic Products and Resins Division

TRADEMARKS...The word Monsanto and the Monsanto block M are Monsanto's most important trademarks and are registered in the U. S. Patent Office. The following index contains other trademarks owned by Monsanto and its subsidiaries. Trademarks which are registered in the U. S. Patent Office are followed by the ® and unregistered trademarks and trademarks for which registration is pending are followed by an asterisk.

ALPHABETICAL PRODUCT INDEX

A	
A-1* Thiocarbamide (Rubber Chemical).....	45
A-12* and A-100* (Rubber Chemicals).....	45
Accelerator B (Rubber Chemical).....	45
Acetates, polyvinyl.....	32
Acetone.....	24
Acetophenetidin U.S.P.....	21
Acidulants	13
Acids and Anhydrides (Carboxylic)	18
Acetylsalicylic Acid (Aspirin).....	21
ACI®.....	54
Acrlan®.....	11
Acyronitrile.....	21
Actanor®.....	49
Adhesives	47
Adipic Acid.....	13
Agricultural and Farm Products	7-10
Aircraft Hydraulic Fluids	15
Alcohol Resins, polyvinyl.....	32
Alkalate 23, 225 and 220.....	54
(Aikyl Benzene — Biodegradable)	
Alkophos® (Aluminum Acid Phosphates).....	27
Alkyd Acid Phosphates.....	21
Alkyl Aryl Phosphate (Santizer® 141).....	41
Alkyl Benzene Biodegradable.....	54
Alkyl Benzene Sulfonate — Biodegradable.....	53
Alkyl Benzene Sulfonic Acid — Biodegradable.....	53
Alkyl Benzene Sulfonic Acid Anhydrous — Biodegradable.....	53
Alkyl Phenol (Nonylphenol).....	54
Alkylamine C-12 (Dodecylamine).....	13
Alpha and Beta Radioactive Sources (Monsanto Research Corp.).....	13
Aluminum Acid Phosphates (Alkophos®).....	27
Aluminum Chloride Solution 32 Be.....	16
Aluminum Sulfate.....	51
Amines	18 and 19
Ammonia, Anhydrous.....	8
Ammonia, Aqua.....	8
Ammonium Nitrate Fertilizer Pellets.....	7
Ammonium Nitrate Fertilizer Pellets (E-20).....	7
Ammonium Nitrate 85% Solution.....	7 and 24
Ammonium Phosphate, di (Fertilizer Grade).....	7 and 24
Ammonium Phosphate, di (Fertilizer Grade).....	7
Ammonium Phosphate, ethyl.....	24
Ammonium Phosphate, mono.....	24
Ammonium Phosphate, triethyl.....	14
Anhydrous Monocalcium Phosphate (Py-Ran®).....	14
Anionic Surface Active Agents	53
Aniline, ortho.....	18
Aniline, para.....	18
Anti-Caking Flow Conditioners	47
Anti-Foaming Agents	48
Antioxidants	48 and 49
Anti-Slip and Anti-Soil Agents	48
Aroclor® Polychlorinated Polyphenyls.....	20
Aspirin.....	21
Avacel®.....	8
Avacel® BW.....	8
B	
Bacteriostats	49
Battery Acid (Electrolyte).....	16
Benthin® Alkyl Resin Intermediate.....	16
Benzene.....	18
Benzole Acid.....	24
Benzyl Benzoate N.F.....	18
Benzyl Chloride.....	20
Benzyl Chloride (inhibited with 0.25% triethylamine).....	18
Beta & Alpha Radioactive Sources.....	13
Biphenyl.....	24
Bisphenol A.....	15
Bisphenol A—Hydrogenated (HBPA*).....	36

Bleaching Compounds	54
Bone Ash.....	50
Bromstrahlung Sources (Monsanto Research Corp.).....	18
Brush-Blitz®.....	9
Brush Killers	9
Brush-O-Cide®.....	9
Buffering Agents	15
Building Products	11
Lustra-Span® Vinyl Building Panels.....	11
Monsanto® Foam Board.....	11
Monsanto Vinyl Gutters and Downspouts.....	11
Monsanto Vinyl Siding.....	11
Silent-Cor® for Sound Control.....	11
Thermo-Lath® Waterproof Insulating Plasterphase.....	11
Butene-2 Concentrate.....	29
Butvar®.....	33
Butvar® Dispersions BR and FP (polyvinyl butyral).....	33
Butyl Benzyl Phthalate (Santizer® 160).....	40
Butyl Decyl Phthalate (Santizer® 603).....	40
Butyl Phthalate Butyl Glycolate (Santizer® B-16).....	41
Butylenes—Mixed Isomers.....	33
Butyral, polyvinyl resins (Butvar®).....	33

C

C. Stream (Mixed Hydrocarbons).....	28
C. Aromatic Concentrate (Mixed Isomers).....	28
Cafene Anhydrous U.S.P.....	13
Calcium Cyclohexane U.S.P. (Dietone®).....	13
Calcium Phosphates	25
Calcium Pyrophosphate.....	25
Calcium Silicate (Slak).....	17
Calibration Radioactive Sources (Monsanto Research Corp.).....	18
Carbon Dioxide.....	16
Carboxylic Acids and Anhydrides	18
Casein and Soybean Adhesives.....	47
Catalysts.....	50
Cauls® Potash.....	17
Cellulose Acetate Sheet Vucapak®.....	44
Chemical Fibers	11 and 12
Chemical Specialty Catalysts	50
Chemstrand® (Acrlan®, Nylon 66, Spandex and polyester).....	11 and 12
Chloramine-T.....	49
Chloroaniline, para.....	19
Chlorophenol, ortho.....	22
Chlorophenol, para.....	22
Chlorosulfonic Acid.....	22
Coagulants	15
Coal Tar Resins	35
Colloidal Silicas (Sytan®).....	30 and 31
Colorants	13
Compressor Lubricant (Pydraul® AC).....	13
Coolanol® 35.....	12
Coolanol® 45.....	12
Coumarin.....	12
Cresyl Diphenyl Phosphate (Gasoline Grade).....	27
Cresyl Diphenyl Phosphate (Plasticizer Grade).....	41
Crop-Guard®.....	9
Curing Agents	50
CWS® Fumaric Acid.....	13
Cyanuric Acid.....	24
Cyclohexanol.....	24
Cyclohexylamine.....	19

D

2,4-D Amine.....	9
2,4-D Butyl Ester.....	9
2,4-D Butyl Ester Concentrate.....	9
2,4-D Granular.....	9
2,4-D Isopropyl Ester.....	9
2,4-D Low Volatile Ester.....	9
2,4-D 2,4,5-T Amine.....	9
2,4-D 2,4,5-T Butyl Ester.....	9
2,4-D 2,4,5-T Low Volatile Ester.....	9
DDBSA 960-B.....	53
DDBSA 960-B.....	54
Defoamer (PC-1244®).....	48
Dentifrice Abrasives	
Dicalcium Phosphate Anhydrous.....	25
Dicalcium Phosphate Dihydrate.....	25
Insoluble Metaphosphate.....	25
Lustr®-Phos®.....	25
Tricalcium Phosphate.....	25
Detergent Intermediates	54
Diammonium Phosphate.....	24
Diammonium Phosphate, Feed Grade.....	7
Diammonium Phosphate, Fertilizer Grade.....	7
Dibutyl Fumarate.....	36
Dibutyl Maleate.....	36
Dibutyl Phthalate.....	37
Dicalcium Phosphate Anhydrous.....	25
Dicalcium Phosphate Dihydrate.....	25
Dicalcium Phosphate, Feed Grade.....	7
3,4-Dichloroaniline, (3,4-DCA).....	19
Dichlorobenzene, ortho.....	20
Dichlorobenzene, para (Santochlor®).....	10
2,4-Dichlorophenol.....	22
Dicyclohexyl Phthalate (DCHP).....	17
Dicyclohexylamine.....	19

0557290

Monsanto

TOWOLDMON0041024

Dielectric Coolant for Electronic Equipment	12
(Coolanol® 45)	12
Diethyl Phthalate	14
Dieton® Calcium Cyclamate U.S.P.	14
Dietosol® Sodium Cyclamate N.F.	17
Di-2-Ethylhexyl Adipate (DOA)	37
Di-2-Ethylhexyl Phthalate (DOP)	37
Dihydroxy Diphenyl Sulfone	22
Disocetyl Adipate (DDA)	38
Disocetyl Phthalate (DIDP)	38
Disocetyl Phthalate (DIDP)	38
Dunethyl Phthalate	38
Di-N-Octyl, N-Decyl Adipate (DNODA)	37
Diethyl Fumarate (DOF)	36
Dioctyl Maleate (DOM)	36
Di-N-Octyl, N-Decyl Phthalate (DNODP)	37
Diphenyl (Biphenyl or Phenylbenzene)	24
Diphenyl Phthalate	37
Diphenylguanidine (DPG)	45
Diphenylguanidine Phthalate (Guanthal®)	45
Disinfectants	49
Sodium Phosphate, Anhydrous	26
Sodium Phosphate, Dihydrate	26
Dispersing Agents	15
Dodecaniline	19
Downspouts and Gutters	11
Drycol® Dry Colorants	30
Dytrol® Paint Brush Preserver	38

E

E-20® Argonum Nitrate Fertilizer Pellets	5
El-Slat® (Rubber Chemical)	47
Elastopar® (Rubber Chemical)	47
Electronic Materials	12 and 13
EMA® Resins	36
Emulsifiers	15
Ethyl Ammonium Phosphate	24
Ethyl Parathion	10
Ethyl POT	23
Ethyl Phthalyl Ethyl Glycolate (Santizer® E-15)	13
Ethyl Vanillin (Ethavan®)	13
Ethylene	28 and 29
Ethylene and Ethylene Co-Products	28 and 29

F

Far-Go®	8
Farm Products	7-10
Feed Supplements	7
Ferrophosphorus (Iron Phosphide)	27
Fertilizers	7 and 8
Fibers	11 and 12
Field-Clean®	9
Fire Retardants	50
Flavors	11
Flecto® H (Rubber Chemical)	46
Foam Board (Monsanto®)	13
Food Ingredients	12-15
Formal polyvinyl resins (Formvar®)	33
Formaldehyde	24
Formaldehyde Resins	37
Formvar® Resins (polyvinyl formal)	33
Fruit Spray (Stop Seal®)	10
Fuel Oil Additives (Santolene®)	29
Fumaric Acid	13
Fumaric Acid (CWS®)	13
Functional Fluids	15 and 16
Fungicides	49
Fungistats	49

G

Gallium Antimonide (Electronic Grade)	12
Gallium Arsenide (Electronic Grade)	12
Gallium Arsenide Phosphide Alloys (Electronic Grade)	12
Gallium Phosphide (Electronic Grade)	12
Gamma Radioactive Sources	18
Monsanto Research Corp.	19
Gear Oil Additives (Santopid®)	29
Gelvat® Copolymer Resins (polyvinyl acetate)	32
Gelvat® Copolymer Solutions (polyvinyl acetate)	32
Gelvat® Emulsions (polyvinyl acetate)	32
Gelvat® Powders 700 and 702 (polyvinyl acetate)	32
Gelvat® Resins (polyvinyl acetate)	32
Gelvat® Resin Solutions (polyvinyl acetate)	32
Gelvat® Resins (polyvinyl alcohol)	32
Germicide Base and Liners	43
Germicides	49
Ger-Pak® Sheeting	44
Ger-Pak® Tape	44
Glass Sodium Phosphate (Olfos®)	45
Guanthal® (Diphenylguanidine Phthalate)	45
Gualacol	20
Gutters and Downspouts	11

H

H Acid	18
Halogen-Containing Compounds	20

Hormone-Type Herbicides	9
HR-40® Partially Hydrogenated Terphenyl	38
Heat Radioactive Sources (Monsanto Research Corp.)	18
Heat Transfer Liquids (Therminol®)	18
Heavy Chemicals	16 and 17
Herbicide Oil No. 1 (Lion)	9
Herbicide Oil Nos. 6 and 7 (Lion)	9
Herbicides (Pre- and Post-Emergence)	8 and 9
Herbicides (Hormone)	9
H.T. Monocalcium Phosphate (Monohydrate)	18
Headsydraniline (Cyclohexylamine)	14
Hydraulic Fluids	12 and 15
Hydrochloric Acid (Muriatic Acid)	17
Hydrogenated Bisphenol A (HBPA®)	36

I

Indium Antimonide (Electronic Grade)	12
Indium Arsenide (Electronic Grade)	12
Indium Phosphide (Electronic Grade)	12
Insecticides	9
Insoluble Metaphosphate	28
Insoluble Sulfur	47
Iron Phosphide (Ferrophosphorus)	27
Isocetyl Isocetyl Phthalate (Santizer® 402)	40

L

Lactic Acid	13
Lambast®	9
Lampblack	51
Leavening Agents	14
Levi-Lite®	14
Lion Herbicide Oil No. 1	9
Lion Herbicide Oil Nos. 6 & 7	9
Lustran® ABS and SAN Molding and Extruding Compounds	31
Lustran® Span® Vinyl Building Panels	25
Lustran® Phos Calcium Ortho-Phosphate	25
Lustran® Styrene Extruding and Calendaring Material	29
Lustran® Styrene Molding Compound	31
Lytrol® Resins	31
Lytrol® Synthetic Resins	31

M

Maleic Anhydride	18
Masterbatch Color Concentrates	13
MCP Amine	9
Melamine-Urea Resins	35
Mersize® (Paper Sizing Agent)	32
Mertone® WB-4 (Precoat for Reproduction Papers)	51
Metal Processing Compounds	50
Methanol	21
Methacrylate Fumarate (Thenylpyrimine Fumarate)	21
Methacrylate Hydrochloride (Thenylpyrimine Hydrochloride)	21
Methionine Hydroxy Analogue (MHA®)	20
Methyl Diphenyl Phosphate (Phostane® MDP)	10
Methyl Parathion	10
Methyl Parathion (Stabilized)	10
Methyl POT	23
Methyl Phthalyl Ethyl Glycolate (Santizer® M-17)	40
Methyl Salicylate U.S.P.	17
Mixed Acid (Nitric Acid)	17
Modanow®	18
Mod-Epo®	28
Monosulfonium Phosphate	14
Monocalcium Phosphate (Monohydrate)	14
Mono Thured® Rubber Chemical	45
Monomers	20 and 21

Monomers for Synthetic Rubber	47
Monopotassium Phosphate	25
Monosodium Phosphate	7 and 26
Monsanto® Foam Board	13
Monsanto® Penta (Pentachlorophenol Technical)	49
Monsanto® Polyethylene Extrusion Coating Materials	34
Monsanto® Polyethylene Film and Sheet Material	34
Monsanto® Polyethylene Molding Compounds	34
Monsanto® Polyethylene Wire & Cable Compounds	34
Monsanto Research Corp.	19
Monsanto® Vinyl Gutters and Downspouts	11
Monsanto® Vinyl Siding	11
Monta® Synthetic Resins	38
Muriatic Acid (Hydrochloric Acid)	17

N

NFB® 80 and 85 (Non-Fuming Aluminum Bright Dip Bath)	50
Niran® 6-3	10
Niran® 10-G	10
Nitrating Acid (Mixed Acid)	17
Nitric Acid	17
Nitroaniline, ortho.	19
Nitroaniline, para.	19
Nitrochlorobenzene, ortho.	20
Nitrochlorobenzene, para.	20
Nitrogen Fertilizer Solutions	20
Nitrophenol, para.	22

Nonionic Surface Active Agents 53 and 54**Non-Nutritive Sweeteners** 14

Nonylphenol-Alkyl Phenol 54

Nuclear Sources 18**Nutrition Supplements** 15

Nutrium® Fertilizer 14

Nylon 66 31

Nylon 6-6 and 6, 10 Resin 31

O**Odorants** 50

Oil Additives (Santolube®) 30

Oils® Glassy Sodium Phosphate 14

Oleum 17

Opalco® Vinyl Chloride Extruding and 33

Calciuming Materials 33

Opalco® Vinyl Chloride Molding Compound 33

Organic Chemicals 18 to 24

Organic Nuclear Reactor Coolant (Santowax® OMP) 16

ortho-Anisidine 18

ortho-Chlorophenol 22

ortho-Dichlorobenzene 20

ortho-Nitroaniline 20

ortho-Nitrochlorobenzene 20

ortho-Phenetidine 49

ortho-Tolyl Biguanide (Sopano®) 49

OS-450 Type III High Temp. Aircraft 12

Hydraulic Fluid 12

OS-450 Type IV High Temp. Aircraft 12

Hydraulic Fluid 12

P

Packaging 43

Paint/Coating Ingredients 51

Pan-O-Lite® 51

Paper Chemicals 51 and 52

Paper-Sizing Agent (Mersize®) 52

para-Anisidine 18

para-Chloroaniline 18

para-Chlorophenol 22

para-Dichlorobenzene (Santochlor®) 10

para-Nitroaniline 18

para-Nitrochlorobenzene 20

para-Nitrophenol 22

para-Phenetidine 49

para-Toluenesulfonamide 23

para-Toluenesulfonyl Chloride 23

Parathion-Ethyl and Methyl 46

PC-1240 Defoamer 46

Pentachlorophenol (Technical Monsanto® Penta) 49

Petro Chemicals 28 and 29**Petroleum Additives** 29 to 30**Pharmaceuticals** 21 and 22

Phenacetin (Acetophenetidin U.S.P.) 21

Phenetidine, ortho 19

Phenetidine, para 19

Phenol 22

Phenols 22

Phenolic and Resorcinol Resins 47

Phenolic Resins (Resinox®) 34 and 35

Phenolic Varnishes (Resinox®) 35

Phenolphthalein U.S.P. 21

Phenolphthalein, Yellow 22

Phenolsulfonic Acid 24

Phos-Chok® 36

Phosgard® C-22-R 36

Phosphate Feed Solution 7

Phosphates (Sodium) 26 and 27

Phosphatic Fertilizer Solution 26

Phospholeum® 8 and 25

Phosphoric Acids 25

Phosphoric Acid (75, 80 and 85%) 25

Phosphoric Anhydride (Phosphorus Pentoxide) 27

Phosphorus and**Phosphorus Derivatives** 24 thru 28

Phosphorus Elemental 27

Phosphorus Oxchloride 27

Phosphorus Pentasulfide 28

Phosphorus Pentoxide (Phosphoric Anhydride) 28

Phosphorus Trichloride 28

Phosane® MDP (Methyl Diphenyl Phosphate) 28

Phthalic Anhydride 36

Phthalyl Chloride 20

Plastic Bottles and Containers 43**Plastic Closures** 43**Plastic Fittings** 43**Plastic Sheet and Film** 43**Plasticizers** 37 to 43**Plastics-Resins-Plasticizers** 28 to 44**Plax® Products** 44**Polyester** 12**Polyethylenes** 44**Polyethylene Film** 44**Polyeth® Sheet** 44**Polyvinyl Acetates** 32

Polyvinyl Acetate Copolymer Resins (Gelva®) 32

Polyvinyl Acetate Copolymer Solutions (Gelva®) 32

Polyvinyl Acetate Emulsions (Gelva®) 32

Polyvinyl Acetate Powders (Gelva®) 32

Polyvinyl Acetate Resins (Gelva®) 32

Polyvinyl Acetate Resin Solutions (Gelva®) 32

Polyvinyl Alcohol Resins (Gelvatol®) 32

Polyvinyl Butyral Resins (Butvar®) 32

Polyvinyl Butyral Resin Dispersions 34

Polyvinyl Formal Resins (Formvar®) 32

Potassium Phosphates 25

Preservative-Stop Soid® Fruit Spray 10

Preservatives 14 and 15

Propylene 28

Protein Interactants 15

Pydraul® AC Compressor Lubricant 15 and 16

Pydraul® Hydraulic Fluids 16

Py-Ran® Anhydrous Monocalcium Phosphate 14

R

R-2 Crystals (Rubber Chemical) 45

Radioactive Sources (Monsanto Research Corp.) 18

Ramrod 9

Ranox® 9

Resinex® T 9

Resinex® Melamine and Resinex® U Urea 35

Resinex® Melamine 35

Resin Materials 36 and 37

Resin Oil 39

Resin PR 29

Resinous Polyol (RJ 100®) 37

Resinox® 35

Resinox® Liquid Phenolic Resins 35

Resinox® Phenolic (Lump, Flake and 34

Resin Compound 35

Resinox® Phenolic Varnishes 35

Resinox® E-50 Resins 35

Resinox® Melamine 35

Resorcinol and Phenolic Resins 47

RJ-100® Resinous Polyol 37

Rock Salt (Sodium Chloride) 17

Rogue® 9

Rubber Chemicals 44 to 47

Accelerators for Natural and Synthetic Rubbers 45

Aldehyde Amine Type 45

Antioxidants and Antiozonants 45

Guandine Type 45

Special Materials 45

Thiocarbamide Type 45

Thiozole Type 45

Ultra Type 45

Monomers for Synthetic Rubber 47

RZ-500-A (Rubber Chemical) 45

RZ-500-B (Rubber Chemical) 45

S

Saccharin (Calcium and Sodium) U.S.P. 14

Safex® Vinyl Butyral 33

Salcyllic Acid, U.S.P. 18

Salt Cake (Sodium Sulfate Anhydrous Technical) 52

Santocel® I-H Plasticizer 40

Santocelizer® 3 Plasticizer 40

Santocelizer® 8 Plasticizer 23 and 40

Santocelizer® 9 Plasticizer 40

Santocelizer® E-15 Plasticizer 41

Santocelizer® B-16 Plasticizer 41

Santocelizer® M-17 Plasticizer 41

Santocelizer® 140 Plasticizer 41

Santocelizer® 163 Plasticizer 41

Santocelizer® 165 Plasticizer 41

Santocelizer® 213 Plasticizer 40

Santocelizer® 214 Plasticizer 41

Santocelizer® 215 Plasticizer 41

Santocelizer® 405 Permanent Plasticizer 41

Santocelizer® 406 Permanent Plasticizer 42

Santocelizer® 409 Polymeric Plasticizer 42

Santocelizer® 411 Plasticizer 42

Santocelizer® 462 Permanent Plasticizer 42

Santocelizer® 480 Permanent Plasticizer 42

Santocelizer® 481 Permanent Plasticizer 42

Santocelizer® 482 Permanent Plasticizer 42

Santocelizer® 483 Permanent Plasticizer 42

Santocelizer® 502 Plasticizer 40

Santocelizer® 503 Plasticizer 40

Santocelizer® 530 Plasticizer 42

Santocelizer® 631 Plasticizer 43

Santocelizer® 636 Plasticizer 43

Santocelizer® 644 Plasticizer 43

Santocelizer® 683 Plasticizer 43

Santobitel® (Sodium Pentachlorophenate, Technical) 49

Santocel® (Silica Aerogel for Industrial Applications) 47

Santocel® (Silica Aerogel for Thermal Insulation) 47

Santocel® 82 Aerogels 47

Santocel® L Aerogels 51

Santocel® Z Aerogels 51

Santochlor® (para-Dichlorobenzene) 10

Santocure® (Rubber Chemical) 44

Santocure® MOR and MOR-90 (Rubber Chemicals) 44

Santocure® NS (Rubber Chemical) 44

Santoflex® AV (Rubber Chemical) 44

Santoflex® DP (Rubber Chemical) 44

Santoflex® 17 (Rubber Chemical) 46

Santoflex® 36 (Rubber Chemical) 46

Santoflex® 75 (Rubber Chemical) 46

Santolene® 217 (Rubber Chemical)	46
Santolene® C-2 Fuel Oil Additive	27
Santolene® C-3 Fuel Oil Additive	29
Santolene® F Fuel Oil Additive	29
Santolite® MHP Resin (Fuel Oil Additive)	23 and 35
Santolite® MS 80* Industrial Resin	23 and 35
Santolube® 70 (Oil Additive)	29
Santolube® 114 Oil Additive	29
Santolube® 302 Oil Additive	29
Santolube® 393 (Oil Additive) Zinc Dialkyl	29
Dithiophosphate	29
Santolube® 304-C (Oil Additive)	30
Santolube® 305-X (Oil Additive)	30
Santolube® 343 (Oil Additive)	30
Santolube® 375 (Oil Additive)	30
Santomase® 11 Odor-Masking Agent	50
Santomerac® No. 1-B	53
Santomerac® 85-B	53
Santomerac® ME-B Slurry	53
Santomerac® Antioxidant	23
Santomax® R	29
Santopet® 1 Germicide	49
Santophen® 1 Solution	49
Santopoid® 22-R1 (Gear Oil Additive)	30
Santopoid® 23-R1 (Gear Oil Additive)	30
Santopoid® 33 (Gear Oil Additive)	30
Santopoid® 35 (Gear Oil Additive)	30
Santopoid® 36 (Gear Oil Additive)	30
Santopour® C-Oil Additive	30
Santoquin® and Santoquin® Mixture No. 6	48
Santostic® Sodium Sulfite Anhydrous	17
Santostic® Paper Slitting Agent	17
Santonac® 23 Basic Chrome Sulfate	52
Santova® A Rubber Chemical	46
Santowax® OMF (Organic Nuclear Reactor Coolant)	46
Santowhite® 34 Rubber Chemical	46
Santowhite® 54-S Rubber Chemical	46
Santowhite® Crystals Rubber Chemical	46
Santowhite® L Rubber Chemical	46
Santowhite® MK Rubber Chemical	46
Santowhite® Powder Rubber Chemical	48
Scipser® 100, 500 Series	32
Scipriter® Series Wet-Strength Resins	52
Sequestrants	
Silent-Cor® for Sound Control	15
Silica Aerogel for Industrial Applications (Santocel®)	47
Silica Aerogel for Thermal Insulation (Santocel®)	47
Silicon - Electronic grade	42
Skydrol® MA-A Fire Resistant Jet Aircraft Hydraulic Fluid	15
Skydrol® 7000 Fire Resistant Jet Aircraft Hydraulic Fluid	15
Slag, Calcium Silicate	32 and 33
Shawinkian Resins Products	32 and 33
Sodium Acid Pyrophosphate	14
Sodium Alkyl Benzene Sulfonate - Biodegradable	33
Sodium Aluminum Phosphate (Levin-Lite®)	14
Sodium Benzoate	15
Sodium Bisulfate (Nitric Acid)	17
Sodium Bisulfite Anhydrous	17
Sodium Cyanate N.F. (Detox®)	17
Sodium Chloride (Rock Salt)	17
Sodium Hexametaphosphate	26
Sodium Metabisulfite Sodium Bisulfite Anhydrous	17
Sodium meta-Nitrobenzene Sulfonate	23
Sodium Pentachlorophenate, Technical (Santobrite®)	49
SODIUM PHOSPHATES	
Sodium Phosphate, U.S.P.	22
Sodium Sulfite Anhydrous Technical	22
Sodium Sulfite Anhydrous (Santocel®)	17
Sodium Tripolyphosphate	26
Soparox® (ortho-Tolyl Bismaleimide)	47
Soyabean and Cassia Adhesives	12
Spanides	47 to 53
Specialty Products	
SQ Phosphate	26
Stabil-90® (Leavening Agent)	14
Stabilized Methyl Parathion	34
Sterox® AJ - Al-100	54
Sterox® AJ - AP-100	54
Sterox® CD	54
Sterox® DF	54
Sterox® NM	54
Sterox® SK	54
Sterox® No. 6	54
Stop-Scale® Fruit Spray	10
Stymer® Vinyl Styrene	33
Styrene Extruding and Calendaring Material	31
Styrene Molding Compound (Lustrex®)	21
Styrene Monomer	31
Styrene Resins/Plastics	
Sulfonamide Resins	35
Sulfonic Acids	22
Sulfosac® R (Rubber Chemical)	47
Sulfosalicylic Acid, Technical	18
Sulfur-Containing Compounds	
Sulfur Dioxide, Liquid	17
Sulfuric Acid and Oleum	17
Sweeteners	
Surface Active Agents	53 and 54
Sweeteners, Non-Nutritive	14
Syton® AS-200 (Colloidal Silica)	48

Syton® C-30 and 200 (Colloidal Silica)	48
Syton® C-40 and 240 (Colloidal Silica)	48
Syton® C-50 and C-250	48
Syton® FS and DS-200 (Colloidal Silica)	48
Syton® P-200 and P-250 (Colloidal Silica)	48
Syton® W-200 (Colloidal Silica)	52

T

2,4,5-T Amine	9
2,4,5-T Butyl Ester	9
2,4,5-T Low Volatile Ester	9
Tanning Agents	
TCC 3,4,4-Trichlorocarbamide	52
Tertiary-Butylamine	14
Tetrapropenylsulfonic Anhydride (TPSA®)	18
Tetrasodium Pyrophosphate	18
Textile Chemicals	
Thaite	45
Thienylpyrimidine Fumarate (Methapyrilene Fumarate)	21
Thienylpyrimidine Hydrochloride	21
Methapyrilene Hydrochloride	21
Thermint® FR (Heat Transfer Liquid)	16
Thermo-Lath® - Waterproof Insulating Plasterbase	11
Thickening Agents	
Tiunite® (MBTS) Rubber Chemical	53
Tioxar® MBTS Rubber Chemical	53
Tiurax® (Rubber Chemical)	45
Threshold Detectors	18
(Monsanto Research Corp.)	18
Toluene	22
Toluenesulfonamide - para	29
Toluenesulfonic Acid	22
Toluenesulfonyl Chloride - para	23
TPSA® - Tetrapropenylsulfonic Anhydride	18
Tributoxy Ethyl Phosphate (TBEF)	30
Tributyl Phosphate (TBP)	39
Tricalcium Phosphate	25
Tricresyl Phosphate	38
Triethylaluminum Phosphate	34
Triphenyl Phosphate	38
Triphenyl Phosphate	38
Tripotassium Phosphate	26
Trisodium Phosphate, Anhydrous	20
Trisodium Phosphate, Crystalline	27
Tri-Uns-Sol® Fertilizer Solution	7

U

Ultracolor® Dry Colorants	31
Ultracolor® Vinyl Chloride (Flexible Film & Sheet)	34
Urea, Feed Grade Coated Microfills	7
Urea, Fertilizer Grade Coated Pellets	8
Urea, Fertilizer Grade Uncoated Pellets	8
Urea, Industrial Grade Uncoated Pellets	37
Urea and Melamine Resins	47
V	
Vanadium Sulfuric Acid Catalyst	50
Venitlin Monsanto U.S.P.	14
Vexadex®	9
Vinyl Acetate Monomer	21
Vinyl Building Plastics (Lustrex®)	33
Vinyl Butral (Safex®)	11
Vinyl Chloride Extruding & Calendaring Material (Opalon®)	33
Vinyl Chloride (Flexible Film & Sheet) Ultracolor®	33
Vinyl Chloride Molding Compound (Opalon®)	33
Vinyl Chloride Monomer	21
Vinyl Grafters and Downspouts	11
VINYL RESINS/PLASTICS	
Vinyl Siding	33 and 34
Vinyl Styrene (Stymer®)	11
Vyram® Rigid Vinyl Compounds	34
Vysac® 69 Resins	51
Vyspak® Cellulose Acetate Sheet	44

W

Wood Preservative (Monsanto® Pentacel®)	49
Wood Killers	9
X	
X-Ray Units (Monsanto Research Corp.)	18
Xylenes, Mixed	29

Z

Zinc Dialkyl Dithiophosphate (Santolube® 393)	29
Zinc Oxide, Technical	52

AGRICULTURAL and FARM PRODUCTS

FEED SUPPLEMENTS

DIAMMONIUM PHOSPHATE, FEED GRADE

INORGANIC DIVISION

FORMULA: $(\text{NH}_4)_2\text{HPO}_4$

MOLECULAR WEIGHT: 132.068

STANDARD FORM: Crystals

TYPICAL ANALYSIS:

Phosphorus	23.1%
Nitrogen	33.7% (Min.)
P ₂ O ₅	53.0% (Min.)

USES: DAP is a concentrated, economical source for non-protein nitrogen and phosphorus in ruminant animal feeds.

SHIPPING INFORMATION: DI Ammonium Phosphate (Feed Grade): 80-lb. net multi-wall paper bags; bulk boxes; and hopper cars.

DICALCIUM PHOSPHATE, FEED GRADE

INORGANIC DIVISION

FORMULA: CaHPO_4

STANDARD FORM: Granules.

TYPICAL ANALYSIS:

	Regular	Suplifo®-23
P	18.7%	23.3%
Ca	22.0%	21.5%
As ₂ O ₃	0.2ppm	0.2ppm
Pb	1.0ppm	1.0ppm
F	0.01%	0.01%
Moisture	2.5%	2.5%

SHIPPING INFORMATION: Phosphate of Calcium. 100-lb. bags; bulk box, hopper cars and bulk trucks.

METHIONINE HYDROXY ANALOGUE (MHA®)

Calcium salt of DL-alpha-hydroxy-gamma-methylmercaptobutyric acid.

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Powder.

SPECIFICATIONS: Assay, 90% as calcium salt of Methionine Hydroxy Analogue; 1% moisture max.; screen analysis, 1% max. on 20 mesh; density 30 lb./cu. ft. (tapped).

PROPERTIES: Nutritionally equivalent to DL-methionine on a gravimetric basis (1.09 lbs. Methionine Hydroxy Analogue; 90%, ca. to 1.0 lbs. DL-methionine, 98%). Free methionine hydroxy analogue is a metabolite in the animal's utilization of methionine.

USES: As a feed supplement in poultry feed to supply requirement of methionine.

SHIPPING INFORMATION: Rail: Condition powders, regulators or tonics, animal or poultry. NOIBN, Truck: Feed Supplements, not frozen, 80-lb. bags.

MONOSODIUM PHOSPHATE

INORGANIC DIVISION

(Also See Page M5/26)

FORMULA: NaH_2PO_4

MOLECULAR WEIGHT: 119.99

STANDARD FORM: Powder and granular.

PROPERTIES: Contains not less than 58% P₂O₅; pH value of 1% solution 4.5.

GRADES: Food; commercial.

USES: A source of phosphorus for potentiated poultry feeds.

SHIPPING INFORMATION: Sodium Phosphate. 100-lb. bags; 350 and 100-lb. drums.

PHOSPHATE FEED SOLUTION

INORGANIC DIVISION

STANDARD FORM: Liquid

PROPERTIES: A special grade of Phosphoric Acid prepared for a phosphate supplement in animal feeds, molasses, and mineral mixes. Phosphorus content—23.7%. Not recommended for other uses.

SHIPPING INFORMATION: Tank cars and tank trucks.

SACCHARIN (CALCIUM AND SODIUM) U.S.P.

See Page M5/14

SANTOQUIN® AND SANTOQUIN® Mixture #6

See Page M5/48

UREA, FEED GRADE COATED MICROPRILLS

AGRICULTURAL DIVISION

STANDARD FORM: Urea microprills with an inorganic material as a coating agent.

ANALYSIS:

Nitrogen (Min.)	42.0%
Moisture (Max.)	0.6%
Bluret (Max.)	1.0%

USES: As a protein source for use in Ruminant feeds.

SHIPPING INFORMATION: Urea Feed Grade (not for human consumption or pharmaceutical use): 90-lb. multiwall paper bags with polyethylene lining. Also in bulk.

FERTILIZERS

DIAMMONIUM PHOSPHATE, FERTILIZER GRADE

AGRICULTURAL DIVISION

FORMULA: $(\text{NH}_4)_2\text{HPO}_4$

MOLECULAR WEIGHT: 132.068

STANDARD FORM: Crystals

TYPICAL ANALYSIS:

Assay	98.4%
P ₂ O ₅	53.7%
NH ₃	25.5%

SHIPPING INFORMATION: Fertilizer NOIBN Diammonium Phosphate: 100-lb. multi-wall bags and 100-lb. and 300-lb. fiber drums. Bulk cars and bulk trucks.

NITROGEN FERTILIZER SOLUTIONS

AGRICULTURAL DIVISION

STANDARD FORM: Clear water solution.

ANALYSIS: Varying analysis containing ammonia, ammonium nitrate and water or ammonia, ammonium nitrate, urea and water to suit varying weather and manufacturing conditions.

USES: Formulation of mixed fertilizers and for direct application to the soil.

SHIPPING INFORMATION: Nitrogen Fertilizer Solution. Insulated and uninsulated tank cars of 8,000 and 10,000 gal. capacity, and tank trucks of approximately 4,000 gal. capacity.

TRI-UNA-SOL® FERTILIZER SOLUTION

AGRICULTURAL DIVISION

STANDARD FORM: Clear water solution.

ANALYSIS: Varying analysis of 28, 30 and 32% nitrogen containing urea, ammonium nitrate and water.

USES: Direct application to the soil and formulation of mixed liquid fertilizers.

SHIPPING INFORMATION: Nitrogen Fertilizer Solution. Insulated and uninsulated tank cars of 8,000 and 10,000 gal. capacity, and tank trucks of approximately 4,000 gal. capacity.

AMMONIUM NITRATE FERTILIZER PELLETS

AGRICULTURAL DIVISION

STANDARD FORM: Ammonium Nitrate in pelleted form coated with a conditioning agent.

ANALYSIS:

Nitrogen (Min.)	33.5%
Moisture	3.5%
Water insoluble	3.0%

SHIPPING INFORMATION: Ammonium Nitrate Fertilizer containing more than 90% ammonium nitrate. Fertilizer compounds (Mfr. Fert.) NOIBN dry in paper, polyethylene bags and in bulk. (Dangerous Placards Applied). Multiwall paper bags with polyethylene lining. packaged in 100-lb. bags, 80-lb. bags and 50-lb. bags.

E-2® AMMONIUM NITRATE FERTILIZER PELLETS**AGRICULTURAL DIVISION**

STANDARD FORM: Ammonium Nitrate in pelleted form uncoated.

ANALYSIS:	
Nitrogen (Min.)	33.5%
Moisture	.3%

SHIPPING INFORMATION: Ammonium Nitrate Fertilizer containing more than 90% ammonium nitrate with no organic coating. Fertilizer Compounds (Mfg. Fert. NOIBN dry in paper, polyethylene bags and in bulk. (Dangerous Placards Applied). Multiwall paper bags with polyethylene lining, packaged in 100-lb. bags, 80-lb. bags, and 50-lb. bags. Also shipped in 50-lb. polyethylene bags and in bulk.

AMMONIUM NITRATE 83% SOLUTION**AGRICULTURAL DIVISION**

ANALYSIS: Typical	
Ammonium Nitrate	83.8%
Water	15.2%
Chlorides	2ppm
Iron	2ppm

USES: Manufacture of military explosives. Pyrotechnic compositions, insecticides and absorbent for nitrogen oxide as well as fertilizer uses.

SHIPPING INFORMATION: Nitrogen Fertilizer Solution. 8,000 and/or 10,000 gal. aluminum steam coiled tank cars.

AMMONIA, AQUA**AGRICULTURAL DIVISION**

MOLECULAR WEIGHT: 35.05

STANDARD FORM: Liquid

PROPERTIES: Pungent, water-white liquid; wt. per gal. 7.48 lbs. (28.34).

USES: A source of nitrogen for plants, either applied directly to the soil or to irrigation water for the formulation of mixed fertilizers, for oxidation in lead chamber sulphuric acid plants and to supply nitrogen requirements and pH control in yeast culture.

SHIPPING INFORMATION: Ammonia Liquid (containing not more than 35% ammonia (NH₃) by weight). Tank cars or tank trucks.

AMMONIA, ANHYDROUS**AGRICULTURAL DIVISION**

MOLECULAR WEIGHT: 17.03

PROPERTIES: Colorless gas, at normal temperatures and pressure, 0.807 times as heavy as air; below critical temperature, 271.2°F., readily condenses by application of pressure to a colorless liquid, wt. per gal. 5.33 lbs.; B.P. -28°F.

USES: A source of nitrogen for plant food, either applied direct or for formulation of mixed fertilizers, liquid or dry. Used as nitrogen source by textile, rubber, paper, petroleum industries, among others.

SHIPPING INFORMATION: Anhydrous Ammonia (Dangerous Placards Applied). Tank cars (approx. 26 tons). Tank trucks (approx. 13 tons).

NUTRIUM® FERTILIZER**AGRICULTURAL DIVISION**

SPECIFICATIONS: Nitrogen—22% min. guarantee Ammonia N 16.2% Nitrate N 12.8%. A. P. A. 14% min. guarantee.

PHYSICAL PROPERTIES: 62 lbs./cu. ft. bulk density.

SHIPMENTS: 30, 40 and 50 ton bag cars, bag or bulk, 90-70 ton hopper cars—bulk. Trucks (50 tons) to Luling, La., plant. (No contract or common carrier truck deliveries).

SPECIAL NOTE: We will ship mixed cars of Nutrium and E-2 Ammonium Nitrate Fertilizer from Luling, La., only. The delivered price on each product will be determined by the total tonnage in the car for the destination concerned. For example, if 30 tons of Nutrium and 10 tons of Ammonium Nitrate Fertilizer are shipped for a total of 50 tons, each product would be priced on the 50 ton car basis.

PHOSPHATIC FERTILIZER SOLUTION**AGRICULTURAL DIVISION**

STANDARD FORM: Liquid

PROPERTIES: Recommended only for use in manufacture of fertilizers. Because this is a crude product no guarantee of analysis is made except for P₂O₅ content which will vary from 54.5% to 58% P₂O₅ (70-80% acid).

SHIPPING INFORMATION: Tank cars and tank trucks. Phosphatic fertilizer solution.

*Monsanto Trademark

PHOSPHOLEUM®

Pyro-Phosphoric Acid or also known as Super Phosphoric Acid.

AGRICULTURAL DIVISION

GENERAL INFORMATION: A clear liquid containing approximately 78% P₂O₅ and equivalent to 105% H₃PO₄. It is an azeotropic mixture of orthophosphoric and polyphosphoric acids which on dilution with water hydrolyze to orthophosphoric acid. Sp. Gr. 1.90 approx. at 75°F.; viscosity, 800 centipoises at 75°F.; temperature rise, 80°F. on dilution to 75% H₃PO₄; freezing point, less than minus 50°C.

GRADE: Food

USES: High analysis liquid fertilizer formulation, metal phosphating and aluminum Bright Dip Bath Component.

SHIPPING INFORMATION: Phosphoric Acid. Tank cars and tank trucks.

UREA FERTILIZER GRADE COATED PELLETS**AGRICULTURAL DIVISION**

STANDARD FORM: Urea in pelleted form coated with an inorganic material as a conditioning agent.

ANALYSIS:	
Nitrogen (Min.)	45.0%
Moisture (Max.)	.3%
Burst (Max.)	1.5%

SHIPPING INFORMATION: Urea having value only for fertilizer purposes (Fertilizer Compound NOIBN). 80-lb. multiwall bags with polyethylene lining. Also in bulk.

UREA FERTILIZER GRADE UNCOATED PELLETS**AGRICULTURAL DIVISION**

STANDARD FORM: Urea in pelleted form without coating agent.

ANALYSIS:	
Nitrogen (Min.)	46.0%
Moisture (Max.)	.5%
Burst (Max.)	1.0%

SHIPPING INFORMATION: Urea having value only for fertilizer purposes (Fertilizer Compound NOIBN). Multiwall paper bags with polyethylene lining in 80-lb. bags. Also in bulk.

PRE-EMERGENCE HERBICIDES**AVAXEX®****AGRICULTURAL DIVISION—LITERATURE AVAILABLE**

STANDARD FORM: Liquid and granular.

GENERAL INFORMATION: Liquid contains 45.7% 2,3-dichloroallyl diisopropylthiocarbamate, or 4 pounds active ingredient per gallon. Granules contain 10% active ingredient.

USES: Controls wild oats and certain other weeds in sugar beets, flax and certain other crops. Liquid mixed with water, applied as a ground or aerial spray.

AVAXEX® BW**AGRICULTURAL DIVISION—LITERATURE AVAILABLE**

STANDARD FORM: Liquid.

GENERAL INFORMATION: Contains 46.3% 2,3,3-trichloroallyl diisopropylthiocarbamate, or 4 pounds active ingredient per gallon.

USES: Controls wild oats in barley, spring wheat, Durum wheat and peas. Mixed with water, applied as a ground or aerial spray.

FAR-GO®**AGRICULTURAL DIVISION—LITERATURE AVAILABLE**

STANDARD FORM: Liquid.

GENERAL INFORMATION: Contains 46.3% 2,3,3-trichloroallyl diisopropylthiocarbamate, or 4 pounds active ingredient per gallon.

USES: Controls wild oats in barley, spring wheat and Durum wheat. Mixed with water, applied as a ground or aerial spray.

LIMIT®**AGRICULTURAL DIVISION**

STANDARD FORM: Liquid.

GENERAL INFORMATION: Contains 48.13% 4-chloro-N-N-diallylacetamide (4 pounds active ingredient per gallon) and 11.54% 2,4-dichlorophenoxyacetic acid (1 pound active ingredient per gallon).

USES: Controls annual grasses and broadleaf weeds in sugar cane.

RAMROD*

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Wettable powder and granular.**GENERAL INFORMATION:** Granules contain 20% 2-chloro-N-isopropylacetanilide. Wettable powder contains 65% 2-chloro-N-isopropylacetanilide.**USES:** Controls both grassy and many broadleaf weeds in hybrid seed and field corn.**RANDOX®**

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid and granular.**GENERAL INFORMATION:** Liquid contains 47.1% a-chloro-N-N-diallylacetamide, or 4 pounds of active ingredient per gallon. Granules contain 20% CDAAs as active ingredient.**USES:** Controls annual grasses in corn, soybeans, onions, sorghum and certain other crops.**RANDOX® T**

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid and granular.**GENERAL INFORMATION:** Liquid contains 28.1% a-chloro-N-N-diallylacetamide and 57.6% trichlorobenzyl chloride, or 3.1 pounds of CDAAs and 2.3 pounds of TCBC as active ingredient per gallon. Granules contain 11.7% CDAAs and 23.3% TCBC as active ingredient.**USES:** Controls annual grasses and certain broadleaf weeds in corn.**VEGADEX®**

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid and granular.**GENERAL INFORMATION:** Liquid contains 46.4% 2-chloroallyl dichlorodithiocarbamate, or 4 pounds active ingredient per gallon. Granules contain 30% CDBC per gallon.**USES:** Controls certain annual grasses and broadleaf weeds in a variety of vegetable crops.**SHIPPING INFORMATION:** Weed Killer (NOIBN).**POST-EMERGENCE HERBICIDES****LAMBAST®**

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**GENERAL INFORMATION:** A "contact" herbicide containing 25.5% 2,4-bis (3-methoxypropylamino)-n-methylthio-s-triazine, or 3 pounds active ingredient per gallon.**USES:** Controls lambquarter and certain other weeds in soyflower. Mixed with water, applied as a ground or aerial spray.**LYON HERBICIDAL OIL NO. 1**

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**GENERAL INFORMATION:** A post-emergence contact herbicide produced by carefully controlled petroleum refining. It is completely volatile and leaves no residue. It is non-corrosive, and its fumes are non-toxic.**USES:** A safe and economical herbicide for weed control in cotton and soybeans. Applied as a spray.**SHIPPING INFORMATION:** Petroleum Naphtha. Tank cars.**LYON HERBICIDAL OIL NOS. 6 AND 7**

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**GENERAL INFORMATION:** Non-selective, general contact herbicides produced by carefully controlled refining from a crude oil naturally high in aromatic compounds. They are slowly volatile and leave no permanently toxic or oily residues when used at recommended rates. Kill only those plants on which they are actually sprayed.**USES:** For control of weeds and grasses on railroad rights-of-way, and wherever a general contact herbicide is required. Applied as a spray.**SHIPPING INFORMATION:** Petroleum distillate fuel oils not suitable for illuminating purposes. Tank cars.

*Monsanto Trademark

ROGUE®

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**GENERAL INFORMATION:** Contains 40% 3,4-dichloropropionaldehyde, or 4 pounds active ingredient per gallon.**USES:** Controls barnyard grass (watergrass) and certain other weeds in rice. Mixed with water, applied as a ground or aerial spray.**SHIPPING INFORMATION:** Weed killer (NOIBN).**HORMONE HERBICIDES**

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

GENERAL INFORMATION: Hormone-type herbicides selectively destroy certain species of unwanted weed and brush pests, depending upon the formulation used. These organic herbicides enter the circulatory system of susceptible plants to completely upset the growth pattern, resulting in death from alteration of enzyme activity.**WEED KILLERS:****2,4-D AMINE:** Contains 49.5% dimethylamine salt of 2,4-dichlorophenoxyacetic acid, equivalent to 4.1% or 4 pounds 2,4-D acid per gallon.**2,4-D ISOPROPYL ESTER:** Contains 45.2% isopropyl ester of 2,4-dichlorophenoxyacetic acid, equivalent to 38% or 3.34 pounds 2,4-D acid per gallon.**2,4-D BUTYL ESTER:** A low concentrate formulation containing 41.4% butyl ester of 2,4-dichlorophenoxyacetic acid, equivalent to 33% or 2.87 pounds 2,4-D acid per gallon.**2,4-D BUTYL ESTER CONCENTRATE:** A high concentrate formulation containing 57.8% butyl ester of 2,4-dichlorophenoxyacetic acid, equivalent to 46% or 4 pounds 2,4-D acid per gallon.**2,4-D LOW VOLATILE ESTER:** Contains 69.7% isooctyl ester of 2,4-dichlorophenoxyacetic acid, equivalent to 46.2% or 4 pounds 2,4-D acid per gallon.**2,4-D GRANULAR:** A formulation of 2,4-dichlorophenoxyacetic acid low volatile ester on 20-40 mesh attapulgite clay granules. Contains 30.2% isooctyl ester of 2,4-dichlorophenoxyacetic acid, equivalent to 20% or 10 pounds 2,4-D acid per 50 pound bag.**MCP AMINE:** Similar in action to 2,4-D, but certain crops, such as flax, rice, oats and some clovers, are more tolerant of MCP than 2,4-D. Formulation contains 52.0% dimethylamine salt of 2-methyl-4-chlorophenoxyacetic acid, equivalent to 42.8% or 4.0 pounds of the acid per gallon.**CROP-GUARD®:** A highly concentrated formulation of 51.4% isobutyl ester and 26.5% butyl ester of 2,4-dichlorophenoxyacetic acid, equivalent to 62.2% or 6.0 pounds of 2,4-D acid per gallon.**FIELD-CLEAN®:** A highly concentrated formulation of 94.5% isooctyl ester of 2,4-dichlorophenoxyacetic acid, equivalent to 62.7% or 6 pounds of 2,4-D acid per gallon.**BRUSH KILLERS:****2,4-D/2,4,5-T AMINE:** Contains 29.7% triethylamine salt of 2,4-dichlorophenoxyacetic acid and 28.5% triethylamine salt of 2,4,5-trichlorophenoxyacetic acid, equivalent to 20.3% or 2 pounds of 2,4,5-T acid per gallon.**2,4-D/2,4,5-T BUTYL ESTER:** Contains 27.5% butyl ester of 2,4-dichlorophenoxyacetic acid and 28.7% butyl ester of 2,4,5-trichlorophenoxyacetic acid, equivalent to 21.9% or 2 pounds of 2,4-D acid and 21.9% or 2 pounds of 2,4,5-T acid per gallon.**2,4-D/2,4,5-T LOW VOLATILE ESTER:** Contains 34.5% isooctyl ester of 2,4-dichlorophenoxyacetic acid and 15.3% of n-butyl ester of 2,4,5-trichlorophenoxyacetic acid. Equivalent to 22.0% or 2 pounds of 2,4-D acid and 22.8% or 2 pounds of 2,4,5-T acid per gallon.**2,4,5-T AMINE:** Contains 58.5% triethylamine salt of 2,4,5-trichlorophenoxyacetic acid, equivalent to 40.5% or 4 pounds of 2,4,5-T acid per gallon.**2,4,5-T BUTYL ESTER:** Contains 37.5% isobutyl ester of 2,4,5-trichlorophenoxyacetic acid and 15.3% of n-butyl ester of 2,4,5-trichlorophenoxyacetic acid, equivalent to 43.3% or 4 pounds of 2,4,5-T acid per gallon.**2,4,5-T LOW VOLATILE ESTER:** Contains 65.3% isooctyl ester of 2,4,5-trichlorophenoxyacetic acid, equivalent to 45.4% or 4 pounds of 2,4,5-T acid per gallon.**BRUSH-O-GUARD®:** A highly concentrated formulation of 46.8% isooctyl ester of 2,4-dichlorophenoxyacetic acid and 44.5% isooctyl ester of 2,4,5-trichlorophenoxyacetic acid. Equivalent to 30.8% or 3 pounds of 2,4-D acid and 30.9% or 3 pounds of 2,4,5-T acid per gallon.**BRUSH-BITZ®:** A highly concentrated formulation of 88.0% isooctyl ester of 2,4,5-trichlorophenoxyacetic acid, equivalent to 61.1% or 6 pounds of 2,4,5-T acid per gallon.**SHIPPING INFORMATION:** Weed Killing Compound (NOIBN); Brush Killing Compound (NOIBN).

INSECTICIDES

ETHYL PARATHION

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 291.3

STANDARD FORM: Liquid.

PROPERTIES: Dark brown liquid; crystallizing point 0°C. minimum; 10.5-10.7 lbs./gal. at 77°F. (25°C.).

GENERAL INFORMATION: Parathion is the designated common name of the German developed insecticide, O,O-diethyl O-p-nitrophenyl phosphorothioate, having the synonymy of E-606; O,O-diethyl O-p-nitrophenyl thiophosphate; diethyl p-nitrophenyl thiophosphate. It controls a broad range in insects, as well as mites, and has residual effect. It therefore possesses certain advantages over standard insecticides and miticides and has established its place among the ranks of modern and effective organic insecticides.

HANDLING PRECAUTIONS: DANGER statement. POISON emblem and antidote required by law.

Parathion is an extremely poisonous material and the customer should clearly understand that it must be handled and formulated with great care. Parathion is highly toxic by any route, whether it be by swallowing, inhaling or absorption through the skin. In addition, the customer must be told that formulations containing this material are also extremely toxic and the same care should be exercised with all formulations to insure safe use.

Complete precautionary information is available upon request.

SHIPPING INFORMATION: Parathion, Insecticides Agricultural, Liquid NOIBN; Class B poison and product label required; not mailable, 55-gal. 100 LTR, 16-gauge, black iron drums lined with one coat A & W 4A lacquer, 2-inch and 5/8-inch Tirsure fittings in head, 550-lbs. net.

Monsanto sells Ethyl Parathion only to agricultural insecticide formulators who are skilled in the handling, formulation and distribution of poisonous insecticides.

METHYL PARATHION

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 263.3

STANDARD FORM: Liquid.

PROPERTIES: Technical methyl parathion, a semi-solid, is sold as an 80% solution in xylene. This very concentrated solution, a liquid above 45°F. (13.3°C.), begins to crystallize as the temperature drops. For this reason, methyl parathion should be stored at temperatures above 65°F. (18.3°C.). Must not be heated above 131°F. (55°C.). 10.2-10.3 lbs./gal. at 77°F. (25°C.).

GENERAL INFORMATION: Methyl Parathion, O,O-dimethyl O-p-nitrophenyl phosphorothioate, is approved for use on cotton, fruits, vegetables, forage and other crops. At dosages of up to one pound of technical material per acre, it will effectively control a wide spectrum of insects. It is particularly effective for the control of boll weevil, but is not effective against the bollworm, the pink bollworm, or two-spotted mite.

Monsanto sells Methyl Parathion only to agricultural insecticide formulators who are skilled in the handling, formulation and distribution of poisonous insecticides.

HANDLING PRECAUTIONS: DANGER statement. POISON emblem and antidote required on label.

Methyl Parathion is an extremely poisonous material and the customer should clearly understand that it must be handled and formulated with great care. Methyl Parathion is highly toxic by any route, whether it be by swallowing, inhaling or absorption through the skin. In addition, the customer must be told that formulations containing this material are also extremely toxic and the same care should be exercised with all formulations to insure safe use.

SHIPPING INFORMATION: Methyl Parathion, Insecticides Agricultural, Liquid NOIBN; Class B poison and product label required; not mailable, 55-gal. 100 LTR, 16-gauge, black iron drums, lined with one coat A & W 4A lacquer, 2-inch and 5/8-inch Tirsure fittings in head, 550-lbs. net.

NIRAN® 6-3

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: Contains 58.28% 9,0-diethyl O-p-nitrophenyl phosphorothioate and 29.01% 0,0-diethyl O-p-nitrophenyl phosphorothioate as active ingredients. Equivalent to 6 pounds of ethyl parathion and 3 pounds of methyl parathion per gallon.

USES: Controls bollworms and boll weevils in cotton and certain other crops.

HANDLING PRECAUTIONS: DANGER statement. POISON emblem and antidote required by law.

*Monsanto Trademark

NIRAN® 10-G

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Granular

PROPERTIES: Contains 10% O,O-diethyl O-p-nitrophenyl phosphorothioate as the active ingredient.

USES: Used to control corn root worms and other soil borne insects.

HANDLING PRECAUTIONS: DANGER statement. POISON emblem and antidote required by law.

SANTOCHLOR® para-DICHLOROBENZENE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 147.01

STANDARD FORM: Crystals

PROPERTIES: White crystals; crystallizing point 52.8°C. min.

GRADES: Standard crystal sizes: No. 0 (approx. 1/4 inch pellets)—For peachtree borers and for insecticide and miscellaneous uses. No. 1 (approx. 1/2 inch nuggets)—For shaker top cans. No. 34 (approx. rice-size granules)—A combination of two uniformly sized crystals. For shaker top cans and for compressing into cakes. No. 84—80% min. between 8 and 16 mesh. Blocking mix—Mixture of sizes under 7 mesh. Fines—Mixture of sizes under 16 mesh.

USES: As a mothicide, for masking odors, for the control of peachtree borers. When vapors are confined, Santochlor is very effective for mildew control.

SHIPPING INFORMATION: Paradichlorobenzol, 200-lb. and 100-lb. fiber drums.

STABILIZED METHYL PARATHION

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 263.3

STANDARD FORM: Liquid.

PROPERTIES: Stabilized Methyl Parathion is a light brown mobile liquid sold as a 80% solution in xylene plus stabilizer. Crystallizing point 61°F. (16°C.). Must not be heated above 131°F. (55°C.). 9.8 lbs./gal. at 77°F. (25°C.).

GENERAL INFORMATION: Stabilized Methyl Parathion O,O-dimethyl O-p-nitrophenyl phosphorothioate, is recommended for use in the manufacture of dust formulations only. Approved for use on cotton. At dosages of 0.25 to 0.5 lbs. of technical material per acre, Methyl Parathion will effectively control a wide spectrum of insects including aphids, some mite species, cotton leafworm, and boll weevil. It is not effective against the bollworm, the pink bollworm or two-spotted mite.

Monsanto sells Stabilized Methyl Parathion only to agricultural insecticide formulators who are skilled in the handling, formulation and distribution of poisonous insecticides.

HANDLING PRECAUTIONS: DANGER statement. POISON emblem and antidote required by law.

Methyl Parathion is an extremely poisonous material and the customer should clearly understand that it must be handled and formulated with great care. Methyl Parathion is highly toxic by any route, whether it be by swallowing, inhaling or absorption through the skin. In addition, the customer must be told that formulations containing this material are also extremely toxic and the same care should be exercised with all formulations to insure safe use.

SHIPPING INFORMATION: Methyl Parathion, Insecticides Agricultural, Liquid NOIBN; Class B poison and product label required; not mailable, 55-gal. 100 LTR, 16-gauge black iron drums, lined with one coat of A & W 4A lacquer, 2-inch and 5/8-inch Tirsure fittings in head, 540-lbs. net.

PRESERVATIVE

STOP SCALD® FRUIT SPRAY

AGRICULTURAL DIVISION

ANALYSIS:

**Active Ingredient:
1,2-dihydro-6-ethoxy-2,2,4-trimethylquinoline..... 70%
Inert Ingredients..... 30%

**Equal to 6 pounds of ethionazin per gallon

STANDARD FORM: Liquid.

USE: Mixed with water and used as either a spray or a dip. Stop Scald prevents common scald of apples and pears in storage.

SHIPPING INFORMATION: Chemicals N.O.I.B.N. 1 gallon and 5 gallon containers.

BUILDING PRODUCTS

LUSTRA-SPAN® VINYL BUILDING PANELS

BUILDING PRODUCTS DEPARTMENT

A tough non-combustible translucent building panel for roof and wall daylighting. Designed for raked outdoor use.

FORMS:

Profile	Corrugation					Panel Width	Cove Length	Stack Length	
	Nominal	Actual		Thick- ness	Weight				
	Cycle Depth	Cycle Depth	Sq. Ft.						
	2 1/2"	1 1/2"	2.48	7 1/2"	600"	8.61	50 1/2"	48"	8', 10', 12'
	2 1/2"	3"	2.41	5"	655"	8.61	50 1/2"	48"	8', 10', 12'
	2 1/2"	1 1/2"	2.67	1 1/2"	552"	8.61	50 1/2"	48"	8', 10', 12'
	4 1/2"	1 1/2"	4.20	1 1/2"	260"	8.61	50 1/2"	48"	8', 10', 12'
Flat Sheets									
					668"	8.61	48"		8', 10', 12'

COLORS:

Color	% Light Transmission*	
	High	Medium
Neutral	80%	40%
Yellow	75	40
Light Green	65	35
Dark Green	50	30

*Based on air at 100% SS glass at 89%.
Also available in selected opaque colors.

PACKAGING:

Lengths	No. of Panels	Area
8 ft.	10	(336.7 sq. ft.)
10 ft.	8	(336.7 sq. ft.)
12 ft.	7	(353.1 sq. ft.)

Standard Packaging (of a single corrugation and color)
ACCESSORIES: A complete line of accessories is available.

MONSANTO® FOAM BOARD

BUILDING PRODUCTS DEPARTMENT

Lightweight insulating material for roofs, walls, ceilings and floors. Common uses are on foundation exterior and interior walls, under slab, plaster base, roofing, insulating heating ducts, etc.

Foam board is an extremely lightweight white insulating material produced by expanding polystyrene into minute individually closed cells. An excellent insulation for residential and commercial structures. Foam board is highly resistant to passage of heat, water and water vapor. It is available in regular or self-extinguishing types.

STOCK SIZES

Finished Boards (Packaged)	Finished Boards (Unpackaged)	Blocks (Untrimmed)
STOCK SIZES	STANDARD NOMINAL SIZES	NON-STANDARD SIZES
Lengths of 48", widths 18" and 24", and thicknesses 1", 1 1/2", 2", 3" and 4"	Lengths of 48", 72" and 144", widths 12", 16", 24", 48", and thicknesses 1", 1 1/2", 2", 3", 4", 5", 6" and 8"	Lengths of 96" and 108", widths 12", 16", 24" and 48", thicknesses 2", 3" and 4"
		24" x 145" x 9"
		48" x 145" x 9"

MONSANTO® VINYL GUTTERS AND DOWNSPOUTS

BUILDING PRODUCTS DEPARTMENT

New maintenance for white vinyl rain carrying equipment offered as complete system. Manufactured of tough, solid vinyl, components will not chip, rust, wear away, blister, peel, support fire or conduct electricity. Doesn't need painting. Standard "K" ("O") shape as designated by U. S. Department of Commerce.

SHIPPING:

Gutter — twenty 10-ft. lengths	per carton
Downspout — twenty 10-ft. lengths	per carton
Collector — 24	per carton
Connector — 100	per carton
End Cap (RH) — 100	per carton
End Cap (LH) — 100	per carton
Inside Corner — 30	per carton
Outside Corner — 30	per carton
Elbow — 24	per carton
Gutter Hanger — 300	per carton
Downspout Hanger — 100	per carton
Cement-Tube — 12	per carton

*Monsanto Trademark

MONSANTO® VINYL SIDING

BUILDING PRODUCTS DEPARTMENT

For maintenance free exteriors, this solid vinyl siding system never needs painting and maintains its sparkling surface beauty for the life of the building. It is self-extinguishing and extremely resistant to corrosion such as seashore or in heavy industrial atmospheres. It shrugs off the impact of driving ball, rocks and accidental bumps. It does not require bonding or rounding for lightning protection.

PACKAGING: Vinyl Siding: 24 pieces to the carton; 9" square carton; 10-lb. carton; 12-6" lengths. Backing Board: 14 pieces to a bundle; 2 bundles square; 30-lb. carton.

SILENT-COR® FOR SOUND CONTROL

BUILDING PRODUCTS DEPARTMENT

Silent-Cor sound deadening board is a flat sheet laminate of closed cell polystyrene and paper facings designed to reduce level of sound transmitted through walls, ceilings and floors.

SIZES:

Width	Length	Thickness
4'	8'	1/4"
4'	10'	1/4"
4'	12'	1/4"

PACKING: Taped 20 sheets per bundle.

Net Weight: approx. 105 lbs./bdl. 4' x 8'

approx. 131 lbs./bdl. 4' x 10'

approx. 157 lbs./bdl. 4' x 12'

THERMO-LATH® WATERPROOF INSULATING PLASTERBASE

BUILDING PRODUCTS DEPARTMENT

Thermo-Lath offers the building industry a low cost, efficient system for the interior finishing of masonry walls with plaster. Panels have special paper facings securely bonded to polystyrene foam core.

ACCESSORIES: Adhesive, spindle clips and lock washers available.

SIZES:

Width	Length	Thickness
16"	48"	1/4"
2'	8'	1"
4'	8'	1 - 1 1/2"
		2"

PACKING: 5 sheets taped together per bundle.

CHEMICAL FIBERS

ACRILAN®

CHEMSTRAND COMPANY DIVISION

STANDARD FORM: Staple or tow.

GENERAL INFORMATION: Full range of deniers in a variety of staple lengths or tow. Regular *Acrlan* and *Acrlan-10* (white) acrylic fiber. Fiberfill and solution-dyed *Acrlan* also available.

USES: Awning fabrics, blankets, carpets, comforters, deep pile fabrics, blanket-type fabrics, furniture covers, half hose, jersey knits, knitting yarns, pile fabrics, pile liners, sweaters, wool system blends, worsted blends, woven goods and upholstery fabrics.

NYLON 66

CHEMSTRAND COMPANY DIVISION

STANDARD FORM: Filament yarns.

GENERAL INFORMATION: Available in monofilament, textile multi filament, and modified cross-section yarns; also textured yarns, tire cord and industrial yarns.

USES: Carpets, coated fabrics, cordage, hosiery, industrial webbing, raschel knitting, surgical hosiery, texturizing, thread, tire cord, tricot fabrics, twine, upholstery fabrics, woven fabrics, weaving and braiding.

POLYESTER

CHEMSTRAND COMPANY DIVISION

STANDARD FORM: Staple fiber.

GENERAL INFORMATION: Deniers and staple lengths suitable for blending with cotton, rayon and other textile fibers.

USES: Apparel fabrics, industrial and military fabrics, woven and knitted.

SPANDEX

CHEMSTRAND COMPANY DIVISION

STANDARD FORM: Elastic filament yarns.

GENERAL INFORMATION: Available in full range of textile deniers.

USES: Braid, circular knitting, narrow fabrics, support hose tapes and webbings, warp knitting.

ELECTRONIC MATERIALS

COOLANOL® 35

ORGANIC DIVISION

COOLANOL 35 is a coolant-dielectric fluid for cooling electronic equipment in ground, shipboard and airborne applications. Chemically and operationally similar to COOLANOL 45. COOLANOL 35 is especially suited for low-temperature applications, with an operating range of -80° to 400°F.

COOLANOL® 45 DIELECTRIC COOLANT FOR ELECTRONIC EQUIPMENT

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A clear, amber liquid with dielectric, heat transfer and hydraulic properties—over a -85°F. to 400°F. temperature range.

USES: Dielectric coolant for both airborne and ground environmental electronic equipment. Also utilized in hydraulic applications in electronic equipment.

SHIPPING INFORMATION: Chemicals NOIBN. 1-qt. cans: 1-gal. cans: 5-gal. cans: 54-gal. drums

GALLIUM ANTIMONIDE Electronic Grade

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Single crystal Czochralski nominal diameter 2.5 centimeters weighing up to several hundred grams.

PURITY: Undoped and doped in various ranges of carrier concentrations, resistivities, mobilities and Hall coefficients.

USES: Ultra high purity Gallium Antimonide for use in the manufacture of electronic semiconductor devices.

SHIPPING INFORMATION: Special containers according to form and quantity. Individual ingots packaged in polyethylene sleeves with data sheet.

GALLIUM ARSENIDE Electronic Grade

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Single and polycrystall ingots boat grown and Czochralski weighing up to several hundred grams. Also epitaxial wafers 1.5 centimeters in diameter.

PURITY: Undoped and doped in various ranges of carrier concentrations, resistivities, mobilities and Hall coefficients.

USES: Ultra-high purity Gallium Arsenide for use in the manufacture of electronic semiconductor devices.

SHIPPING INFORMATION: Special containers according to form and quantity. Individual ingots packaged in polyethylene sleeves with data sheet.

GALLIUM ARSENIDE PHOSPHIDE ALLOYS

Electronic Grade

INORGANIC DIVISION

STANDARD FORM: Epitaxial wafers 1.5 cm. in diameter of gallium arsenide phosphide on gallium arsenide and film thickness up to 300 microns.

PURITY: Available in various ranges of carrier concentrations, resistivities, mobilities and Hall coefficients.

USES: Ultra-high purity for use in the manufacture of electronic semiconductor devices.

SHIPPING INFORMATION: Special containers according to form and quantity. Individual ingots packaged in polyethylene sleeves with data sheet.

GALLIUM PHOSPHIDE Electronic Grade

INORGANIC DIVISION

STANDARD FORM: Polycrystalline ingots with semicircular cross section approximately 2.0 cm. wide and weighing approximately 50 grams.

PURITY: Available in various ranges of carrier concentrations, resistivities, mobilities and Hall coefficients.

USES: Ultra-high purity for use in the manufacture of electronic semiconductor devices.

SHIPPING INFORMATION: Special containers according to form and quantity. Individual ingots packaged in polyethylene sleeves with data sheet.

INDIUM ARSENIDE Electronic Grade

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Single crystal Czochralski nominal diameter 1.5 centimeter and polycrystall ingots with rectangular cross section 1.5 x 2.0 centimeters and weighing up to several hundred grams.

PURITY: Available in various ranges of carrier concentrations, resistivities, mobilities and Hall coefficients.

USES: Ultra-high purity Indium Arsenide for use in the manufacture of electronic semiconductor devices.

SHIPPING INFORMATION: Special containers according to form and quantity. Individual ingots packaged in polyethylene sleeves with data sheet.

INDIUM ANTIMONIDE Electronic Grade

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Single crystal Czochralski nominal diameter 2.5 centimeters weighing up to several hundred grams.

PURITY: Undoped and doped in various ranges of carrier concentrations, resistivities, mobilities and Hall coefficients.

USES: Ultra-high purity Indium Antimonide for use in manufacture of electronic semiconductor devices.

SHIPPING INFORMATION: Special containers according to form and quantity. Individual ingots packaged in polyethylene sleeves with data sheet.

INDIUM PHOSPHIDE Electronic Grade

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Polycrystall ingots with semi-circular cross section approximately 2.0 centimeters wide and weighing approximately 50 grams.

PURITY: Available in various ranges of carrier concentrations, resistivities, mobilities and Hall coefficients.

USES: Ultra-high purity Indium Phosphide for use in the manufacture of electronic semiconductor devices.

SHIPPING INFORMATION: Special containers according to form and quantity. Individual ingots packaged in polyethylene sleeves with data sheet.

OS-45® TYPE III HIGH TEMPERATURE AIRCRAFT HYDRAULIC FLUID.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A clear, amber liquid with outstanding hydraulic properties over a -85°F. to 400°F. temperature range.

USES: High temperature hydraulics for both airborne and ground environmental application.

SHIPPING INFORMATION: Chemicals NOIBN. 1-qt. cans: 1-gal. cans: 5-gal. cans: 54-gal. drums.

OS-45® TYPE IV HIGH TEMPERATURE AIRCRAFT HYDRAULIC FLUID.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A clear amber liquid with outstanding hydraulic properties over a -85°F. to 500°F. temperature range.

USES: High temperature hydraulic for both airborne and ground environmental applications.

SHIPPING INFORMATION: Chemicals NOIBN. 1-qt. cans: 1-gal. cans: 5-gal. cans: 54-gal. drums.

SILICON Electronic Grade

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Single-crystal float zone ingots: single-crystal Czochralski ingots; slices, lapped wafers and polished wafers of both float zone and Czochralski material; epitaxial silicon wafers; polycrystall silicon as rods, chunks or unit crucible charges.

PURITY: Less than 0.2 parts per billion base boron content. Dopants added to achieve resistivity levels desired by customers.

(Continued on next page)

GENERAL INFORMATION: Material available in various electrical resistivity ranges, conductivity types, diameters, lengths, water thicknesses, etc., according to individual customer requirements.

USES: Single-crystal silicon used directly in the manufacture of semiconductor devices such as diodes, rectifiers, transistors and solar cells. Epitaxial wafers are also used for transistors and diode manufacture as well as integrated circuits. Polycrystalline silicon is used in the production of single-crystal ingots via the Czochralski or float zone techniques.

SHIPPING INFORMATION: Special containers according to form and quantity. Data sheets on material enclosed with shipment.

FOOD INGREDIENTS

ACIDULANTS

ADIPIC ACID, FOOD AND TECHNICAL GRADES

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 146.14

STANDARD FORM: White crystalline powder.

SPECIFICATIONS: Food Grade: White crystalline powder: Assay 99.7% min.; Melting point first maximum 152.0°C. min.; complete melt 152.0°C. min.; Ash 12 ppm max.; Iron 2 ppm max.; Water 0.2% max.

Technical Grade: Assay 99.7% min.; M. P. 152.0°C. min.; Ash 12 ppm max.; Color 50 grams in 100 ml. methanol) APHA 10 max.; Water 0.2% max.; Iron 2 ppm max.

GRADES: Food and Technical.

USES: Food Grade: Used in any non-standardized food as an acidulant.

Technical Grade: A resin intermediate in the surface-coating and polymer industries where it is used for viscosity control and to impart softness and flexibility to the cured resins.

SHIPPING INFORMATION: Acid, NOIBN, dry, 50-lb. bags.

CW50 FUMARIC ACID, FOOD AND TECHNICAL GRADES

ORGANIC DIVISION—LITERATURE DEPARTMENT

STANDARD FORM: White, finely ground powder.

SPECIFICATIONS: White, finely ground powder: Assay 98.3% min.; fumaric acid, 0.4% DSS (disodium sulfite) (acid); max. particle size 60 microns; min. mean particle size 7 microns.

USES: Used now in dry beverage basis because of its rapid solubility in cold water. Should be considered wherever a rapidly soluble, fruit flavored acid is needed.

SHIPPING INFORMATION: Acid NOIBN dry.

FUMARIC ACID, FOOD AND TECHNICAL GRADES

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 110.07

STANDARD FORM: Fine crystals or granular.

SPECIFICATIONS: Food Grade: Fine crystals or granular: Assay 99.6% min.; Moisture 0.25% max.; Iron 3 ppm max.

Technical Grade: Assay 99.6% min.; Ash 0.01% max.; Color (5% in alcohol) APEA 10 max.; Iron 3 ppm max.; Moisture 0.25% max.

GRADES: Food and Technical.

USES: Food Grade: Used in fruit drinks, pie fillings, gelatin desserts, wine, refrigerated biscuit doughs, jelling aids and sour type bread. Should be considered wherever citric acid, tartaric acid, malic acid or potassium bitartrate are now used.

Technical Grade: A resin intermediate in surface coatings, paint ink and polyester resins.

SHIPPING INFORMATION: Acid NOIBN dry, 250-lb. fiber drums and 50-lb. bags.

H. T. MONOCALCIUM PHOSPHATE, MONOHYDRATE

See Next Page

LACTIC ACID, FOOD AND TECHNICAL GRADES

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 90.08

STANDARD FORM: Liquid.

SPECIFICATIONS: Food Grade: Clear liquid: Color 50 APHA max.; Assay for 50% concentration, 50.0% min. total acidity as lactic acid; for 88% concentration, 88.0% min. total acidity as lactic acid.

Technical Grade: Clear liquid: Color 200 APHA max.; Assay for 50% concentration, 88.0% min. total acidity as lactic acid.

GRADES: Food and Technical.

USES: Food Grade: Used as a food acidulant in green olives, cheese, carbonated beverages, jams, jellies and sherbets.

Technical Grade: Used as a pH adjuster in tanning and textile finishing; raw material for plasticizers and alkylid resins; intermediate for lactic acid esters and salts.

SHIPPING INFORMATION: Lactic acid 50% concentration in 500-lb. drums, 88% concentration in 325-lb. drums.

MONOAMMONIUM PHOSPHATE

See Page M5/24

MONOSODIUM PHOSPHATE

See Pages M5/7 and 26

PHOSPHORIC ACID (75, 80 and 85%)

See Page M5/25

FLAVORS

CAFFEINE ANHYDROUS U.S.P.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 870.86

STANDARD FORM: Crystalline Powder.

SPECIFICATIONS: White powder; no foreign odor; M.P. 236.0 min.; moisture 0.25% max.

GRADES: Anhydrous powder or hydrated powder.

USES: Used in soft drinks for its distinctive taste and as a mild stimulant. Used in pharmaceutical preparations for increased wakefulness, to stimulate mental activity and for diuretic activity. Prevalent along or in combination with aspirin and acetophenetidin.

SHIPPING INFORMATION: Chemicals NOIBN, 100-lb. fiber drums.

ETHAVAN® Ethylvanillin

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 166.17

STANDARD FORM: Fine crystalline needles.

SPECIFICATIONS: Fine white crystalline needles; completely soluble in ethyl alcohol 95% (1:2); ash 0.03% max.; M.P. 76.5°C. min.

USES: A flavoring and aromatic. Has a flavor similar to that of vanillin but not identical with it. The relative flavoring strength of Ethavan approximates three times that of vanillin.

SHIPPING INFORMATION: Chemicals NOIBN, 100-lb. fiber drums; 25-lb. fiber drums.

METHYL SALICYLATE U.S.P.

ORGANIC DIVISION—LITERATURE AVAILABLE

SPECIFICATIONS: Colorless liquid: assay essentially 100%; Color: APHA 10 max.; Odor, characteristic; Refractive Index at 20°C. 1.558; Specific Gravity at 20/20°C. 1.180 to 1.185; Solubility in 70% alcohol (1:7) complete; Turbidity, none; Solubility in normal Potassium Hydroxide (1:10); Color, faint yellow, max.; Heavy Metals, meets USP; Weight per gallon, 9.9 lbs.; meets all requirements of USP.

USES: As artificial oil of wintergreen, Methyl Salicylate USP is used to flavor fondants in cookies, cream wafers, lozenges, chewing gum. . . wherever a "mint" flavor is wanted. It is also widely used in sprays, as well as various kinds of insecticides, disinfectants, etc.

SHIPPING INFORMATION: 500-lb. drums-returnable; 500 and 50-lb. drums-nonreturnable. Methyl Salicylate (Essential Oil NOIBN).

0557300

Monsanto

TOWOLDMON0041034

VANILLIN MONSANTO U.S.P.

Vanillin U. S. P.; also known as methylpropiocatechoic aldehyde and 3-methoxy-4-hydroxybenzaldehyde.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 152.14

STANDARD FORM: Fine crystals.

SPECIFICATIONS: Fine, white crystalline needles; M.P. 81.8°C. min.; no foreign flavor (in sugar solution); moisture 0.06% max.; solubility in alcohol (1:2) complete.

USES: As a flavoring agent in foodstuffs and beverages and as an odorant in rubber.

SHIPPING INFORMATION: Chemicals NOIBN. 100-lb. fiber drums; 25-lb. fiber drums.

LEAVENING AGENTS**DICALCIUM PHOSPHATE, ANHYDROUS AND DIHYDRATE**

See Page M5/25

H. T. MONOCALCIUM PHOSPHATE, Monohydrate.

ORGANIC DIVISION

FORMULA: $\text{Ca}(\text{H}_2\text{PO}_4) \cdot 2\text{H}_2\text{O}$

MOLECULAR WEIGHT: 252.17

STANDARD FORM: Powder to granular.

PROPERTIES: A free-flowing bead form of MCP; soluble in water, giving an acid reaction.

GRADES: Differ in particle size only. Regular for phosphated and self-rising flour and baking powder. Granular for baking powder. Fine for bread improvers and yeast food. All grades meet U. S. Pure Food Law requirements. Special grades will be supplied on request.

USES: Leavening agent in biscuits and crackers and acid leavening agent in pancakes; sole acid agent or mixed with sodium aluminum sulfate or sodium acid pyrophosphate in baking powders; in making self-rising, phosphated plain flour and prepared flours; to control pH of solution in malt. Used as ingredient in manufacture of glass.

SHIPPING INFORMATION: Phosphate of Calcium. 100-lb. bags; 350-lb. drums.

LEVN-LITE*

INORGANIC DIVISION—LITERATURE AVAILABLE

PROPERTIES: Sodium Aluminum Phosphate-based product.

USES: As a leavening in cake mixes; characterized by its delayed leavening properties; conforms to all Federal and State Pure Food Laws.

SHIPPING INFORMATION: Phosphate of Soda. Packaged in 100-lb. fiber drums.

PAN-O-LITE®

INORGANIC DIVISION—LITERATURE AVAILABLE

PROPERTIES: Sodium Aluminum Phosphate-based product.

USES: As a leavening agent in pancake mixes and cake mixes; characterized by its delayed leavening properties. Conforms to all Federal and State Pure Food Laws.

SHIPPING INFORMATION: Sodium Aluminum Phosphate. Packaged in 100-lb. fiber drums.

PY-RAN® ANHYDROUS MONOCALCIUM PHOSPHATE

INORGANIC DIVISION

FORMULA: $\text{CaH}_2\text{P}_2\text{O}_6$ or $\text{CaH}_2(\text{PO}_3)_2$

MOLECULAR WEIGHT: 234.17

PROPERTIES: An anhydrous monocalcium phosphate used as an acid component for leavening agents in self-rising flours and corn meal, also baking powders and prepared mixes. Has delayed leavening properties. Conforms with all Federal and State Pure Food Laws.

SHIPPING INFORMATION: Phosphate of Calcium. 100-lb. bags.

SODIUM ACID PYROPHOSPHATE

INORGANIC DIVISION

FORMULA: $\text{Na}_2\text{H}_2\text{P}_2\text{O}_7$

MOLECULAR WEIGHT: 221.97

STANDARD FORM: Powder.

PROPERTIES: White powder, soluble in water; min. neutralizing value 74; pH of 1% solution 4.2.

*Monsanto Trademark

GRADES: Food and Industrial. Food Grade meets all U. S. and State Pure Food Law requirements.

USES: As baking acid for prepared flours, refrigerated doughs, doughnut flours; in manufacture of baking powders and baking creams; in oil well drilling muds.

SHIPPING INFORMATION: Sodium Phosphate. 100-lb. bags; 325 and 100-lb. drums.

STABIL -9® LEAVENING AGENT

INORGANIC DIVISION—LITERATURE AVAILABLE

PROPERTIES: Sodium Aluminum Phosphate blended with calcium phosphates.

USES: A leavening in self-rising flour and mixes. Conforms with all Federal and State Pure Food Laws.

SHIPPING INFORMATION: Sodium Aluminum Phosphate. Packaged in 100-lb. bags.

NON-NUTRITIVE SWEETENERS**SACCHARIN (CALCIUM AND SODIUM) U.S.P.**

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 183.18

STANDARD FORM: Powder, coarse powder and granular.

SPECIFICATIONS: White crystalline powder; assay 98% min.; M.P. 227.0°C. min. to start; moisture 0.5% max.; retained on 80 mesh, 0.4% max.

GRADES: All U.S.P.

USES: Used as a non-nutritive sweetener for all low calorie foods and beverages, and for toothpastes, mouthwashes and pharmaceutical preparations and tobacco products.

SHIPPING INFORMATION: Chemicals NOIBN. 100-lb. drums.

DIETOSE® CALCIUM CYCLAMATE U.S.P.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 432.58

STANDARD FORM: Fine white crystalline powder.

SPECIFICATIONS: Fine white crystalline powder; water not less than 6% nor more than 9%; heavy metals not more than 20 ppm; purity 98.0% min.; 100.5% max.; dry basis $\text{CaH}_2\text{N}_2\text{O}_6 \cdot \text{H}_2\text{O}$; Solubility in water 1 gm. per 4 ml.

USES: Used as a non-nutritive sweetener for all low-calorie foods and beverages and for pharmaceuticals, toothpaste, mouthwashes and tobacco products.

SHIPPING INFORMATION: Chemicals NOIBN. 100-lb. drums.

DIETOSE® SODIUM CYCLAMATE N.F.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 201.23

STANDARD FORM: Fine white crystalline powder.

SPECIFICATIONS: Fine white crystalline powder; loss on drying not more than 1%; heavy metals not more than 20 ppm; purity 98.0% min.; 101% max. dry basis $\text{C}_6\text{H}_{11}\text{N}_2\text{O}_6\text{S}$; solubility in water 1 gm. per 5 ml.

USES: Used as a non-nutritive sweetener for all low-calorie foods and beverages and for pharmaceuticals, toothpaste, mouthwashes and tobacco products.

SHIPPING INFORMATION: Chemicals NOIBN. 100-lb. drums.

PRESERVATIVES**BENZOIC ACID, U.S.P. AND TECHNICAL**

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 122.12

STANDARD FORM: Fine powder, flakes or crystalline needles.

SPECIFICATIONS: U.S.P. Grade: White crystalline needles or fine powder; assay 99.5% min.; solution in alcohol (1:2.5) and in 10% sodium carbonate (1:8) clear and colorless; meets U.S.P. test for carbonizable impurities; 2% max. powder retained on 60 mesh. Technical Grade: White to yellow-white flakes or powder; assay 99.0% min.; solution in 10% Na_2CO_3 (1:8) complete. Crystallizing point: 121.5°C. min.

GRADES: U.S.P. and Technical.

USES: U.S.P. grade used in medicinal preparations; preservative in foodstuffs.

Technical grade used in the manufacture of benzoates and benzoyl compounds; intermediate in the manufacture of dyes, etc.

SHIPPING INFORMATION: U.S.P.—100-lb. fiber drums. Technical Grade—200-lb. fiber drums and 50-lb. bags. U.S.P. Grade: Food Preserving Compound NOIBN. Technical Grade: Dye Intermediate NOIBN.

SODIUM BENZOATE, U.S.P. AND TECHNICAL

ORGANIC DIVISION—LITERATURE AVAILABLE
MOLECULAR WEIGHT: 144.11

STANDARD FORM: Powder.

SPECIFICATIONS: U.S.P. Grade: Thin white flakes or white powder; solubility in water (10:100 at 25°C.) complete; solubility in 90% ethyl alcohol (1:50 at 25°C.) complete; 0.30 ml. 10% N/10 NaOH to 0.20 ml N/10 HCl per 2.0 grams; moisture 0.50% max.; assay 99.5% min.; chlorides (as NaCl) 0.10% max.

Technical Grade: White or slightly tinted powder; assay 99.0% min. (dry basis); solution in water (10:10) essentially complete but slightly inferior to U.S.P. quality; heavy metals 20 ppm; moisture 0.5%.

GRADES: U.S.P. and Technical.

USES: U.S.P. Grade: For preserving foods, tobacco and medicinal preparations.

Technical Grades: As an industrial preservative and rust inhibitor.

SHIPPING INFORMATION: Sodium Benzoate, 100-lb., 50-lb. and 25-lb. fiber drums.

SODIUM BISULFITE ANHYDROUS

See Page M5/17

**BUFFERING AGENTS/COAGULANTS/DISPERSING AGENTS/
EMULSIFIERS/PROTEIN INTERACTANTS/SEQUESTANTS/
NUTRITION SUPPLEMENTS**

ADIPIC ACID, FOOD AND TECHNICAL GRADES

See Page M5/13

BENZOIC ACID, U.S.P. AND TECHNICAL

See Page M5/14

DICALCIUM PHOSPHATE, ANHYDROUS AND DIHYDRATE

See Page M5/25

DISODIUM PHOSPHATE, DIHYDRATE

See Page M5/26

FUMARIC ACID, FOOD AND TECHNICAL GRADES

See Page M5/13

H. T. MONOCALCIUM PHOSPHATE, MONOHYDRATE

See Page M5/14

MONOSODIUM PHOSPHATE

See Pages M5/7 and 26

PHOSPHORIC ACID (75, 80 and 85%)

See Page M5/25

SODIUM ACID PYROPHOSPHATE

See Page M5/14

SODIUM HEXAMETAPHOSPHATE

See Page M5/26

SODIUM TRIPOLYPHOSPHATE

See Page M5/26

TETRASODIUM PYROPHOSPHATE

See Page M5/27

TRICALCIUM PHOSPHATE

See Page M5/25

TRISODIUM PHOSPHATE, CRYSTALLINE

See Page M5/27

FUNCTIONAL FLUIDS: AIRBORNE, INDUSTRIAL, SPECIALTY

AIRBORNE AND SPECIALTY

COOLANOL 45[®] DIELECTRIC COOLANT FOR ELECTRONIC EQUIPMENT

See Page M5/12

OS-45[®] TYPE III HIGH TEMPERATURE AIRCRAFT HYDRAULIC FLUID.

See Page M5/12

OS-45[®] TYPE IV HIGH TEMPERATURE AIRCRAFT HYDRAULIC FLUID.

See Page M5/12

SKYDROL[®] 500-A FIRE RESISTANT JET AIRCRAFT HYDRAULIC FLUID

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Moisture, 20% max.; neutralization number 0.10 max.; Sp. Gr. 25°/25°C. 1.060-1.068; viscosity at 100°F. 11.7±0.4 cs.

PROPERTIES: A clear, purple, fire-resistant hydraulic fluid with excellent lubricity. Operational at -65°F.

USES: Hydraulic fluid for hydraulic systems in turbo jet and turbo prop aircraft, which must be operational at -65°F.

SHIPPING INFORMATION: Hydraulic system fluids other than petroleum. 1-qt. cans; 1-gal. cans; 5-gal. cans; 54-gal. drums.

SKYDROL[®] 7000 FIRE RESISTANT AIRCRAFT HYDRAULIC FLUID

ORGANIC DIVISION—LITERATURE AVAILABLE

TYPICAL ANALYSIS: Cloud point below 0°F.; moisture 0.25% max.; neutralization number 0.2 max.; Sp. Gr. 1.060 to 1.068 at 25°/25°C.; pour point -70°F. or lower.

PROPERTIES: A clear, green fire-resistant hydraulic fluid with outstanding lubricity, stability, non-corrosiveness, excellent viscosity-temperature characteristics, and resistance to oxidation.

USES: Hydraulic fluid in aircraft cabin superchargers, expansion turbines for air-conditioning systems and the aircraft hydraulic system itself.

SHIPPING INFORMATION: Hydraulic system fluids other than petroleum. 1-qt. cans; 1-gal. cans; 5-gal. cans; 54-gal. drums.

INDUSTRIAL

PYDRAUL[®] AC COMPRESSOR LUBRICANT

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

(Continued on next page)

TYPICAL ANALYSIS: Viscosity at 100°F.—405 SSU, 210°F.—42 SSU; moisture—0.16% max.; neutralization number (acid)—0.16 max.; sp. gr. at 25°/25°C.—1.340-1.360.

PROPERTIES: A clear blue, mobile straight synthetic fire resistant air compressor lubricant with excellent lubricity.

USES: A fire and explosion resistant lubricant for air compressors, such as those used in air separation plants, plant air systems, ammonia synthesis plants, gas transmission booster stations and other type processing plants.

SHIPPING INFORMATION: Chemicals NOIBN. 54-gal. steel drums; 5-gal. cans.

PYDRAUL® F-9 HYDRAULIC FLUID

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Viscosity at 100°F.—345 SSU, 210°F.—45 SSU; moisture—0.20% max.; neutralization number (acid)—0.30 max.; sp. gr. at 25°/25°C.—1.270-1.300.

PROPERTIES: A cloudy blue liquid; straight synthetic fire resistant fluid with excellent lubricity and pumping characteristics; non-corrosive, extremely stable to both heat and air; recoverable by filtration; designed for long service life.

USES: Fire resistant hydraulic fluid in die-casting machines, hydraulic presses, automatic welding machines and similar applications requiring a medium viscosity fluid.

SHIPPING INFORMATION: Hydraulic system fluids other than petroleum. 55-gal. steel drums and 5-gal. cans.

PYDRAUL® 60 HYDRAULIC FLUID

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Viscosity at 100°F.—60 SSU, 210°F.—34 SSU; moisture—0.10% max.; neutralization number (acid)—0.25 max.; sp. gr. at 25°/25°C.—1.088-1.091.

PROPERTIES: A cloudy blue liquid, straight synthetic fire resistant hydraulic fluid with excellent lubricating and pumping characteristics.

USES: A fire resistant hydraulic fluid in systems requiring extremely low viscosity.

SHIPPING INFORMATION: Hydraulic system fluids other than petroleum. 54-gal. steel drums and 5-gal. cans.

PYDRAUL® 150 HYDRAULIC FLUID

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Viscosity at 100°F.—150 SSU, 210°F.—50 SSU; moisture—0.15% max.; neutralization number (acid)—0.17 max.; sp. gr. at 25°/25°C.—1.119-1.136.

PROPERTIES: A cloudy blue liquid, straight synthetic fire resistant hydraulic fluid of low viscosity with excellent lubricity and low temperature pumping characteristics.

USES: Fire resistant hydraulic fluid in equipment which operates out of doors at low temperatures part of all of the time, such as Aklanta Regulator Equipment, fork-lift trucks and similar equipment with cold weather fluid requirements.

SHIPPING INFORMATION: Hydraulic system fluids other than petroleum. 54-gal. steel drums; 5-gal. cans.

PYDRAUL® 625 HYDRAULIC FLUID

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Viscosity at 100°F.—625 SSU, 210°F.—45 SSU; moisture—0.15% max.; neutralization number (acid)—0.30 max.; sp. gr. at 25°/25°C.—1.340-1.370.

PROPERTIES: A cloudy blue liquid, straight synthetic fire resistant hydraulic fluid of high viscosity with excellent lubricity and pumping characteristics.

USES: A fire resistant hydraulic fluid in equipment requiring a high viscosity medium, such as large forging presses, extrusion presses and some die-casting machines.

SHIPPING INFORMATION: Hydraulic system fluids other than petroleum. 54-gal. steel drums; 5-gal. cans.

PYDRAUL® A-200 HYDRAULIC FLUID

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Viscosity at 100°F.—230 SSU, 210°F.—41.9 SSU; moisture—0.05% max.; neutralization number (acid)—0.60-1.10 max.; sp. gr. at 25°/25°C.—1.418-1.430.

*Monsanto Trademark

PROPERTIES: A cloudy blue liquid, straight synthetic, fire-resistant hydraulic fluid with excellent lubricity; non-corrosive, extremely stable to both heat and air; is designed to be permanent; fluid spilled and leaked can be easily reclaimed by filtration; does not thicken with use; resists "breakdown" even under extreme conditions; passes ASTM D-965-A rust test with perfect score; A-200 is shear stable and undergoes no loss of viscosity after years of severe use.

USES: Fire resistant hydraulic fluid in die-casting machines, hydraulic presses, automatic welding machines and similar applications requiring a medium viscosity fluid.

SHIPPING INFORMATION: Hydraulic system fluids other than petroleum. 54-gal. steel drums; 5-gal. cans.

THERMINOL® FR — HEAT TRANSFER LIQUIDS

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: Clear, colorless liquids with high boiling points above 800°F.; thermally and oxidatively stable to 800°F. and extremely fire resistant.

USES: Therminol FR liquids are fire resistant heat transfer media produced to rigid specifications important to heat transfer.

There are three Therminol FR products: Therminol FR-1 with low temperature fluidity; excellent for processes requiring both heating and cooling; Therminol FR-2 with the optimum balance of properties for use in most common industrial heat transfer systems; Therminol FR-3 with the highest boiling point for special processing equipment applications.

SANTOWAX® OMP — ORGANIC NUCLEAR REACTOR COOLANT

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Solid

PROPERTIES: A high boiling thermal and radiation resistant heat transfer medium.

USES: Organic nuclear reactor coolant and high temperature industrial heat transfer medium.

HEAVY CHEMICALS

ALUMINUM CHLORIDE SOLUTION 32° B_é.

INORGANIC DIVISION

MOLECULAR WEIGHT: 266.7

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Neutral salt, low in iron content; solutions have an acid reaction but contain no free acid. AlCl₃-6H₂O, 50.3%; Al₂O₃, 10.6%; Fe, 0.005%.

USES: Carbonizing fine wool such as piece goods, raw stock or shoddy, resulting in an exceptionally white, lofty wool; carbonizing colored goods where it has very little stripping action; soap manufacture for treatment of dyestuffs; uses where chloride of alumina is more desirable than sulfate.

SHIPPING INFORMATION: Aluminum Chloride Liquid. Tank cars; tank trucks.

ALUMINUM SULFATE

See Page M5/51

BATTERY ACID

Electrolyte.

INORGANIC DIVISION

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Practically colorless liquid; H₂SO₄, 93.2% min.; iron 0.005% max.; nitrogen compounds (as HNO₃) 0.001% max.; Sp. Gr., 1.158.

USES: Electrolyte is sulfuric acid, especially adapted to the needs of the storage battery trade.

SHIPPING INFORMATION: Sulfuric Acid. "Corrosive" label required. Tank trucks and tank cars.

CARBON DIOXIDE

INORGANIC DIVISION

FORMULA: CO₂

MOLECULAR WEIGHT: 44.0

PROPERTIES: Marketed in liquid form which is colorless and odorless.

USES: As inert gas atmosphere, for fire extinguishers, in carbonated beverages, and for carbon dioxide blasting.

SHIPPING INFORMATION: Carbon Dioxide. Steel cylinders and tank cars.

CAUSTIC POTASH**INORGANIC DIVISION**

FORMULA: KOH

MOLECULAR WEIGHT: 56.1

STANDARD FORM: 45% Solution.

GRADES: Available as both technical grade and low chloride grade.

USES: Due to the greater solubility of the salts of Caustic Potash permitting higher solids content in liquid formulations. Caustic Potash has use in formulating liquid soaps and detergents. In the manufacture of many Organic and Inorganic Potassium salts, petroleum redings, and in detergents.

SHIPPING INFORMATION: 10,000, 8,000 and 4,000 gal. lined and coiled tank cars. Tanktrucks also available.

MIXED ACID Nitrolic Acid**INORGANIC DIVISION**

STANDARD FORM: Liquid.

TYPICAL ANALYSIS:

	80-15	45-53
Nitric Acid (HNO ₃)	80.0 %	45.0 %
Sulfuric Acid (H ₂ SO ₄)	15.0 %	53.0 %
Oxides of Nitrogen (NO ₂)	0.25 %	0.25 %

USES: Nitrating in the chemical industry, particularly in the manufacture of explosives and dyestuffs. Special mixtures can be formulated to meet individual requirements.

SHIPPING INFORMATION: Nitrating Acid, Corrosive Liquid (white label required). 110-gal. drums; 75 and 50-ton tank cars.

MURIATIC ACID Hydrochloric Acid**INORGANIC DIVISION—LITERATURE AVAILABLE**

FORMULA: HCl

MOLECULAR WEIGHT: 36.47

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: 18° Be., 27.9% HCl; 20° Be., 31.5% HCl; 22° Be., 35.2% HCl.

USES: Used extensively in the starch, glucose, gelatin, steel galvanizing, paper, leather and glass industries.

HYDROCHLORIC ACID PLANTS. Complete plants offered by Engineering Sales Department to electrolyze by-product HCl and produce pure chlorine and hydrogen.

NITRIC ACID**INORGANIC DIVISION—LITERATURE AVAILABLE**FORMULA: HNO₃

MOLECULAR WEIGHT: 63.01

STANDARD FORM: 36° Be., 38° Be., 40° Be., and 42° Be.

TYPICAL ANALYSIS: % HNO₃: 36° Be., 52.3%; 38° Be., 56.5%; 40° Be., 61.4%; 42° Be., 67.2%; Strong acid 68-69%, sp. Gr. will not vary more than .05° terms of Be. H₂SO₄ 0.05% max.

USES: Manufacture of insecticides, dyestuffs, drugs, pharmaceuticals, explosives, photoregraving, nitrates and nitro products.

SHIPPING INFORMATION: Nitric Acid, Corrosive Liquid (white label required). Tank trucks; 50-ton tank cars.

SLAG, CALCIUM SILICATE**INORGANIC DIVISION**

STANDARD FORM: Granular solid.

PROPERTIES: CaO, 47.18%; SiO₂, 40.44%; Al₂O₃, 7.62%; Fe₂O₃, 0.20%; F, 2.82%; P, 0.56%; K₂O, 0.97%; Na₂O, 0.44%; MgO, 0.02%; Mn, 0.13%; SO₂, 0.56%; C, 0.10%.

USES: Constituent of glass mix.

SHIPPING INFORMATION: Slag, Bulk.

SODIUM BISULFITE ANHYDROUS

Also known as Sodium Metabisulfite.

ORGANIC DIVISION—LITERATURE AVAILABLEFORMULA: Na₂SO₃

MOLECULAR WEIGHT: 190.11

STANDARD FORM: Faint yellow, free-flowing crystals.

TYPICAL ANALYSIS: SO₂-68.6%; Na₂SO₃-0.7%; Na₂SO₄-1.25%.

GRADES: Meets purity limits for Sodium Bisulfite USP.

USES: In dye manufacture; as source of SO₂ for reducing sodium dichromate to basic chrome sulfate in tanning; bleaching of vegetable tan extracts; production of hydro-sulfite for vat dyeing; antichlor in bleaching round wood; etc.

SHIPPING INFORMATION: Sodium Bisulfite—dry.

SODIUM BISULFATE NITRE CAKE**INORGANIC DIVISION**FORMULA: NaHSO₄

MOLECULAR WEIGHT: 120.07

STANDARD FORM: Globular.

TYPICAL ANALYSIS: 38% available H₂SO₄.

USES: Used in viscose rayon spinning baths, dyeing woolen goods; refining nickel ores; manufacture of sulfate pulp; in tanneries for pickling, deliming and making one-bath tan solutions; as an acid scour for household use; as a bowl cleaner in sanitary trade.

SHIPPING INFORMATION: Nitre Cake. 100-lb. bags and 400-lb. drums.

SODIUM CHLORIDE (Rock Salt)**INORGANIC DIVISION—CONTACT PRODUCT PLANNING DEPT.**

FORMULA: NaCl

STANDARD FORM: Mine Run or Screen Grades.

CHEMICAL PURITY: 98.5 to 99.1% NaCl depending upon grade.

SHIPPING INFORMATION: Normal shipment — Barge loads: 1400 tons each. Rail shipment at various transfer points.

PRODUCING POINT: Cote Blanch Island, La. 131 miles west of New Orleans on Intercoastal Waterway.

SANTOSITE® SODIUM SULFITE ANHYDROUS TECHNICAL**ORGANIC DIVISION—LITERATURE AVAILABLE**FORMULA: Na₂SO₃

MOLECULAR WEIGHT: 126.06

STANDARD FORM: Powder.

TYPICAL ANALYSIS: Tan to slightly pink crystalline powder; assay (Na₂SO₃) 97.7% min.; color of filtrate from 10% solution in water not darker than APHA 70.

PROPERTIES: Will oxidize to sodium sulfate if not kept dry. Normally contains less than 1% sodium chloride; less than 0.1% iron; less than 0.2% insoluble; less than 0.2% organic matter. The balance of impurity is sodium sulfate. The untreated water solution has a brown color due to suspended Fe (OH)₃. Normally all of the product will pass through a No. 20 U. S. Standard sieve.

USES: As a reducing agent in oxygen removal from boiler feed water; depressant in ore flotation; manufacture of rubber and cordage.

SHIPPING INFORMATION: Sodium Sulfite. 100-lb. paper bags and hopper cars.

SULFUR DIOXIDE, LIQUID**INORGANIC DIVISION—LITERATURE AVAILABLE**FORMULA: SO₂

MOLECULAR WEIGHT: 64.07

STANDARD FORM: Liquid.

SPECIFICATIONS: Colorless; non-volatile residue 0.0025% max.; moisture 0.005% max.

USES: In leather tanning, oil refining, refrigeration, air conditioning, sugar refineries; antichlor in textiles; hydrosulfite in textiles; diluent in manufacture of sulfuric acids; manufacture of sulfuryl chloride; fruit preservation; wine making; manufacture of gelatin and corn products.

SHIPPING INFORMATION: Sulfur Dioxide. Tank cars and 1-ton containers.

SULFURIC ACID AND OLEUM**INORGANIC DIVISION—LITERATURE AVAILABLE**FORMULA: H₂SO₄

MOLECULAR WEIGHT: 98.08

STANDARD FORM: 60° Be., 66° Be., 98% H₂SO₄; all strengths oleum.

SULFURIC ACID PLANTS. Complete manufacturing plants using the contact process and Monsanto Vanadium Catalyst offered by Engineering Sales Department.

USES: Used extensively in steel mills, enameling works, oil refineries, pigment works, by-product gas plants, fertilizer plants, tanneries and many other industries.

SHIPPING INFORMATION: Sulfuric Acid. Tank trucks; tank cars.

NUCLEAR SOURCES

Radioactive Sources

Alpha from Am. Po. Pu
Beta from available isotopes
Gamma from available isotopes
Calibration from available isotopes
Bremsstrahlung from available isotopes
Heat from available isotopes

Threshold Detectors from Pu, Np, U

X-Ray Units

Special Projects and Development

For information, please write or call:

J. L. Richmond or H. A. Malson
MONSANTO RESEARCH CORPORATION
Station B, Box 8
Dayton, Ohio 45407
Phone: (513) 298-5481

ORGANIC CHEMICALS

ACIDS AND ANHYDRIDES (CARBOXYLIC)

ADIPIC ACID, FOOD AND TECHNICAL GRADES

See Page M5/13

BENZOIC ACID, U.S.P. AND TECHNICAL

See Page M5/14

FUMARIC ACID, FOOD AND TECHNICAL GRADES

See Page M5/13

H ACID 8-Amino-1-Naphthol-3, 6-Dialanine Acid, Sodium Salt

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 341.29

STANDARD FORM: Powder.

TAR SPECIFICATIONS: Tan solid: 88% monosodium salt.

USES: As a principal intermediate in the manufacture of dyestuffs such as fast reds, violet azos and blue azo dyes.

SHIPPING INFORMATION: Dye intermediate NOIBN. 200-lb. fiber drums.

MALEIC ANHYDRIDE

ORGANIC DIVISION

MOLECULAR WEIGHT: 98.06

STANDARD FORM: Briquettes, fused mass.

SPECIFICATIONS: White briquettes or fused mass, crystallizing point (as produced) 52.5°C. min.; water solution (4 gms. in 10 ml): clear and colorless; assay 98.5% min., color of melt 20 APHA max. Heat test color (2 hrs. @ 140°C.) 40 APHA max.

USES: Used alone or in combination with other acids in the manufacture of alkyd and polyester resins; a versatile intermediate for chemical synthesis.

SHIPPING INFORMATION: Maleic Anhydrides 50-lb. bags; 250-lb. fiber drums; tank cars, tank trucks.

MODAFLOW®

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Very viscous clear liquid free of solids.

GENERAL INFORMATION: Soluble in toluene, kerosene, petroleum ether, carbon tetrachloride, ethyl acetate, higher alcohols. Insoluble in water, ethanol and methanol.

USES: An additive for improving flow, leveling and adhesion properties of surface coating formulations — especially enamels, vinyls, epoxies and polyesters. Uses at 0.1–2.0% based on resin solids.

SHIPPING INFORMATION: Chemicals NOIBN. 55-gal. non-returnable drums, 20-gal. drums and 5-gal. cans.

PHTHALIC ANHYDRIDE

See Page M5/36

SALICYLIC ACID U.S.P.

ORGANIC DIVISION

MOLECULAR WEIGHT: 138.12

STANDARD FORM: Needles or powder.

SPECIFICATIONS: U.S.P. Grade: White needles or powder; assay 99.5% min.; M.P. 158.0°C. min.; conforms to U.S.P. test for carbonizable substances; ash 0.05% max.; powder 0.4% max. retained on 100 mesh. Industrial Grade: Light tan powder; M.P. 158.0°C. at start.

GRADES: U.S.P. and industrial.

USES: Manufacture of medicinals and dyestuffs; industrial preservative; intermediate in many organic syntheses.

SHIPPING INFORMATION: Salicylic Acid, 200-lb. and 100-lb. fiber drums. Industrial Grade, 250-lb. fiber drums.

5-SULFOSALICYLIC ACID (Technical)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 218

STANDARD FORM: Tan crystalline solid.

ASSAY: 95% 5-sulfosalicylic acid (min.).

USES: Metal ion chelator, dye intermediate, preparation of surfactants, catalysts and grease additives.

CONTAINERS: 200-lb. net polyethylene lined fiber drums.

SHIPPING CLASSIFICATION: Acid NOIBN Dry.

TPSA® Monsanto's Brand of TETRAPROPENYLSUCCINIC ANHYDRIDE

(Dodecenylnsuccinic Anhydride)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 268

STANDARD FORM: Liquid.

GENERAL INFORMATION: The dodecenyln substituent is present in a number of isomeric forms.

SPECIFICATIONS: Appearance: clear light yellow, viscous liquid; Liquid color: 400 APHA max.; Neutral Number: 395–432 mg. KOH/g. refractive index @ 25°C. 1.4740–1.4780.

USES: Corrosion inhibitor, epoxy curing agent, intermediate.

CONTAINERS: 450-lb. net 55-gal. drums; bulk.

SHIPPING CLASSIFICATION: Chemicals, NOIBN.

AMINES

ortho-ANISIDINE

ORGANIC DIVISION

MOLECULAR WEIGHT: 123.15

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance: reddish brown to amber liquid; Crystallizing Point 5.3°C. min. (with low seeds); Distilling Range: first drop 223.0°C. minimum, 95% (1–90) within 1.5°C. and to include 224.5°C. (decomposes at 226.0°C.)

USES: A component of azo dyes.

CONTAINERS: 55-gallon, 18-gauge drums.

SHIPPING CLASSIFICATION: Poisonous Liquid NOS (Dye Intermediate NOIBN).

para-ANISIDINE

Also known as para-methoxy-aniline and para-aminomethoxy

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 123.15

STANDARD FORM: Cast solid or flakes.

SPECIFICATIONS: Brownish crystalline mass or flakes when produced, darkens on aging; crystallizing point 57.2°C. min.; distillation range: first drop 241.0°C. min., 95% 1.0°C. max.; to include 242.0 at 0.2°C. Solution in HCl complete.

USES: A component of various azo dyestuffs; intermediate in chemical synthesis. CAUTION: This product is toxic. Avoid breathing its vapors. Avoid contact with the skin.

SHIPPING INFORMATION: Dye Intermediate NOIBN "Poison" label required. 475-lb. galv. steel drums, 150-lb. fiber drum.

tertiary-BUTYLAMINE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 73.14

STANDARD FORM: Volatile liquid.

ASSAY: 98% minimum.

USES: Intermediate.

CONTAINER: 300-lb. net 55-gal. drums; bulk.

SHIPPING CLASSIFICATION: Flammable liquid NOS (t-butylamine-Chemicals NOIBN).

ortho-CHLOROANILINEAlso known as *ortho-amino-chlorobenzene* and *2-chloroamino-benzene*

ORGANIC DIVISION

MOLECULAR WEIGHT: 127.07

STANDARD FORM: Liquid.

SPECIFICATIONS: Amber liquid that discolors readily in air; assay 99.0% min.; crystallizing point -2.3°C . min. Distillation range: first drop 58.0°C . min.; 95% (1-96 ml) 1.0°C . max.; to incl. 209.0°C .

USES: An intermediate in the production of dyestuffs and insecticides. **CAUTION:** This product is toxic. Avoid breathing its vapor and skin contact.

SHIPPING INFORMATION: Dye intermediate NOIBN "Poison" label required. 550-lb. steel drums.

para-CHLOROANILINEAlso known as *para-amino-chlorobenzene* and *4-chloro-amino-benzene*

ORGANIC DIVISION

MOLECULAR WEIGHT: 127.07

STANDARD FORM: Cast solid, flakes.

SPECIFICATIONS: Yellow-white solid; crystallizing point 49.5°C . min. Assay 99% min.; Distillation range: first drop 230.0°C . min.; 95% (1-96 ml) 1.5°C . max.; incl. $231.7^{\circ} \pm 0.2^{\circ}\text{C}$.

USES: Dyestuffs intermediate. **CAUTION:** This product is toxic. Avoid breathing its vapor and skin contact.

SHIPPING INFORMATION: Dye Intermediate NOIBN "Poison" label required. 500-lb. steel drums.

CYCLOHEXYLAMINE Also known as *hexahydroaniline*

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 99.17

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, practically colorless liquid; Sp. Gr. $0.899-0.873$ at $15.5^{\circ}/15.5^{\circ}\text{C}$. Distillation range: first drop 132.0°C . min.; 95% (1-96 ml) 4.0°C . max.; dry point 137.0°C . max.

USES: Dyestuff intermediate; petroleum additive; corrosion inhibitor in boiler systems; petroleum oils, greases, glycol and methanol antifreezes; organic synthesis; synthetic sweeteners.

SHIPPING INFORMATION: Chemical NOIBN. 385-lb. calv. drums. bulk.

3,4-DICHLOROANILINE (3,4-DCA)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 182

STANDARD FORM: Cast solid.

SPECIFICATIONS: Appearance, white to tan solid, darkens with age; Crystallizing Point, 70.5° min.; assay 99.0% min.

USES: Intermediate in synthesis of biologically active compounds; dye intermediate.

CONTAINERS: 900-lbs. net—55 gal. drums.

SHIPPING CLASSIFICATION: Poisonous solid (NOS)—Dye Intermediate, NOIBN.

DICYCLOHEXYLAMINE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 181.31

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, practically colorless liquid; Sp. Gr. $0.913-0.919$ at $15.5^{\circ}/15.5^{\circ}\text{C}$. Distillation range: first drop 252.0°C . min.; 95% (1-96 ml) 4.0°C . max.; dry point 258.0°C . max.

USES: As a corrosion inhibitor (see Cyclohexylamine) and in production of dicyclohexyl ammonium nitrate (used as a vapor-phase rust inhibitor, Shell Oil Company patent), rust-preventative oil additives, dyes and dry-cleaning soaps.

SHIPPING INFORMATION: Chemical NOIBN. 410-lb. steel drums.

DODECYLANILINE (Formerly Alkylaniline C-12)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

GENERAL INFORMATION: Dark reddish brown liquid, darkens on age. Infra red analysis shows 90-95% of the alkyl substitution is in the para position; the dodecyl substituent is present in a number of isomeric forms.

USES: Corrosion inhibitor, intermediate for synthesis of hydrocarbon soluble chemicals.

CONTAINERS: 375-lbs. net—55-gal. drums—bulk.

SHIPPING CLASSIFICATION: Chemicals NOIBN.

ortho-NITROANILINE Also known as *ortho-aminonitro-benzene*

ORGANIC DIVISION

MOLECULAR WEIGHT: 138.12

STANDARD FORM: Flakes.

SPECIFICATIONS: Orange flakes; crystallizing point 69.7°C . min.

PROPERTIES: Tends to form lumps on standing. Milling to desired fineness just before use is recommended. Addition of 0.5% tricalcium phosphate reduces the caking tendency.

USES: Manufacture of lakes and toners (dyes) such as ONA Black, ONA Orange and Hansa Yellow 5G; synthesis of co-catalysts, photographic anti-fogging agents and benzotriazoles (a rust inhibitor patented by Proctor and Gamble).

CAUTION: This product is toxic. Avoid breathing its dust and skin contact.

SHIPPING INFORMATION: Dye Intermediate NOIBN "Poison" label required. 175-lb. fiber drums.

para-NITROANILINE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 138.12

SPECIFICATIONS: Appearance, yellow to amber crystals; Ash 0.2% max.; Color of HCl solution, NPA, No. 4 max.; Inorganic Chlorides, as Cl, 0.020% max.; Melting Point 147.9°C . min.

USES: Manufacture of anti-oxidants, anti-ozonants, gasoline gum inhibitors; medical compounds for poultry, dyestuffs, color and pigments.

CONTAINERS: 350-lb. fiber drums.

SHIPPING CLASSIFICATION: para-Nitroaniline (Dye Intermediate NOIBN).

ortho-PHENETIDINEAlso known as *ortho-amino-phenylethyl ether*, *ortho-aminophenetole* and *2-amino-ethoxybenzene*.

ORGANIC DIVISION

MOLECULAR WEIGHT: 137.18

STANDARD FORM: Liquid.

SPECIFICATIONS: Dark red liquid; crystallizing point -4.0°C . min. Distillation range: first drop 231.0°C . min.; 95% (1-96 ml) 2.0°C . max.; and to incl. $232.3^{\circ} \pm 0.2^{\circ}\text{C}$.

USES: An intermediate in the production of dyestuffs, **CAUTION:** This product is toxic. Avoid breathing its vapors and contact with skin.

SHIPPING INFORMATION: Dye Intermediate NOIBN. "Poison" label required. 475-lb. steel drums.

para-PHENETIDINEAlso known as *para-amino-phenylethyl ether*, *para-aminophenetole* and *4-amino-ethoxybenzene*.

ORGANIC DIVISION

MOLECULAR WEIGHT: 137.18

STANDARD FORM: Liquid.

SPECIFICATIONS: Light yellow liquid; crystallizing point 4.2°C . min.; distillation range: first drop 248.3°C . min.; 95% (1-96 ml) 2.0°C . max.; and to incl. $250.0^{\circ} \pm 0.2^{\circ}\text{C}$.

USES: An intermediate in the production of dyestuffs and pharmaceuticals. **CAUTION:** This product is toxic. Avoid breathing its vapors and avoid contact with the skin.

SHIPPING INFORMATION: Dye Intermediate NOIBN. "Poison" label required. 480-lb. steel drums.

FLAVORINGS**CAFFEINE ANHYDROUS U.S.P.**

See Page M5/12

ETHAVAN® Ethylaniline.

See Page M5/13

METHYL SALICYLATE U.S.P.

See Page M5/13

SACCHARIN (CALCIUM AND SODIUM) U.S.P.

See Page M5/14

VANILLIN MONSANTO U.S.P.

See Page M5/14

HALOGEN-CONTAINING COMPOUNDS (MISC.)

ACL®

See Page M5/54

AROCOR® POLYCHLORINATED POLYPHENYLS

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquids, resins or solids.

PROPERTIES: Chlorinated aromatic hydrocarbons varying from water-white mobile liquids and pale yellow viscous oils to light amber resins and opaque crystalline solids.

GENERAL INFORMATION: Aroclor liquids have excellent electrical characteristics, high dielectric strength and resistivity, low power factor; certain of the liquids have a high dielectric constant as compared with mineral oils.

USES: Aroclor liquids are used as dielectrics for condensers or capacitors and transformers. They are used to impregnate carbon resistors, and when combined with other plastic materials, they are excellent sealers or impregnating agents for a variety of electrical apparatus. Aroclor compounds also find use as liquid thermostat fluids; vacuum diffusion pump fluids; swelling agents for automotive transmission seals; and, as additives and base stocks for specialty lubricants, oil and greases.

SHIPPING INFORMATION: Resin Synthetic NOIBN without filler, 600-lb. steel drums; 500-lb. net fiber drums; 100-lb. net bags.

BENZYL CHLORIDE Also known as alpha-chlorotoluene.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 126.58

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, colorless liquid; Sp. Gr. 1.104-1.110 at 15.5°/15.5°C. Boiling range at 760 mm 2°C. max. including 179.4°C.

USES: A highly reactive aralkyl halide used in the production of the following: dyestuffs; perfume bases such as benzyl alcohol, acetate and other esters; plasticizers; resins; wetting agents; germicides; rubber accelerators; gasoline gum inhibitors; benzyl benzoate; and pharmaceuticals.

SHIPPING INFORMATION: Chemicals NOIBN. Corrosive liquid (white label required), 475-lb. nickel drums; 2000-gal. 2-compartment nickel tank trucks.

BENZYL CHLORIDE, inhibited with 0.25% triethylamine

ORGANIC DIVISION—LITERATURE AVAILABLE

SPECIFICATIONS: Same as for preceding product.

CONTAINERS: 475-lb. lacquer-lined drums.

CHLORAMINE-T

See Page M5/49

ortho-DICHLOROBENZENE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 147.01

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, practically clear; Color, 30 APHA max.; Crystallizing Point, 27.5°C. max.; Boiling Range—first drop 177.7°C. min.—90% (1-91 mil.) 4.1°C. max.—dry point 198.6°C. max.

USES: Degrading formulations; tar, grease, paint and carbon removers; spotting agents in dry cleaning; metal pollishes; wool and felt scouring; insecticide formulations; and treating of sewage and garbage for odor control.

SHIPPING INFORMATION: Chemicals NOIBN. Dichlorobenzol. 55-gal., 18-gauge black iron drums, bulk.

GUAIACOL

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 124.13

STANDARD FORM: Light yellow liquid.

SPECIFICATIONS: Crystallizing Point 27.5°C. min.

USES: Chemical intermediate in the manufacture of flavors, perfumes and pharmaceuticals. Also used as an "anti-skinning" agent for paints and as an inhibitor in certain petroleum specialties.

SHIPPING INFORMATION: Chemicals NOIBN. 500-lb. drums.

ortho-NITROCHLOROBENZENE

Also known as ortho-chloronitrobenzene.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 157.56

STANDARD FORM: Cast solid.

SPECIFICATIONS: Green-yellow crystalline mass; crystallizing point 31.8°C. min. (dry basis).

USES: An intermediate in the synthesis of o-aminophenol (dyestuffs intermediate and photographic developer), o-chlorobenzidine (chroma-dyestuffs intermediate), and many other organic intermediate chemicals; and a solvent in synthetic-petroleum processes. CAUTION: This material is toxic. Avoid breathing its vapors. Avoid contact with the skin. Toxicity reference: U. S. Public Health Bulletin No. 271 (1941).

SHIPPING INFORMATION: Dye Intermediate NOIBN "Poison" label required. 600-lb. steel drums; tank cars.

para-NITROCHLOROBENZENE

Also known as para-chloronitrobenzene.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 157.56

STANDARD FORM: Flakes.

SPECIFICATIONS: Appearance light yellow flakes or crystalline mass; crystallizing point 92.8°C. min.

USES: In the manufacture of disodium-benzene-meta-disulfonate; para-aminophenol; 2-chloro-5-nitrobenzene sulfonic acid; 2,6-dichloro-4-nitrobenzene; and 5-amino-2-aniline benzene sulfonic acid; pharmaceutical acetophenide; "Dibione" an agent for treatment of Hansen's disease (Abbott patent); and a variety of anti-oxidants and gum inhibitors. CAUTION: This product is toxic. Avoid breathing its vapors and avoid contact with the skin. Toxicity reference: U. S. Public Health Bulletin No. 271 (1941).

SHIPPING INFORMATION: Dye Intermediate NOIBN "Poison" label required. 325-lb. fiber drums.

MONSANTO® PENTA Pentachlorophenol, Technical.

See Page M5/49

PHTHALYL CHLORIDE Phthaloyl Chloride.

ORGANIC DIVISION

MOLECULAR WEIGHT: 203.03

STANDARD FORM: Liquid.

SPECIFICATIONS: Yellowish liquid; assay 95.0% min.; crystallizing point 0.0°C. min.

USES: Manufacture of plasticizers and resins, general organic synthesis.

SHIPPING INFORMATION: Chemicals NOIBN. Corrosive liquid (white label required), 605-lb. nickel drums.

SANTOCHLOR® para-DICHLOROBENZENE

See Page M5/10

SANTOPHEN® 1 GERMICIDE ortho-benzyl-parachlorophenol.

See Page M5/49

SANTOPHEN® 1 SOLUTION

See Page M5/49

TCC 3, 4 Trichloroacetonitrile.

See Page M5/49

MONOMERS

ACRYLONITRILE

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 53.03

STANDARD FORM: Liquid.

SPECIFICATIONS: Form, clear liquid; color, water white, not over 15 APHA platinum-cobalt scale; distillation range, 74.5-78.5°C. at 760 mm; refractive index 25°C. 1.3882-1.3891; water, 0.25-0.45%; inhibitor 35-45 ppm (Monsanto M-9); acidity not greater than 20 ppm (calculated as acetic acid); aldehydes not greater than 100 ppm (calculated as acetaldehyde); divinylacetylene not greater than 5 ppm; hydrogen cyanide not greater than 5 ppm; in (soluble) not greater than 0.2 ppm; methyl vinyl ketone not greater than 0.01%; peroxides not greater than 1 ppm (calculated as hydrogen peroxide); non-volatile matter not greater than 0.01%; stability not less than 4 hours (exposed to oxygen at 100 pounds per square inch and 100°C.).

PROPERTIES: A bi-functional monohydrocarbon, it is stable under ordinary conditions, yet can be made to react with a wide variety of other materials. Will copolymerize with most commercial vinyl monomers, will join chemically with a variety of natural or synthetic resin-formers.

USES: Production of synthetic textile fibers, nitrile synthetic rubber, copolymers, and chemical intermediates.

INDUSTRIAL USERS: Chemical, Rubber, Textile.

SHIPPING INFORMATION: Tank cars, drums (350 lbs.), tank trucks. Rail & Truck: Chemicals NOIBN

BUTADIENE

HYDROCARBONS AND POLYMERS DIVISION

MOLECULAR WEIGHT: 54.0

STANDARD FORM: Liquefied Gas.

SPECIFICATIONS: 99% minimum; inhibited with tertiary butyl catechol.

PROPERTIES: Highly reactive hydrocarbon containing 2 double bonds; polymerizes and co-polymerizes readily, particularly if oxygen is present.

USES: Production of styrene-butadiene rubbers, acrylonitrile-butadiene rubbers, and polybutadiene rubbers; production of various types of latex for use in paints and as binder for non-woven fabrics; raw material for adiponitrile production; manufacture of tetrahydrofuran anhydride; production of acrylonitrile-butadiene-styrene plastics.

INDUSTRY USERS: Rubber; plastics; surface coatings; chemical manufacturers.

SHIPPING INFORMATION: Pressure tank cars and tank trucks. ICC Red gas label; MCA warning label.

METHANOL

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 32.04

STANDARD FORM: Liquid.

USES: Methanol is used for the manufacture of formaldehyde, as an antifreeze; as a solvent; a denaturant; and as a chemical intermediate.

INDUSTRY USERS: Chemicals; Petroleum.

SHIPPING INFORMATION: Tank cars, tank trucks; drums (350-lb.) Rail & Truck; Methanol; Liquid.

STYRENE MONOMER

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid inhibited with TBO.

SPECIFICATIONS: (Styrene Monomer 100) Color (APHA Platinum-Cobalt Scale) not over 10 units; free from suspended matter and sediment; assay 99.6% min.; viscosity 0.80 cps at 25°C.; tertiary butyl catechol 10-15 ppm; aldehydes (benzaldehyde) 0.02% max.; peroxide (hydrogen peroxide) 0.01% max.; chlorides 0.01% max.; sulfur 0.003% max.; polymer content 15 ppm max.

SPECIFICATIONS: (Styrene Monomer 120) Color (APHA Platinum-Cobalt Scale) not over 20 units; free from suspended matter and sediment; assay 99.2% min.; viscosity 0.80 cps at 25°C.; tertiary butyl catechol 10-15 ppm; aldehydes (benzaldehyde) 0.03% max.; peroxide (hydrogen peroxide) 0.01% max.; chlorides 0.015% max.; sulfur 0.005% max.; polymer content 0.305% max.

PROPERTIES: An aromatic hydrocarbon with an aliphatic side chain containing a double bond which permits polymerization, copolymerization and other reactions. A colorless material that polymerizes and copolymerizes with other light-colored materials to yield clear or light-colored products. USES: Production of styrene molding compounds, synthetic rubber, copolymers, ion exchange resins, polyesters, styrene modified oils and alkyds for surface coatings.

INDUSTRY USERS: Paint; Varnish and Lacquer. Chemicals, Rubber.

SHIPPING INFORMATION: Tank trucks, drums (410 lbs.). Rail: Styrene Liquid.

VINYL ACETATE MONOMER

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 86.1

STANDARD FORM: Liquid at ordinary temperature and pressure.

SPECIFICATIONS: HQ Grade—Vinyl Acetate Monomer—DPA is also available containing Diphenylamine inhibitor.

PROPERTIES: A reactive monomer having a double bond which permits polymerization, copolymerization and other reactions.

USES: Production of latexes for the paint and surface coatings industry and copolymers for extrusion and molding compounds.

INDUSTRY USERS: Paint manufacturers; chemical manufacturers.

SHIPPING INFORMATION: Tank cars; tank trucks. VAM dangerous placards apply.

VINYL CHLORIDE MONOMER

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 62.50

STANDARD FORM: Liquefied gas shipped either inhibitor free or inhibited with phenol.

PROPERTIES: A reactive monomer having a double bond which permits polymerization, copolymerization and other reactions.

USES: Production of polyvinyl chloride resins, compounds, copolymers and chemical intermediates.

INDUSTRY USERS: Chemical manufacturers.

SHIPPING INFORMATION: Tank cars, cylinders (200 lbs.). Rail & Truck: Vinyl Chloride Monomer "Dangerous" Placards Apply.

PHARMACEUTICALS**ACETOPHENETIDIN U.S.P.** Also known as *phenacetin*.

ORGANIC DIVISION

MOLECULAR WEIGHT: 179.21

STANDARD FORM: Crystalline powder.

SPECIFICATIONS: White crystalline powder; solubility in ethyl alcohol 95% (1:15) complete; M.P. 135.0°C. min.; ash 0.05% max.; 5% max. powder retained on 100 mesh.

USES: Commonly used pharmaceutical product, primarily as an anti-pyretic. Prescribed alone or in combination with aspirin and caffeine.

SHIPPING INFORMATION: Chemical NOIBN. 200-lb. and 100-lb. fiber drums.

ASPIRIN

ORGANIC DIVISION

MOLECULAR WEIGHT: 180.15

STANDARD FORM: Crystalline solid.

SPECIFICATIONS: White crystals; assay 99.5% min.; solubility in ethyl alcohol 95% (1:5) complete; solubility in 10% NaCO₃ (1:20) complete; ash 0.05% max.; conforms to U.S.P. test for heavy metals, carbonizable impurities, chloride, sulfate and free salicylic acid.

GRADES: 20 mesh; 40 mesh; 60 mesh.

USES: Acetylsalicylic Acid is analgesic and antipyretic. It is used for the treatment of acute and chronic rheumatic states, and for headache, neuralgia and influenza.

SHIPPING INFORMATION: Acetylsalicylic Acid. 250-lb. and 100-lb. fiber drums.

CAFFEINE ANHYDROUS U.S.P.

See Page MS/13

METHAPYRILENE FUMARATE

Thienopyrimine Fumarate

ORGANIC DIVISION

MOLECULAR WEIGHT: 270.98

STANDARD FORM: Powder.

SPECIFICATIONS: White crystalline powder; ash 0.05% max.; assay 99.0% min.; moisture 0.5% max.; M.P. 133°C. min.

USES: In pharmaceutical and antihistaminic preparations.

SHIPPING INFORMATION: Chemicals NOIBN. 100-lb. and 25-lb. fiber drums; 5-lb. fiberpaks.

METHAPYRILENE HYDROCHLORIDE

Thienopyrimine Hydrochloride

N,N-dimethyl-N',2'-pyridyl-N'-2'-thienylthene-diamine hydrochloride.

ORGANIC DIVISION

MOLECULAR WEIGHT: 297.85

STANDARD FORM: Crystalline solid.

SPECIFICATIONS: White or yellow-white crystals; assay 99.2% min.; ash 0.05% max.; moisture 0.1% max.; M.P. 161.5°C. min. to start; 1.0% max. retained on 40 mesh.

GRADES: Thienopyrimine can also be supplied in the form of the fumarate salt, which is preferred in certain applications.

USES: In pharmaceutical preparations for antihistaminic activity or for sleep inducing (non-prescription).

SHIPPING INFORMATION: Chemicals NOIBN. 100-lb. and 25-lb. fiber drums; 5-lb. fiberpaks.

PHENOLPHTHALEIN U.S.P.

ORGANIC DIVISION

MOLECULAR WEIGHT: 318.31

STANDARD FORM: Crystals.

SPECIFICATIONS: White crystals; M.P. 259.0°C. min.; solubility in alcohol (1:15) complete; acidity (ml N/1000 NaOH/2 gm. sample); 3.0 ml max.; ash 0.1% max.; arsenic 0.001% max.; conforms to U.S.P. test for fluorine and heavy metals; trace max. retained on 100 mesh.

USES: Pharmaceutical preparations as a gentle irritant purgative.

SHIPPING INFORMATION: Chemicals NOIBN. 250-lb. and 100-lb. fiber drums.

PHENOLPHTHALEIN, YELLOW

ORGANIC DIVISION

SPECIFICATIONS: Fine yellow powder; loss on drying (3 hrs./110°C.) 0.50% max.; ash 0.10% max.

USES: Pharmaceutical preparations as gentle irritant purgative.

0557308

Monsanto

TOWOLDMON0041042

SODIUM SALICYLATE, U.S.P.**ORGANIC DIVISION****MOLECULAR WEIGHT:** 180.11**STANDARD FORM:** Powder or crystals.**SPECIFICATIONS:** White powder or crystals; assay 99.5% min.; conforms to U.S.P. tests for heavy metals and carbonizable impurities; loss on drying at 105°C. 0.5%; powder trace max. retained on 60 mesh, 1.0% on 80 mesh, 2.0% on 100 mesh; crystals 80% max. on 40 mesh, 80% max. on 80 mesh.**USES:** Pharmaceutical product as an antipyretic and analgesic. Its principal use is in the treatment of acute rheumatic fever.**SHIPPING INFORMATION:** Chemical NOIBN, 200-lb. and 100-lb. fiber drums.**PHENOLS****BISPHENOL A**

See Page M5/36

ortho-CHLOROPHENOLAlso known as *ortho*-hydroxy-chlorobenzene and 2-chloro-hydroxybenzene**ORGANIC DIVISION****MOLECULAR WEIGHT:** 128.56**STANDARD FORM:** Liquid.**SPECIFICATIONS:** Yellow-to-brown liquid; monochlorophenol 98.0% min. Distillation range: first drop 173.0°C. min.; 95% (1-96 ml) 2.0°C. max.; dry point 178.0°C. max.**USES:** An intermediate for the production of alizarin dye, pyrocatechol, tertiary-butylcatechol, etc. **CAUTION:** This product is toxic. Avoid breathing its vapors and skin contact.**SHIPPING INFORMATION:** Dye Intermediate NOIBN. Product label required. 500-lb. steel drums.**para-CHLOROPHENOL**Also known as *para*-hydroxy-chlorobenzene and 4-chloro-hydroxybenzene**ORGANIC DIVISION—LITERATURE AVAILABLE****MOLECULAR WEIGHT:** 128.56**STANDARD FORM:** Cast solid.**SPECIFICATIONS:** Appearance crystalline mass; crystallizing point 43°C. min.**USES:** An intermediate in the manufacture of Quinizarin Violet, Oscillon Fast Red, Violet RN, Indanthrene Brown BR1 and Alizarin Cyanine Blue dyes; poultry-feed supplement to prevent coccidiosis (divanilol Patent); and germicides, miticides and pharmaceuticals.**SHIPPING INFORMATION:** Dye Intermediate NOIBN. Product label required. 550-lb. skiv. drums. bulk.**2, 4-DICHLOROPHENOL**

Also known as 2, 4-dichloro-hydroxybenzene.

ORGANIC DIVISION**MOLECULAR WEIGHT:** 183.01**STANDARD FORM:** Cast Solid.**SPECIFICATIONS:** Yellow-to-brown crystalline mass; crystallizing point 41.5°C. min.; distillation range: first drop 214.2°C. min.; 95% (1-96 ml) 3.0°C. max.**USES:** An intermediate in the production of dyestuffs, herbicides, germicides and fungicides. **CAUTION:** Care should be exercised in handling this material. Avoid skin contact and breathing its vapor.**SHIPPING INFORMATION:** Dye Intermediate NOIBN. Product label required. 600-lb. steel drums.**DIHYDROXY DIPHENYL SULFONE**Also known as *disulfoni* bis phenol.**ORGANIC DIVISION—LITERATURE AVAILABLE****STANDARD FORM:** Fine powder.**TYPICAL ANALYSIS:** Dihydroxy Diphenyl Sulfone**PURITY**

65-82% of 4,4' ISOMER

35-18% of 2,4' ISOMER

SPECIFICATIONS: Crystallizing point 220-234°C., moisture 0.5% max.**PROPERTIES:** Readily nitrated and sulfonated and converted to esters, ethers, etc. Can be chlorinated but less readily than phenol.**USES:** Electroplating bath addition agent (U. S. Steel "Ferrosulfan" patent); base for phenolic resins; intermediate in organic syntheses; and antioxidant in polyvinyl chloride resin manufacture.**SHIPPING INFORMATION:** Chemical NOIBN, 200-lb. fiber drums.**para-NITROPHENOL** Also known as *para*-hydroxy-nitrobenzene.**ORGANIC DIVISION****MOLECULAR WEIGHT:** 139.11**STANDARD FORM:** Granules.**SPECIFICATIONS:** Brown granular mass M.P. (dry basis)

112.0°C. min.; assay 99.0% min.; water-insoluble material 0.20% max.; methanol-insoluble material 0.80% max.

USES: An intermediate in the production of dyestuffs from para-aminophenol. Photographic chemicals such as para-aminophenol and methyl para-aminophenol and parathion insecticides; fungicides. **CAUTION:** This product is toxic. Avoid breathing its dust or vapors and avoid contact with the skin.**SHIPPING INFORMATION:** Dye Intermediate NOIBN. Product label required. 200-lb. fiber drums.**NONYLPHENOL** *Alkyl Phenol*

See Page M5/54

PHENOL**ORGANIC DIVISION—LITERATURE AVAILABLE****MOLECULAR WEIGHT:** 94.11**STANDARD FORM:** Solid or liquid solutions.**SPECIFICATIONS:** U.S.P.: White crystalline solid; crystallizing point 40.6°C. min. Distillation range: first drop 183.0°C. min.; 100% (first drop to dry point) 2.0°C. max.; 50% to dry point 0.2°C. max. Solutions: Colorless mobile liquids; assay: liquid 85%, 80.0-86.0%; liquid 90%, 90.0-91.0%; liquid 92%, 92.0-93.0%.**GRADES:** Crystalline solid. U.S.P.; liquid 85%; liquid 90%; liquid 92%.**USES:** An intermediate in the production of molding resins; varnishes, emulsions, lacquers, paints, plywood adhesives, explosives, tanning materials, pharmaceuticals, medicinals, antiseptics, germicides, preservatives, deodorants, soaps, embalming fluids, vermifuge, external use, in acids, oil additives, rubber compounds, photographic chemicals, and dyestuffs; a disinfectant; a selective solvent in lubricant production; and in textile printing. **CAUTION:** This product is toxic. Avoid breathing its vapors and contact with the skin.**SHIPPING INFORMATION:** Phenol. "Poison" label required. Tank cars; tank trucks: 475-lb. steel drums; 200-lb. tins.**SULFONIC ACIDS****CHLOROSULFONIC ACID****INORGANIC DIVISION—LITERATURE AVAILABLE****FORMULA:** ClSO₃H**MOLECULAR WEIGHT:** 116.53**STANDARD FORM:** Liquid.**TYPICAL ANALYSIS:** Heavy mobile liquid; assay 99.3% ClSO₃H; Fe—3 ppm.**USES:** In chlorosulfonation reactions. **CAUTION:** Chlorosulfonic acid reacts violently with water forming hydrochloric and sulfuric acids.**SHIPPING INFORMATION:** Chlorosulfonic Acid. Corrosive liquid (white label required). 700-lb., 55-gal. steel and stainless steel drums; 5-lb. bottles single; 80-lb. cases of tet; tank cars and tank trucks.**DBBSA 99-B**

See Page M5/53

DBBSA 99U-B

See Page M5/53

PHENOLSULFONIC ACID98 + % *para* isomer; remainder *ortho* isomer.**ORGANIC DIVISION—LITERATURE AVAILABLE****MOLECULAR WEIGHT:** 174.17**STANDARD FORM:** Oily liquid or crystalline mass. (65% aqueous solution).**PROPERTIES:** Light brown-to-black liquid or crystalline mass depending on temperature; assay 65% min.**SPECIFICATIONS:** Assay 65.0-67.5%; free phenol 2.0% max.; free sulfonic acid 3.0% max.; Sp. Gr. at 15.5/15.5°C. 1.345-1.365.**USES:** Ferrosulfon process for tin plating (U. S. Steel Co. patent); manufacture of pharmaceuticals, dyestuffs, tanning agents, and other chemical intermediates.**SHIPPING INFORMATION:** Acid NOIBN liquid. 600-lb. steel drums.**TOLUENESULFONIC ACID**Mixture of about 80% *para* and 20% *ortho* isomers.**ORGANIC DIVISION—LITERATURE AVAILABLE****MOLECULAR WEIGHT:** 172.20**STANDARD FORM:** Liquid or semi-crystalline solid.**SPECIFICATIONS:** Viscous liquid or semi-crystalline solid. Toluenesulfonic acid 95.0% min.; H₂SO₄ 1.0% max.; sulfone 0.4% max.; sulfonic 1.5% max.**USES:** Acid catalyst in production of alkyl resins, phenol-formaldehyde resins and phthalate esters; and in other organic syntheses; production of dyes, acid-resistant cements, cresols, herbicides, epoxy-resin varnishes and tung-oil coater; and refining of toluene.**SHIPPING INFORMATION:** Chemical NOIBN, 575-lb. steel drums, bulk.

SULFUR-CONTAINING COMPOUNDS (MISC.)

SODIUM meta-NITROBENZENE SULFONATE

ORGANIC DIVISION

MOLECULAR WEIGHT: 225.15

STANDARD FORM: Wet powder.

SPECIFICATIONS: Acidity 7% max. as H_2SO_4 ; water 21% max.; assay 70% min.; sulfates 2% max. as Na_2SO_4 .

USES: An electroplating-bath additive; an intermediate in the manufacture of dyestuffs; a mild oxidant in synthetic-fiber dye baths.

SHIPPING INFORMATION: Chemicals NOIBN. 250-lb. Polyethylene-lined fiber drums.

para-TOLUENESULFONAMIDE

Also known as para-toluene-sulfonic acid amide and para-sulfonamidatoluene.

ORGANIC DIVISION

MOLECULAR WEIGHT: 171.22

STANDARD FORM: Crystalline powder.

SPECIFICATIONS: White, crystalline powder; crystallizing point (dried material) 136.0°C. min.; moisture 0.5% max.

USES: In the preparation of antiseptics and pharmaceuticals, plasticizers and resins (as a base), and in the preparation of dyestuffs; and as a fungicide for protective coatings.

SHIPPING INFORMATION: Chemicals NOIBN. 275-lb. fiber drums.

para-TOLUENESULFONYL CHLORIDE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 190.65

STANDARD FORM: Briquettes.

SPECIFICATIONS: White briquettes. Assay 98% min.; crystalline point 96.5°C. min. (toluene free).

USES: As an intermediate in preparation of dyestuffs such as Brilliant Sulfox Red, Polar Red, Polar Yellow, azo and triphenylmethane dyes, tanning materials, pharmaceuticals, acid resistant cements, acid-oxidants, disinfectants; and photographic chemicals.

SHIPPING INFORMATION: Chemicals NOIBN. 300-lb. fiber drums. Product label required.

METHYL PCT (O, O-dimethyl phosphorochloridithionate)

ORGANIC DIVISION

MOLECULAR WEIGHT: 180.51

STANDARD FORM: Liquid.

SPECIFICATIONS: Light yellow liquid; assay 98% min.; specific gravity 25°/15.5°C., 1.315-1.325.

USES: Widespread use in the manufacture of biological toxicants. This chemical intermediate will allow the incorporation of the dialkyl thiophosphoryl group into any system with a suitable reactive center. The well-known contribution to the group to flame resistance polymer stabilization, and biological activity will suggest many uses.

CONTAINERS: 500-lb. 55-gallon, 16 gauge, lacquer-lined steel drums.

SHIPPING CLASSIFICATIONS: Corrosive Liquid NOS. (Chemicals NOIBN.) Product label required.

ETHYL PCT (O, O-diethyl phosphorochloridithionate)

ORGANIC DIVISION

MOLECULAR WEIGHT: 188.53

STANDARD FORM: Liquid.

SPECIFICATIONS: Colorless to yellow liquid; assay 90.0% min.; specific gravity 25°/15.5°C., 1.190-1.200.

USES: Widespread use in the manufacture of biological toxicants. This chemical intermediate will allow the incorporation of the dialkyl thiophosphoryl group into any system with a suitable reactive center. The well-known contribution to the group to flame resistance polymer stabilization and biological activity will suggest many uses.

CONTAINERS: 525-lb. 55-gallon, 16 gauge, lacquer-lined steel drums.

SHIPPING CLASSIFICATIONS: Chemicals NOIBN. Product label required.

SANTICIZER® 1-H PLASTICIZER

See Page M5/40

SANTICIZER® 3 PLASTICIZER

See Page M5/40

SANTICIZER® 8 PLASTICIZER

Mixture of N-Ethyl-ortho- and para-Toluenesulfonamides.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 199.27

STANDARD FORM: Liquid.

SPECIFICATIONS: Light yellow, viscous liquid; odor slight, characteristic; unsubstituted amide 9-13%; acidity (as acetic acid) 0.80 meq/100 gms. max.; color of melt 200 APHA max.

PROPERTIES: Readily miscible with all common organic solvents except the petroleum hydrocarbons in which it is only very slightly soluble. In water, soluble to approx. 0.1% at 25°C., 0.21% at 48°C.; solubility in water decreased by presence of ammonia but increased by other alkalies; soluble in castor oil, slightly soluble in chinawood oil; insoluble in linseed oil; retentivity in cellulose acetate approx. 90 parts by weight to 100 of acetate; imparts a high degree of plasticity. A solvent for both nitrocellulose and cellulose acetate.

USES: An excellent plasticizer for cellulose acetate, giving a brilliance and polish not obtainable with other plasticizers.

SHIPPING INFORMATION: Resin Plasticizer, 530-lb. and 50-lb. drums.

SANTOLITE® MHP RESINS

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Hard resin.

SPECIFICATIONS: Hard, practically colorless resin; refractive index (25 gms. in 75 gms. normal butyl acetate) 1.4290—1.4310; penetration (200 gm. load for 5 seconds at 25°C.) 2.0 mm. max.

GENERAL INFORMATION—PROPERTIES: An aryl sulfonamide-formaldehyde resin similar to Santolite MS in characteristics, except that it is much harder, softening at about 62°C., brittle at normal temperatures. Nearly colorless, well adapted to specialty and heat-sealing lacquers, fabric coatings, molding compositions and the like. Being incompatible with drying oils it cannot be used as a varnish material.

USES: Can be used in spraying, dipping or brushing lacquers to make clear, colorless, odorless coatings of good adhesion and cohesion. It does not materially increase the viscosity of the solution and permits the building up of a high-solids content in the lacquer. Compatible with all the common plasticizers.

CONTAINERS: 60-lb. cased cans.

SHIPPING CLASSIFICATION: Resin Synthetic NOIBN Without Filler.

SANTOLITE® MS 80% Industrial Resin.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Light-colored, viscous liquid; free-flowing at temperatures above 20°C.; composition 78.9—81.2% Santolite MS, 18.8 to 21.2%.

PROPERTIES: Soft, practically colorless resin made by the condensation of formaldehyde with aromatic sulfonamides.

USES: Santolite MS, like Santolite MHP, is compatible with both nitrocellulose and cellulose acetate; as a solvent for both, it can be used in any proportion. Forms a brittle composition with both resins but the addition of a plasticizer makes such combinations permanently flexible.

SHIPPING INFORMATION: Resin Synthetic NOIBN Without Filler, 450-lb. approx., 55-gal. drums; 45-lb. approx., 5-gal. drums.

SANTONOX® ANTIOXIDANT

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Solid.

SPECIFICATIONS: Appearance, light gray to light tan powder; Ash, 0.1% max.; melting point, 150°C. min.; moisture, 1.0% max.; fineness, 50 mesh (trace, max.).

PROPERTIES: Santonox is probably the best antioxidant available for both low and high density polyethylene. It maintains the melt index and recovery of the polyethylene in extrusion operations better than competitive products. It has little or no effect on electrical properties.

USES: Santonox is used as an antioxidant for polyethylene. It offers the best price performance characteristics of all the available antioxidants. Santonox is approved by the FDA as an antioxidant for high pressure (low density) polyethylene at 0.05% level for all applications except fatty foods. (Antioxidant for synthetic resins.)

SHIPPING INFORMATION: Chemicals NOIBN. 150-lb. fiber containers.

SANTONOX® R

See Page M5/39

0557310

Monsanto

TOWOLDMON0041044

SANTOWHITE® CRYSTALS

See Page M5/45

OTHER ORGANIC CHEMICALS**ACETONE**

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 58.08.

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear water-white liquid. Color APHA 5 max.; specific gravity 20°C/20°C, 0.791 to 0.793; distillation range, 1.0°C to include 56.1°C.; moisture 0.5% max.

USES: Solvent, chemical intermediate.

SHIPPING INFORMATION: Acetone NOIBN. Flammable liquid and product labels required. Tankcar, tank wagon.

BENZYL BENZOATE N.F.

ORGANIC DIVISION

MOLECULAR WEIGHT: 212.24

STANDARD FORM: Liquid.

SPECIFICATIONS: Essentially colorless liquid; crystallizing point 18.3°C. min.; refractive index 1.568-1.570 at 20°C.; total chlorine 0.03% max.; assay 99.0% min.; Sp. Gr. 25°/25°C, 1.174-1.180.

PROPERTIES: High-boiling ester having a pleasant odor.

USES: A miticide (acaricide); fixative in perfumes; preparation of delousing and insect-repellent formulations; medicinally in the treatment of scabies.

SHIPPING INFORMATION: Insect Repellent NOIBN. 500-lb. drums.

BIPHENYL Also known as diphenyl and phenylbenzene

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 154.20

STANDARD FORM: Flakes.

SPECIFICATIONS: Colorless to pale yellow crystallized solid or flakes. Freezing point 68.7°C. min.

USES: Biphenyl is used as a wrapping-paper impregnate to reduce citrus-fruit spoilage; a dye carrier and accelerator for synthetic fibers; in the manufacture of ceramics; a low-pressure, high-temperature, non-corrosive heat-transfer medium; and raw material in the manufacture of a great variety of products, since it is easily chlorinated, sulfonated, nitrated and hydrogenated.

SHIPPING INFORMATION: Biphenyl, 100-lb. bags; 225-lb. bbls.; 100-lb. kegs.

CYANURIC ACID

INORGANIC DIVISION—LITERATURE AVAILABLE

USES: Intermediate for chlorine derivatives; cross-linking agent in polyepoxide resins; in manufacture of fire-retardant plastics.

TYPICAL ANALYSIS: White crystalline solid; Cyanuric Acid 98% min.; Ammonia 2.5% chlorides (as Cl) 0.1%; Ammonia (as NH₃) 0.05%; Moisture 0.5% max.; Apparent density 0.8 gm/cc; pH (1 gm/100 ml H₂O) 3.9.

SHIPPING INFORMATION: Packed in 200-lb. net open head fiber drums with a polyethylene bag liner. Shipped as Acid, NOIBN, Dry.

CYCLOHEXANOL

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 100.16

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, colorless, viscous liquid; Color 10 APHA max.; Unsaturates (as Phenol), 0.01% max.; Ketones (as Cyclohexanone), 0.05% max.

USES: Intermediate for plasticizers; in dye cleaning and textile industries; solvent in dyestuff operations; manufacture of cyclohexanone and adipic acid.

CONTAINERS: 55-gal. steel drums, bulk.

SHIPPING CLASSIFICATIONS: Lacquer Solvent NOIBN. Product label required.

FORMALDEHYDE

PLASTIC PRODUCTS AND RESINS DIVISION

STANDARD FORMS: A 37% aqueous solution inhibited with methanol, 44% methanol free, 37% methanol free.

SPECIFICATIONS: Clear and free of foreign sediment; color not greater than 5 APHA; Sp. Gr. 1.0829-1.1136 depending on methanol content; assay 37.0% by weight, minimum;

acidity no greater than 0.02% as formic acid; iron no greater than 1 part per million; methanol 0 to 1% (methanol-free) and 7 to 8% (inhibited).

USES: A preservative, disinfectant and chemical intermediate used in the preparation of melamine and phenolic resins.

INDUSTRIAL USERS: Chemical manufacturers.

SHIPPING INFORMATION: Tank trucks, Rail & Truck: Formaldehyde, Liquid.

HYDROGENATED BISPHENOL A (HBPA®)

See Page M5/36

SODIUM BENZOATE, U.S.P. AND TECHNICAL

See Page M5/15

PHOSPHORUS and PHOSPHORUS DERIVATIVES**AMMONIUM PHOSPHATES****DIAMMONIUM PHOSPHATE**

INORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 132.088

STANDARD FORM: Crystalline or powdered material.

PROPERTIES: Brilliant white crystalline or powdered material; stable in air; very soluble in water; pH value of 1% solution 7.75; above 70°C. aqueous solutions lose ammonia readily.

DISSOCIATION PRESSURE: According to Britzke and Dittmar (Z. anorg. Chem. 1927) and Warren (JACS 49, 1904, 1827):

Temp. °C. 98 111 125 135 147
NH₃ in mm. Hg. 3.2 10.7 26.0 55.2 123.4

GRADES: Food (meets all U. S. Pure Food Law requirements).

USES: As a source of phosphorus and non-protein nitrogen for ruminant feeds; fire retardant; yeast food by yeast producers and breweries; as bread improvers, to control pH of soda crackers; catalyst for urea-formaldehyde resins; chrome dyeing of wool; source of N and P₂O₅ for soluble fertilizers.

SHIPPING INFORMATION: Phosphate of Ammonia, 100-lb. bags; 300 and 100-lb. fiber drums.

ETHYL AMMONIUM PHOSPHATE

INORGANIC DIVISION

TYPICAL ANALYSIS: 65% solution of Ethyl Acid Phosphate neutralized with ammonia 33% P₂O₅; Sp. Gr. on 25°C., 1.21 or 10.1 lbs. per gal.

SHIPPING INFORMATION: 135-lb. and 500-lb. drums.

MONOAMMONIUM PHOSPHATE

INORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 115.07

STANDARD FORM: Crystalline or powdered material.

PROPERTIES: A brilliant white crystalline or powdered material; stable in air; soluble in hot and cold water; pH of 1% solution 4.7.

GRADES: Food (meets all U. S. Pure Food Law requirements).

USES: Fungusproofing paper, wood, textiles; prevents afterglow in matches; for special medicinal purposes; nutrient solutions; manufacture of yeast, vinegar, yeast foods, bread improvers; acidulant in dye bath.

SHIPPING INFORMATION: Phosphate of Ammonia, 100-lb. bags; 300 and 100-lb. fiber drums.

TRIETHYLAMMONIUM PHOSPHATE

INORGANIC DIVISION

GENERAL INFORMATION: An additive for non-aqueous materials for stabilizing corrosive and iron-sensitive liquids such as lacquers in metal containers.

SHIPPING INFORMATION: 40-lb. and 450-lb. drums.

CALCIUM PHOSPHATES

CALCIUM PYROPHOSPHATE

INORGANIC DIVISION

FORMULA: $\text{Ca}_2\text{P}_2\text{O}_7$

MOLECULAR WEIGHT: 254.20

STANDARD FORM: Powder.

PROPERTIES: Finely subdivided powder; contains CaO , 43.8%; P_2O_5 , 56.5%.

USES: Food fortification and vitamin tablets as a mineral supplement and dentifrice polishing agent.

SHIPPING INFORMATION: Calcium Phosphate. 100-lb. bags; 400-lb. drums; 100-lb. drums.

DICALCIUM PHOSPHATE, ANHYDROUS

INORGANIC DIVISION

FORMULA: CaHPO_4

MOLECULAR WEIGHT: 136.07

STANDARD FORM: Finely divided powder.

TYPICAL ANALYSIS: Total P_2O_5 -51.3%; total CaO . Conforms with all state and federal food laws and meets N.F. requirements.

PROPERTIES: White, tasteless, finely divided powder.

USES: Primarily as a polishing agent in tooth pastes and powders, and as a mineral supplement in foods and cereals.

SHIPPING INFORMATION: 50-lb. bags; 350 and 100-lb. drums.

DICALCIUM PHOSPHATE, DIHYDRATE

INORGANIC DIVISION

FORMULA: $\text{CaHPO}_4 \cdot 2\text{H}_2\text{O}$

MOLECULAR WEIGHT: 172.10

STANDARD FORM: Powder.

TYPICAL ANALYSIS: Phosphorus 18.1%; calcium 23.7%.

PROPERTIES: White tasteless crystalline powder; soluble in dilute citric acid solution; very slightly soluble in water; insoluble in alcohol and glycerin. The stabilized dentifrice grade is prepared specially for use in dentifrices and does not set-up hard when used to formulate tooth paste.

GRADES: Regular N.F. grade + stabilized dentifrice grades.

USES: Medicinal; mineral supplement for foods and cereals; polishing ingredient in tooth pastes and powders.

SHIPPING INFORMATION: Calcium Phosphate. 60 and 100-lb. bags; 100 and 225-lb. fiber drums.

DICALCIUM PHOSPHATE, FEED GRADE

See Page M5/7

H. T. MONOCALCIUM PHOSPHATE, Monohydrate

See Page M5/14

LUSTRE-PHOS

INORGANIC DIVISION

FORMULA: Calcium Ortho-phosphate.

PROPERTIES: White tasteless crystalline powder. Insoluble in water and alcohol.

GRADES: Dentifrice grades.

USES: In dentifrices as a controlled abrasive to impart optimum cleaning and polishing of the teeth.

PY-RAN® ANHYDROUS MONOCALCIUM PHOSPHATE

See Page M5/14

TRICALCIUM PHOSPHATE

INORGANIC DIVISION

FORMULA: $3\text{Ca}(\text{PO}_3)_2 \cdot \text{Ca}(\text{OH})_2 \cdot 3\text{H}_2\text{O}$

MOLECULAR WEIGHT: 1,058.7

USES: Toothpaste and tooth powder formulations; as a mineral supplement in foods and pharmaceuticals; to prevent caking in salt, sugar, talc and other powder materials. Meets industry limits as outlined in the National Formulary XI, Edition (1960).

SHIPPING INFORMATION: Phosphate of Calcium. 60-lb. bags and 150-lb. drums.

*Monsanto Trademark

PHOSPHORIC ACIDS

PHOSPHORIC ACID (75, 80 and 85%)

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: H_3PO_4

MOLECULAR WEIGHT: 98.00

GRADES: U.S.P.: food, meets all U.S. Pure Food Law requirements; commercial, clear, water-white liquid.

SPECIFICATIONS: Clear, water-white liquid miscible with water in all proportions; 75%, 80% and 85% H_3PO_4 .

PHOSPHORIC ACID PLANTS. Complete, wet phosphoric acid manufacturing plant using the Frayon process offered by Engineering Sales Department.

USES: Manufacture of sodium phosphates, ammonium phosphates, calcium phosphates and other phosphates; drying agent in the synthesis of various intermediate chemicals and dyes; process engraving and litho trades; the manufacture of gelatin; substrate for tartaric and citric acids in jellies, preserves and soft drinks; opacifier in glass manufacture; manufacture of certain pharmaceutical chemicals and dental cements; manufacture of rustproofing compounds; silage preservation; defecating and clarifying agent in sugar; for brightening the color of silk; dyeing of cotton; calico printing; water softening and correction of alkalinity; electro polishing of stainless and carbon steels; steel pickling; manufacture of special bricks; petroleum catalyst; aluminum bright dip bath component.

SHIPPING INFORMATION: Phosphoric Acid. 200 and 700-lb. stainless steel drums; 700-lb. lacquer lined drums; tank cars and tank trucks.

PHOSPHOLEUM®

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: H_3PO_4

MOLECULAR WEIGHT: 98.00

GRADES: Industrial, commercial liquid.

SPECIFICATIONS: Clear miscible with water in all proportions 100% H_3PO_4 .

USES: Natural desiccant; sequestrant for trace minerals; catalyst or dehydrator in organic synthesis; drying agent in the synthesis of various intermediate chemicals and dyes; manufacture of rustproofing compounds; steel pickling; manufacture of special bricks; petroleum catalyst.

SHIPPING INFORMATION: Phosphoric Acid. Tank cars and tank trucks.

POTASSIUM PHOSPHATES

MONOPOTASSIUM PHOSPHATE

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: KH_2PO_4

MOLECULAR WEIGHT: 136.09

STANDARD FORM: White crystals.

TYPICAL ANALYSIS: P_2O_5 , 61.69%; K_2O , 34.31%; ignition loss 13.24%; SO_4 none; pH 4.6.

USES: To control pH of culture media in penicillin manufacture; special medicinal purposes; soluble fertilizers.

SHIPPING INFORMATION: Potassium Phosphate. 350 and 150-lb. net drums; 100-lb. bags.

TETRAPOTASSIUM PYROPHOSPHATE

INORGANIC DIVISION

FORMULA: $\text{K}_4\text{P}_2\text{O}_7$

MOLECULAR WEIGHT: 330.34

STANDARD FORM: Powder.

PROPERTIES: White powder, hygroscopic in air; pH value in 1% solution 10.4 at 25°C; solubility 190 gms. in 100 gms. water at 25°C.

USES: In textile oils and soaps to increase emulsifying values and to prevent formation of insoluble hard water soaps; clarifying agent; to improve cleaning action of soaps.

SHIPPING INFORMATION: Washing Compound Dry. 350 and 150-lb. drums.

0557312

Monsanto

TOWOLDMON0041046

TRIPOTASSIUM PHOSPHATE**INORGANIC DIVISION****FORMULA:** K_3PO_4 **MOLECULAR WEIGHT:** 212.27**STANDARD FORM:** Powder.**PROPERTIES:** White crystalline powder soluble in water; insoluble in alcohol; very hygroscopic.**GRADES:** Hydrated.**USES:** Used in synthetic (cold) rubber manufacturing.**SHIPPING INFORMATION:** Potassium Phosphate, 300-lb. net fiber drums.**SODIUM PHOSPHATES****DISODIUM PHOSPHATE, ANHYDROUS****INORGANIC DIVISION****FORMULA:** Na_2HPO_4 **MOLECULAR WEIGHT:** 141.98**STANDARD FORM:** Powder.**PROPERTIES:** Soluble in water; insoluble in alcohol; on exposure to air will absorb 5-7 mols H_2O depending on humidity and temperature; loses molecular water at $240^\circ C$, forming tetrasodium pyrophosphate; pH of 1% solution 8.8 at $25^\circ C$. One lb. anhydrous product equivalent to 2.5 lbs. crystalline (dodecahydrate).**GRADES:** Food (Granular and Powdered); Medicinal, U.S.P.**USES:** For boiler water treatment; in making glazes for pottery, porcelain and chinaware; as an emulsifier in making process cheese; in various chemical processes; in manufacture of dyestuffs such as Schnitzler's green; in the preparation of enamels; in tinning and soldering; in leather tanning; as a bath ingredient in galvanoplastic work; in the manufacture of pigments such as cobalt phosphate; in the weighing of silk and impregnating of textiles in dyeing and calico printing; in the adjustment of condensed milk; medicinal.**SHIPPING INFORMATION:** Disodium Phosphate, 100-lb. bags; 350 and 100-lb. drums.**DISODIUM PHOSPHATE, DIHYDRATE****INORGANIC DIVISION****FORMULA:** $Na_2HPO_4 \cdot 2H_2O$ **MOLECULAR WEIGHT:** 178.0**STANDARD FORM:** Crystalline powder.**PROPERTIES:** Soluble in water, insoluble in alcohol; equivalent to 82% of sodium phosphate, di. anhydrous (see preceding product for further information on properties.)**GRADES:** Food (conforms with Federal and State Pure Food Laws).**USES:** Especially recommended for use in preventing coagulation during condensation of milk and as an emulsifying agent in processing cheese.**SHIPPING INFORMATION:** Disodium Phosphate, 100-lb. bags.**INSOLUBLE METAPHOSPHATE****INORGANIC DIVISION****FORMULA:** $(NaPO_3)_x$ **MOLECULAR WEIGHT:** (102).**STANDARD FORM:** Powder.**PROPERTIES:** Insoluble in water and alcohol.**GRADES:** Powdered.**USES:** Primarily in toothpastes and powders. Considered compatible with fluorides in toothpastes.**SHIPPING INFORMATION:** Phosphate of Soda, 60-lb. bags; 325 and 100-lb. drums.**LEVN-LITE***

See Page M5/14

MONOSODIUM PHOSPHATE**INORGANIC DIVISION****FORMULA:** NaH_2PO_4 **MOLECULAR WEIGHT:** 119.99**STANDARD FORM:** Powder and granular.**PROPERTIES:** Contains not less than 58% P_2O_5 ; pH value of 1% solution 4.6.

* Monsanto Trademark

GRADES: Food; commercial.**USES:** Acid phosphate in metal cleaners, water conditioner, electrodeplate solution buffer, textile dyeing aid. Emulsified in process cheese, mineral supplement, pharmaceutical ingredient.**SHIPPING INFORMATION:** Sodium Phosphate, 100-lb. bags; 350 and 100-lb. drums.**OILFOS® GLASSY SODIUM PHOSPHATE****INORGANIC DIVISION****STANDARD FORM:** Dry powder.**PROPERTIES:** Oilfos is used exclusively for controlling viscosity of oil well drilling muds.**SHIPPING INFORMATION:** Phosphate of Soda, 100-lb. net paper bags; triotex bags.**PAN-O-LITE®**

See Page M5/14

SODIUM ACID PYROPHOSPHATE

See Page M5/14

SODIUM HEXAMETAPHOSPHATE**INORGANIC DIVISION—LITERATURE AVAILABLE****FORMULA:** An amorphous glass of composition equivalent to $Na_6P_6O_{18}$.**AVERAGE MOLECULAR WEIGHT:** 1490**STANDARD FORMS:** Glass platelets, granules and powder.**TYPICAL ANALYSIS:** 32.5% total NaO; 67.0% total P_2O_5 ; pH 1% solution, 6.9; less than 1.0 ppm Pb; less than 1.0 ppm F; 0.1 ppm AsO₃; trace SO₃; 0.01% iron.**PROPERTIES:** Infinitely soluble in water. Bulk density—glass platelets, 77.5 lbs./cu. ft.; granules, 99.5 lbs./cu. ft.; powder, 100.0 lbs./cu. ft.**USES:** Water softener; in treatment of boiler water; in dishwashing compositions and detergents; deflocculating agent; textile and food processing.**SHIPPING INFORMATION:** Sodium Phosphate, NOIBN, 100-lb. net multiwall paper bags; 100-lb. net burlap bags.**SODIUM TRIPOLYPHOSPHATE****INORGANIC DIVISION****FORMULA:** $Na_5P_3O_{10}$ **MOLECULAR WEIGHT:** 367.93**STANDARD FORM:** Granules or powder.**PROPERTIES:** White granular material or white powder; water-soluble with excellent water-softening and detergent properties; pH 9.5 of 1% solution. A calcium sequestering agent and also has a high binding power for most of the metals of Group II and Group IV.**USES:** Soap builder; detergent and water softener; conditioning oil drilling muds; eliminates scum and soap curds in hard water.**SHIPPING INFORMATION:** Phosphate of Soda, 100-lb. bags; 350 and 100-lb. drums.**SQ PHOSPHATE****INORGANIC DIVISION****STANDARD FORM:** Dry powder.**TYPICAL ANALYSIS:** P_2O_5 83.0%; NaO 36.0%; pH 1% solution 7.9.**PROPERTIES:** SQ Phosphate is a glassy poly phosphate with high calcium sequestering properties. It is used in formulating industrial cleaning compounds such as dishwashing and dairy cleaners.**SHIPPING INFORMATION:** Phosphate of soda, 100-lb. net paper bags or triotex bags.**STABIL -9® LEAVENING AGENT**

See Page M5/14

TRISODIUM PHOSPHATE, ANHYDROUS**INORGANIC DIVISION****FORMULA:** Na_3PO_4 **MOLECULAR WEIGHT:** 164**STANDARD FORM:** Granular, nearly white crystals.**TYPICAL ANALYSIS:** Assay, $NaPO_3$ —97.9%. Loss on ignition at $500^\circ C$ —4.0%.**USES:** The same as ordinary Trisodium Phosphate but where higher concentration or less bulk is desired, one pound is equivalent to 2.33 pounds of the crystalline grade.**SHIPPING INFORMATION:** Trisodium Phosphate, 100-lb. bags; 350 and 100-lb. drums.

TRISODIUM PHOSPHATE, CRYSTALLINE

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: $\text{Na}_3\text{PO}_4 \cdot 12\text{H}_2\text{O}$

MOLECULAR WEIGHT: 380.16

STANDARD FORM: Crystalline material.

SPECIFICATIONS: White crystalline material, uniformly sized; quickly soluble in water giving an alkaline reaction; pH of 1% solution 11.8.

USES: Principally in cleaners and detergents for both household and industrial use; in fruit cleaning to remove insecticide sprays and inhibit growth of fruit mold; in water treatment for softening and conditioning water.

SHIPPING INFORMATION: Trisodium Phosphate, 100-lb. bags; 325 and 100-lb. drums.

TETRASODIUM PYROPHOSPHATE

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: $\text{Na}_2\text{P}_2\text{O}_7$

MOLECULAR WEIGHT: 268.05

STANDARD FORM: Crystals or granules.

PROPERTIES: White crystalline material or white granular powder; pH of 1% solution 10.2; solubility: 6 parts in 100 parts of water at 15°C., 40 parts in 100 parts of water at 100°C.

GRADES: Anhydrous.

USES: As a soap builder; conditioning oil drilling wells; in bleaching, especially for straw, and as an ink eraser; in manufacture of iron pyrophosphate and other pyrophosphates; household and industrial cleaner and detergent; in dye bath for putting certain types of dye in complete solution; electroplating; metal cleaning; electrolytic separation of various metals; as emulsifier in process cheese manufacture; dyes; ammonia textiles; stabilizing hydrogen peroxide baths; reagent for de-inking newsprint.

SHIPPING INFORMATION: Sodium Phosphate, Regular—100-lb. paper bags; 300-lb. and 100-lb. drums; Powdered—100-lb. paper bags; 350-lb. and 100-lb. drums.

OTHER PHOSPHORUS AND PHOSPHORUS DERIVATIVES

ALKALOPHOS[®] Aluminum Acid Phosphate.

INORGANIC DIVISION

STANDARD FORM: Liquid.

PROPERTIES:

	Alkalophos C	Alkalophos CE
P ₂ O ₅	33.1%	36.0%
Al ₂ O ₃	8.6%	11.0%
Sp. Gr. 25°/15.5°C.	1.47	1.60

USES: Coating for electrical steel transformer and motor laminations; binder for high temperature insulation brick and other refractories; high temperature water insoluble binder or adhesive.

SHIPPING INFORMATION: Aluminum Phosphorus, 175-lb. and 600-lb. drums.

ALKYL ACID PHOSPHATES

INORGANIC DIVISION—LITERATURE AVAILABLE

TYPICAL ANALYSIS:

Phosphoric Acid Ester	P ₂ O ₅ , %	Sp. Gr. @ 25°C.	Lbs. per Gal.	Acid No. Mg KOH/g
Amyl	40	1.09	9.1	362
n-Butyl	40	1.13	9.4	396
Ethyl	44	1.29	10.7	523
n-Propyl	45	1.21	10.1	455

USES: Additions to paint and varnish compositions to improve adhesion to metal surfaces; as catalyst in urea resin formation; as polymerizing agents for resins and oils.

SHIPPING INFORMATION: Acids Liquid NOIBN, Amyl: 135-lb. and 500-lb. drums, n-Butyl: 135-lb. and 500-lb. drums, Ethyl: 100-lb. and 675-lb. drums, n-Propyl: 140-lb. and 525-lb. drums.

CRESYL DIPHENYL PHOSPHATE (Gasoline Grade)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Clear, light amber liquid.

SPECIFICATIONS: Color NPA 1.5 max.; Sp. Gr. 1.200—1.215 at 25/25°C.; Phosphorus 8.7—9.2%; Acidity 0.2 mg. KOH/gram trim.

GENERAL INFORMATION: Soluble in aromatic and aliphatic solvents; insoluble in water. Soluble in kerosene at dosage normally used.

USES: Effective in combating abnormal combustion due to glowing combustion chamber deposits and fouled spark plugs. A proved surface ignition control agent and combustion deposit modifier. Recommended dosage 0.4—0.6 cc Cresyl Diphenyl Phosphate per gallon of gasoline (varies depending on lead content of gasoline).

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. non-returnable black iron drums; tank cars and tank trucks.

CRESYL DIPHENYL PHOSPHATE (Plasticizer Grade) SANTICIZER[®] 140

See Page M5/41

FERROPHOSPHORUS (Iron Phosphide)

INORGANIC DIVISION

STANDARD FORM: Chill cast lumps, egg size, ¼ inch or less.

TYPICAL ANALYSIS: A gray alloy of iron and phosphorus which fractures easily; contains 23—26% phosphorus.

USES: Used in iron and steel castings to increase fluidity; in sheet steel to prevent sticking of sheets in final rolling; in wire to give stiffness and better surface for drawing; paint pigment.

SHIPPING INFORMATION: Ferrophosphorus, Bulk: 500-lb. bbls.

METHYL DIPHENYL PHOSPHATE (Phosane[®] MDP)

See Page M5/29

PHOSPHORUS, ELEMENTAL

INORGANIC DIVISION—LITERATURE AVAILABLE

PROPERTIES: Light yellow, wax-like semi-transparent solid; burns spontaneously in air to form P₂O₅, M.P. 44.1°C.; very soluble in carbon disulfide; insoluble in water.

GRADES: Monsanto process of manufacture provides over 99.9% purity.

USES: Manufacture of phosphorus alloys, phosphoric anhydride, phosphorus compounds, phosphoric acid, rodent poisons, flares, smoke screens, etc.

SHIPPING INFORMATION: Phosphorus Yellow, toxic and inflammable (yellow label required), 400-lb. drums; tank cars.

PHOSPHORUS OXYCHLORIDE

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: POCl₃

MOLECULAR WEIGHT: 153.35

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Water-white liquid; assay 99.75% POCl₃; Sp. Gr. 15.3°C./15.5°C., 1.685; free Cl₂ trace; PCl₅ 0.12%; distillation range 7°C.; first drop 106.7, 1-99 ml 1.0, dry point 107.9.

USES: A chlorinating agent and catalyst in the preparation of various intermediates, dyes, dyestuffs, medicinals; reagent in the preparation of acetic anhydride and organic phosphates.

CAUTION: Care must be exercised in handling this product. Avoid breathing its vapors. Avoid contact with the skin. It reacts with water with explosive violence.

SHIPPING INFORMATION: Phosphorus Oxychloride, Corrosive liquid (white label required), 725-lb. nickel drums, 4,000 and 8,000-gal. nickel tank cars.

PHOSPHORUS PENTASULFIDE

INORGANIC DIVISION

FORMULA: P₂S₅

MOLECULAR WEIGHT: 444.58

STANDARD FORM: Light greenish yellow granular powder.

PROPERTIES: Monsanto is unique in offering both highly reactive and low reactive grades distilled for highest purity.

USES: Manufacture of lubricating oil additives; thiophosphate insecticides; thiophosphate salts for ore flotation; also as a catalyst in production of blown asphalt; and as an intermediate in organic synthesis.

SHIPPING INFORMATION: Chemicals NOIBN, 160 and 325-lb. drums.

PHOSPHORUS PENTOXIDE (Phosphoric Anhydride)

INORGANIC DIVISION

FORMULA: P₂O₅

MOLECULAR WEIGHT: 141.96

STANDARD FORM: White microcrystalline powder.

(Continued on next page)

0557314

Monsanto

TOWOLDMON0041048

PROPERTIES:

Vapor Pressure: (after J. C. Southard and R. A. Nelson—JACS, 58, 911-1937-)

P—vapor pressure in cm. of mercury

T—absolute temperature

A (low temperature form)

B (high temperature form)

L (liquid)

Log₁₀P = 9.792—(5000/T)

Log₁₀P = 11.113—(7850/T)

Log₁₀P = 8.809—(4320/T)

Atmospheric sublimation temperature: 358.9°C.

Heat of vaporization:

A—22,300 calories per gm. molecule

B—36,200 calories per gm. molecule

L—19,700 calories per gm. molecule

Heat of fusion: 18,500 calories per gm. molecule

Probable molecular formula of vapor: P₂O₅

TYPICAL ANALYSIS: P₂O₅—99.5%, lower oxides .01% as P₂O₅; color 90% water solution 50 APHA.

USES: As a desiccant; in the production of alkyl phosphates; a catalyst in air blown asphalt; in the manufacture of fluoro-phosphates; in the making of phosphorus insecticides; and in the production of oil additives.

SHIPPING INFORMATION: Phosphoric Anhydride, (Flammable—yellow label required); 400 and 60-lb. drums.

PHOSPHORUS TRICHLORIDE

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: PCl₃

MOLECULAR WEIGHT: 137.36

TYPICAL ANALYSIS: Water-white liquid; assay 99.75% PCl₃; Sp. Gr. 15.8°C./15.8°C. 1.586; distillation range °C.: first drop 74.6, 1-96 ml 9.9, dry point 76.0.

USES: A chlorinating agent and catalyst in the preparation of various intermediates and dyestuffs; reagent in the preparation of acetic anhydride, organic phosphates, germicides and medicinal; manufacture of phosphorus oxychloride and phosphorus pentachloride; in producing iridescent metallic deposits.

CAUTION: Care must be exercised in handling this product. Reacts with water. Avoid breathing its vapors. Avoid contact with the skin.

SHIPPING INFORMATION: Phosphorus Chloride, "Corrosive liquid" label required. 675-lb. (approx.) nickel drums; 4,000 and 8,000-gal. nickel tank cars.

TRICRESYL PHOSPHATE See Page M5/39

TRIPHENYL PHOSPHATE See Page M5/39

TRIPHENYL PHOSPHITE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 310.28

SPECIFICATIONS: Light yellow solid or oily liquid; Sp. Gr. 1.179 to 1.183; free phenol 0.8% max.; hydrolyzable chlorine 0.01% max.; color APHA 150 max.; refractive index at 25°C. 1.587 to 1.590.

PROPERTIES: A crystalline solid at slightly below room temperature; at higher temperatures is an oily liquid weighing about 9.85 lbs. per gal.

USES: A color improver and metal scavenger in alkyl resin production. Also used as a stabilizer in polyvinyl chloride compounds. Monsanto's patent No. 2,572,671 covers this and removers and users must be licensed.

SHIPPING INFORMATION: Chemicals NOIBN. 55 and 5-gal. drums.

PETRO CHEMICALS

ETHYLENE AND ETHYLENE CO-PRODUCTS

BENZENE

HYDROCARBONS AND POLYMERS DIVISION

FORMULA: C₆H₆

MOLECULAR WEIGHT: 78.1

STANDARD FORM: Liquid.

GENERAL INFORMATION: Benzene is an aromatic hydrocarbon, used in the manufacture of styrene, phenol, cyclohexane, synthetic detergents, and many other organic chemicals and intermediates.

SHIPPING INFORMATION: Benzol. Flammable liquid. Red label. Tank cars, tank trucks.

BUTENE-2 CONCENTRATE

HYDROCARBONS AND POLYMERS DIVISION

FORMULA: CH₃CH=CHCH₃

MOLECULAR WEIGHT: 58.1

STANDARD FORM: Liquid (under pressure).

GENERAL INFORMATION: Butene-2 Concentrate is a colorless olefinic hydrocarbon used as a cross-linking agent in the manufacture of chemical intermediates and in specialty solvent applications. It is predominantly *cis* and *trans* butene-2.

SHIPPING INFORMATION: Liquefied petroleum gas. Flammable gas; red gas label. Tank cars, tank trucks.

BUTYLENES Mixed Isomers

HYDROCARBONS AND POLYMERS DIVISION

FORMULA: C₄H₈

MOLECULAR WEIGHT: 58.1

STANDARD FORM: Liquid (under pressure).

GENERAL INFORMATION: Mixed butylenes are used in the manufacture of resins and chemical intermediates. Principal constituents are *iso*-butylene and *n*-butene-1.

SHIPPING INFORMATION: Liquefied petroleum gas. Flammable gas; red gas label. Tank cars, tank trucks.

C₃ STREAM Mixed Hydrocarbons

HYDROCARBONS AND POLYMERS DIVISION

STANDARD FORM: Liquid.

GENERAL INFORMATION: This mixed C₃ stream contains primarily mono and di-olefin five-carbon hydrocarbons, including isoprene, piperylenes, and various pentylene isomers. It is used in resins and other polymers.

SHIPPING INFORMATION: Flammable liquid. NOS (Petroleum Oil, NOIBN). Red label. Tank cars, tank trucks.

C₆ AROMATIC CONCENTRATE Mixed Isomers

HYDROCARBONS AND POLYMERS DIVISION

FORMULA: (C₆H₅)₂C=C₆H₅

MOLECULAR WEIGHT: 120.2

STANDARD FORM: Liquid.

GENERAL INFORMATION: This is a highly concentrated C₆ aromatic stream containing primarily tri-methyl-benzene isomers. It is used in specialty solvent applications and in manufacture of chemical intermediates.

SHIPPING INFORMATION: Petroleum Naphtha. Tank cars, tank trucks.

ETHYLENE

HYDROCARBONS AND POLYMERS DIVISION

STANDARD FORM: Gas

FORMULA: C₂H₄

MOLECULAR WEIGHT: 28.05

TYPICAL ANALYSIS: 99.80% min.

USES: Major uses are in the production of polyethylene, ethyl alcohol, ethylene glycol and styrene and various other chemical intermediates.

SHIPPING INFORMATION: Ethylene Gas by Pipeline.

PROPYLENE

HYDROCARBONS AND POLYMERS DIVISION

FORMULA: CH₃CH=CH₂

MOLECULAR WEIGHT: 42.1

STANDARD FORM: Liquid (under pressure).

GRADES: 92% min. purity; 80% min. purity.

GENERAL INFORMATION: Propylene is an olefinic hydrocarbon raw material used in manufacture of alcohols, acrylonitrile, phenol and other chemical intermediates. The other principal component in both grades is propene.

SHIPPING INFORMATION: Liquefied petroleum gas. Flammable gas; red gas label. Tank cars, tank trucks.

RESIN OIL

HYDROCARBONS AND POLYMERS DIVISION

STANDARD FORM: Liquid.**GENERAL INFORMATION:** Resin Oil is a highly unsaturated alkyl-aromatic hydrocarbon mixture used in the manufacture of high-grade petroleum resins.**SHIPPING INFORMATION:** Petroleum naphtha. Tank cars, tank trucks.**RESIN PR**

HYDROCARBONS AND POLYMERS DIVISION

DESCRIPTION: An aromatic resinous petroleum residue.**USES:** In the production of petroleum coke, carbon black and miscellaneous other industrial applications.**SHIPPING CLASSIFICATION:** "Resinous petroleum residue—by-product of ethylene production." In barges, tank cars and trucks.**TOLUENE**

HYDROCARBONS AND POLYMERS DIVISION

FORMULA: C_6H_5 ; C_7H_8 **MOLECULAR WEIGHT:** 92.1**STANDARD FORM:** Liquid.**GENERAL INFORMATION:** Toluene is an aromatic hydrocarbon, used in the manufacture of a variety of organic intermediates and in a broad range of solvent applications.**SHIPPING INFORMATION:** Toluol. Flammable liquid; red label. Tank cars, tank trucks.**XYLENES, MIXED** *Mixture of isomers*

HYDROCARBONS AND POLYMERS DIVISION

FORMULA: $(\text{C}_6\text{H}_4)_2$; C_8H_{10} **MOLECULAR WEIGHT:** 106.2**STANDARD FORM:** Liquid.**GENERAL INFORMATION:** Mixed Xylenes are used in manufacture of chemical intermediates and in specialty solvent applications.**SHIPPING INFORMATION:** Xylol. Flammable liquid; red label. Tank cars, tank trucks.**PETROLEUM ADDITIVES****METHYL DIPHENYL PHOSPHATE** *(Phosfon® MDP)*

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Clear, oily liquid.**SPECIFICATIONS:** Color APFA 200 max.; Sp. Gr. 1.225–1.235 at 25°/25° C.; phosphorus 11.8% min.; pour point –85°F.**USES:** Effective in combating abnormal combustion due to glowing combustion chamber deposits and fouled spark plugs. A proved surface film-forming control agent and combustion deposit modifier.**SHIPPING INFORMATION:** Carbon, Gum or Sludge Removing Compounds, NOIBN; 55-gal., non-returnable black iron drums, tank cars, tank trucks.**SANTOLENE® C FUEL OIL ADDITIVE**

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**PROPERTIES:** Viscosity @ 100°F. 250 SUS, Flash Point, °F. 170. Sp. Gr. 60°/60°F. 0.884.**USES:** Corrosion and rust inhibitor in light petroleum distillates resulting in significant reduction of rusting and corrosion of pipelines and other petroleum product transmission equipment.**SHIPPING INFORMATION:** Petroleum Oil NOIBN. 55-gal. steel drums; tank cars.**SANTOLENE® F-C FUEL OIL ADDITIVE**

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**PROPERTIES:** An oily liquid having the following typical properties: Sp. Gr. 60°/60°F. 1.02; color ASTM diluted 7; barium 10%; sulfur 2%.**USES:** Functions as a dispersant in burner fuel oils to prevent screen clogging and reduce rusting. Concentrations as low as .002% have been satisfactory.**SHIPPING INFORMATION:** Petroleum Oil NOIBN. 54-gal. black iron drums.**SANTOLENE® J FUEL OIL ADDITIVE**

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**PROPERTIES:** An amber colored liquid having the following typical properties: Viscosity of 130 centistokes at 210°F.; Flash Point 300°F.; Specific Gravity at 60°/60°F. of 0.840.**USES:** Fuel oil stabilizing agent designed to prevent color degradation and sediment formation and reduce rusting in fuel oils. A concentration of 25 pounds per 1000 barrels is satisfactory for most base oils.**SHIPPING INFORMATION:** Chemicals NOIBN. 55-gal. black iron drums; tank cars.**SANTOLUBE® 70 OIL ADDITIVE**

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**PROPERTIES:** An oily viscous liquid having the following typical properties: Sp. Gr. 0.926 at 60°/60°F.; Saybolt Universal viscosity 240 seconds at 210°F.**USES:** Rust inhibitor for turbine oils.**SHIPPING INFORMATION:** Chemicals NOIBN. 55-gal. steel drums.**SANTOLUBE® 314 OIL ADDITIVE**

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**PROPERTIES:** An oily liquid fluid having the following typical properties: Sp. Gr. 60°/60°F. of 1.04; Wt. per gallon 60°/60°F. 78.65; Viscosity @ 210°F. SUS, 130; Flash Point 000°F., 365; Barium, % wt. 0.55; Calcium, % wt. 2.15; Phosphorus, % wt. 0.35; Sulfur, % wt. 2.25; and Zinc, % wt. 0.35.**USES:** Santolube 314 is a multi-functional additive for crankcase lubricants that at 12.0% to 13.0% volume is designed to meet the requirements of Caterpillar specification Series III, M11. Spec. MIL-L-46199 and ASTM Service MS.**SHIPPING CLASSIFICATION:** Petroleum Oil NOIBN.

55-gal. steel drums; tank cars and tank trucks.

SANTOLUBE® 392 OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**PROPERTIES:** Flash Point 330°F.; phosphorus 7.3%; sulfur 19.2%; zinc 6.3%; viscosity at 100°F. 1200 SUS, at 210°F. 60 SUS; Sp. Gr. at 60°/60°F. 1.104.**USES:** An effective inhibitor and motor oil anti-oxidant for upgrading the quality of straight base oils when used alone and which is also used in combination with detergent-dispersant additives (e.g., Santolubes 203-C, 333, 401, 410) to meet operating conditions imposed by passenger cars, trucks, tractors and other equipment powered by petroleum fuels.**SHIPPING INFORMATION:** Petroleum Oil NOIBN. 55-gal. black iron drums or tank cars.**SANTOLUBE® 393 OIL ADDITIVE
(ZINC DIALKYL DITHIOPHOSPHATE)**

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.**PROPERTIES:** A liquid with the following typical properties: Viscosity at 100°F. of 150 centistokes; Flash Point 260°F.; Sp. Gr. 60°/60°F. of 1.120.**USES:** An effective and versatile anti-oxidant and bearing corrosion inhibitor for lubricating oils. Finds wide application in compounding Premium and Heavy Duty Motor Oils.**SHIPPING INFORMATION:** Chemicals NOIBN. 55-gal. black iron drums; tank cars.

0557316

Monsanto

TOWOLDMON0041050

SANTOLUBE® 394-C OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: An amber, viscous liquid with the following approximate properties: viscosity 15 to 25 cts. at 210°F.; Sp. Gr. 1.02 at 60°/60°F.; phosphorus 4.7%; sulfur 13.1%.

USES: An effective and versatile anti-oxidant and bearing corrosion inhibitor for engine lubricating oils. Finds wide application in compounding Premium and Heavy Duty Motor Oils.

SHIPPING INFORMATION: Petroleum Oils NOIBN. 55-gal. steel drums; tank cars.

SANTOLUBE® 395-X OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: An amber liquid with the following typical characteristics: Viscosity 12 to 18 cts. at 210°F.; Sp. Gr. 1.005 at 60°/60°F.; phosphorus 3.7%; sulfur 11%; barium 1.1%.

USES: An oxidation and bearing corrosion inhibitor for crankcase oils designed to meet Premium Motor Oil requirements.

SHIPPING INFORMATION: Petroleum Oil NOIBN. 55-gal. steel drums; tank cars.

SANTOLUBE® 845 OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: An oily liquid fluid having the following typical properties: Sp. Gr. 60°/60°F. 1.03; Wt. per gal. 8.57; Viscosity 60°/60°F. SUS. 2.75; Flash Point COC°F. 350; Calcium, % wt. 4.3; Phosphorus, % wt. 1.21; Sulfur, % wt. 2.85; and Zinc, % wt. 1.30.

USES: In appropriate base stocks, Santolube 845 offers engine performance designated by A.F.I. DG and DM classifications and by Mil Spec. MIL-L-2104A.

SHIPPING CLASSIFICATION: Petroleum Oil NOIBN.

55-gal. steel drums; tank cars and tank trucks.

SANTOLUBE® 875 OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: An oily liquid fluid having the following typical properties: Sp. Gr. 60°/60°F. 1.03; Wt. per gal. 8.60°/60°F. 8.57; Viscosity 60°/60°F. SUS. 2.75; Flash Point COC°F. 350; Calcium, % wt. 4.3; Phosphorus, % wt. 1.21; Sulfur, % wt. 2.85; and Zinc, % wt. 1.30.

USES: Santolube 875 is a multi-functional crankcase lubricant additive designed to 5.5% to 5.8% volume to give 1955 "MS" and Mil Spec. MIL-L-2104B performance.

SHIPPING CLASSIFICATION: Petroleum Oil NOIBN.

55-gal. steel drums; tank cars and tank trucks.

SANTOPOID® 22-RI GEAR OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A foam-inhibited, dark, oily liquid having superior rust preventive properties and having the following typical properties: Sp. Gr. 60°/60°F. 1.135; Flash Point 300°F.; sulfur 13.3%; phosphorus 4.0%; chlorine 14.5%; zinc 3.7%.

USES: Used in compounding gear lubricants as defined by the American Petroleum Institute as GL-4 type service. Also used in compounding gear lubricants complying with MIL-L-21021A Ordinance (this specification will be called MIL-L-2105B when it receives full acceptance by the armed services as anticipated).

SHIPPING INFORMATION: Chemicals NOIBN. 54-gal. black iron drums; tank cars.

SANTOPOID® 23-RI GEAR OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A foam-inhibited, dark liquid having superior rust preventive properties and the following typical properties: Pour Point +15°F.; flash point 300°F.; Sp. Gr. 60°/60°F. 1.130; vis. at 100°F. 750 SUS; sulfur 13.3%; chlorine 14.0%; phosphorus 4.0%; zinc 3.7%.

USES: To compound multipurpose Hypoid lubricants providing adequate performance in automotive axles equipped with limited-slip mechanisms, and as well to formulate gear lubricants complying with MIL-L-21021A Ordinance (this specification will be called MIL-L-2105B when it receives full acceptance by the armed services as anticipated).

SHIPPING INFORMATION: Chemicals NOIBN. 54-gal. black iron drums; tank cars.

SANTOPOID® 33 GEAR OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A foam inhibited, dark, oily, viscous liquid with the following typical properties: Sp. Gr. 1.13 at 60°/60°F.; Flash Point 250°F.; Saponification viscosity 90 at 210°F.; sulfur 8.5%; chlorine 20.0%; phosphorus 0.50%.

USES: Recommended for compounding gear lubricants formerly known as Military Specification MIL-L-2105 quality.

SHIPPING INFORMATION: Petroleum Oil NOIBN. 55-gal. steel drums; tank cars.

SANTOPOID® 35 GEAR OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A foam inhibited, dark, oily, viscous liquid with the following typical properties: Sp. Gr. 60°/60°F. approx. 1.15; flash point 250°F.; viscosity 60 cts. at 210°F.; sulfur 8.4%; chlorine 25%; phosphorus 0.54%.

USES: Used for compounding gear lubricants of former MIL-L-2105 quality.

SHIPPING INFORMATION: Petroleum Oil NOIBN. 55-gal. black iron drums; tank cars.

SANTOPOID® S OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A dark, oily, viscous liquid, chemically a chlor-naphthalene xanthate. Sp. Gr. approximately 1.19 at 60°/60°F.; Flash Point 250°F.; viscosity 63 cts. at 100°F.; sulfur 11%; chlorine 31%.

USES: Santopoid S may be used for compounding extreme pressure lubricants. Lower percentages are used for milder S. P. Products.

SHIPPING INFORMATION: Petroleum Oil NOIBN. 55-gal. steel drums; tank cars.

SANTOPOUR® C OIL ADDITIVE

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A dark liquid with the following typical properties: Flash Point 360°F.; viscosity 1020 SUS at 210°F.; Sp. Gr. 60°/60°F. 0.910.

USES: An effective and economical pour point depressant for all types of wax-bearing oils. Effective at concentrations as low as 0.02%.

SHIPPING INFORMATION: Petroleum Oil NOIBN. 55-gal. black iron drums; tank cars.

PLASTICS RESINS PLASTICIZERS

COLORANTS**DRYCOL® DRY COLORANTS**

GERING PLASTICS COMPANY

STANDARD FORM: Free-flowing powder.

PROPERTIES: Available in any matched color, specially formulated for polyethylene, styrene and styrene copolymers, vinyl, butyrate, acetate, polypropylene, acrylic, ABS, nylon and styrene acrylonitrile. Special wetting agent added to assure dustless blending and good dispersion.

USES: Principal application is in-plant dry coloring of natural thermoplastics, accomplished by adding a pre-measured amount of Drycol to a given amount of natural thermoplastic resin and tumbling to assure good dispersion.

SHIPPING INFORMATION: Available in pre-measured bags for blending with 50 or 100 lbs. of natural thermoplastic resin. Also available in bulk form, packed in drums.

MASTERBATCH COLOR CONCENTRATES

GEIANG PLASTICS COMPANY

STANDARD FORM: Uniform pellets.

PROPERTIES: Available as a color pigment concentration, specially compounded in thermoplastic resin and supplied in pellet form. Made in various concentrations to permit let-down ratios with natural resins up to 100:1. Any thermoplastic material in any matched color, can be furnished in Masterbatch color concentrated form.

USES: For use as in-plant colorant of natural thermoplastic. This is accomplished, in a 10X (10 strength) concentration, by adding 1 part of Masterbatch to 10 parts of natural thermoplastic and tumbling in a drum. Recommended for extrusions, including monofilament, as well as injection and blow molding applications.

SHIPPING INFORMATION: Available in 50-pound bags or in bulk form.

"UC" DRYCOL® DRY COLORANTS

GEIANG PLASTICS COMPANY—LITERATURE AVAILABLE

STANDARD FORM: Free-flowing powder.

PROPERTIES: Available in a range of stock colors. UC Drycol is a specially formulated dry colorant that is compatible with any of the following thermoplastics: styrene and styrene acrylics, acetate, butyrate, vinyl, styrene acrylonitrile, acrylic, polyethylene, ABS, polypropylene and nylon. Where more critical color matching is required, conventional Drycol or (Gering) Masterbatch Color Concentrates are recommended. Combined with a special wetting agent to assure uniform blending and excellent dispersion.

USES: For use as in-plant dry colorant of natural thermoplastic, accomplished by adding a pre-measured amount of UC Drycol to a given amount of natural thermoplastic resin and tumble to assure good dispersion.

SHIPPING INFORMATION: Available in pre-measured bags for blending 50 or 100 pounds of natural thermoplastic resin. Also available in bulk, packed in drums.

NYLON RESIN

NYLON 6/6 AND 6/10 RESIN

Chestrand Nylon Resin for molding and extrusion

CHESTRAND COMPANY DIVISION

STANDARD FORM: Natural and colored pellets.

GENERAL INFORMATION: Prime 6/6 and 6/10 resin for molding and extrusion.

ORDERS: Include color, heat, hydrolysis and weather stabilized.

USES: Fasteners, insulation, machine stock, gears, bearings, and monofilament bristle jacks.

STYRENE RESINS/PLASTICS

LUSTRAN® ABS AND SAN MOLDING AND EXTRUDING COMPOUNDS

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

Lustran I ABS

Extrusion	Molding	
781	710	Highest shock resistance, greatest elongation, greatest flexibility.
	610	High shock resistance, good tensile strength, intermediate rigidity.
461	410	Medium shock resistance, intermediate rigidity, high tensile strength, hard surface, high gloss.
281	210	Highest tensile strength, highest gloss, best chemical resistance, best abrasion resistance.
	720	Excellent for use in applications requiring higher heat resistances.
	620	
	420	
	220	Physical properties same as 61 series. Primary use for profile extrusions with high gloss application.
	202	
	402	
	702	

Lustran A SAN

Extrusion & Molding

Transparency, high strength, highest rigidity, chemical resistance to such chemicals as acids, bases and petroleum derivatives.

20 Series

LUSTREX® STYRENE MOLDING COMPOUND

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORMS: Monsanto *Lustrex*, one of the lightest and most widely used thermo-plastic molding materials, is available for compression molding, injection molding and extrusion in all types of machines and molds. Special formulations available for sheet extrusion and vacuum forming applications. Special formulations for general purpose application: *Lustrex Hi-Flow 55* (improved Blow), *Lustrex Hi-Flow 66* (good flow, moderate set-up), *Lustrex Hi-Flow 77* (good flow, fast set-up), medium impact and high impact strength applications. *Lustrex Hi-Test 42-1* and *Lustrex Hi-Test 48* (medium impact), *Lustrex Hi-Test 88* (high impact); heat resistance applications: *Lustrex High-Heat 99*, 101, 102, *Lustrex Hi-Test 91-1* (heat resistant, high impact).

GENERAL INFORMATION: Other special formulations available for applications requiring ultra-violet light stability (general purpose and impact *Lustrex perma-fine*) and dust resistance (general purpose and impact formulations of *Lustrex Lo-Stat*).

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Molding Compound. Monsanto *Lustrex* is tasteless, odorless and non-toxic with high dimensional stability, hardness, rigidity and dielectric strength. It can be molded to any sharply defined detail and finish. Available in a broad range of transparent, translucent and opaque colors as well as crystal.

USES: A wide range of typical applications includes: Refrigerator parts, toys, packaging, conditioner cabinets, radios, housewares, wall tile, television components, displays, electrical equipment, lighting fixtures, furniture drawers and phonograph records.

INDUSTRIAL USERS: Automotive, Construction, Electronics, Machinery and Appliances, Packaging, Toys, Housewares, Furniture, Lighting.

SHIPPING INFORMATION: Hopper Cars (Dri-Flo) fiberboard containers (1000 lbs.), multiwall bags (50 lbs.), drums (350 lbs.), Rail: Plastics, Synthetic, Other Than Liquid, NOIBN, Truck: Plastics, Granules.

LUSTREX® STYRENE EXTRUDING AND CALENDERING MATERIAL

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Monsanto *Lustrex* styrene is furnished in pellets, either natural or colored.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Extruding and calendaring material. Can be extruded as sheet or profile shapes for various applications requiring high impact strength.

USES: Monsanto *Lustrex* styrene is widely used for such applications as: Refrigerator door liners, toys, lighting fixtures and games.

INDUSTRIAL USERS: Automotive, Construction, Electronics, Machinery and Appliances, Packaging, Toys, Housewares, Furniture, Lighting.

SHIPPING INFORMATION: Hopper Cars (Dri-Flo), fiberboard containers (1,000 lbs.), multiwall bags (50 lbs.), drums (350 lbs.), Rail: Plastics, Synthetic, Other Than Liquid, NOIBN, Truck: Plastics, Granules.

LYTRON® RESINS

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Powder.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Surface coating resins. Promotes adhesion, stabilizes, hardens and thickens emulsion systems.

USES: Alkali-soluble resins used in water and latex coating systems.

INDUSTRIAL USERS: Paint, Varnish and Lacquer, Automotive, Chemicals, Machinery and Appliances, Packaging, Pulp and Paper, Rubber, Textiles, Emulsion floor waxes, Detergents.

SHIPPING INFORMATION: Bags, Rail: Plastics, Synthetic, Other Than Liquid, NOIBN, Truck: Plastics, Granules.

LYTRON® SYNTHETIC RESINS

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Water emulsion.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Industrial Resin. Used as binders or dispersing agents.

USES: *Lytron* emulsions are used as a binder for glass fibers employed in battery separators, filters, etc. In powder form *Lytron* is used to prevent clay balls in foundry sand and waste water clarification systems.

INDUSTRIAL USERS: Chemicals, Construction.

SHIPPING INFORMATION: Steel Drums (475 lbs.), tank cars, tank trucks, Rail: Plastics, Synthetic Liquid, NOIBN, Truck: Plastics, Liquid, NOI.

0557318

Monsanto

TOWOLDMON0041052

POLYVINYL ACETATES

GELVA® COPOLYMER SOLUTIONS

SHAWINGHAM RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: Water white or slightly yellow solvent solutions.

PROPERTIES: Available in two types of solvent solutions—GELVA C-254B in benzene and GELVA C-254H in a mixture of hexane-heptane. Viscosity of GELVA C-254B is 1200 cps. while GELVA C-254H has a viscosity of 500 cps. Both materials are supplied at 35% solids.

USES: An effective release coating for pressure sensitive tapes. Gives controlled release when used in combination with common backing agents which have been applied to paper from organic solutions.

SHIPPING INFORMATION: Available in 55-gallon, resin-lined, closed-head, steel drums, 420 lbs. net weight for GELVA C-254B, 330 lbs. net weight for GELVA C-254H. Also shipped in truckload quantities (20,000 lbs. min.).

GELVA® POLYVINYL ACETATE COPOLYMER RESINS

SHAWINGHAM RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: White, fine beads.

PROPERTIES: Available in six grades of carboxylated polyvinyl acetate resins which have all the properties of polyvinyl acetate but are also soluble in dilute alkali. The resins are also soluble in organic solvents. Films produced from solvent solutions are water resistant, yet may be removed with dilute alkali. Viscosity of 96 grams of resin in 1000 ml. of ethanol ranges from 10 cps. for GELVA C-3 V-10 to 110 cps. for GELVA M-7 V-100. Softening points range from 23° to 180°C. The copolymers have outstanding adhesion to such materials as metals, leather and celluloses.

USES: Typical applications include hot melt and solvent adhesive; heat-sealable clear coatings for paper and plastic films with excellent gloss, printability, grease-proofness, wet rub and abrasion resistance; sizing for rayon, cotton and acetate yarns; anti-tarnish lacquers for silver and metal objects and temporary protective coatings for metal surfaces in aircraft and ships. The alkali soluble nature of copolymer coatings allows easy recovery of scrap in a number of applications.

SHIPPING INFORMATION: Available in non-returnable fiber drums, 100 lbs. net weight.

GELVA® POLYVINYL ACETATE EMULSIONS

SHAWINGHAM RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: Aqueous dispersions of polyvinyl acetate resins—milk-white in color.

PROPERTIES: Available in a full range of homopolymers and copolymers which vary in viscosity, particle size, molecular weight, film forming properties and performance on various substrates. Some grades are borax stable, dextrine compatible and have varying solvent tolerance. Emulsions are also compatible with a wide range of plasticizers, resins and extenders, pigments and dyes. Films and coatings produced from the different emulsions vary in adhesion, tensile strength, hardness, heat-sealing temperature, water resistance and other physical properties.

USES: Typical applications are in the manufacture of adhesives for paper, wood, vinyl, leather, cloth, polyethylene, foil and a wide variety of surfaces, as binders for paper pulp, cork and textile fabrics; as coatings for paper, cloth, wood, metals and ceramics; as fast drying, tough, odorless paints; as coatings and impregnators for paper and paperboard; as pigment binders for paper and paperboard coatings; and as textile sizes and finishes.

SPECIFIC USES: Each grade of emulsion generally has a number of broad end uses. However, in some cases, the emulsions are highly suited for specific applications. GELVA Latex 925 makes a high pick resistant, non-yellowing, odorless pigment binder for paper coatings. GELVA Emulsion TS-100 is used in making adhesives with good performance on various surfaces such as vinyl, Mylar and similar surfaces. GELVA Emulsions S-8 and S-96, which are dextrine compatible, are used in making removable adhesives. GELVA Emulsions S-8 and S-96 are used as wet-end additives in producing tough, bend-resistant paperboards. GELVA Emulsion S-53 has superior compounding stability, quick tack and bond strength and is used in a wide number of adhesive applications. GELVA Emulsions TS-30, TS-70 and TS-100 are used in formulating quality exterior and interior paints. Films cast from GELVA C-3 Emulsion are highly water resistant, but, due to carboxyl groups on the polymer chain, are soluble in dilute alkali. Other emulsions are available for specific adhesive, paint and paper coating applications.

SHIPPING INFORMATION: Available in non-returnable steel drums or fiber containers, 500 lbs. net weight in tank trucks (1,000–3,000 gals.) and in rail tank cars (4,500–8,000 gals.).

GELVA® POLYVINYL ACETATE POWDERS 700 AND 702

SHAWINGHAM RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: White or cream-colored free-flowing powders.

PROPERTIES: Available in two grades of spray dried powder—GELVA Powder 700 and GELVA Powder 702. GELVA Powder 700 has long term stability and may be added to dry mix formulations for greater flexibility, toughness, cohesive and adhesive strength and resiliency. GELVA Powder 702 is used where borax stability and dextrine compatibility are essential. Used to produce high solids, low viscosity adhesives and building products which are tough, fast drying, flexible and easy to prepare.

USES: Principal applications are in manufacture of dry mix adhesives and building products. In adhesives, the Powders impart water insensitivity, toughness, flexibility and blocking resistance. Also used as a binder in various cementitious building products.

SHIPPING INFORMATION: Available in polyethylene bags within non-returnable fiber drums, 100 lbs. net weight.

GELVA® POLYVINYL ACETATE RESINS

SHAWINGHAM RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: Granules and lumps.

PROPERTIES: Available in eight different grades with viscosities ranging from 1.35 cps. to 900 cps. 98 grams of resin in 1000 ml. of benzene. GELVA Resins are thermoplastic, transparent, colorless, odorless and tasteless with excellent adhesion to a wide variety of surfaces. The grades also differ in tensile strength, flexibility and softening point. Soluble in ketones, esters, chlorinated and aromatic hydrocarbons, and certain alcohols. Compatible with many plasticizers, including phthalates and o-phthalates.

USES: Typical applications for GELVA Resins include hot melt and solvent based adhesives, paper and textile coatings, printing inks, and as a base for chewing gum.

SHIPPING INFORMATION: Available in multi-wall bags, 50 lb. net weight. GELVA Resins V-14 shipped in non-returnable fiber drums, 70 lbs. net weight; GELVA Resin V-24 shipped in fiber drums, 83 lbs. net.

GELVA® RESIN SOLUTIONS

SHAWINGHAM RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: Viscous solvent solutions of polyvinyl acetate.

PROPERTIES: Available in four types of GELVA solutions—V-55-E26, V-55-E30 and V-55-E34 in ethyl alcohol; and V-7-M30 in methyl alcohol. Viscosity ranges from approximately 2,500 cps. for V-7-M30 to approximately 55,000 cps. for V-55-E34. Total solids range from 28% to 50%. Films and coatings produced from the solutions have excellent gloss, clarity and water resistance. They are also non-corrosive and neutral.

USES: Can be used for bonding paper, wood, glass, leather, textiles, ceramics, metal foil and many plastic materials. Used in shoe cements, in laminating metal foil to cellophane and for preparing plastic adhesives for the adhesives in the paper industry, solutions are used to produce transparent high gloss coatings, which adhere well to surfaces and are unusually stable to light and oxygen. Also used as overprint varnishes, greaseproof coatings and pigment binders.

SHIPPING INFORMATION: Available in non-returnable steel drums, 400 lbs. net weight, and in truckloads (20,000 lbs. min.) and carloads (30,000 lbs. min.).

POLYVINYL ALCOHOL RESINS

GELVATOL®

SHAWINGHAM RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: White, high bulk density powder.

PROPERTIES: Available in a large number of grades which differ in degree of polymerization, per cent hydrolysis and residual acetate content. Resins are water soluble and dextrine is the most widely used plasticizer. Viscosity of a 4% aqueous solution ranges from approximately 10 cps. for GELVATOL 40-10 to 90 cps. for GELVATOL 1-30. The resins are non-dusting, have high bulk densities which make storage and handling easier. Resins are used in water films cast from GELVATOL are extremely tough and have excellent solvent, oil and grease resistance, high tensile strength, and a high degree of heat stability.

USES: Typical applications include dry mix adhesives and building products; textile sizing and finishing; paper coating and sizing; as protective colloids or surface active agents for emulsion polymers and latexes; as binders for ceramics, etc.; as photo sensitive coatings on stencil screens and printing plates; and as water soluble films for packaging, space, de-fogging, chemicals, etc.

SHIPPING INFORMATION: Available in multi-wall paper bags, 50 lbs. net.

POLYVINYL BUTYRAL RESINS

BUTVAR®

SHAWINIGAN RESINS CORPORATION—LITERATURE AVAILABLE
STANDARD FORM: White free-flowing powder.

PROPERTIES: Produced in five types or grades varying in viscosity and hydroxyl content. Viscosity of 10% solution in ethyl alcohol ranges from 75 cps. (for BUTVAR B-98) to 1570 cps. (for BUTVAR B-72A). The resins are generally soluble in alcohols, glycol esters and certain mixtures of polar and non-polar solvents. They are compatible with a number of plasticizers including phthalates, phosphates, castor oils and others.

USES: Used in making metal primers and conditioners; wood primers and sealers, structural and non-structural adhesives, textile coatings and printing inks. As a coating for rainwear and other textiles, BUTVAR provides outstanding adhesion, flexibility, abrasion resistance, water resistance and is transparent. As an additive to metal and wood coatings and primers, the resins upgrade intercoat adhesion, flexibility, impact and abrasion resistance, and flow properties. Can be used to upgrade coating performance of such thermosetting materials as phenolics, ureas, melamines, epoxies, alkyds, polyurethanes and polyesters.

SHIPPING INFORMATION: Available in lined, non-returnable fiber drums, 120 lbs. net weight. BUTVAR B-98 is available in 110 lb. net weight fiber drums.

POLYVINYL BUTYRAL RESIN DISPERSIONS

BUTVAR® DISPERSIONS BR AND FP

SHAWINIGAN RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: Aqueous dispersion of plasticized polyvinyl butyral resin. Milk-white in color.

PROPERTIES: Dispersions are supplied in two grades which differ in viscosity and plasticizer content. BUTVAR Dispersion BR has a viscosity of 1500 cps. and contains 40 parts plasticizer per 100 parts resin. BUTVAR Dispersion FP has a viscosity of 150 cps. and contains 5 parts plasticizer. Films cast from Dispersion BR are tough, light transparent and dry at room temperature. Dispersion FP films require heating to achieve continuity and non-redispersibility. They dry to clear, colorless films which are unaffected by boiling water. Films of both dispersions are strong and adhere well to a range of surfaces; resistance to water, heat and sunlight is excellent.

USES: Used in textile industry to impart abrasion resistance, durability, strength, slippage control and reduced color crocking to a variety of materials. Used as abrasion resistant finish for automobile seat belts and parachute harnesses. They are also used in the textile industry as a soft, full-bodied finish for rayon, cotton, or nylon; as a durable, non-ravelling finish for filament yarns; and as a finish for curtain and drapery fabrics, glass fabrics, upholstery goods, webbing, awnings, canvas and duck. Also used as a rug backing, and greaseproof, washable coatings for wallpaper, window shades and packaging materials.

SHIPPING INFORMATION: Available in non-returnable 5-gallon steel drums, 425 lbs. net. Less than one drum lots packaged in 5-gallon containers.

POLYVINYL FORMAL RESINS

FORMVAR® RESINS

SHAWINIGAN RESINS CORPORATION—LITERATURE AVAILABLE

STANDARD FORM: White, free-flowing powder.

PROPERTIES: Available in six basic grades varying in viscosity and solubility. Viscosity of a 5% solution in ethylene chloride ranges from 7-11 cps. for FORMVAR 7/70 to 50-80 cps. for FORMVAR 15/95E. The resins are soluble in phenols, some chlorinated hydrocarbons, and mixtures of alcohols and aromatic hydrocarbons. FORMVAR 7/70, with a high acetate content, is also soluble in glycol esters, lower molecular weight esters and ketones. Plasticizers for the resins include phthalates, phosphates, alkydols and many others.

USES: FORMVAR 15/95E is widely used in making tough, heat-resistant wire enamels for hermetic systems. Enamels are solderable, bondable, have high cut-through and burnout resistance, and excellent resistance to common refrigerants. FORMVAR resins are also used in structural and hot melt adhesives; in wash primers, can and drum linings; and as wood sealers and knot sealers.

SHIPPING INFORMATION: Available in non-returnable fiber drums—FORMVAR 7/95 and 7/70, 100 lbs. net; FORMVAR 12/85, 110 lbs. net; and FORMVAR 15/95, 130 lbs. net.

STYMER® VINYL STYRENE

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Stymer LF is vinyl resin, soluble with ammonium hydroxide; Stymer S is styrene copolymer resin, soluble in water.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Textile Resin. Outstanding as sizing agents for acetate. Stymer LF-25 designed as durable size. Stymer S is water soluble removable size.

USES: Sizes for filament acetates.

INDUSTRIAL USERS: Textiles.

SHIPPING INFORMATION: Stymer LF-25—drums (100 lbs.). Stymer S—multiwall bags (50 lbs.); drums (250 lbs.). Rail & Truck: 8-mil. NOBLEN.

VINYL RESINS / PLASTICS

OPALON® VINYL CHLORIDE EXTRUDING AND CALENDERING MATERIAL

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Resins and compounds produced in several formulations for diversified industrial applications.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Opalon® 660 & 650 resins supplied for calendering and extrusion are especially recommended for dry blending, provide color depth, uniformity, toughness and flexibility at low temperatures. Opalon® 630 resin for ease of processing. Opalon® 410 and 440 is a specially developed paste resin for vinyl plastisol compounding, supplied as a "stir-in" powder to increase speed and ease of preparation.

USES: Typical applications are wire & cable insulation, rainwear, upholstery, floor tile, coatings (metal, paper, fabrics and glass), foams, spacers, garden hose, slush moldings, and dipping operations.

SHIPPING INFORMATION: Multiwall bags (50 lbs.); resins in slide cars (10,000 lbs.), Resins: Rail—Plastics, Synthetic. Other than liquid NOBLEN, Truck—Plastics, Powder, Compounds: Rail—(same as above) Truck—Plastics, Granules

OPALON® VINYL CHLORIDE MOLDING COMPOUNDS

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Free-flowing resins available to formulate opaque, translucent or transparent compounds. Compounds available in granular form for injection and compression molding.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Molding material. Outstanding heat stability, moldability, short molding cycles and low shrinkage. Resistant to moisture, oxidation, most acids and alkalis, petroleum and many common organic solvents.

USES: Appliance parts, toys, masks, goggles, swim accessories, zirconia, sporting goods, handles, knobs, coil forms, housings, wiring devices, electrical system components, housewares and phonograph records.

INDUSTRIAL USERS: Automotive, Construction, Machinery and Appliances, Rubber, Textiles.

SHIPPING INFORMATION: Multiwall bags (50 lbs.). Resin to slide cars (10,000 lbs.). Rail: Plastics, Synthetic. Other Than Liquid, NOBLEN, Truck: Plastics, Powder.

SAXFLEX® VINYL BUTYRAL

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: A continuous adhesive film supplied in clear, translucent, tinted or graded color, for the plastic interlayer in laminated safety glass.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Laminating material. Tough and resilient; transparency of a superior quality; excellent adhesion to glass.

USES: Saxflex is used as a protective interlayer for laminating safety glass in automotive, aircraft, and architectural applications. It can be printed in decorative patterns or used for laminating emblems between layers of glass for room divider, shower stalls, interior doors and wall panels, exterior doors and table tops. Industrial uses of Saxflex include light and heat control, ultra-violet excluding and safety applications.

SHIPPING INFORMATION: Standard 15 in. and 30 in. film supplied in 750 ft. rolls; heavier gauges available in 400 to 800 ft. rolls; shipments made in tubes or on pallets. Rail: Plastics, Sheets, not woven, NOBLEN, Truck: Plastic film, transparent or translucent, not woven, not printed, not printed in sheets, not further processed than cut to size.

STYMER[®] VINYL STYRENE

See Page MS/33

ULTRON[®] VINYL CHLORIDE Flexible Film and Sheeting.

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Flexible film, embossed or plain, in gauges .0027 to .0307 and widths up to 75". Special formulated film with "built-in" properties and varying degrees of flexibility are available for specific industrial and agricultural applications.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Fabricating material. *Ultron* film is noted for its uniformity of gauge and color clarity. Water resistant, abrasion resistant. Available as translucent, opaque or transparent film which may be printed, embossed or molded. Tasteless, tough, pliable and long-lasting. *Ultron* film is highly adaptable to various manufacturing techniques such as laminating and heat sealing.

USES: Low temperature formulations are used as protective coverings for machinery. Industrial applications include moisture barriers, industrial and electrical tapes. As a laminating material, *Ultron* has proven valuable for wall covering materials, flooring, glass heat insulation, paper and swimming pool liners.

INDUSTRIAL USERS: Agriculture, Automotive, Construction, Machinery and Appliance, Textiles, Furniture, Housewares, Wire and Cable, Luggage.

SHIPPING INFORMATION: Cardboard Box, (150 lbs.) Heavy duty Kraft paper wrap, (500 lbs.) Roll: Plastics, sheets not woven NOIBN. Truck: Transparent or translucent material: Plastic film, transparent or translucent other than cellulose, not woven, not printed in rolls exceeding 85" in diameter. Opaque: Plastic film or sheeting not woven other than cellulose, other than transparent or translucent.

VYRAM[®] RIGID VINYL COMPOUNDS FOR EXTRUSION AND MOLDING

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Free-flowing 1/8 inch cubes in natural and colors.

Vyram 2645 Translucent ultra-violet stabilized rigid vinyl extrusion compound, intermediate impact for architectural applications requiring light transmission.

Vyram 2738 A Type 2 high impact rigid vinyl extrusion compound for industrial applications.

Vyram 2746 An intermediate impact rigid vinyl extrusion compound for industrial applications.

Vyram 2745 An intermediate rigid vinyl extrusion compound ultra violet outdoor stabilized for structural applications.

Vyram 3000 An intermediate impact rigid vinyl extrusion and injection molding material formulated expressly for pipe and fittings. Meets NSF requirements for use with potable water.

PROPERTIES: Balanced combinations of high strength, toughness, chemical resistance, abrasion resistance, non-combustible and ultra-violet light resistance. This product's ease of fabrication, uniform quality and increased extrusion rates mean lower processing costs and improved part quality.

SHIPPING INFORMATION: Supplied in 50-lb. bags or bulk carloads.

POLYETHYLENES**MONSANTO[®] POLYETHYLENE MOLDING COMPOUNDS**

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Pelleted molding compounds are available for blow molding and are readily processed by dry blending into a broad range of colors.

GENERAL PROPERTIES AND PERFORMANCE CHARACTERISTICS: Molding compound. One of the most useful and versatile of all plastics, Monsanto Polyethylene, natural, is chemically inert, non-toxic and odorless. Products molded from Monsanto Polyethylene resins are tough and resilient with a high impact resistance and flexibility over a wide temperature range.

USES: Some of the typical applications are: Packaging and packaging components, "squeeze" bottles, vials, molded fibers and closures.

MPE 200 High density (.950) blow molding resin
MPE 201 High density (.950) blow molding resin, anti-stat
MPE 210 High density (.955) blow molding resin
MPE 211 High density (.955) blow molding resin, anti-stat
MPE 80 Low density for squeeze bottles

SHIPPING INFORMATION: Hopper cars; fiberboard containers (2 types, both 1,500 lbs.); multiwall bags (50 lbs.); Roll—Plastics Synthetic Other than Liquid, NOIBN. Truck—Plastics, Granules.

MONSANTO[®] POLYETHYLENE EXTRUSION COATING MATERIALS

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Supplied in pellet form.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Paper and coating resin. Fortifies surface with high dielectric and scuff resistance. Heat sealable. Improves printability of wax coatings.

USES: A reinforcement for paper and board coatings for packaging and coating for flexible packaging materials.

MPE 70 General Purpose
MPE 71 High-speed coating and laminating resins

MPE 72 Slip-grade coating resin
MPE 75 Approved milk carton and military barrier coating resin

MPE 76 For use in multiwall bag and food board construction
MPE 77 Versatile, high-strength

MPE 10406 Black compound; high-strength; excellent bonding

SHIPPING INFORMATION: Hopper cars; fiberboard containers (2 types—1,500 lbs.); multiwall bags (50 lbs.)

MONSANTO[®] POLYETHYLENE FILM AND SHEET MATERIAL

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Supplied in pelleted form.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Extruding material. Monsanto Polyethylene is a tough, impact-resistant resin, extruded film is chemically resistant, flexible over wide temperature ranges, non-toxic, odorless, nonpolar, low dielectric and easily processed by dry blending into a wide range of colors.

USES: Packaging films, vapor barrier materials, agriculture films, and high clarity films.

MPE 40 High molecular weight, low-density film resin for heavy-duty packaging

MPE 41 High molecular weight, low-density film resin for high-slit, high-strength films

MPE 49 High molecular weight, low-density film resin for anti-static, high-strength films

MPE 99 General purpose packaging and industrial film

MPE 706 Tough, industrial

MPE 34 For farmnet bag use

MPE 35 & 39 High-clarity medium impact

MPE 48 High-clarity overwrap

SHIPPING INFORMATION: Synthetic Resin Granules. Hopper cars; fiberboard containers (2 types, both 1500 lbs.); multiwall bags (50 lbs.); 10 mil polyethylene bags (50 lbs.); for wire and cable compounds. Roll—Plastics, Synthetic. Other than Liquid, NOIBN. Truck—Plastics, Granules

MONSANTO[®] POLYETHYLENE WIRE AND CABLE COMPOUNDS

HYDROCARBONS AND POLYMERS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Pelleted form, natural and black.

PROPERTIES & PERFORMANCE CHARACTERISTICS: Extruding material. Monsanto Polyethylene is used for wire insulation and jacketing. All compounds contain electrical grade antioxidants, are of high purity, low dielectric, and can be processed by dry blending into a wide range of colors.

MPE 12553 Natural compound for insulation

MPE 12 Black compound for line and drop wire

MPE 12 & 11302 Black compound for jacketing

MPE 11 Black compound for infantry field wire insulation

MPE 16A Black compound for telephone cable jacketing, requiring maximum stress crack resistance

MPE 17 Black compound for insulation of line and service drop wires

MPE 18 Black compound for telephone cable jacketing especially R&A type cables

SHIPPING INFORMATION: Synthetic Resin Granules. Hopper cars; fiberboard containers (2 types, both 1500 lbs.); multiwall bags (50 lbs.); 10 mil polyethylene bags (50 lbs.); for wire and cable compounds. Roll—Plastics, Synthetic. Other than Liquid, NOIBN. Truck—Plastics, Granules

PHENOLIC RESINS**RESINOX[®] PHENOLIC** Lump, Flake and Resin Compound

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Powder, lump or flake.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Industrial Resin. Excellent resistance to high heat, maximum bond strength and good chemical resistance.

USES: Manufacturing of Resinoid grinding wheels, brake linings, pulp moldings and for bonding of foundry sand in the production of shell molds and cores.

INDUSTRIAL USERS: Automotive, Chemicals, Electronics, Jets, Missiles, Machinery and Appliance, Foundry, Abrasives.

SHIPPING INFORMATION: Multiwall bags (50 lbs.); non-returnable fiber drums (20-275 lbs.); Roll—Plastics, Synthetic. Other Than Liquid, NOIBN. Truck—Plastics, Powder.

RESINOX® LIQUID PHENOLIC RESINS

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Water solutions.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Industrial Resin. Excellent resistance to high heat, maximum bond strength and good chemical resistance.

USES: For impregnating or coating filler materials such as paper, cloth, wood (compex) veneers, glass and mineral wool. Bonding material for Resinoid grindline wheels. Resin for impregnated paper for automotive battery separators. For glass and rock wool thermal and acoustical insulation. Fidelity sand core binder.

INDUSTRIAL USERS: Foundry, Automotive, Chemicals, Construction, Electronics, Jets, Missiles, Machinery and Appliances, Pulp and Paper.

SHIPPING INFORMATION: Steel drums (450-550 lbs.); tank cars, tank trucks, Rail—Plastics, Synthetic, Liquid, NOIBN; Truck—Plastics, Liquid, NOI.

RESINOX® PHENOLIC VARNISHES

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Supplied in alcohol solutions for laminating filler materials—paper, cloth, glass or asbestos. Special high heat resistant formulations are available for use with glass, asbestos and similar fillers for jet and rocket components.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Industrial Resin. Provides tough, durable, heat resistant bonds that also resist acids and weak alkalis.

USES: For impregnating laminate filler materials such as paper, cloth, glass or asbestos. Special high heat resistant formulations are available for jet and rocket components. Used in decorative laminate core stock; electrical and mechanical grade laminates for radio, TV and home electrical appliances; as well as seats, ball-bearing races, pulleys; bushings for light and heavy machinery; cars, planes and ships; oil, chemical and paper filters; sand binders for shell molding.

INDUSTRIAL USERS: Foundry, Automotive, Chemicals, Construction, Electronics, Jets, Missiles, Machinery and Appliances, Pulp and Paper, Rubber.

SHIPPING INFORMATION: Steel drums (450-550 lbs.); tank cars, tank trucks, Rail and Truck, Varnish, NOIBN.

RESINOX®

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Phenolic liquid, solutions.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Surface coating resin. Imparts high heat resistance and promotes good chemical resistance.

USES: Based enamel and industrial finishes for can, drum and tank car linings, special primers and coatings and wire enamels.

INDUSTRIAL USERS: Paint, Varnish and Lacquer, Automotive, Chemical, Machinery and Appliances.

SHIPPING INFORMATION: Steel drums (450 lbs.), Rail—Plastics, Synthetic Liquid, NOIBN, Truck—Plastics, Liquid, NOI.

MELAMINE AND UREA RESINS

RESIMENE® MELAMINE AND RESIMENE® U UREA

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Supplied in organic liquid solution.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Surface coating resin. Imparts improved surface hardness, weathering, alkali and chink resistance. Promotes fast cure and excellent color retention.

USES: Melamine and urea-formaldehyde resins improve baked enamel and industrial finishes on appliances, automobiles and other fabricated metal items.

INDUSTRIAL USERS: Paint, Varnish and Lacquer, Automotive, Chemical, Machinery and Appliances.

SHIPPING INFORMATION: Steel drums (450 lbs.), Rail—Plastics, Synthetic, Liquid, NOIBN, Truck—Plastics, Liquid, NOI.

RESIMENE® MELAMINE

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Available in water-alcohol, soluble spray-dry powders.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Industrial resin. Produces laminates displaying strong durable surface that is heat, flame and chemically resistant. Color stability and high electrical arc resistance are additional characteristics.

USES: Resimene Melamine powder solutions can be combined with paper, cloth and glass fibers to provide a durable surface for all types of furniture, counter tops, cabinets, walls and industrial electrical components.

INDUSTRIAL USERS: Chemicals, Construction, Electronics, Missiles, Machinery and Appliances, Pulp and Paper.

SHIPPING INFORMATION: Multivul bags (50 lbs.); fiber drums (200 lbs.), Rail—Plastics, Synthetic, Other Than Liquid, NOIBN, Truck—Plastics, powder.

RESLOOM® MELAMINE

PLASTIC PRODUCTS AND RESINS DIVISION

STANDARD FORM: Available in powder (Resloom HP) or liquid form (M-75, M-80) as a series of essentially monomeric melamine resin.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Textile resin. Permanently effective to fabrics made from a wide range of textile fibers.

USES: To impart shrinkage control, wrinkle resistance and textural effects to cotton, rayons, synthetics and wools.

INDUSTRIAL USERS: Textiles.

SHIPPING INFORMATION: M-75—550 lb. drums; Resloom HP—100 lb. drums; E-63—325 lb. drums; (except Resloom HP which is in powder form). Powder: Rail—Plastics, Synthetic, Other Than Liquid, NOIBN, Truck—Plastics, Powder, Liquid, Rail—Plastics, Synthetic Liquid, NOIBN, Truck—Plastics, Liquid, NOI.

RESLOOM® E-30 RESINS

See Page M5/52

COAL TAR RESINS

MONTAR® SYNTHETIC RESINS

See Page M5/38

SULFONAMIDE RESINS

SANTOLITE® MHP RESINS

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Hard resin.

SPECIFICATIONS: Hard, practically colorless resin; refractive index (25 gms. in 75 gms. normal butyl acetate) 1.4280-1.4310; penetration (200 gm. load for 5 seconds at 25°C.) 2.0 mm. max.

GENERAL INFORMATION—PROPERTIES: An aryl sulfonamide-formaldehyde resin similar to Santolite MS in characteristics, except that it is much harder, softening at about 42°C., brittle at normal temperatures. Nearly colorless, well adapted to specialty and heat-sealing lacquers, fabric coatings, molding compositions and the like. Being incompatible with drying oils it cannot be used as a varnish material.

USES: Used in spraying, dipping or brushing lacquers to make clear, colorless, odorless coatings of good gloss and adhesion. It does not materially increase the viscosity of the solution and permits the building up of a high-solids content in the lacquer. Compatible with all the common plasticizers.

CONTAINERS: 60-lb. cased cans.

SHIPPING CLASSIFICATION: Resin Synthetic NOIBN Without Filler.

SANTOLITE® MS 80% Industrial Resin.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Light-colored viscous liquid; free-flowing at temperatures above 30°C.; composition 78.8—81.2% Santolite MS, 18.8 to 21.2% solvent.

PROPERTIES: Soft, practically colorless resin made by the condensation of formaldehyde and aromatic sulfonamides.

USES: Santolite MS like Santolite MHP, is compatible with both nitrocellulose and cellulose acetate as a solvent for both. It can be used in any proportion. Forms brittle compositions with both resins but the addition of a plasticizer makes such combinations permanently flexible.

SHIPPING INFORMATION: Resin Synthetic NOIBN Without Filler. 450-lbs. approx., 55-gal. drums; 45-lbs. approx., 5-gal. drums.

RESIN MATERIALS

ADIPIC ACID, FOOD AND TECHNICAL GRADES

See Page M5/13

BISPHENOL A

ORGANIC DIVISION

MOLECULAR WEIGHT: 228.28

STANDARD FORM: White flakes.

SPECIFICATIONS: Off-white flakes; crystallizing point 154.2°C. min.; iron 0.7 ppm max.; free phenol 0.15 max.; moisture 0.15% max.; color in acetone (25-30 ml) 150 APHA max.

USES: An intermediate in the production of epoxy resins (used in surface coatings, adhesives, die-making, laminating, potting, encapsulating and as rigid foams); polycarbonate resins (used in heat-resistant, dimensionally stable, electrically-insulating films, moldings and fibers); oil-soluble phenolic resins; and as an oxidant for oils, greases and vinyl compositions.

SHIPPING INFORMATION: Chemicals NOIBN, 50-lb. bags.

DIBUTYL FUMARATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 248

STANDARD FORM: Liquid.

SPECIFICATIONS: Acidity 0.20 meq/100 grams max.; Color 40 APHA max.; Crystallizing Point -21.0°C. min.; Moisture (KF in methanol) 0.10% max.; Sp. Gr. 25°/25°C. 0.982-0.986.

USES: Internal plasticizing resin former for copolymerizing with vinyl acetate and vinyl chloride for adhesives, textile, paint and paper coatings. Intermediate for chemical synthesis.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal., 18-gauge steel drums with tight heads, 2-inch and 4-inch openings in the head. Gross weight: 498 lbs. Also tankcars or tank trucks 2,000-gal. minimum.

DIBUTYL MALEATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 248

STANDARD FORM: Liquid.

SPECIFICATIONS: Acidity 0.12 meq/100 grams max.; Color 10 APHA max.; Moisture (KF in methanol) 0.15% max.; Sp. Gr. 1.117±0.005.

USES: Internal plasticizing resin former for copolymerizing with vinyl acetate and vinyl chloride for adhesives, textile, paint and paper coatings. Intermediate for chemical synthesis.

SHIPPING INFORMATION: Resins Plasticizer, 55-gal., 20-gauge steel drums with tight heads, 2-inch and 4-inch openings in the head. Gross weight: 540 lbs. Also tankcars or tank trucks—2,000-gal. minimum.

DIOCTYL FUMARATE (DOF)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Acidity 0.20 meq/100 gms. max.; Color, APHA 75 max.; Moisture (KF in Methanol) 0.10% max.; Sp. Gr. 25°/25°C. 0.927-0.940.

PROPERTIES: Dioctyl Fumarate is a clear mobile liquid important as a monomer for polymerization and copolymerization. Polymers varying in physical properties from hard brittle resins to soft, internally plasticized elastic materials, can be made by various monomers and adjusting reaction conditions.

USES: Copolymers of Dioctyl Fumarate with vinyl acetate, vinyl chloride, acrylic and styrene for surface coatings, free films, synthetic lubrication, pigment binders, paper coatings and floor waxes.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, gross 475 lbs.; tankcars and tank trucks.

DIOCTYL MALEATE (DOM)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Acidity 0.20 meq/100 gms. max.; Color APHA 50 max.; Moisture (KF in Methanol) 0.10% max.; Sp. Gr. 25°/25°C. 0.940-0.943.

PROPERTIES: Dioctyl Maleate is a clear mobile liquid especially important as a monomer for polymerization and copolymerization. Polymers varying in physical properties from hard brittle resins to soft, internally plasticized elastic materials, can be made by using various monomers and adjusting reaction conditions.

*Monsanto Trademark


USES: Copolymers of Dioctyl Maleates with vinyl acetate, vinyl chloride styrene and acrylates are of special value in the following: surface coatings; free films; adhesives; oil additives; elastomers; paper coatings; and pigment binders.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 475 lbs. gross; tankcars and tank trucks.

EMA* RESINS (Ethylene Maleic Anhydride Copolymers)

INORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA:



STANDARD FORM: Fine water-soluble powders available as both straight-chain and cross-linked polymers in a variety of molecular weights.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: The EMA resins are easily converted to the free-acid form; and to its sodium and ammonium salts and are readily reacted with alcohols and substituted alcohols and with amines to form esters and resins. By selecting the proper reactant, the following types of derivatives can be prepared: transparent film-formers, polymeric liquids, waxy solids and polyampholytes.

SUGGESTED USES: Beneficiation agent for clays used in oil-well drilling muds; stabilizers and thickeners in liquid detergent and cosmetic formulations; thickeners for water-based latex paints, textile sizes, textile print pastes and binders; suspending agents for ink pigments, thickeners for aqueous resin systems, adhesives, binder for foundry cores, etc.

SHIPPING INFORMATION: Multiwall bags (50 lbs.), F. O. B. Texas City, Texas. Rail and Truck. Sizing NOIBN.

FUMARIC ACID, FOOD AND TECHNICAL GRADES

See Page M5/13

HYDROGENATED BISPHENOL A (HBPA®)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 240.35

STANDARD FORM: Cast solid.

SPECIFICATIONS (TENTATIVE): Color 30% in Methanol 50 APHA max.; Hydroxyl content 430 min.; Ash 0.03% max.; Iron 3 ppm max.; Moisture 0.3% max.

USES: Unsaturated polyester raw material to give chemical resistant properties.

CONTAINERS: Light-gauge metal cans.

SHIPPING CLASSIFICATION: Chemicals NOIBN.

MALEIC ANHYDRIDE

See Page M5/18

PHOSGARD® C-22-R

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Viscous Liquid.

SPECIFICATIONS: Appearance clear viscous liquid; Color APHA 50 max.; Refractive Index 25°C. 1.492-1.494; Acidity 0.05% meq/gm max.; Chlorine %12 lbs.

PROPERTIES: Phosgard C-22-R is a flame retardant organophosphorus compound with high efficiency through high phosphorus and chlorine content, essentially non-volatile, excellent color stability on UV and heat exposure, long storage stability and good hydrolytic stability.

USES: Phosgard C-22-R gives excellent flame retardance in Urethane foams, phenolics, polymethylmethacrylates, polyester resins and epoxies.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 672 lbs. gross; tankcars and tank trucks.

PHTHALIC ANHYDRIDE

ORGANIC DIVISION

MOLECULAR WEIGHT: 148.11

STANDARD FORM: White flakes or fused mass.

SPECIFICATIONS: Solubility in benzene (1:20) clear. Assay 99.5% min.; O.P. 130.0°C. min.

USES: An intermediate in the production of alkyl and polyester resins; dyestuffs; perfume bases; alcohol denaturants; pharmaceuticals; and plasticizers such as dioctyl phthalate, dibutyl phthalate, dimethyl phthalate, diethyl phthalate and phthalyl glycolates.

SHIPPING INFORMATION: Phthalic Anhydride, 80-lb. bags; tank cars; tank trucks.

RJ-100® RESINOUS POLYOL

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Supplied in flake form.

PROPERTIES & PERFORMANCE CHARACTERISTICS: Low molecular weight. Resinous polyol contributing chemical and corrosion resistance in paints and varnishes. Also RJ-100 esters emulsify readily, leading to excellent water-based coating.

USES: Alkyd manufacture, water-soluble, coatings, printing inks, esters for latex modifications, urethane coatings.

SHIPPING INFORMATION: 200-lbs. net per drums.

STYRENE MONOMER

See Page MS-21

VINYL CHLORIDE MONOMER

See Page MS-21

FORMALDEHYDE RESINS**UREA, INDUSTRIAL GRADE UNCOATED PELLETS**

ORGANIC DIVISION

STANDARD FORM: Urea pelleted form without coating agent.

ANALYSIS:	
Nitrogen (Min.)	46.0%
Moisture (Max.)	0.6%
Buret (Max.)	1.0%

USES: Urea formaldehyde resins for adhesives, plastics, paper and textiles, chemicals, intermediate, cosmetics, detergents, explosive stabilizer, paints, dentifrice, fermentation, finishes.

SHIPPING INFORMATION: Urea, 80-lb. multiwall paper bags with polyethylene lining. Also in bulk.

PLASTICIZERS**AROCLOR® POLYCHLORINATED POLYPHENYLS**

See Page MS-20

DI-2-ETHYLHEXYL ADIPATE (DOA)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 370.58

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, oily liquid; color APEA 25 max.; odor mild; acidity (as adipic acid) 0.02% max.; Sp. Gr. 0.924 ±0.002 at 25°/25°C.

USES: A primary plasticizer which imparts excellent low temperature flexibility to polyvinyl chloride resins and synthetic rubbers. Used in conjunction with DOP and Santizer 100 to make quality vinyl garden hose. Imparts low viscosity to vinyl plastisols for cloth coating, wire coating, etc. Imparts excellent heat and light stability and superior softness to vinyl film and upholstery.

SHIPPING INFORMATION: Resin Plasticizer, 55 and 5-gal. drums; tank cars, tank trucks wherever possible.

DI-2-ETHYLHEXYL PHTHALATE (DOP)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 390.54 (Pure compound)

STANDARD FORM: Liquid.

SPECIFICATIONS: Color APEA 25 max.; odor, very slight characteristic; Sp. Gr. 0.990-0.995 at 25°/25°C.; refractive index 1.4945-1.4958 at 25°/25°C.; acidity (as phthalic) 0.01% max.

PROPERTIES: Di (2-ethylhexyl) Phthalate (DOP) is the largest volume plasticizer consumed in polyvinyl-chloride resins. It imparts very good low temperature flexibility, low volatility and good heat and light stability to a vinyl composition. It is often used with Santizer 141 to give a composition of improved light stability, resistance to embrittlement and aging, flame resistance and ease of processing. In vinyl electrical compositions, DOP imparts excellent electrical characteristics with good aging properties.

USES: This plasticizer is widely used in plasticizing polyvinyl chloride for electrical insulation. DOP is also compatible with most of the other resins commonly used in the plastic industry. It is an excellent general purpose plasticizer for use in vinyl plastics. It has been widely used in such vinyl applications as shower curtains, aprons, rainwear, upholstery, draperies, garden hose and many others which require good flexibility and aging characteristics.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. (445-lb.) and 5-gal. (40-lb.) black iron drums; tank cars, tank trucks wherever possible.

*Monsanto Trademark

DI-N-OCTYL, N-DECYL ADIPATE (DNODA)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; color, APEA 50 max.; Sp. Gr. 25°/25°C. 0.912-0.903; refractive index, 25°/25°C. 1.443-1.447; moisture, 0.10% max.; acidity, 0.35 meq/100 gms. max.

PROPERTIES: DNODA is a primary plasticizer for polyvinyl chloride and imparts excellent low temperature flexibility and efficiency along with softness, superior hand and drape, permanence, odor resistance, heat and light stability. It has the best balance of properties of all adipates and on a cost/performance basis is the first choice of all low temperature flexibilizing plasticizers.

USES: The major use of DNODA is as a low temperature flexibilizing, specialty plasticizer used with basic type esters, such as DOP. It finds widespread use in film, sheeting and coated fabric. It will improve flexibility in surface and extrusion compounds and improve low temperature exposure characteristics of electrical jacketing formulas.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. (415-lb.) and 5-gal. (40-lb.) black iron drums; tank cars, tank trucks wherever possible.

DI-N-OCTYL, N-DECYL PHTHALATE (DNODP)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; Acidity, as Phthalic, 0.01% max.; Color, APEA, 50 max.; Odor slight ester; Refractive Index, 25°/25°C. 1.4910-1.4940; Sp. Gr. 25°/25°C. 0.9680-0.9770.

PROPERTIES: DNODP is widely used in PVC to impart superior low temperature flexibility and low processing volatility. It is miscible with most common solvents, thinners and oils.

USES: This plasticizer is useful in imparting excellent cold temperature flexibility along with good heat and light stability in film and sheeting. It is widely used in PVC appliance wiring. It imparts excellent flexibility to profile extrusions.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 490-lb. gross; 5 gal. drums, 40-lb. gross; tank truck and tank cars.

DIBUTYL PHTHALATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 278.34

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, oily liquid; color APEA 20 max.; odor slight; acidity (as phthalic acid) 0.01% max.; Sp. Gr. 1.0445-1.0465 at 25°/25°C.; refractive index, 1.4951-1.4915 at 25°/25°C.; assay (ester content) 99% min.; sulfur (copper-strip test) negative.

USES: One of the most widely used plasticizers for nitrocellulose and polyvinyl acetate; miscible with all the common organic solvents and with oils; soluble in water only to 0.001% at 30°C.; excellent light stability which permits its use in colorless, white or delicately tinted products. The stability of dibutyl phthalate and its high solvent power for most plastic materials make it one of the most acceptable plasticizers for general use in cellulose and vinyl acetate.

SHIPPING INFORMATION: Dibutyl Phthalate, 475-lb. steel drums; 40-lb. drums; tank cars; tank trucks.

DICYCLOHEXYL PHTHALATE (DCHP)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 330

STANDARD FORM: White solids.

SPECIFICATIONS: Appearance, white solid; color of melt, 100 APEA max.; odor, moderate aromatic, slight phthalic; moisture in methanol, 0.1% maximum; melting point, 83°C. minimum; acidity (as phthalic acid), 0.01% max.; ester content 98.0% min.

PROPERTIES: Dicyclohexyl Phthalate is an excellent primary plasticizer for ethyl cellulose, polystyrene, acrylics and chlorinated rubber. It is partially compatible with cellulose acetate butyrate, polyvinyl butyral, polyvinyl chloride and incompatible with cellulose acetate.

USES: This plasticizer is widely used as a plasticizer for nitrocellulose lacquers where it contributes adhesion, oil resistance, heat sealability and hardness. It is also used in combination with liquid plasticizers for plasticizing polyvinyl acetate to make heat setting adhesives.

SHIPPING INFORMATION: Resin Plasticizer, 350-lb. metal containers.

DIETHYL PHTHALATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 222.23

STANDARD FORM: Liquid

(Continued on next page)

0557324

Monsanto

TOWOLDMON0041058

SPECIFICATIONS: Clear, water white oily liquid; Color, APHA 10 max.; Acidity, 0.12 meq/100 gm. max.; Odor, slight aromatic; Moisture, 0.15% max.; (KF in methanol); Specific Gravity, 1.117-0.005 at 25°C.

USES: A plasticizer for cellulose acetate for use in molding compounds. It gives improved properties in polyvinyl acetate for adhesives and surface coatings. It imparts quick tack to polyvinyl emulsions. It has had FDA approval for use in food packaging for some time.

SHIPPING INFORMATION: Diethyl Phthalate, 55 gal., 20-ounce steel drums with tight heads, 2-inch and 3/4-inch openings in head. Gross weight, 50 lbs. Also available in tank cars and trucks, 2,000-gal. minimum.

DIISODECYL ADIPATE (DIDA)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 426.67

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear oily liquid; color APHA 100 max.; odor mild; acidity (as adipic acid) 0.04% max.; Sp. Gr. 0.916-0.003 at 25/25°C.; moisture (by KF in methanol) 0.10% max.

USES: A low volatile, low temperature plasticizer for polyvinyl chloride resins. It is similar to dioctyl adipate in properties imparted to vinyls, but has the advantage of lower volatility. Diisodecyl adipate is an excellent coplasticizer with DOP or DDP for vinyls and chloroacrylates. DIDA imparts very low initial viscosity to plastisols and a noticeable increase in viscosity on storage.

SHIPPING INFORMATION: Resin Plasticizer, 55 and 5-gal. drums; tank cars, tank trucks wherever possible.

DIISODECYL PHTHALATE (DIDP)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 446.65

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear oily liquid; color APHA 50 max.; odor slight; acidity (as phthalic acid) 0.01% max.; Sp. Gr. 0.982 at 25/25°C.

USES: A general purpose primary plasticizer for polyvinyl chloride being similar to dioctyl phthalate (DOP) but with lower volatility characteristics and superior resistance to soapy water extraction. Especially useful for wire compounds, floor tile and vinyl plastisols where it imparts low initial viscosity and very little viscosity build-up on prolonged storage at elevated temperatures (40-50°C.). For the electrical industry Monsanto offers DIDP-E, a special grade of DIDP stabilized with 0.25% Bisphenol A for improved electrical characteristics and retention of physical properties of heat aging.

SHIPPING INFORMATION: Resin Plasticizer, 55 and 5-gal. drums; tank cars, tank trucks wherever possible.

DIISOCTYL PHTHALATE (DIOP)

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 390.55

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, oily liquid; color APHA 35 max.; odor slight; acidity (as phthalic acid) 0.10% max.; Sp. Gr. 0.980 at 25/25°C.

USES: General purpose primary plasticizer for polyvinyl chloride. Uses similar to those for DOP, DIOP superior for vinyl organosols and plastisols having lower initial viscosity and lower viscosity build-up on storage than DOP.

SHIPPING INFORMATION: Resin Plasticizer, 55 and 5-gal. drums; tank cars, tank trucks wherever possible.

DIMETHYL PHTHALATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 194.18

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, water-white oily liquid; color APHA not darker than 10; odor not more than slightly aromatic; acidity (as phthalic acid) 0.01% max.; Sp. Gr. 1.109-0.001 at 25/25°C.; refractive index 1.5133-0.001 at 25°C.; sulfur (copper-strip test) negative.

PROPERTIES: A solvent plasticizer for cellulose acetate; miscible with all common organic solvents and with oils (except petroleum oils); solubility in water 0.4% at 32°C.; excellent light stability; B.P. 326°C.; crystallizing point 0°C.; wt. per gal. 10 lbs.

USES: Widely used in cellulose acetate molding compounds and polyvinyl acetate adhesives. Its motor use is primarily in the cellulose acetate field where, as a general rule, it is used in combination with diethyl phthalate or some other plasticizer.

SHIPPING INFORMATION: Dimethyl Phthalate, 550 and 40-lb. steel drums. Tank cars and tank trucks wherever possible.

DIPHENYL PHTHALATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 318.31

STANDARD FORM: Fused solid.

SPECIFICATIONS: Essentially white fused solid; free acid (as phthalic acid) 0.20% max.; free phenol 0.20% max.

PROPERTIES: Crystallizing point approx. 69°C.; readily soluble in ketones, esters and chlorinated hydrocarbons; solubility in alcohols, turpentine and linseed oil rather low, approx. 5.0 gm. per 100 cc. of solvent at 25°C.; completely insoluble in water and gives insoluble water resistance to all compositions in which it is used.

USES: Compatible with nitrocellulose and with the sulfonamide, phenolic, polystyrene and vinyl types of synthetic resins. In nitrocellulose lacquers produces hard coatings that have excellent gloss retention and weather resistance. Mixtures of diphenyl phthalate with either Santalac MS-80 or Santolac MHP Industrial Resins are excellent plasticizers for nitrocellulose in adhesives, flexible, adhesive coatings. Especially recommended for vinyl resins, polystyrene, ethyl cellulose and some of the natural resins such as damar.

SHIPPING INFORMATION: Resin Plasticizer, 400-lb. fiber drums.

DYROL® Paint brush preserver.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear, oily liquid; color, APHA 100 max.; Sp. Gr. 25/25°C., 1.088-1.091; refractive index at 25°C., 1.507-1.510; moisture, 0.10% max.

PROPERTIES: Dyrol is a non-volatile, non-flammable, pleasant smelling liquid that possesses a strong softening action on paints, lacquers, varnishes, etc. It is non-toxic and miscible with most common solvents, thinners and oils.

USES: The characteristics of Dyrol suggests its use as a preservative for paint brushes. It is also useful as a reconditioner for paint brushes containing dried paint or for removing paint from the skin after a paint job.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. (495-lb.) and 5-gal. (45-lb.) steel drums; tank trucks.

HB-40® PARTIALLY HYDROGENATED TERPHENYL

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A clear, mobile, high-boiling hydrocarbon; almost colorless, oily liquid with faint, pleasant odor; density 1.001-1.007 at 25/15.6°C.; wt. per gal. 5.37 (average); refractive index 1.5650-1.5690 at 25°C.; insoluble in water; miscible in all proportions at room temperature with several solvents and oils.

USES: Low-cost, secondary plasticizer for vinyl sheeting, films and fabric or paper coating. Plasticizer for vinyl protective coatings and adhesives. Used to plasticize vinyl profile extrusions, tubing, wire coating and injection- and slush-molding compounds. Plasticizer for styrene-water dispersion paints, paper coatings, adhesives and styrene casting resins.

SHIPPING INFORMATION: Resin Plasticizer, Tank cars; 460-lb. drums.

MOD-EPOX®

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid (solid below 77°F.)

SPECIFICATIONS: Color, APHA 150 max.; neutralization number (mg. of KOH/gm.), 0.2 max.

PROPERTIES: Mod-Epoxy is a unique modifier for epoxy resins. It reduces the viscosity of liquid epoxy resins, accelerates the cure, improves compressive yield strength, electrical characteristics and adhesion characteristics. It does not adversely affect such important characteristics as hardness, solvent resistance or water resistance. Since Mod-Epoxy is considerably lower in price than the epoxy resins the use of this product results in decreased costs.

USES: Mod-Epoxy is used in the tool and die industry, electronic potting compounds, encapsulations, adhesives, surface coatings, body solder compounds and other applications being developed in epoxy resins.

SHIPPING INFORMATION: Chemicals NOIRN, 55-gal. (510-lb.) and 5-gal. (45-lb.) galvanized drums.

MONTAR® SYNTHETIC RESINS

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Resin.

PROPERTIES: A series of related brown-to-black resins of the following characteristics:

	Softening Point	% Cl	% CaO	% Fe
Montar 1	120-170°C.	50-52	5-10	0.3-0.6
Montar 4	140-200°C.	54-56	5-10	0.5-1.0
Montar 5	180-220°C.	58-60	5-10	0.2-0.5
Montar 6	150-210°C.	59-61	2-5	0.2-0.4
Montar 9	130-180°C.	—	—	0.2-0.4

USES: Used primarily to impart fire resistance and to reduce cost of resin formulations.

SHIPPING INFORMATION: Coal Tar Resins, Catch-weight drums.

SANTONOX® ANTIOXIDANT

See Page M5/23

SANTONOX® R

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Solid.

SPECIFICATIONS: Appearance, light colored crystalline material; ash 0.05% max.; melting point, 155°C. min.; heat loss, 1.0% max.

PROPERTIES: Santonox R is probably the best antioxidant available for both high and low pressure polyethylene. It offers the same advantages as Santonox; but, in addition, offers the added advantages of lower color, reduced odor, larger particle size and 10-15% greater efficiency.

USES: Santonox R is used as an antioxidant for polyethylene. It has been approved by the FDA as an antioxidant in high pressure (low density) polyethylene at a 0.05% level for all uses except fatty foods.

SHIPPING INFORMATION: Chemicals NOIBN. 150-lb. fiber containers.

SANTOWHITE® POWDER

See Page M5/46

TRICRESYL PHOSPHATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 388.38

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, practically colorless liquid; Sp. Gr. 1.168-1.008 at 25/25°C.; acidity (as H_2PO_4) 0.01% max.; potassium permanganate test, no change in 30 minutes.

PROPERTIES: High boiling point; relatively non-volatile; evaporation loss less than 0.10% in 100 hours at 100°C. Refractive index is approx. 1.556 and 20°C. Viscosity increases rapidly at temperatures below normal; at approx. -35°C. a solid transparent mass without crystalline structure. Miscible with all the common solvents and thinners, linseed, china wood and castor oils; solubility in water less than 0.002% at 85°C. Imparts good moisture resistance to nitrocellulose films. The ortho isomer which is reputed to be the toxic element in normal tricresyl phosphate, has been virtually eliminated from Tricresyl Phosphate Monsanto, thereby reducing toxicity dangers to a minimum and making the product more suitable for many applications. Elimination of the ortho isomer causes no impairment in plasticizing qualities.

USES: The standard fire-retarding plasticizer for nitrocellulose and vinyls.

SHIPPING INFORMATION: Resin Plasticizer, 550-lb. and 45-lb. steel drums; tank cars; tank trucks wherever possible.

TRIPHENYL PHOSPHATE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 328.28

STANDARD FORM: Flakes.

SPECIFICATIONS: White flakes, faintly aromatic; M.P. 48.5°C. min. start; permanganate test, no change in 30 minutes; acidity (as H_2PO_4) 0.03% max.

PROPERTIES: Miscible with the common solvents and thinners and with vegetable oils; solubility in water 0.001% at 34°C., 0.002% at 54°C. Imparts some moisture resistance to cellulose-acetate films. Retentivity in cast cellulose-acetate films nearly 80%; that is, it can be incorporated in the proportion of 8-10% of acetate without separation and blooming. Imparts good flexibility and gives clear, tough compositions without tendency toward tackiness. One of its most valuable properties is that of fire retarding. When used alone on cellulose-acetate films an amount of triphenyl phosphate equal to 20% of the cellulose-acetate weight produces films which will not support combustion.

USES: Triphenyl phosphate is primarily used as a flame retardant plasticizer for cellulose. It also is of interest in heat sealing coatings and adhesives.

SHIPPING INFORMATION: Resin Plasticizer, 225-lb. fiber drums.

TRIBUTYL PHOSPHATE (TBP)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear mobile liquid; Sp. Gr. 25/25°C., 0.978-0.979; Color, APHA 30 max.; Acidity (as H_2PO_4) 0.03% max.; Odor, characteristic ester; Moisture (KF) 0.2% max.

PROPERTIES: Tributyl Phosphate is a practically colorless liquid of low viscosity. It is a primary plasticizer and solvent for nitrocellulose, cellulose acetate and chlorinated rubbers. It is recommended as an anti-foaming agent and high-boiling solvent used in 2-4-D concentrates and uranium recovery.

USES: Anti-foaming agent at 1% or less in rubber-based paints and similar emulsions. Solvent and blending agent for 2,4-D acid concentrates.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 400 lbs. gross; 5-gal. drums, 46 lbs. gross; tank trucks and tank-cars.

TRIBUTOXY ETHYL PHOSPHATE (TBEP)

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear mobile liquid; Odor, mild ester; Color, APHA 30 max.; Acidity, as Acetic acid, 0.05% max.; Refractive Index @ 25°C., 1.4340-1.4370; Moisture (KF) 0.12% max.; Sp. Gr. 20/20°C., 1.019-1.020.

PROPERTIES: TBEP is a colorless liquid plasticizer which is a strong solvent for most resins, particularly cellulose acetate and polyvinyl acetate.

USES: Plasticizer for leveling agent for self-polishing floor waxes. Offers flame retardance, but not as good as TCP. Imparts good low temperature flexibility to resins.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 500 lbs. gross; 5-gal. drums, 46 lbs. gross; tank trucks and tank-cars.

TRIPHENYL PHOSPHITE

See Page M5/28

SANTICIZER® 140 PLASTICIZER

See Page M5/41

SANTICIZER® 141 PLASTICIZER

See Page M5/41

SANTICIZER® 160 PLASTICIZER

Butyl Benzyl Phthalate

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 312.35

STANDARD FORM: Liquid.

SPECIFICATIONS: Color APHA 40 max.; Sp. Gr. 1.113-1.121 at 25/25°C.; acidity (as phthalic acid) 0.02% max.

PROPERTIES: A clear oily liquid plasticizer having a slight characteristic odor. Gives good low temperature performance; possesses good heat and light stability and low volatility.

USES: A relatively non-volatile plasticizer for polyvinyl chloride, polyvinyl chloride-acetate, polyvinyl butyral, ethyl cellulose and nitrocellulose. Superior to many other commonly used plasticizers in its permanence, oil resistance, flexibility and stability. Because of its high plasticizing efficiency, it is of outstanding value in increasing output of processing equipment such as extruders and calenders. Used successfully in vinyl ozonolysis which are useful for coatings and films. An excellent plasticizer for polyvinyl butyral and for low-molecular weight polystyrene, which is further polymerized later for coating and impregnating work.

The FDA has amended the following food regulations: 121.2511 - Resins in Polymeric Substances, 121.2514 - Resinoids and Polymeric Coatings, 121.2520 - Adhesives, 121.2526 - Resinoids and Polymeric Coatings for Paper and Paper Board, 121.2589 - Resinoids and Polymeric Coatings, Polyolefins, and 121.2597 - Components of Paper and Paper Board in Contact With Dry Foods for the use of Butyl Benzyl Phthalate in food packaging applications.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. and 5-gal. drums; tank cars; tank trucks.

SANTICIZER® 213 PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Sp. Gr. 1.040-1.045 at 25/25°C.; acid value, 0.33 meq/100 grs; color APHA 75 max.

PROPERTIES: A clear, oily liquid with unusual properties in PVC, particularly in plasticols.

USES: Low-cost primary plasticizer for polyvinyl chloride. Santicizer 213 has the unique ability to reduce "surface tack" of vinyl surfaces. It is of special value in plastisol formulations—contributes low initial viscosity, slow viscosity build-up, and fast fusion in a single plasticizer. Santicizer 213 improves mold release in plastic molded vinyls.

SHIPPING INFORMATION: Resin Plasticizer, Tank cars, tank trucks; 55-gal. and 5-gal. drums.

SANTICIZER® 214 PLASTICIZER

See Page M5/41

0557326

Monsanto

TOWOLDMON0041060

SANTICIZER® 215 PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, oily liquid, free of sediment or turbidity; color APHA 100 max.; acidity 0.12% max.; Sp. Gr. 0.974-0.980 at 25°/25°C.**USES:** Santicizer 215 is a low-cost phthalate type ester designed for use in the electrical wiring field. Its primary use is in competitive 60- and 70-watt and NM applications. It can also be used in semirigid insulation and as the vinyl cover jacket in type NM wiring for homes.**SHIPPING INFORMATION:** Resin Plasticizer. Tank cars: tank trucks.**SANTICIZER® 602 PLASTICIZER***Isocetyl Isododecyl Phthalate.*

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, oily liquid; color APHA 75 max.; odor mild; acidity (as phthalic acid) 0.01% max.; Sp. Gr. 0.967-0.977 at 25°/25°C.**USES:** A primary plasticizer for polyvinyl chloride with lower volatility than dioctyl phthalate (DOP). Imparts lower initial viscosity and less viscosity build-up in plastisols than DOP. Has excellent soapy water extraction and alkali resistance. Used in vinyl floor tile, film and sheeting.**SHIPPING INFORMATION:** Resin Plasticizer. Tank cars: tank trucks.**SANTICIZER® 603 PLASTICIZER***Butyl Decyl Phthalate.*

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, oily liquid; color APHA 100 max.; acidity 0.01% max. (as phthalic acid); odor, characteristically mild; Sp. Gr. 0.977 to 0.987 at 25°/25°C.**PROPERTIES:** A low-cost primary plasticizer that offers an attractive pound/volume cost. Its good color and low odor enable the film, sheeting, extrusion and plastisol compounder to offset cost savings with minimum loss of quality.**USES:** Santicizer 603 is a low-cost primary plasticizer for polyvinyl chloride and copolymer resins. Santicizer 603 imparts good low-temperature flexibility and is useful in calendared vinyl products such as film and sheeting for shower curtains, drapes and upholstery. Santicizer 603 imparts good viscosity characteristics to vinyl plastisols and organosols and is useful in aqueous emulsion compounds, dolls and formulations for coated fabrics.**SHIPPING INFORMATION:** Resin Plasticizer. Tank cars: tank trucks; 55-gal. and 5-gal. drums.**SANTICIZER® 9 PLASTICIZER***Mixture of ortho and para-Toluenesulfonamides.*

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 171.21

STANDARD FORM: Fine granules.

SPECIFICATIONS: Appearance, fine white to light cream colored particles; moisture, 1.0% max.; color (334% by weight in acetone) APHA 90 max.**PROPERTIES:** Solubility quite low in coal-tar hydrocarbons and negligible in petroleum hydrocarbons; readily soluble in most other solvents, and in hot linseed, chinawood and castor oils; soluble in water only about 1.0% at 94°C, but more soluble in alkali; least soluble Monsanto plasticizer in ethylene dichloride and benzene; solubility in ethylene dichloride approx. 4%. In benzene approx. 1.5%, each at 30°C.**USES:** Santicizer 9 differs greatly from other plasticizers in its action. Relatively small amounts impart a gloss to polished articles, give smooth working and uniform curing of molded thermosetting products. Blends readily with most synthetic resins, does not impart the softening action of liquid plasticizers. Particularly valuable to the makers of molding compositions. In some phenol-aldehyde resins it appears to act not only as a lubricant, but also as a promoter, giving more uniform and thorough curing. In amounts of about 20 parts per 100, has a temporary plasticizing action on protein compounds, such as corn protein and soybean protein. In melamine coating and laminating resins, Santicizer 9 promotes solution stability and compatibility, improves flowout, during baking or curing, and increases impact strength and abrasion resistance.**SHIPPING INFORMATION:** Resin Plasticizer. 250-lb. fiber drums.**SANTICIZER® 3 PLASTICIZER***N-Ethyl para-Toluenesulfonamide.*

ORGANIC DIVISION—LITERATURE AVAILABLE

Available on Special Manufacturing only.

MOLECULAR WEIGHT: 199.27

STANDARD FORM: Crystalline solid.

SPECIFICATIONS: Practically White crystalline solid; O.P. 58.0°C. min.; acidity (as acetic acid) 0.10% max.; moisture (by KF in methanol) 0.25% max.**USES:** Santicizer 3 is a solid, sulfonamide plasticizer. It has limited compatibility with commonly used resins but is widely used in combination with other plasticizers. Either in combination or alone it imparts high gloss, toughness and hardness. It sharpens the softening point of some thermoplastic resins, especially the cellulose esters. Its use makes possible such products as heat-sealing lacquer coatings and acetate parts per 100 parts of resin. In addition to its effect on toughness and gloss, it improves the flow of molding composition and lowers moisture permeability. It is about as compatible with polyvinyl formal as with cellulose acetate and its use improves flow and imparts excellent gloss.**SHIPPING INFORMATION:** Resin Plasticizer. 400-lb. steel drums.**SANTICIZER® 8 PLASTICIZER***Mixture of N-Ethyl-ortho- and para-Toluenesulfonamides.*

ORGANIC DIVISION—LITERATURE AVAILABLE

Available On Special Manufacturing Only

MOLECULAR WEIGHT: 199.27

STANDARD FORM: Liquid.

SPECIFICATIONS: Light yellow, viscous liquid; odor slight characteristic; unsubstituted amide 9-13%; acidity (as acetic acid) 0.80 meq/100 gms. max.; color of melt 200 APHA max.**PROPERTIES:** Readily miscible with all common organic solvents except the petroleum hydrocarbons in which it is only very slightly soluble. In water, soluble to approx. 0.13% at 23°C., 0.21% at 45°C.; solubility in water decreased by presence of ammonia but increased by other alkalis; soluble in castor oil, slightly soluble in chinawood oil, insoluble in linseed oil; relatively insoluble in cellulose acetate approx. 90 parts by weight to 100 of acetate; imparts a high degree of plasticity. A solvent for both nitrocellulose and cellulose acetate.**USES:** An excellent plasticizer for cellulose acetate, giving a brilliant and polish, not obtainable with other plasticizers. Being practically insoluble in petroleum hydrocarbons, it is a valuable plasticizer for coatings designed to withstand abrasion and related products. Has some plasticizing action on such protein compounds as casein, glue, soybean protein and corn protein. May be used alone or in conjunction with other materials such as glycerine or similar compounds; greatly increases the flexibility of shellac with considerable adhesion. Santicizer 8 is one of the best plasticizers known for synthetic polyamides such as nylon and related resins.**SHIPPING INFORMATION:** Resin Plasticizer. 530-lb. and 50-lb. drums.**SANTICIZER® 1-H PLASTICIZER***N-Cyclohexyl para-Toluenesulfonamide.*

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 253.36

STANDARD FORM: Yellow-brown fused mass.

SPECIFICATIONS: O.P. 82.5°C. min.; moisture 0.15% max.; color of melt APHA 300 max.**PROPERTIES:** Santicizer 1-H is a solid plasticizer which is relatively light stable and of a low order of toxicity. It is soluble in alcohol, esters, ketones, aromatic hydrocarbons and vegetable oils. It is insoluble in water. It is compatible with a wide variety of resins including most of the cellulose and vinyl resins.**USES:** Santicizer 1-H is used in special crystallizing finishes, paper coatings, textile coatings and adhesives. It is a useful plasticizer in nitrocellulose lacquers, imparting a relatively sharp softening point. It is also used to incorporate incompatible components such as paraffin wax in water-drying special coating effects such as crystallizing lacquers. For improved adhesion with certain resins, it is highly recommended. It is used in combination with dibutyl phthalate or Santicizer 180. It improves the moisture resistance of cellulose acetate and improves flexibility, hardness and light stability of ethyl cellulose. It is compatible with and imparts good flexibility to shellac and kauri resin.**SHIPPING INFORMATION:** Resin Plasticizer. Approx. 320 lbs. fiber drums.**SANTICIZER® M-17 PLASTICIZER***Methyl Phenyl Ethyl Glycolate.*

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 266.24

STANDARD FORM: Liquid.

SPECIFICATIONS: Color APHA 20 max.; Sp. Gr. 1.217-1.227 at 25°/25°C.; acidity (as acetic acid) 0.25% max.; odor, slight characteristic; sulfur (copper-strip test) negative.**PROPERTIES:** A solvent for both nitrocellulose and cellulose acetate; imparts a high degree of plasticity undiminished even in extremely thin films exposed to air currents for a long time. Very light-stable and may be used in transparent or tinted articles without danger of yellowing. Readily miscible with other organic solvents; solubility in water 0.02% at 30°C., but imparts a considerable degree of resistance to moisture penetration to both nitrocellulose and cellulose acetate film.

(Continued on next page)

USES: Probably the best cellulose acetate plasticizer available. Dissolves *Santolite* resins, and as both are very resistant to petroleum products and compatible with so many film-forming materials, they make an excellent combination for producing gasoline-resistant coatings.

SHIPPING INFORMATION: Resin Plasticizer, 550-lb. steel drums; 5-gal. drums. Tank cars; tank trucks.

SANTICIZER® E-15 PLASTICIZER

(Ethyl Phenyl Ethyl Glycolate).

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 290.27

STANDARD FORM: Liquid.

SPECIFICATIONS: Color APHA 20 max.; Sp. Gr. 1.180-1.185 at 25/25°C.; acidity (as acetic acid) 0.02% max.; odor slight; sulfur (copper-strip test) negative.

PROPERTIES: Miscible with the common organic solvents except the petroleum hydrocarbons; when heated miscible with vegetable oils but partially separates on cooling; solubility in water 0.0075% at 30°C.

USES: Solvent for both nitrocellulose and cellulose acetate and for most resins. Light-fast; does not evaporate even from the thinnest films. With both cellulose acetate and nitrocellulose gives clear, tough, flexible films which have high resistance to moisture penetration. Highly recommended for use with cellulose acetate. Has been approved by Bureau of Animal Industry as a nontoxic plasticizer; may be used in cellulose-based lacquers for paper or in foils for food wrapping and packaging.

SHIPPING INFORMATION: Resin Plasticizer, 550-lb. steel drums; 5-gal. drums; tank cars; tank wagons.

SANTICIZER® B-16 PLASTICIZER

Buyl Phenyl Butyl Glycolate.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 336.37

STANDARD FORM: Liquid.

SPECIFICATIONS: Color APHA 45 max.; Sp. Gr. 1.093-1.103 at 25/25°C.; acidity (as acetic acid) 0.02% max.; essentially odorless; sulfur (copper-strip test) negative.

PROPERTIES: A practically colorless liquid plasticizer; B.P. 119°C. at 5 mm.; does not crystallize at temperatures as low as -35°C.; water solubility 0.0012% at 30°C.; extremely light stable; darkens on heating above 290°C.

USES: A widely used polyvinyl chloride plasticizer where a tasteless and non-toxic composition is required; has complete FDA approval for use in vinyl food wrappings. Imparts good heat and light stability. Especially useful in beverage tubing, food packaging, hospital sheeting and anatomical restorations. Solvent for nitrocellulose; compatible with most resins, imparting good flexibility. Miscible with castor, linseed and chinawood oils; somewhat retards gel formation in the latter on heating. An excellent plasticizer for chlorinated rubber, from 10 to 25 parts per 100 usually required. An exceptionally good plasticizer for polystyrene. Mixtures of *Santicizer* B-16 and *Santolite* resins may be used to plasticize casein and corn protein.

SHIPPING INFORMATION: Resin Plasticizer, 500-lb. steel drums, 5-gal. drums; tank cars; tank wagons.

SANTICIZER® 140 PLASTICIZER

Mixed Cetyl Phenyl Phosphate.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear mobile liquid; color APHA 40 max.; Sp. Gr. 1.233-1.213 at 25/25°C.; refractive index 1.550-1.570 at 25°C.; acidity (as H₃PO₄) 0.01% max.; moisture (by KF in methanol) 0.16 max.

PROPERTIES: An essentially odorless and colorless liquid plasticizer; B.P. approx. 258°C. at 10 mm.; pour point -37°C. approx.

USES: Quite similar to tricresyl phosphate in that it imparts flame retardance, excellent permanence and chemical stability and equal heat and light stability; gives better low-temperature flexibility and abrasion resistance; is a stronger solvent and slightly more efficient than tricresyl phosphate. Can be used wherever tricresyl phosphate is used. Improved flexibility imparted by *Santicizer* 140 is preferable to tricresyl phosphate in many applications such as vinyl sheeting, lacquers and paper coatings. Considerably more

compatible than tricresyl phosphate with cellulose acetate. As a liquid, it is much easier to handle so it is often used in cellulose acetate films, especially in conjunction with other active plasticizers. Other resins with which it is useful are cellulose nitrate, ethyl cellulose, cellulose acetate-propionate, polyvinyl formal and polyvinyl butyral.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. and 5-gal. drums; tank cars; tank trucks.

SANTICIZER® 141 PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Color APHA 100 max.; odor, slight characteristic; Sp. Gr. 1.089-1.093 at 25/25°C.; refractive index 1.507-1.510 at 25°C.; acidity (as H₃PO₄) 0.01% max.; moisture (by KF in methanol) 0.10% max.

PROPERTIES: *Santicizer* 141 combines into one compound the non-flammability of tricresyl phosphate, and the efficiency and permanence of other vinyl plasticizers. Imparts superior low-temperature flexibility, improved abrasion and moisture resistance and good electrical properties. Gives excellent resistance to embrittlement and deterioration to polyvinyl-chloride compositions exposed to sunlight.

USES: Excellent for use in polyvinyl chloride films, sheets, extrusions, moldings, organosols and plastisols—in any application where an efficient, permanent, flame-retardant plasticizer is required. Small amounts (5-7 PFR) considerably improve light stability of vinyl compounds. Especially recommended in flexible films for curtains, aprons, rainwear and hospital sheeting and in soft, pliable coatings for tablecloths, upholstery and drapery. Suitable for use in products that touch the human body. *Santicizer* 141 has FDA approval as a nontoxic plasticizer for food packaging.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. and 5-gal. steel drums; tank cars; tank wagons.

SANTICIZER® 165 Mixed-alcohol phthalates.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; color, APHA 30 max.; acidity, 0.12 meq/100 gms. max.; moisture, 0.12% max.; refractive index at 25°C., 1.484-1.487; Sp. Gr. 25/25°C., 0.989-0.994.

PROPERTIES: *Santicizer* 165 is a low-cost, fast-fusing, primary plasticizer for polyvinyl chloride and nitrocellulose. It offers good, general-purpose properties at lower cost than Dioctyl Phthalate.

USES: Since *Santicizer* 165 is slightly more volatile than Dioctyl Phthalate, its use is recommended for average rather than severe conditions. The main applications for this plasticizer are in film, sheeting, floor tile and extrusions.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. (445-lb.) and 5-gal. (40-lb.) black iron drums; tank cars; tank wagons.

SANTICIZER® 214 PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Color, APHA 100 max.; appearance, clear oily liquid, essentially free of suspended matter or turbidity; acidity 0.15 meq/100 gms. max.; moisture, 0.12% max.; refractive index at 25°C., 1.483-1.485; Sp. Gr. 25/25°C., 0.950-0.955.

PROPERTIES: *Santicizer* 214 is an unusual primary plasticizer for polyvinyl chloride. The initial plastic viscosity of this material is very low. It allows formulators to produce a low viscosity formulation which is harder than usual after curing.

USES: *Santicizer* 214 imparts unique properties to polyvinyl chloride compounds. In proper concentration it gives the finished product a hard, tough surface, especially in vinyl coatings on metal.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. (440-lb.) and 5-gal. (40-lb.) black iron drums; tank cars; tank trucks.

SANTICIZER® 405 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; Color 50 ml: 50 ml, 95% ethanol, APHA 250 max.; Acidity, 1.0 meq/100 gms., 1.0 max.; Odor, slight ester; Moisture (KF methanol) 0.16 max.; Specific Gravity, 25/25°C., 1.128-1.132; Viscosity, 25°C., 105-135 ks.

(Continued on next page)

PROPERTIES: Santicizer 405 has unusually excellent permanence in three major vinyl application areas: migration resistance; extraction resistance; and low volatility.

USES: Santicizer 405 is used to impart superior permanence in industrial tapes, vinyl upholstery, baby pants and electrical, 105°C. wire and cable insulation.

SHIPPING INFORMATION: Resin Plasticizer, 55 gal. 490 lbs., drums, 5 gal., 44 lbs., drums, tank car and tank truck.

SANTICIZER® 406 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear, 25°C., clear oily liquid; Color, 50 ml/50 ml, 95% ethanol, 200 APHA max.; Acidity, meq/100 gms., 1.6 max.; Moisture (KF Methanol), 0.15% max.; Odor, slight ester; Specific Gravity, 25/25°C., 1.086-1.091; Viscosity, at 25°C., 88-95 ka.

PROPERTIES: In the Dow Mandrel refrigerator gasketing tests, Santicizer 406 had 50% retention of critical elongation, and in the Westinghouse Stress-Mandrel test, it had 87.5% retention of flexural strength.

USES: Santicizer 406 was primarily developed to meet the needs of plasticizer vinyl refrigerator gasketing where plasticizer migration to polystyrene and ABS terpolymers have been a problem. It has excellent electrical properties for use in 105°C. wire insulation and jacketing.

SHIPPING INFORMATION: Resin Plasticizer, 55 gallon drums, 490 lbs. net; 5 gallon 40 lbs. net; and tank trucks and cars.

SANTICIZER® 409 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear, viscous liquid; color of solution (50 ml. in 2-B alcohol), 250 APHA max.; moisture (KF in methanol), 0.15 max.; odor, very faint ester; Sp. Gr. (25/25°C.), 1.081-1.084; viscosity at 210°F., 115 to 130 centistokes; acidity, 2.0 meq/100 gms. max.

PROPERTIES: Santicizer 409 combines the ideal properties of several plasticizers for polyvinyl chloride in one primary polymeric plasticizer. Santicizer 409 has low specific gravity, color and toxicity. Polyvinyl chloride compositions plasticized with Santicizer 409 show excellent compatibility, excellent permanence, superior electrical properties, fast fusion, good low-temperature flexibility, good heat and light stability and excellent retention of physical properties.

USES: Because of its excellent electrical properties, Santicizer 409 is especially useful in wire coatings and tapes. It is also widely used in high-quality film and sheeting (adhesive backed), organosol fabric coatings, refrigerator gasketing and in other applications requiring a high degree of permanence and resistance to extraction. It is compatible with polyvinyl chloride, ethyl cellulose, cellulose acetate-butyrate and nitrocellulose.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. (450-lb.) and 5-gal. (45-lb.) steel drums; tank cars.

SANTICIZER® 411 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Viscous, some solids on standing.

SPECIFICATIONS: Color APHA 300 max. (50% ethanol solution); Acidity 1.0% max.; odor, slight characteristic; Sp. Gr. 1.101-1.105 at 25°C.

USES: Santicizer 411 is a low-cost permanent polymeric plasticizer with unusual resistance to solvent extraction and rubber migration. Santicizer 411 is designed for application in outerwear, baby pants, coated cloth (for automobile and furniture upholstery, etc.), wall covering, wire coatings, modified plastisols and organosols, vinyl-metal laminates, and high density foam vinyl where its excellent resistance-to-extraction and rubber migration properties are required.

SHIPPING INFORMATION: Resin Plasticizer, Tank cars, tank trucks; 55-gal. and 5-gal. drums.

SANTICIZER® 462 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; Color, APHA 150 max.; Odor, characteristic ester; Acidity meq/100 gms., 0.24%; Moisture (KF in Methanol), 0.15 max.; Refractive Index at 25°C., 1.507-1.510; Sp. Gr. 25/25°C., 1.073-1.076.

PROPERTIES: Santicizer 462 offers excellent humidity compatibility, DOP-like processability, good plastisol viscosity, minimum migration and low volatility.

USES: Santicizer 462 finds excellent application in coating for rubber saturated paper, for cloth coatings, foamed vinyl outerwear and general purpose unsupported film and sheeting.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 490 lbs. net; 5-gal. drums, 40 lbs. net; and tankcars and tank trucks.

SANTICIZER® 480 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; Acidity meq/100 gms., 0.60%; Color APHA 200 max.; Moisture (KF in Methanol), 0.15% max.; Sp. Gr. 25/25°C., 1.046-1.052.

PROPERTIES: Santicizer 480 has been designed to offer low cost permanence.

USES: Santicizer 480 finds application in supported and unsupported film and sheeting, coated fabrics, foamed vinyl and wall coverings.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 500 lbs. gross; 5-gal. drums, 45 lbs. gross; tankcars and tank trucks.

SANTICIZER® 481 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; Acidity meq/100 gms., 0.85% max.; Color APHA 300 max.; Moisture (KF in Methanol) 0.15% max.; Sp. Gr. 25/25°C., 1.072-1.078.

PROPERTIES: Santicizer 481 has good extraction resistance, low cost and permanence comparable to Santicizer 409.

USES: Santicizer 481 has good electrical properties in 900 wire insulation, high efficiency in film and sheeting and expanded vinyl.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 490 lbs. gross; 5-gal. drums, 45 lbs. gross and tankcars and tank trucks.

SANTICIZER® 482 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; Acidity meq/100 gms., 1.1 max.; Color, APHA 325 max.; Moisture (KF in Methanol) 0.15% max.; Sp. Gr. 25/25°C., 1.097-1.103.

PROPERTIES: Santicizer 482 is designed to meet the permanence requirements of vinyl insulation, 105°C. wire and cable coatings. It has overall good permanence.

USES: Santicizer 482 finds good use in appliance wiring and in industrial machinery wiring. It has very low migration to rubber materials and nitrocellulose.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 490 lbs. gross; 5-gal. drums, 45 lbs. gross; and tankcars and tank trucks.

SANTICIZER® 483 PERMANENT PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Appearance, clear oily liquid; Acidity meq/100 gms., 0.24 max.; Color APHA 125 max.; Moisture (KF in Methanol) 0.15% max.; Sp. Gr. 25/25°C., 1.047-1.050.

PROPERTIES: Santicizer 483 is a permanent plasticizer designed for plastisols. It has a low "per se" viscosity, low initial viscosity and low viscosity build-up for long shelf life.

USES: Santicizer 483 has excellent application in plastisol coated paper and fabrics.

SHIPPING INFORMATION: Resin Plasticizer, 55-gal. drums, 520 lbs. gross; 5-gal. drums, 45 lbs. gross; and tankcars and tank trucks.

SANTICIZER® 630 MODIFIED-PHTHALATE PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Color, APHA 70 max.; acidity, 0.12 meq/100 gms. max.; moisture (by KF in methanol), 0.10%; max.; refractive index at 25°C., 1.5096-1.5160; Sp. Gr. 25/25°C., 0.987-0.994.

(Continued on next page)

PROPERTIES: Santicizer 630 is a low cost, primary plasticizer for polyvinyl chloride plastics in some characteristics Santicizer 630 is superior to Dioctyl Phthalate especially in migration resistance to nitrocellulose and in plastisol-viscosity stability. Since this material is much more volatile than Dioctyl Phthalate, it is not recommended for applications where permanence is essential.

USES: Santicizer 630 is useful in formulating vinyl plastisol extrusions, coatings or sheeting compounds. It imparts to vinyl compounds properties comparable to those imparted by DOP, but it costs less.

SHIPPING INFORMATION: Resin Plasticizer. Tank trucks and tank cars only.

SANTICIZER® 631 MODIFIED-PHTHALATE PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Color APHA 60 max.; acidity, 0.12 meq/100 gms. max.; moisture (by K₂Cr₂O₇ in methanol), 0.10% max.; refractive index at 25°C., 1.4990-1.5045; Sp. Gr. 25°/25°C., 0.984-0.990.

PROPERTIES: Santicizer 631 is a low cost, primary plasticizer for polyvinyl chloride plastics. It offers a unique balance of good versus performance in this resin. Santicizer 631 is better than DOP in migration resistance to nitrocellulose and in plastisol-viscosity stability.

USES: Santicizer 631 is useful in formulating vinyl plastisols, extrusions, coatings or sheeting compounds. It imparts properties to PVC compounds in the range of those imparted by DOP and is used when cost is a decisive factor. It lies between Santicizer 630 and DOP in price versus performance.

SHIPPING INFORMATION: Resin Plasticizer. Tank trucks and tank cars only.

SANTICIZER® 644 PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

SPECIFICATIONS: Clear, oily liquid, free of sediment or turbidity; color APHA 50 max; acidity 0.35 meq/100 grams, max.; Sp. Gr. 0.917-0.922 at 25°/25°C.

USES: Santicizer 644 is a primary plasticizer for PVC and other resins to which it imparts excellent low temperature flexibility. Its use assures low volatility, excellent efficiency and superior flexibility. Santicizer 644 offers low initial viscosity and excellent viscosity stability in plastisols. Santicizer 644 is predominantly used in vinyl film, sheeting and coated fabric to impart flexibility without sacrificing volatility or efficiency. Plastisols widely use Santicizer 644 to provide excellent viscosity characteristics along with improved fusion characteristics.

SHIPPING INFORMATION: Resin Plasticizer. Tank cars, tank trucks; 55-gal. and 5-gal. drums.

SANTICIZER® 636 2-Ethylhexyl Isoderyl Phthalate

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Color, APHA 75 max.; acidity, 0.12 meq/100 gms. max.; moisture (by Karl Fischer), 0.10% max.; refractive index at 25°C., 1.478-1.488; Sp. Gr. 25°/25°C., 0.989-0.977.

PROPERTIES: Santicizer 636 is a practically colorless, high-boiling liquid of low viscosity and excellent electrical properties. It is miscible with most common solvents, thinners and oils. Santicizer 636 combines good low temperature properties, good resistance to migration and to water extraction, and excellent heat and light stability.

USES: Santicizer 636 is especially useful in plastisols where it offers lower viscosity build-up on aging than does Dioctyl Phthalate. It is also useful in electrical compounds where the higher molecular weight and lower volatility result in improved permanence of these products in end applications.

SHIPPING INFORMATION: Resin Plasticizer. Tank trucks and tank cars only.

SANTICIZER® 683 PLASTICIZER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, oily liquid free of sediment or turbidity; color APHA 100 max.; acidity 0.12 meq/100 gms. max.; Sp. Gr. 0.968-0.974 at 25°/25°C.

USES: Santicizer 683 is a modified phthalate ester. It is offered as a low-cost primary plasticizer for polyvinyl chloride. In some characteristics it is superior to DOP. It is particularly good in plastisols because of low initial viscosity and viscosity stability imparted. Resistance to N/O migration is excellent. Santicizer 683 is used in compounding vinyl plastisols, extrusions, coatings, film and sheeting.

SHIPPING INFORMATION: Resin Plasticizer. Tank cars, tank trucks.

SANTOLITE® MHP RESINS

See Page M5/35

SANTOLITE® MS 80% Industrial Resin

See Page M5/35

HB-40® PARTIALLY HYDROGENATED TERPHENYL

See Page M5/38

PLASTIC BOTTLES AND CONTAINERS

PACKAGING DIVISION—LITERATURE AVAILABLE

TYPE: Plax® blow molded for thermoformed containers.

STOCK: High and low density polyethylene available in stock shaped containers.

CUSTOM: Custom designed containers to meet specific market requirements can be produced in an unlimited number of shapes. Dependent upon the specific needs, these custom containers can be made from polyethylene (high or low density), polypropylene, styrene, nylon, vinyl (rigid and flexible), Delrin and many other thermoplastics.

SIZE: 5cc capacity to 15 gallons.

USES: Safe, lightweight containers for a wide variety of consumer and industrial products.

100 E. I. duPont De Nemours & Co.

PLASTIC CLOSURES

PACKAGING DIVISION—LITERATURE AVAILABLE

TYPE: Injection molded.

GENERAL INFORMATION: These closures are available in a variety of sizes as companion pieces to many Plax® plastic containers.

PLASTIC FITMENTS

PACKAGING DIVISION—LITERATURE AVAILABLE

TYPE: Injection molded.

STOCK: Variety of fitments for Plax® plastic containers for dispensing liquids or powders in drop, spray, squirt, shake or pour form.

CUSTOM: Fitments can be designed to meet specific dispensing requirements.

PLASTIC SHEET AND FILM

GERING® BAGS AND LINERS

GERING PLASTICS COMPANY—LITERATURE AVAILABLE

DESCRIPTION: Low density polyethylene bags and liners, available either individually or on Hand-E-Rolls®, continuous rolls serrated for easy detachment.

(Continued on next page)

IND USES: Packaging bulk chemical, lining boxes, cans or drums, protection against water damage.

GAUGES AND SIZES: Thicknesses from .001" to .010", in widths up to 56" flat face, with or without gussets. Lengths to 114 inches.

GER-PAK® SHEETING

GERING PLASTICS COMPANY—LITERATURE AVAILABLE

DESCRIPTION: Low density polyethylene. In stock rolls up to 100 feet long. Longer lengths, colors and special embossing available.

IND USE: Covering equipment, dust partitions, temporary glazing.

GAUGES: Any thickness from .001" to .010", in widths up to 40 feet.

GER-PAK® TAPE

GERING PLASTICS COMPANY—LITERATURE AVAILABLE

DESCRIPTION: Pressure sensitive polyethylene tape with pre-lit paper backing. In cutter edge dispenser.

IND USES: Patching, sealing, closing plastic and paper bags or liners.

SIZES: .004" gauge, 2" wide and 100' long, clear or black.

MONSANTO® PLASTIC NESTABLE CONTAINERS

PACKAGING DIVISION

DESCRIPTION: Plazware® plastic vending cups
7 oz. hot drink cups
8 oz. hot drink cups
8 oz. cold drink cups (translucent)
Packed 2,000 cups per case

Plazware® nestable plastic containers for cottage cheese. Capacities available: 8, 12, 16, 32 oz. sizes. Clear Polyflex® biaxially oriented polystyrene companion lids are available for these containers.

POLYFLEX® SHEET

PACKAGING DIVISION—LITERATURE AVAILABLE

DESCRIPTION: Biaxially oriented polystyrene sheet available in rolls.

Types

Code 0116 (thermoforming grade) gauges .00275" and .00475"
Code 0401 (thermoforming grade) clear and color in gauges .005", .0075", .010", .0125", .015" controlled monomer.
Code 0404 (thermoforming grade) clear in gauges .005", .0075", .010", .0125", .015", and .020" controlled monomer.

End Uses

Document protectors, wallet inserts.
Trays and inner packages for food products.
Trays and inner packages for highly sensitive foods.

POLYFLEX® FILM

PACKAGING DIVISION—LITERATURE AVAILABLE

PACKAGING GRADE FILM: Code 0301. Gauges .001", .00125", .0015", .002". Available on rolls.

DESCRIPTION: Biaxially oriented polystyrene, crystal clear, excellent dimensional stability, heat sealable, heat shrinkable and "breathing" characteristics necessary for packaging fresh produce.

VUEPAK® CELLULOSE ACETATE SHEET

PACKAGING DIVISION

DESCRIPTIONS: Transparent, rigid packaging material available in rolls and sheets in gauges .005", .0075", .010", .015" and .020".

IND USES: Fabricated display packages, signs, document protectors.

*Monsanto Trademark

RUBBER CHEMICALS

ACCELERATORS FOR NATURAL AND SYNTHETIC RUBBERS

ORGANIC DIVISION

THIOZOLE TYPE

EL-SIXTY® 1, 3-bis (2-benzothiazolylthio)propylmercaptan.

SPECIFICATIONS: (Treated to reduce dusting). Appearance and condition—buff powder; ash—0.5% max.; fineness (20 mesh)—0.5% max.; retained; heat loss—0.5% max.; melting point—220°C. min.; dedusting agent—5.0-15.5%; sp. gr.—1.36 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. May be used alone but, for best results, in activator; is usually desirable. Gives excellent processing and curing characteristics to many types of compounds. Effective in compounds containing high loads of retarding pigments such as clay.

SANTOCURE® N, cyclohexyl-2-benzothiazolylthioformamide.

SPECIFICATIONS: Appearance and condition—light tan or buff flakes or powder; ash—0.5% max.; fineness (20 mesh)—trace max.; retained; melting point—84°C. min.; moisture—1% max.; ether insolubles—5.0% max. when shipped; sp. gr.—1.27 at 25°C.

USES: Delayed action vulcanization accelerator for natural and synthetic rubbers. Activators are sometimes desirable but not always needed. Exceptionally safe at processing temperatures but powerful at curing temperatures. Give high modulus and tensile.

SANTOCURE® 26 2-(2,4-dimethyl-4-morpholinethio)benzothiazole

SPECIFICATIONS: Appearance and condition, cream to light yellow powder; ash 0.5% max.; fineness (10 mesh) trace max.; retained; melting point 98°C. min.; moisture 0.5% max.; ether insolubles 2.0% max. when produced; sp. gr. 1.36 @ 25°C.

USES: Delayed action vulcanization accelerator for natural and synthetic rubbers. Activators are sometimes desirable but not always needed. Exceptionally safe at processing temperatures but powerful at curing temperatures. Gives high modulus and tensile.

SANTOCURE® MOR 2-(morpholinethio)benzothiazole

SPECIFICATIONS: Appearance and condition, buff to brown flakes; ash 0.5% max.; melting point, 80°C. min.; moisture, 0.5% max.; ether insolubles, 1% max. when shipped; specific gravity (approx.) 1.34 @ 25°C.

USES: Santocure MOR is used in the same way as the other Santocure products and responds in much the same manner to secondary accelerators. In most applications, its delayed action appears to lie between Santocure NS and Santocure 26.

SANTOCURE® MOR-90 Blend of Santocure MOR and thiazole

SPECIFICATIONS: Appearance, light buff to brown flakes; ash, 0.5% max.; moisture, 0.5% max.; ether insolubles, 1.5% max. when shipped; crystallizing point, 70°C. min.; specific gravity (approx.) 1.36 @ 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers.

SANTOCURE® NS N-t-butyl-2-benzothiazolylthioformamide.

SPECIFICATIONS: Appearance and condition, light blue powder or flakes; ash 0.5% max.; fineness (20 mesh) trace max.; retained; melting point 104°C. min.; moisture 0.5% max.; ether insolubles 1% max. (when shipped); sp. gr. 1.29 at 25°C.

USES: Delayed action vulcanization accelerator for natural and synthetic rubbers. Santocure NS is used in the same way and for the same purposes as Santocure. It provides even greater delayed action. Santocure NS is a little stronger than Santocure and it is customary to reduce the dosage by about 10% when making the substitution.

THALAN

ORGANIC DIVISION

FORMULA: 98% Phthalic Anhydride; C. H. (CO)₂O

SPECIFICATIONS: Texas Oil 511 — Monsanto Raw Material No. 49590, greenish-blue oil. Color ASTM standard 3 max.; sp. gr. 15.6°/15.6°C. is 0.910 to 0.93; Viscosity at 100°F. is 33-2 to 44.8 CS. Other specifications upon request.

USES: Phthalic anhydride milled and containing 2% Texas Oil 511. Vulcanization modifier and oxidation retarder.

SHIPPING INFORMATION: 50-lb. bags. Standard Monsanto red and white label.

THIOFIDE® (MBTS)

2,2'-dithiobis(benzothiazole), also called benzothiazyl disulfide and 2,2'-dibenzothiazyl disulfide.

SPECIFICATIONS: Appearance and condition: cream powder; ash 0.5% max.; fineness (100 mesh) —0.1% max.; retained: melting point —108°C. min.; moisture —0.5% max.; petroleum ether extractable —0.5±1.5%; sp. gr. —1.54 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. An activator is usually desirable. Safe handling when properly activated. Can be used successfully in a wide variety of stocks. *Thiofide* is treated to reduce dusting and aid dispersion.

THIOTAX* (MBT) 2-mercaptobenzothiazole.

SPECIFICATIONS: Appearance and condition: cream to light yellow powder; ash 0.5% max.; assay (MBT content) 91% min.; fineness (100 mesh) trace max.; retained: melting point 70°C. min.; degassing agent 2.0-4.5%; moisture 0.5% max.; sp. gr. 1.30 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. An activator is not needed but is often desirable. Activator must be adjusted carefully to avoid scorch difficulties. *Thiotax* is treated to reduce dusting and aid dispersion.

ALDEHYDE AMINE TYPE**A-32*** Reaction product of butyraldehyde and butyldiene aniline.

SPECIFICATIONS: Appearance and condition—red-yellow to orange liquid, may be faintly turbid; moisture—no liquid separation on standing; sp. gr. —1.01 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. Used mostly for hard rubber.

A-100* Reaction product of butyraldehyde, acetaldehyde and aniline.

SPECIFICATIONS: Appearance and condition: dark, red brown oily liquid; moisture—no liquid separation on standing; sp. gr. —1.01 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. Used mostly for hard rubber.

ULTRA TYPE**RZ-50®-A**

50% Solution in Cellosolve of the *N,N*-dimethylcyclohexylamine salt of dibutyl-dithiocarbamic acid.

SPECIFICATIONS: Appearance and condition—clear brown liquid color (NPA) 8.0 max. (when produced); assay 50±2%; sp. gr. 0.96 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. Used in dry rubbers and cements. Very fast curing.

RZ-50®-B

50% Solution in Cellosolve of the *N,N*-dimethylcyclohexylamine salt of dibutyl-dithiocarbamic acid, with emulsifying agent added.

SPECIFICATIONS: Appearance and condition: clear brown liquid; sp. gr. 0.96 at 25°C.; assay 50±2%; color (when produced) (NPA) 8.0 max.

USES: For latex emulsions, RZ-50B is especially effective. Vulcanization accelerator for natural and synthetic rubber latex. Gives fast cures.

THAN: Ethylene Glycol Monoethyl Ether of Union Carbide & Carbon Chemicals Corporation.

*Monsanto Trademark

R-2 CRYSTALS

Reaction product of carbon disulfide and 1,1'-methylendipiperidine.

SPECIFICATIONS: Appearance and condition: grey white pellets; melting point 58°C. min.; sp. gr. 1.22 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. Used mostly in cements and latex.

MONO THIURAD®

Bis(dimethylthiocarbonyl)disulfide, also called tetramethylthiuram monosulfide.

SPECIFICATIONS: (Standard Powder): Appearance and condition—lemon yellow powder; ash—0.5% max.; fineness (200 mesh)—1% max.; retained: 100 mesh—trace max.; retained: melting point—103°C. min.; moisture—0.5% max.; sp. gr.—1.39 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. Available in oiled and unoled powder and pellet form.

THIURAD®

Bis(dimethylthiocarbonyl)disulfide, also called tetramethylthiuram disulfide.

SPECIFICATIONS: (Standard Powder): Appearance and condition—light buff to white powder; ash—0.5% max.; fineness (100 mesh) trace max.; retained: melting point—144°C. min.; heat loss—0.5% max.; sp. gr.—1.41 at 25°C.

USES: Sulfur bearing vulcanization accelerator for natural and synthetic rubbers. Available in oiled and unoled powder form and pellet form.

ACCELERATOR B

SPECIFICATIONS: Accelerator B is a physical blend of 2 parts *Thiurad* and 1 part *Thiotax*. *Thiurad* and *Thiotax* are commonly used in this ratio as accelerators for butyl. Monsanto pre-blends the two compounds, offering the 2:1 mix as a convenience for the user.

GUANIDINE TYPE**DPG** Diphenylguanidine.

SPECIFICATIONS: Appearance and condition: pinkish-white powder; ash 0.3% max.; fineness (100 mesh) trace max.; retained: melting point 146°C. min.; heat loss 0.5% max.; degassing agent 1.0±3.9%; sp. gr. 1.20 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. Used mostly as a secondary for thiazoles. DPG is treated to reduce dusting and aid dispersion.

GUANTAL® Diphenylguanidine phthalate.

SPECIFICATIONS: Appearance and condition—white powder; ash—0.3% max.; fineness (200 mesh)—0.5% max.; retained: melting point—178°C. min.; heat loss—3.5% max.; sp. gr.—1.20 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers. Used mostly as a secondary for thiazoles.

THIOCARBANILIDE TYPE**A-1* THIOCARBANILIDE**

Also called 1,2-diphenyl-2-thioureac and *N,N'*-diphenylthiourea.

SPECIFICATIONS: Appearance and condition—gray powder; ash—0.5% max.; fineness (100 mesh)—trace max.; retained: melting point—148°C. min.; heat loss—0.75% max.; sp. gr.—1.32 at 25°C.

USES: Vulcanization accelerator for natural and synthetic rubbers—special applications.

05 57332

Monsanto

TOWOLDMON0041066

ANTIOXIDANTS AND ANTIOZONANTS

FLECTOL® H

polymerized 1,2-dihydro-2,2,4-trimethylquinoline.

SPECIFICATIONS: Appearance and condition, brown powder or flakes; ash—0.5% max.; fineness: powder—200 mesh 0.5% max., retained; flakes—40 mesh 0.5% min., retained; moisture—0.5% max.; sp. gr. 1.03 at 25°C.; melting range, initial melt 70–100°C.

USES: For protection of rubber against heat deterioration and normal aging. It causes less discoloration than most other full-power antioxidants. It is an accelerator for Neoprene vulcanization. *Flectol H* is excellent for reducing frosting on dry heat cured compounds. For maximum protection use 1% to 2% based on the rubber.

SANTOFLEX® AW 6-ethoxy-1,2-dihydro-2,2,4-trimethylquinoline.

SPECIFICATIONS: Appearance and condition—dark viscous liquid; heat loss—1% max.; insolubles (benzene)—trace max.; sp. gr.—1.04 at 45°C.

USES: For reducing the harmful effect of ozone attack and in this respect it appears to be somewhat more effective with SBR than natural rubber. It is particularly suggested for compounds used in dynamic service where waxes are somewhat undesirable. *Santoflex AW* is a fairly good antioxidant for the prevention of the usual deterioration on aging. It also has considerable merit as a flex-cracking inhibitor. Discolor and stain very badly.

SANTOFLEX® DD 6-Dodecyl-1,2-dihydro-2,2,4-trimethylquinoline.

SPECIFICATIONS: Appearance and condition—dark, viscous liquid; ash—0.1% max.; nitrogen content—3.1% max.; sp. gr.—0.93 at 45°C.

USES: For inhibiting flex-cracking and oxidation. It is especially recommended for rubber articles used in dynamic service but is equally effective in any type of rubber compound. It causes rather severe discoloration and staining. 1% to 2% on the hydrocarbon is usually sufficient but up to 4% can be used with improved results.

SANTOFLEX® 17 N,N'-Bis(1-ethyl-3-methylpentyl)-p-phenylenediamine

TYPICAL PROPERTIES: Appearance and condition, dark reddish brown liquid; sediment, trace max.; heat loss 2 hr. @ 105°C, 6.5% max.; copper content 10 ppm max.; vapor pressure @ 25°C, less than 1 micron; Sp. Gr. 0.90 approx.; wt. per gal. 7.5 lbs.

USES: An antioxidant to protect against degradation in poly unsaturated elastomers.

SANTOFLEX® 36 N-isopropyl-N'-phenyl-p-phenylenediamine

SPECIFICATIONS: Appearance and condition, dark gray to black flakes; ash 0.5% max.; crystallizing point range 72–76°C; Sp. Gr. (approx.) 1.04 @ 25°C.

USES: *Santoflex 36* is an outstanding antidegradant for the protection of rubbers against oxidation, ozone, flex-cracking and poisoning by copper and manganese. It has high activity with all commonly used elastomers and may be used with other protective agents to achieve enhanced effects.

Santoflex 36 disperses most easily during mill or Banbury mixing. It stains and discolors rather severely. Depending upon the application, the recommended dosage varies from 1 to 3% on the rubber.

SANTOFLEX® 73

Mixture of N,N'-diphenyl-p-phenylenediamine (DPPD), 75%, and 6-dodecyl-1,2-dihydro-2,2,4-trimethylquinoline ("Santoflex" DD), 25%.

SPECIFICATIONS: Appearance and condition—dark flakes; ash—0.5% max.; sp. gr.—1.04 at 25°C.

USES: For reducing aging and oxidation effects. *Santoflex 73* contains a high percentage of N,N'-diphenyl-p-phenylenediamine. It is designed for those who wish to use a high dosage of this material, with a lower amount of regular antioxidant. More than 0.4% on the hydrocarbon is liable to cause blooming.

SANTOFLEX® 217 N,N'-Bis(1-methylheptyl)-p-phenylenediamine.

TYPICAL PROPERTIES: Appearance and condition, dark reddish brown liquid; sediment, trace max.; heat loss 2 hr. @ 105°C, 0.5% max.; copper content 10 ppm max.; vapor pressure @ 25°C, less than 1 micron; Sp. Gr. @ 80°F, 0.90 approx.; wt. per gallon 7.5 lb.

USES: An antioxidant to protect against degradation in poly unsaturated elastomers.

SANTOVAR® A 2,5-di-(tert-amyl) hydroquinone.

SPECIFICATIONS: Appearance and condition—buff powder; ash—0.5% max.; fineness (100 mesh)—trace max.; retained; melting point—172°C, min.; heat loss—1% max.; sp. gr.—1.05 at 25°C.

USES: For the protection of uncured rubber against oxidation. It also inhibits oxygen attack on unsaturated resins and oils. Cold flow of uncured compositions is reduced by a stiffening effect of Santovar A. Excellent for adhesives or other uncured films. It is non-staining and non-discoloring. Use 0.5% to 4% on the material to be protected.

SANTOWHITE® 54 A modified hindered phenol

SPECIFICATIONS: Appearance and condition, clear, viscous, straw-colored liquid; ash 0.25% max.; crystallizing point, will not crystallize but forms glass below -10°C.; heat loss 0.5% max.; Sp. Gr. (approx.) 0.96 @ 25°C.

USES: *Santowhite 54* is an outstanding antioxidant from the standpoints of discoloration and staining. It is easily emulsified for use in latex and incorporates readily in dry rubbers. It is employed at 1 to 2% based upon the hydrocarbon.

SANTOWHITE® 54-5 Solid form of Santowhite 54

COMPOSITION: Two parts of active material and 1 part of inert filler.

USES: Antioxidant (See *Santowhite 54*).

SANTOWHITE® CRYSTALS 4,4'-thiobis-(6-tert-butyl-m-cresol).

SPECIFICATIONS: Appearance and condition—light gray to tan powder; ash—0.5% max.; fineness (50 mesh)—trace max.; retained; melting point—150°C, min.; moisture—1% max.; sp. gr.—1.10 at 25°C.

USES: For the protection of light colored rubber from oxidation. It is also useful in any rubber product used in contact with surfaces such as lacquer or enamel which are subject to staining by ordinary antioxidants. *Santowhite Crystals* provides excellent protection against normal aging. Use 1% to 2% on the hydrocarbon. Excellent for the protection of non-staining Neoprene compounds against heat deterioration.

SANTOWHITE® L (Euxanthyl) thiobis-(di-sec-amylphenol).

SPECIFICATIONS: Appearance and condition—dark, viscous liquid; ash—0.25% max.; heat loss—0.5% max.; softening point—0°C, max.; sp. gr.—0.99 at 50°C.

USES: For protection of rubber and rubber latex from oxidation. It is easily emulsified and has no effect on latex stability. It is a non-staining and non-discoloring antioxidant of medium strength.

SANTOWHITE® MK

Reaction product of 6-tert-butyl-m-cresol and SCH.

SPECIFICATIONS: Appearance and condition—dark, viscous liquid; ash—0.5% max.; heat loss—3% max.; softening point—20° to 35°C.; sp. gr.—1.06 at 25°C.

USES: For protection of rubber from oxidation. It is excellent from the standpoints of staining and discoloration. Use 1% to 2% on the hydrocarbon. Gives good protection to uncured SBR latex compounds.

SANTOWHITE® POWDER 4,4'-butylenedioxy-bis-(6-tert-butyl-m-cresol).

SPECIFICATIONS: Appearance and condition—white powder; ash—0.3% max.; fineness (100 mesh)—trace max.; retained; melting point—209°C, min.; heat loss—0.5% max.; sp. gr.—1.03 at 25°C.

USES: For protection of latices and dry rubber against oxidation. It is unequaled from the standpoints of staining and discoloration. Use 1% to 2% on the hydrocarbon.

SPECIAL MATERIALS

SULFASAN® R 4,4'-dithiodimorpholine.

SPECIFICATIONS: Appearance and condition—gray to tan powder; ash—0.5% max.; heat loss—0.5% max.; melting point—122°C min.; fineness (100 mesh)—0.1% max. retained; (200 mesh)—2.0% max. retained; sulfur—26 to 29%; sp. gr.—1.36 at 25°C.

USES: Vulcanizing agent. Stocks containing Sulfasan R give excellent aging and freedom from cured bloom. It does not discolor white compounds. Especially effective with Sulfenamide accelerators.

ELASTOPAR®

N-Methyl-N,4-dithiosuccinimide (33 1/3%) plus inert diluent (66 2/3%).

SPECIFICATIONS: Appearance and condition—light colored, free flowing powder; assay—31.6-35.0%; fineness (30 mesh)—trace max. retained; heat loss—0.5% max.; sp. gr.—2.05@25°C.

USES: For chemically modifying butyl rubber. Used in a range of 0.5 to 1.25% on the butyl. When mixed at about 300°F. under proper conditions, the following results may be expected: improved resilience; increased modulus; slightly lower hardness; increased resistance to abrasion; better low-temperature flexibility; increased electrical resistivity; reduced cold-flow of unvulcanized gum; reduced Mooney viscosity.

NOTE: Butyl and Elastopar should be reacted in the absence of curatives and other reactive compounds. In a Banbury, the reaction will take place in about one minute at 300°F. Lower temperatures should be avoided and higher temperatures do no harm.

INSOLUBLE SULFUR 60

SPECIFICATIONS: Appearance and condition—greenish yellow powder; fineness (45 mesh)—trace max. retained; heat loss—1.4% max.; insolubles (carbon disulfide) 55% min.; sp. gr.—2.0 at 25°C.

USES: Used to retard sulfur bloom on uncured natural rubber or synthetic rubber surfaces. Used in the same amount as regular sulfur. With this type of sulfur there is usually a slightly enhanced rate of cure.

MONOMERS FOR SYNTHETIC RUBBER

ACRYLONITRILE

See Page M5/20

STYRENE MONOMER

See Page M5/21

SPECIALTY PRODUCTS

ADHESIVES

CASEIN AND SOYBEAN ADHESIVES

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Dry powder.

PROPERTIES: Exceptionally good for low-temperature bonding applications where average to superior water resistance is desired.

USES: Cold-setting glues used in the manufacture of plywood, furniture, assembly gluing, case goods of all types. Also used in Monsanto's patented NO-CLAMP Process for making plywood, as well as in nail pressure gluing operations.

INDUSTRIAL USES: Plywood and Forest Products Industries.

SHIPPING INFORMATION: Multiwall bags (100-lbs.). Glues Dry. NOIBN.

PHENOLIC AND RESORCINOL RESINS

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquids.

PROPERTIES: Various properties are available for requirements demanding an extremely high degree of water resistance. Bonds can be made capable of withstanding continuous boiling.

USES: Glues for plywood, hardboard, particle board and general woodworking. Used for hot and cold pressing and for radio frequency work.

INDUSTRIAL USES: Plywood, Hardwood, Particle Board and General Woodworking Industries.

SHIPPING INFORMATION: Metal drums (500-lbs.); tank trucks and tank cars. Glues Liquid, NOIBN.

UREA AND MELAMINE RESINS

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquids; dry powders.

PROPERTIES: Various properties are available for uses requiring varying degrees of water and weather resistance, speed of set and strength.

USES: Hot and cold setting adhesives for the plywood and woodworking industries. Bonding agent for particle board. Can be formulated for high frequency equipment.

INDUSTRIAL USES: Plywood, Particle Board, and Forest Products Industries.

SHIPPING INFORMATION: Fiber drums (250-lbs.) for powdered melamine resins. Metal drums (550 lbs.), tank trucks and tank cars for liquid urea resins. Dry Powders: Rail—Plastics. Synthetic, other than liquid, NOIBN. Truck—Plastics. Powder, Liquid: Rail—Plastics. Synthetic. NOIBN. Truck—Plastics, Liquid, NOIBN.

ANTI-CAKING FLOW CONDITIONERS

SANTOCOL® Silica Aerogel for Industrial Applications.

INORGANIC DIVISION—LITERATURE AVAILABLE

TYPICAL ANALYSIS:

Range of Various Grades

	Unit	SANTOCOL
Bulk Density	lb/cu. ft.	5-6
Particle Size (AV)	microns	3-5
Surface Area	sq. meters/gm	130-390
Oil Absorption	gm. oil/gm	3.0-3.5
SiO ₂	%	90.0-98
Volatiles	%	3.5-5.0
Na ₂ SO ₄	%	0.03-3
pH		3.5-3.8
Index of Refraction	—	1.45-1.46
Absolute density	lb/gal.	17.1

GRADES: Santocel O, Santocel OS, Santocel OX, Santocel 54, Santocel FR-O, Santocel O2, Santocel Z.

USES: Flattening agent to produce matte finishes in coatings of all types (lacquers, varnishes, vinyl resin coatings and resin dispersions); bonding agent in printing inks; bulking agent for dry powders, free-flowing and anti-caking agent for dry powders; insecticide for stored industrial grains; application aid for rubber cements; reinforcing agent for silicone rubbers; bonding agent to make lubricating greases; dry grinding aid for P.D.T. and other sticky powders; to raise heat distortion point, as in molded brake linings; mold lubricants for hard rubber; bonding agent for paint removers; anti-setting agent for plasters; anti-slip agent in paste floor waxes; flattening agent for free film and textile coatings. Imparts thixotropic properties to polyester and epoxy resin dispersions and solutions; thickening and thixotropic agent for polyvinyl chloride plasticizers and plasticizer dispersions.

SHIPPING INFORMATION: Silica NOIBN less than 10 lb. per cu. ft. Multiwall bags, G. OS, FR-O—25-lb.; OX—15-lb.; 54—20-lb.

SANTOCOL® Silica Aerogel for Thermal Insulation.

INORGANIC DIVISION

STANDARD FORM: Santocel A—sugar-sized particles.

TYPICAL ANALYSIS: Approximate analysis for all insulation grades of Santocel: SiO₂ 93.0-96.0%; volatile* 0.5-1.5%; Na₂SO₄ 2.5-3.5%; Fe₂O₃ and Al₂O₃ 1%.

*Volatile in water, alcohol, acetaldehyde.

PROPERTIES: Known technically as a silica aerogel, it possesses the lowest coefficient of thermal conductivity known. Dry bulk density: Santocel A, 5-lbs. per cu. ft.; absolute density 7.1 lbs. per gal.; specific heat 0.234; angle of repose 12.5°; thermal conductivity (mean temp. 60°F.) 0.150 BTU/HR./Ft.²/in.²/°F.

(Continued on next page)

0557334

Monsanto

TOWOLDMON0041068

USES: Adapted for any use where efficiency or space saving is a factor in thermal insulation, especially in freezers, shipping containers, insulated trucks, trailers and freight cars, liquid oxygen manufacture and storage, and cold-storage room floors.

SHIPPING INFORMATION: Silica NOIBN. Less than 10 lb. per cu. ft. Multivall paper bags 20-lbs. net.

ANTI-FOAMING AGENTS

PC-1244® DEFOAMER

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Clear light yellow liquid.

SPECIFICATIONS: Color ASTM 0.5; Sp. Gr. 0.86 at 60°/60°F.; viscosity, SFS at 100°F., 100-7.72-lus. per gallon.

GENERAL INFORMATION: Solubility—PC-1244 is soluble in benzene, toluene, kerosene, petroleum ether, carbon tetrachloride, isopropanol, tertiary amyl alcohol, butyl cellosolve and ethyl acetate. It is not soluble in water, methanol, ethanol, and methyl cellosolve.

USES: Foam control in non-aqueous systems. In paraffin wax formulations it not only controls foam, but also imparts a leveling action. Unusually effective in neutral or acidic media.

SHIPPING INFORMATION: Chemicals NOIBN. 53-gal. non-returnable black iron drums; 5-gal. cans; tank cars.

ANTI-SLIP AND ANTI-SOIL AGENTS

SYTON® AS-200 COLLOIDAL SILICA

INORGANIC DIVISION—LITERATURE AVAILABLE

GENERAL INFORMATION: Most carpet fabrics can have their soiling properties improved by a treatment of a very finely divided colloidal silica dispersion. Wool-raxon blends, cotton and other synthetic carpets can be markedly improved against soiling by a silica sol treatment. Pure wool carpets are less subject to improvement than the synthetics or blends. In combination with certain film formers, paper surfaces can be made soil resistant. When directly applied to hard surfaces, soil resistance results.

USES: For use as an anti-soilant for pile fabrics.

SHIPPING INFORMATION: Colloidal Silica, Liquid (NB Freezes 32°F. Keep from freezing). 550-lb. drums.

SYTON® C-30 AND 200 COLLOIDAL SILICA

INORGANIC DIVISION

TYPICAL ANALYSIS:

	Syton C-30	Syton 200
SiO ₂	70%	30%
Water	30%	70%
Na ₂ SO ₄	0.15%	0.10%
Sp. Gr.	1.3	1.2
pH	10.0	8.7
Appearance	Milky white	Slightly turbid liquid
Ultimate particle size	350-400 angstroms	100-250 angstroms

GENERAL INFORMATION: Colloidal dispersion of silica in water. Will freeze at 32°F. and the silica is precipitated irreversibly.

USES: Anti-blackening agent in water finishes. Gloss control agent in water finishes. Increase bond strength of rubber latex adhesives. Increase modulus of latex film and thread. Surface harden water base laminating resins. Suspending agent for pigments in water systems. Mold lubricant. Binder for precision casting molds. Flame retarding agent for water-based paints. Improves soil resistance of hard surfaces. Improves scrub and soil resistance of water-based paints.

SHIPPING INFORMATION: Colloidal Silica, Liquid (NB: Freezes 32°F. Keep from freezing). 550-lb. drums.

SYTON® C-40 & 240 COLLOIDAL SILICA

INORGANIC DIVISION—LITERATURE AVAILABLE

Typical Physical and Chemical Properties

	C-40	240
SiO ₂	40	40
Water	60	60
Specific Gravity	1.28-1.30	1.28-1.30
Viscosity Centipoise		

(25°C, Brookfield #1

Appearance**

pH at 25°C

Compatibility

Ultimate particle size

Clarity (% trans-

mission by

Electrophotometer)

Lbs. per gallon

Lbs. SiO₂ per gallon

Milky White

Dispersion

Excellent with nonionic and anionic

surfactants

350-400 Angstroms

35-40 millimicrons

10

10.77

4.30

Slightly turbid

liquid

Excellent with nonionic and anionic

100-250 Angstroms

10-25 millimicrons

50

10.77

4.30

**The visual differences can be related to differences in ultimate particle size using light scattering techniques.

A 40% concentration of SiO₂ in the form of colloidal silica sol. Have the same application as the 30% grades with added advantage of freight warehouse and handling savings. These particles are inert, chemically inert, pure SiO₂. The colloidal suspension has a low viscosity and may be applied by rolling, spraying, brushing or dipping. Syton is used where frictionless, slip, reinforcing or surface modifying properties are desired. Heat stability tests show that Syton undergoes no increase in viscosity when heated even as long as 200 hours at 770°F. in a closed container. If the water is allowed to evaporate, either at room or higher temperatures, Syton 240 or Syton C-40 will exhibit a greater tendency toward formation of silica scale or deposits due to higher silica concentrations.

SYTON® C-30 AND 250

INORGANIC DIVISION

Typical Physical and Chemical Properties

	C-50	250
SiO ₂	50	50
Water	50	50
Specific Gravity	1.38	1.38
Viscosity Centipoise		
(25°C, Brookfield #1		
Spindle)	20	17.5
pH at 25°C.	9.6	9.6

A 50% concentration of SiO₂ in the form of colloidal silica sol. Same applications as 30% and 40%, with added benefits of freight, warehouse and handling savings.

SYTON® DX AND DS-200 COLLOIDAL SILICA

INORGANIC DIVISION—LITERATURE AVAILABLE

GENERAL INFORMATION: Extremely fine colloidal aqueous dispersions of silica. In textile spinning, controls the slippage between fibers, thereby increasing tensile strength of spun yarns, permitting less twist in some cases, or fewer breaks during spinning and weaving. In textile finishing, controls slippage in woven rayons, gives dry worsted-like hand, delusters in higher concentrations.

USES: Spinning, wet processing and finishing textiles.

SHIPPING INFORMATION: Colloidal Silica, Liquid (NB: Freezes 32°F. Keep from freezing). 550-lb. drums.

SYTON® W-200 COLLOIDAL SILICAS

INORGANIC DIVISION—LITERATURE AVAILABLE

GENERAL INFORMATION: Syton W-200 is an extremely fine colloidal aqueous silica dispersion and is used in wax emulsions primarily to give anti-slip properties to the wax applications.

USES: For use as an anti-slip agent in wax emulsion polishing compounds.

SHIPPING INFORMATION: Colloidal Silica, Liquid (NB: Freezes 32°F. Keep from freezing). 550-lb. drums.

ANTIOXIDANTS

SANTOQUIN® AND SANTOQUIN® Mixture No. 6

ethoxyquin, 1,2-dihydro-6-ethoxy 2,2,4 trimethylquinoline

AGRICULTURAL DIVISION—LITERATURE AVAILABLE

GENERAL INFORMATION: Santoquin is added to manufactured animal feeds to protect the important nutrients against oxidative destruction. The addition of 0.0125% or 0.25 pounds liquid or 8 ounces dry form per ton of complete animal feeds will preserve the carotenes and xanthophyll pigments as well as Vitamins A and E.

Santoguin is also an antioxidant used in dehydrated forage crops for the preservation of carotenes and Vitamin E. The use level permitted in the Regulation issued by the United States Food and Drug Administration is 0.015% or 0.3 pounds liquid form per ton of forage crops.

LIQUID FORM: Dark liquid - varies from yellow to black but biological activity is independent of color. Liquid Santoguin is a 100% biologically active antioxidant.

DRY FORM (MIXTURE #1): Contains 66.6% Liquid Santoguin and 33.4% food grade vermiculite (verxite). A brown, free-flowing granular material with a density of 23 pounds per cubic foot.

EMULSION FORM: Contains 70% Liquid Santoguin, 7% emulsifier, and 23% water. Santoguin emulsion should be diluted with water to provide uniform distribution. To be used in preserving dehydrated forage crops only.

50PANOX® ortho-TOLYL BIGUANIDE

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 200.24

STANDARD FORM: Powder.

SPECIFICATIONS: White to off-white powder; assay 90% min.; loss on drying 5% max.; melting point 185°C. min.; trace retained on a 30 mesh sieve; alcohol insolubles 0.5% max.

PROPERTIES: An amino compound effective in minute quantities in restraining the oxidation of soap and the resulting rancidity, discoloration and other adverse qualities, all of which must be avoided in producing a product of highest grade.

USES: Our experience shows that *Santoguin* satisfies the exacting demands of manufacturers of soaps produced from animal or vegetable oils, filled or unfilled. Particularly valuable in preventing discoloration or refined toilet soaps.

SHIPPING INFORMATION: Chemicals NOIBN. 150-lb. lever paks.

BACTERIOSTATS / DISINFECTANTS / FUNGICIDES FUNGISTATS / GERMICIDES

ACL®

See Page M5/54

ACTAMER® 2, 2' (thiobis[4,6-dichlorophenol])

ORGANIC DIVISION—LITERATURE AVAILABLE

SPECIFICATIONS: White powder; assay 99.0% min.; color of solution (10:100 of Acetone): 100 APIFA max.; loss on drying 0.025% max.; screen test retained on 50 mesh 1.0% max.; retained on 200 mesh 20.0% max.; melting point 167°C. min. (first melt/caus).

USES: *Actamer* is an effective skin bacteriostat, a non-toxic, low cost, royalty-free degerming agent recommended for incorporation in soaps and other topically applied pharmaceutical and cosmetic preparations.

SHIPPING INFORMATION: Chemicals NOIBN. 200 and 50-lb. fiber drums.

CHLORAMINE-T

Also known as N-hydroxy-N-chloro-pyrazolene-sulfonamide.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 281.70

STANDARD FORM: Crystalline powder.

SPECIFICATIONS: White or faintly yellow powder or crystals; solubility in water (2:15) complete; moisture 18.0-20.0%; available chlorine 24.5-25.2%; assay 97.3% min.; trace max. retained on 10 mesh; 15% retained on 35 mesh.

USES: A water-soluble, chlorine-bearing powder used as a germicide, disinfectant and deodorant.

SHIPPING INFORMATION: Disinfectant Other Than Medicinal NOIBN. 300-lb. fiber drums; 125-lb. lever-paks.

MONSANTO® PENTA

Pentachlorophenol, Technical

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 266.35

STANDARD FORM: Flakes. *Monsanto Penta* Oiled also available. Contains 3-lbs. oil per 100-lbs. of *PENTA TETRACHLOROL*. Oil decreases somewhat the dusting tendency of the product.

SPECIFICATIONS: Dark, grayish flakes; crystallizing point 174.0°C. min.; melt; insoluble material 1.0% max.; assay 96.0% min.; pine oil solution NPA 5.5 max. Meets Federal Specification TT-W-570.

PROPERTIES: Chlorophenolic odor; bulking value 45.5 lbs. per cu. ft.; stable under ordinary conditions; relatively non-hydroscopic and unreactive chemically; soluble to various degrees in organic solvents; relatively insoluble in water.

USES: Highly toxic to fungi, termites and many forms of bacteria. Used industrially where the growth of microorganisms must be prevented or controlled: to protect wood and against rot, termites and Lyctus (Powder-Pot) beetles; as an effective herbicide. *Penta* is used frequently in oil solutions or as the sodium salt (see *Santobrite*).

SHIPPING INFORMATION: *Pentachlorophenol*, 100-lb. fiber container; 50-lb. multiwall paper bags. Oiled *Penta* 16½-gal. lever-pak; 51-lb. multiwall paper bags.

SANTOBRITE® SODIUM PENTACHLOROPHENATE, TECHNICAL

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 288.36

STANDARD FORM: Neutral powder, pellets, fines or briquettes.

SPECIFICATIONS: Light tan powder, pellets, fines or briquettes; assay 98.0% min.; free alkali (as NaOH) 0.5-0.9%.

PROPERTIES: Comparatively odorless; stable under ordinary atmospheric conditions when stored in dry place; bulking value: briquettes 40-50 lbs./ft.³, pellets 35-40 lbs./ft.³, powder 50-60 lbs./ft.³; soluble in water and various organic polar solvents. Relatively inert toward organic compounds.

USES: A water-soluble industrial preservative, fungicide and herbicide. Used for the manufacture of termite-resistant cellulose insulating board and for the preservation of wood, cellulose products, textiles, starches, adhesives, leather, oils, paints, latex and rubber. Also for control of algae and algae; manufacture of herbicides; as a fermentation disinfectant; for control of sap stain in green lumber.

SHIPPING INFORMATION: Sodium Pentachlorophenolate, 100-lb. fiber containers.

SANTOPHEN® 1 GERMICIDE *ortho-benzyl-parachlorophenol*

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 218.68

STANDARD FORM: Flaked solid.

SPECIFICATIONS: White to light tan or pink flakes; crystallizing point 45.0°C. min.; Sp. Gr. 1.186-1.190 at 55°/15.5°C.; free acidity (as HCl) 0.01% max.; odor slight phenolic max.

PROPERTIES: *Santophen 1* possesses high bactericidal and fungicidal activity, but low toxicity to higher animals. When properly formulated for disinfectant use, it is considered nonirritating in use dilutions. Insoluble in water, but highly soluble in alcohol and other organic solvents; dispersible in aqueous media with the aid of soaps or synthetic dispersing agents. Noncorrosive to most metals or other engineering materials. *Santophen 1* can be easily rendered water soluble by converting it to the sodium salt.

USES: Used as the active chemical agent for finished products that destroy harmful microorganisms that attack human beings, animals and naturally derived materials.

SHIPPING INFORMATION: Disinfectant Other Than Medicinal NOIBN. 55 and 22-gal. jacquer-lined drums.

SANTOPHEN® 1 SOLUTION

75% *Santophen 1*, 25% *isopropanol*.

ORGANIC DIVISION

STANDARD FORM: Liquid

SPECIFICATIONS: Straw to amber colored liquid; assay 75.0 to 77.0%; Sp. Gr. 1.080-1.090 at 15.5°/15.5°C.; color: Barrett Std. No. 3 max.; moisture 0.25% max.

USES: Used as the germicidal active principle, or as an enhancing agent for disinfectants. *Santophen 1* solution is convenient for formulators who normally dissolve the compound in isopropyl alcohol. The use of *Santophen 1* solution saves one step in formulation procedures.

SHIPPING INFORMATION: Disinfectant Other Than Medicinal NOIBN. 55 and 15-gal. drums.

TCC 3, 4, 4' Trichlorocarbazine.

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 315.6

STANDARD FORM: Micronized and unmicronized.

SPECIFICATIONS: Fine white to grayish white powder; loss on drying at 110°C., 0.15%; melting point 250.0°C. (first melt); particle size:

micronized	30 microns max.
	microns ave.
unmicronized	0.1% retained on a 30 mesh screen

USES: 3,4,4' trichlorocarbazine is recommended for incorporation into soap and other topically applied preparations as a degerming agent.

SHIPPING INFORMATION: Chemicals NOIBN. 100-lb. fiber drums—micronized, 200-lb. fiber drums—unmicronized.

CHEMICAL SPECIALTY CATALYSTS

VANADIUM SULFURIC ACID CATALYST

ENGINEERING SALES—INORGANIC DIVISION

GENERAL INFORMATION: Sold in conjunction with complete plants of Monsanto design and also for replacement purposes in any contact plant.

USES: In manufacture of sulfuric acid by contact process. (Not suitable for other purposes.)

SHIPPING INFORMATION: Chemicals NOIBN. 50-Liter Leverpak.

CURING AGENTS

CATALYSTS

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORMS: Catalyst AO is light yellow liquid compatible in resin baths with most cationic, anionic, anionic and nonionic softeners and penetrators. Catalysts AO is used with *Neoslon* HP finishes. Catalyst AC-4 and AC-8 are clear, compatible liquids. AO-7 is an organometallic catalyst designed for curing formaldehyde-containing resins used in the textile industry.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Speeds cure of cyclic-urea and melamine treating resins.

USES: To provide rapid and uniform resin cure and retention in treatment of fabrics, including rayons, cottons and the synthetics.

INDUSTRIAL USES: Textiles.

SHIPPING INFORMATION: AO—475-lb. drums; AC-2 thru AO-7—500-lb. drums. All AO series can be shipped in liquid bulk. Glue Catalyst NOIBN.

FIRE RETARDANTS

PHOS-CHEK®

INORGANIC DIVISION—LITERATURE AVAILABLE

SPECIFICATIONS:	Phos-Chek 201	Phos-Chek 202	Phos-Chek 208
% P ₂ O ₅	46.5 min.	47.0 min.	47.7
Viscosity, cpa. @ 75°F. (1)	600 min.	400 min.	100-250
Corrosion: (2)			
On Aluminum	1 mil/yr. max.	1 mil/yr. max.	1 mil/yr. max.
On Copper	1 mil/yr. max.	1 mil/yr. max.	1 mil/yr. max.
(1) Brookfield Viscometer, 60 rpm. Spindle #4 on a 13% solution.			
(2) Alternating 30 sec. immersion and drain cycles @ room temp. for 72 hours.			
USES: For preparing fire fighting solutions. 201 and 202 are designed for application from aircraft; 208 is applied from ground equipment and helicopters.			

FLAVORINGS

CAFFEINE ANHYDROUS U.S.P.

See Page M5/13

ETHAVAN® Ethylvanillin

See Page M5/13

VANILLIN MONSANTO U.S.P.

See Page M5/14

*Monsanto Trademark

Monsanto

METHYL SALICYLATE U.S.P.

See Page M5/13

SACCHARIN (CALCIUM AND SODIUM) U.S.P.

See Page M5/14

METAL PROCESSING COMPOUNDS

BONE ASH

INORGANIC DIVISION—LITERATURE AVAILABLE

PROPERTIES: A very finely divided bone ash used as a mold-wash for coating molds used in casting copper wire, bars, ingots and slabs. A superior mold coating for certain steel and aluminum casting operations. This product is also used in producing high-grade chinaware.

SHIPPING INFORMATION: Bone Ash.

NFB® 80 AND 85 Non-fuming Aluminum Bright Dip Bath

INORGANIC DIVISION

FORMULA: 80% H₂PO₄ + trace additives
85% H₂PO₄ + trace additives

STANDARD FORM: Liquid

TYPICAL ANALYSIS:	NFB® 80	NFB® 85
Sp. Gravity at 15.5°C.	1.64	1.7
P ₂ O ₅	56.0%	61.6%
H ₂ PO ₄	80.0%	85.0%
Copper	.01%	.01%

USES: Proprietary solutions used exclusively in the aluminum bright dipping industry as direct replacements for 80% and 85% phosphoric acid and various additives now used. It decreases nitric oxide fumes and chemical cost of operations, frequently with improved work quality.

SHIPPING INFORMATION: Phosphoric Acid. Tank car and tank truck.

ODORANTS

COUMARIN

ORGANIC DIVISION—LITERATURE AVAILABLE

MOLECULAR WEIGHT: 146.14

STANDARD FORM: Crystalline solid.

SPECIFICATIONS: White crystals; melt (liquid) clear and colorless; M.P. 68.8°C. min.; solubility in ethyl alcohol (1:10) complete; moisture 0.10% max.; ash 0.05% max.; conforms to N.F. test for acetalid.

GRADES: Crystals.

USES: Deodorizing and odor enhancing agent; used in perfumes, soaps, tobacco, inks, rubber and other products where aromatic ingredients are required.

SHIPPING INFORMATION: Chemicals NOIBN. 200 and 25-lb. fiber drums.

METHYL SALICYLATE U.S.P.

See Page M5/13

SANTOMASK® II ODOR-MASKING AGENT

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

SPECIFICATIONS: Clear, light yellow liquid; pleasant characteristic odor; Sp. Gr. 23°/25°C. 1.18 to 1.20; color NPA 2.0 max.; chill test, clear @ 0°C.

USES: Odor-masking ingredient for interior paints, printing inks and similar products having objectionable natural odors. Will not affect drying time, color durability and other characteristics of paints and inks.

SHIPPING INFORMATION: Chemicals NOIBN. 250 and 45-lb. drums.

0557337

TOWOLDMON0041071

VANILLIN MONSANTO U.S.P.

See Page M5/14

PAINT/COATING INGREDIENTS

BENTHAL® ALKYD RESIN INTERMEDIATE

ORGANIC DIVISION

STANDARD FORM: White flakes.

TYPICAL ANALYSIS: Moisture 0.20% max.; C.P. 121.5°C. (min.); boiling value 12.7 lbs./gal.

USES: Benthal is used in short oil alkyds which are primarily baked finishes for appliance and automotive enamels. By reducing excess amounts of alcohol in the formulation and introducing Benthal in quantities of 3-20% by weight on the phthalic anhydride, enamels show substantial improvement in gloss, hardness and durability. The Benthal acts as a chain terminator hence retarding the viscosity increase until low acid values are obtained in the resin.

SHIPPING INFORMATION: Resin Plasticizer. 200-lb. net wt. fiber drums. 50-lb. bags.

BISPHENOL A

See Page M5/36

D. P. SOLUTION® Dibutylamine Pyrophosphate.

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: Pale straw-colored liquid; wt. per gal. 8.2 lbs.; 40% sol. in equal parts of ethyl alcohol and acetone.

USES: An anticorrosion agent in lacquers and cotton solutions; an agent to prevent the settling of "Santocel" in flat lacquer formulations; for light and heat stabilization of vinyl chloride and vinyl copolymer resins.

SHIPPING INFORMATION: Chemicals NOIBN. 55 and 5-gal. Heresite-lined steel drums.

DIBUTYL FUMARATE

See Page M5/36

DIBUTYL MALEATE

See Page M5/36

DIOCTYL FUMARATE (DOF)

See Page M5/36

DIOCTYL MALEATE (DOM)

See Page M5/36

HYDROGENATED BISPHENOL A (HBPA®)

See Page M5/36

LAMPBLACK

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Powder.

PROPERTIES:

Grade	% Free Car-	% 40L/Black Absorp-	Tinting Strength*	Under Tone	Top Tone
Black	bon	tion			
J1	99.37	1.14	238	Blue	Black
AA	97.97	1.05	225	Blue-Brown	Brown-Black
J2	99.42	1.29	206	Blue-Gray	Gray-Black
#8	91.49	1.54	205	Blue	Brown-Black
S-100	98.08	1.37	170	Blue	Black
BTA	98.62	1.42	160	Blue	Blue-Black
B-4	98.92	1.34	140	Blue	Blue-Black
J10	99.29	1.25	100	Blue-Gray	Gray
J100	99.10	1.26	105	Blue-Gray	Gray

*NOTE: The figures in the column TINTING STRENGTH are relative values using No. 10 lampblack as a standard. For example, A value of 225 for tinting strength of AA lampblack means that this black is 2 1/4 times as intense as No. 10 lampblack.

USES: Pigment in paints, varnishes, enamels, inks, leather finishes, stencils, crayons, pollaxes; in pressed forms as electrodes, carbon brushes and molded carbon products.

SHIPPING INFORMATION: Lampblack NOIBN when wt. per cu. ft. is under 17-lbs.; Lampblack Compressed when wt. per cu. ft. is 17-lbs. or over. Paper bags and cartons.

MALEIC ANHYDRIDE

See Page M5/18

MERTONE® WB-4 Precoat for Reproduction Papers.

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Liquid.

PROPERTIES: A 30% colloidal dispersion of silica in water; odorless.

USES: As a precoat on blueprint and other reproduction papers for clearer, more legible prints. On blueprint a darker, more lively blue is obtained. Also used on diazo paper, blueprint cloth, negative paper and Van Dyke paper. Precoating is performed by coaters. U. S. reissue patent No. 23510 (Andrews Paper and Chemical Co.) relates to the precoating of photosensitive papers with colloidal silica.

SHIPPING INFORMATION: Chemicals NOIBN. 55-gal. lined steel drums.

MODAFLOW®

See Page M5/18

PHTHALIC ANHYDRIDE

See Page M5/36

RESIMENE®, RESIMENE®, MELAMINE, RESINOX®, PHENOLIC VARNISHES

See Pages M5/34 and 35

SANTOCEL® Silica Aerogel for Industrial Applications.

See Page M5/47

SANTOCEL® 62 AEROGELS

INORGANIC DIVISION—LITERATURE AVAILABLE

Flattening agent for clear and pigmented protective and decorative coatings. High flattening efficiency, short dispersion times in pebble mill or high speed mixers. Yields final film of excellent smoothness. Settling on storage only slight and can be easily redispersed.

SANTOCEL® L AEROGELS

INORGANIC DIVISION—LITERATURE AVAILABLE

A silica aerogel used as an additive for drying emulsion paint films without flocculation. Improves hiding power of TiO₂, film integrity and thixotropic properties.

SANTOMASK® II ODOR-MASKING AGENT

See Page M5/50

SYTON® AS-200 COLLOIDAL SILICA

DISPERSION FOR WATER-BASED PAINTS

See Page M5/48

VYSET® 69 RESINS First Resin of Series

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Supplied in organic liquid solution.

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Surface coatings, thermosetting acrylic type prepolymer crosslinked with dipoxy resins. Imparts superior stain, solvent and chemical resistance to property cures and formulated coatings.

USES: Appliances, laboratory and hospital furniture and other metal finishes that require these excellent properties.

PAPER CHEMICALS

ALUMINUM SULFATE

ORGANIC DIVISION

FORMULA: Al₂(SO₄)₃ · 14.5 H₂O (dry); Al₂(SO₄)₃ (liq.)

MOLECULAR WEIGHT: 903.35.

STANDARD FORMS: Dry: white powder, ranging to small lumps. Liq: Clear liquid.

USES: Paper sizing and water treatment.

SHIPPING INFORMATION: Aluminum Sulfate. 100-lb. paper bags.

MERSIZE® Paper Sizing Agent.

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Paste, powder and liquid.**GENERAL INFORMATION:** *Mersize TFL 70%, 77% and 80%* solids paste sizes; *Mersize RM Dry* a dry granular powder; *Mersize CD-2* a 50% solids solution; *Mersize CD-2* a dry powder.**USES:** *Mersize TFL 70%, 77% and Mersize RM Dry* are forms of chemically fortified rosin-based sizes that are ready to use in a paper mill to reduce sizing costs, improve resistance to ink, water and other aqueous solutions, give better feathering resistance and more uniform deposable sizing. *Mersize CD-2* and *Mersize CD-2 Dry* are used in conjunction with typical rosin sizes to obtain the same results.**SHIPPING INFORMATION:** Tank cars, 500-lb. steel drums and 50-lb. bags. Rosin Sizing NOIBN.**SALT CAKE SODIUM SULFATE, ANHYDROUS TECHNICAL**

ORGANIC DIVISION

MOLECULAR WEIGHT: 142.06**STANDARD FORM:** Powder.**TYPICAL ANALYSIS:** The 93-95% grade is typical white salt cake. The 96-99% grade is a special material having a light tan color and Na₂SO₃ content of approximately 99%.**USES:** Manufacture of sulfate pulp and glass.**SHIPPING INFORMATION:** Salt Cake, Bulk car loads.**SANTOBRITE® SODIUM PENTACHLOROPHENATE** Paper Mill Sulfonate.

See Page M5/49

SANTOSITE® SODIUM SULFITE ANHYDROUS

ORGANIC DIVISION—LITERATURE AVAILABLE

FORMULA: Na₂SO₃**MOLECULAR WEIGHT:** 126.06**STANDARD FORM:** Powder.**TYPICAL ANALYSIS:** Tan to slightly pink crystalline powder; assay (Na₂SO₃) 97.7% min.; color of filtrate from 10% solution in water not darker than APHA 70.**PROPERTIES:** Will oxidize to sodium sulfate if not kept dry. Normally contains less than 1% sodium chloride; less than 0.1% iron; less than 0.1% insoluble; less than 0.2% organic matter. The balance of impurity is sodium sulfate. The undiluted water solution has a brown color due to suspended Fe (OH)₃. Normally all of the product will pass through a No. 20 U. S. Standard sieve.**USES:** Manufacture of paper, highly efficient in the semi-chemical pulping of straw and wood for paper manufacture.**SHIPPING INFORMATION:** Sodium Sulfite, 100-lb. paper bags and hopper cars.**SANTOSIZE® PAPER SIZING AGENT**

ORGANIC DIVISION

GENERAL USE INFORMATION: Santosize 70% and 80% pale un-fortified rosin size and Santosize DFS 70% and 80% FF grade dark rosin size are used in specific applications where higher efficiency *Mersize TFL* is not required.**SHIPPING INFORMATION:** Tank cars, 500-lb. and 55-gal. drums.**SCRIPSET® 100, 300 SERIES**

Specialty Coating Resins

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: *Scriptset 100, 450*—Low-viscosity, clear liquids. *Scriptset 300, 350, 550 & 550*—Free-flowing white powders.**PROPERTIES AND PERFORMANCE CHARACTERISTICS:** Paper coating resin. Outstanding polyelectrolyte resins which improve the surface characteristics and printability of paper products and have good wax hold-out properties. Also used as resin binders in clay coatings.**USES:** Paper manufacturing.**INDUSTRIAL USERS:** Paper and Pulp Industry.**SCRIPTITE® SERIES WET-STRENGTH RESINS**

ORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORMS: *Scriptite 330*—finely divided powder*Scriptite 400*—Trans. colloidal solution**PROPERTIES AND PERFORMANCE CHARACTERISTICS:** Melamine Formaldehyde and Urea Formaldehyde resins.**USES:** To impart exceptional wet-strength to paper and paper-board.**SODIUM HEXAMETAPHOSPHATE**

See Page M5/26

STEROX® DF/STEROX® DJ/STEROX® NJ

See Page M5/54

SYTON® P and P-200 COLLOIDAL SILICA

ORGANIC DIVISION—LITERATURE AVAILABLE

GENERAL INFORMATION: The application of an extremely fine colloidal aqueous dispersion of silica applied either by spray or roller to multilayer paper bags or most any type of paper-board boxes or liner board will materially reduce slippage between the coated surfaces. Syton P is proving to be the most effective anti-skid agent.**USES:** For use on paper containers to make slip-resistant coatings.**SHIPPING INFORMATION:** Colloidal Silica, Liquid (NB: Freezeze 32°F. Keep from freezing). 50-lb. drums.**TRISODIUM PHOSPHATE, ANHYDROUS and CRYSTALLINE**

See Page M5/26 and 27

[NOTE: For complete listing of all pulping, paper-making and coating chemicals, request "Chemicals for the Paper Industry" from Paper Chemicals Department, St. Louis, Missouri, 63166.]

SWEETENERS**SACCHARIN (CALCIUM AND SODIUM) U.S.P.**

See Page M5/14

DITOSE® CALCIUM CYCLAMATE U.S.P.

See Page M5/14

DITOSE® SODIUM CYCLAMATE N.F.

See Page M5/14

TANNING AGENTS**SANTOTAN® KR BASIC CHROME SULFATE**

INORGANIC DIVISION

FORMULA: Contains approximately 50% of $\text{Cr}(\text{SO}_4)_2(\text{OH})_2$ **STANDARD FORM:** Crystals.**TYPICAL ANALYSIS:** Dark green crystals; solution in water 5.500; color, basicity (CrO₄/SO₄) 101-103; basicity (Schriemmer) 57.5-59.7; chromium as CrO₃ 53.4% min.**USES:** In chrome tanning of calf, cow and horse hides and sheepskins.**SHIPPING INFORMATION:** Tanning Extract Dry NOIBN, 100-lb. paper bags.**ZINC OXIDE, TECHNICAL**

INORGANIC DIVISION

FORMULA: ZnO**MOLECULAR WEIGHT:** 81.38**SPECIFICATIONS:** Light gray or tan powder assaying 99.0% min. ZnO.**GENERAL INFORMATION:** This technical grade has been found acceptable in the rubber trade and paper manufacture.**SHIPPING INFORMATION:** Zinc Oxide Dry, 50-lb. bags.**TEXTILE CHEMICALS****RESLOOM® E-50 RESINS**

PLASTIC PRODUCTS AND RESINS DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Supplied as 50% solids cyclic ethylene urea formaldehyde resin in liquid form.

(Continued on next page)

PROPERTIES AND PERFORMANCE CHARACTERISTICS: Textile Resin, gives permanent textured effects, dimensional stability and wrinkle resistance to cottons, rayons and other synthetics.
USES: Assures permanent wash and wear finish for textiles.
INDUSTRIAL USERS: Textiles.
SHIPPING INFORMATION: Drums (525 lbs.); tank cars, tank trucks, Rail—Plastics, Synthetic, Liquid, NOIBN. Truck—Plastics, Liquid, NOI.

STYMER® VINYL STYRENE

See Page M5/33

STYON® DS-200 COLLOIDAL SILICA DISPERSION

See Page M5/48

THICKENING AGENTS

EMA® RESINS

See Page M5/36

SANTOCOL® Z AEROGELS

INORGANIC DIVISION—LITERATURE AVAILABLE

Designed to perform thixotropic and thickening functions in polyvinyl chloride plastisols and in various plasticizer dispersions. Offers the following advantages to vinyl plastisol manufacturers: more efficient on a cost/performance basis; 65-70% more efficient thickening power; at low and shear rates; imparts higher degree of thixotropy at equivalent loading levels; less tendency to settle.

WOOD PRESERVATIVE

MONSANTO® PENTA

Pentachlorophenol, Technical.

See Page M5/49

SURFACE ACTIVE AGENTS, DETERGENTS and BLEACHES

ANIONIC SURFACE ACTIVE AGENTS

DBBSA 99-B (Alkyl Benzene Sulfonic Acid—Biodegradable)

INORGANIC DIVISION

MOLECULAR WEIGHT: 316

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Active 98.0%; Total Sulfate as H₂SO₄, 1.0%; water and unsulfonated matter 3.0%.

GENERAL INFORMATION: It is produced by the sulfonation of refined linear alkyl benzene with SO₃ and contains a minimum amount of free sulfuric acid. It can be neutralized with various bases.

USES: Intermediate for the preparation of neutral alkyl aryl sulfonates. Primary use is in liquid detergents. See uses of Santomerse®.

*Monsanto Trademark

SHIPPING INFORMATION: Washing compound liquid, NOIBN. Tank cars and tank trucks: 450-lb. drums.

DBBSA 99U-B (Alkyl Benzene Sulfonic Acid Anhydrous—Biodegradable)

INORGANIC DIVISION

MOLECULAR WEIGHT: 316

STANDARD FORM: Liquid.

TYPICAL ANALYSIS: Active 98% total sulfate as H₂SO₄, 1.5%; water and unsulfonated matter 1.1%.

GENERAL INFORMATION: DBBSA 99U-B is a concentrated sulfonic acid derived from the SO₃ sulfonation of refined linear alkyl benzene.

USES: DBBSA 99U-B is a special low moisture content version of DBBSA, developed for use in solvent based emulsions.

SHIPPING INFORMATION: Washing compound NOIBN, liquid. Tankcars and tank trucks: 450-lb. drums.

SANTOMERSE® NO. 1-B (Alkyl Benzene Sulfonate—Biodegradable)

INORGANIC DIVISION

PROPERTIES: Neutral flakes, granular and powder form. 40% active.

GENERAL INFORMATION: Santomerse No. 1-b is an anionic high-foaming, all-purpose surface active agent which is stable in acid and alkaline solutions. It is used in all types of detergent formulations and has wide application wherever good wetting is essential.

SHIPPING INFORMATION: Washing compound, dry. 75-lb. bags and 175-lb., 200-lb. and 225-lb. drums depending on type of flake.

SANTOMERSE® 85-B (Alkyl Benzene Sulfonate—Biodegradable)

INORGANIC DIVISION

PROPERTIES: Neutral flakes or powder. 85% active.

GENERAL INFORMATION: Santomerse 85-b is an 85% active anionic surface active agent designed for use where a high active content is desirable and the presence of small amounts of sodium sulfate is not detrimental.

SHIPPING INFORMATION: Washing compound NOIBN powder, 200-lb. fiber drums.

SANTOMERSE® ME-B SLURRY

(Sodium Alkyl Benzene Sulfonate—Biodegradable)

INORGANIC DIVISION

PROPERTIES: Slurry.

TYPICAL ANALYSIS: Active 57-60%, total solids 60-63%. Unsulfonated oils as is basis 1.0% (P.E. extraction), alcohol insoluble 1.0%.

GENERAL INFORMATION: Santomerse ME-b Slurry is a special high solid, high active linear alkyl benzene sulfonate developed for detergent formulations.

SHIPPING INFORMATION: Washing compound, NOIBN, liquid. Tanktruck and tankcar: 3,000 gal. minimum.

NONIONIC SURFACE ACTIVE AGENTS

STEROX® AJ

STEROX® AJ-100

INORGANIC DIVISION—LITERATURE AVAILABLE

CHEMICAL COMPOSITION: Tricresoleethylene oxide condensates. (Polyoxyethylene ether)

PROPERTIES: Sterox AJ-100 is 100% active in a soft paste form. Sterox AJ is 85% active and a clear liquid. Each is soluble in water, and produces a moderate amount of foam. Extremely efficient as a surface active agent.

USES: Recommended for powdered detergent formulations, as an emulsifier in a variety of applications, and as an aid in textiles, paper and leather processing.

SHIPPING INFORMATION: Washing compound—NOIBN liquid. Tank cars and tank trucks: 450-lb. drums.

STEROX® AP**STEROX® AP-100**

INORGANIC DIVISION—LITERATURE AVAILABLE

CHEMICAL COMPOSITION: Tridodecyl ethylene oxide condensates. (Polyoxyethylene ether)**PROPERTIES:** Higher molecular weight than Sterox AJ-100. Sterox AP-100 is 100% active in soft paste form, while Sterox AP is 80% active and a clear more foam than Sterox AJ-100 and are more soluble in water solutions, in presence of other materials.**USES:** Generally same as Sterox AJ-100, but specifically designed for use in liquid detergents, or where greater solubility or solubilizing of other materials is desired.**SHIPPING INFORMATION:** Washing compound—NOIBN Liquid. Tank cars and tank trucks: 450-lb. drums.**STEROX® CD**

INORGANIC DIVISION—LITERATURE AVAILABLE

CHEMICAL COMPOSITION: Tall olethylene oxide condensate. (Polyoxyethylene ester)**PROPERTIES:** Nonionic, 100% active surface-active agent with high detergent action accompanied by low foaming. Compatible with other type detergents and builder materials. Light amber liquid.**USES:** Mixed with builder materials, an unusually high cleaning action is obtained with little sudsing. Used as a dedusting and conditioning agent for detergent compositions. Used in insecticide and herbicide formulations. Excellent rewetting agent for paper towels and products to increase water absorbency.**SHIPPING INFORMATION:** Washing Compound NOIBN Liquid. Tank cars and 475-lb. drums.**STEROX® DF**

INORGANIC DIVISION

CHEMICAL COMPOSITION: Dodecyl phenol-ethylene oxide condensate. (Alkyl aryl polyoxyethylene ether)**PROPERTIES:** Liquid, 100% active miscible with water at room temperature. Soluble in nonpolar solvents. Excellent emulsifier. Chemically stable, low foaming.**USES:** Designed as an intermediate for sulfation, thus producing high foaming, highly soluble surface active agents for liquid detergents. Per se, an excellent emulsifier, oil soluble, useful in metal cleaning, textile and paper processing, etc.**SHIPPING INFORMATION:** Washing Compound NOIBN Liquid. Tank cars and tank trucks: 470-lb. drums.**STEROX® DJ**

INORGANIC DIVISION

CHEMICAL COMPOSITION: Dodecyl phenol-ethylene oxide condensate. (Alkyl aryl polyoxyethylene ether)**PROPERTIES:** Liquid, 100% active, soluble in water. Low odor and color. Higher molecular weight than Sterox DF. Chemically stable, low foaming. Optimum detergency.**USES:** For low foaming powdered and liquid detergents. Excellent detergency properties. Low odor and color levels give more sales appeal to finished detergents.**SHIPPING INFORMATION:** Washing Compound NOIBN Liquid. Tank cars and tank trucks: 470-lb. drums.**STEROX® NJ**

INORGANIC DIVISION

CHEMICAL COMPOSITION: Nonyl phenol-ethylene oxide condensate. (Alkyl aryl polyoxyethylene ether)**PROPERTIES:** Liquid, 100% active soluble in water. Chemically stable, medium foam. Low odor and color levels.**USES:** General purpose nonionic for use in powdered and liquid detergents, textile, leather and paper processing, metal cleaning, toxicant formulations, deduster, etc.**SHIPPING INFORMATION:** Washing Compound NOIBN Liquid. Tank cars and tank trucks: 470-lb. drums.**STEROX® NM**

INORGANIC DIVISION

CHEMICAL COMPOSITION: Nonyl phenol-ethylene oxide condensates. (Alkyl aryl polyoxyethylene ether)**PROPERTIES:** Liquid, 100% active, soluble in water. Chemically stable, medium foam. Higher molecular weight than Sterox NJ.**USES:** Designed for use in liquid detergents, or where higher solubility or solubilizing power is desired. Other uses similar to Sterox NJ.**SHIPPING INFORMATION:** Washing Compound NOIBN Liquid. Tank cars and tank trucks: 470-lb. drums.**STEROX® SK**

INORGANIC DIVISION—LITERATURE AVAILABLE

CHEMICAL COMPOSITION: Polyoxyethylene thioether.**PROPERTIES:** Light amber liquid, 100% active nonionic-type surface-active agent and detergent. Extremely fast wetting action, good detergency and emulsifying properties.**USES:** Wetting agent and penetrant for insecticidal and herbicidal formulations. Wetting agent with low foam characteristics for wet collection dust systems. De-emulsifier for some hydrocarbon-water emulsions.**SHIPPING INFORMATION:** Washing Compound, NOIBN Liquid. Tank cars and tank trucks: 465-lb. drums.**STEROX® NO. 6**

INORGANIC DIVISION—LITERATURE AVAILABLE

CHEMICAL COMPOSITION: Polyoxyethylene thioether.**PROPERTIES:** Nonionic surface-active agent, designed especially for operations where exceptionally fast wetting and high scouring efficiency is desired. Compatible with principle textile operations. 85% active liquid without inorganic salts.**USES:** Designed especially for textile operations where fast wetting, good scouring and emulsification of grease soil are needed. Scouring efficiency particularly advantageous for raw wool and woolen piece goods scouring. Effective rewetting agent for textiles.**SHIPPING INFORMATION:** Washing Compound, NOIBN Liquid. Tank cars and tank trucks: 450-lb. drums.**BLEACHING COMPOUNDS****ACL®**

INORGANIC DIVISION—LITERATURE AVAILABLE

STANDARD FORM: Powder and granular. A series of solid, organic chlorine liberating compounds, useful as active ingredients in household and commercial laundry bleaches, scouring cleansers, machine dishwashing compounds, sanitizing agents, etc.**PRODUCT DESCRIPTION:**

ACL® Grade	Chemical Name	Typical % Available Chlorine
85	Trichloroisocyanuric Acid	90
70	Dichloroisocyanuric Acid	80
59	Potassium dichloroisocyanurate	60

SHIPPING INFORMATION: Fiber drums with polyethylene bag liner. ACL-85 and ACL-59 270-lbs. net. ACL-70 225-lbs. net.**DETERGENT INTERMEDIATES****ALKYLATE 215, 225 AND 230**

(Alkyl Benzene — Bisdodecylate)

INORGANIC DIVISION

FORMULA: C₁₈H₃₅Cl

MOLECULAR WEIGHT:	215	225	230
	231-241	246-254	256-264

STANDARD FORM: Liquid.**TYPICAL ANALYSIS:** Appearance, clear sparkling liquid. Residue, less than 0.005 volume % (60/90°F). 0.85-0.88 Color (before sulfonation) less than 10 APHA; Refractive index 25°C — 1.4815-1.4890; Bromine No. 0.002; Unsaponifiables 0.3%.**USES:** Alkylate is a ether extraction alkyl benzene 1.2% specially designed for use in the manufacture of synthetic organic detergents.**SHIPPING INFORMATION:** Petroleum Oil NOIBN, 4,000, 8,000 and 10,000 gal. tank cars, 390-lbs. net (440-lbs. gross) weight, black iron drums, nonreturnable.**NONYLPHENOL Alkyl Phenol**

INORGANIC DIVISION

STANDARD FORM: Liquid.**TYPICAL ANALYSIS:** Appearance, clear sparkling liquid; Odor, characteristic phenolic; Color, 40 APHA; 50% Distillation Range, 558-560°F.; Hydroxyl No. 245; Refractive index 25°C — 1.5110; Water 0.05%.**USES:** Mونسanto's nonylphenol is an alkyl phenol specifically designed for use in the manufacture of synthetic organic detergents.**SHIPPING INFORMATION:** Nonylphenol (Chemicals, NOIBN): 415-lb. net (465-lbs. gross) Hersesta lined drums, 10,000, 8000 and 4000 gallon tank cars.

A wholly owned subsidiary concerned with the conduct of specific scientific and technological research programs for the Government. With headquarters at St. Louis, the company has laboratories at Dayton, Ohio and Boston, Massachusetts, and operates Mound Laboratory at Miamisburg, Ohio, which Monsanto Company built for the Atomic Energy Commission.

Monsanto Research Corporation also produces and markets a range of conveniently packaged nuclear sources of alpha, beta or neutron radiation, as well as custom-tailored nuclear sources.

For Information:

*John L. Richmond, Manager
Nuclear Sources Department
MONSANTO RESEARCH CORPORATION
1515 Nicholas Road
P. O. Box 8 — Station B
Dayton, Ohio 45407
Tele: AM 8-3411 (area code: 513)*

Monsanto Research Corporation

A wholly owned subsidiary with offices at Chicago, Illinois, engaged in engineering and construction chiefly for the process industry and particularly of chemical plants designed by Monsanto's engineering sales department. It has a Canadian subsidiary, Lenconco Construction Limited, with its main office at Ottawa.

For Information:

*LEONARD CONSTRUCTION COMPANY
37 South Wabash Avenue
Chicago, Illinois 60603
Tele: State 2-5041 (area code: 312)*

Leonard Construction Company

0557342

TOWOLDMON0041076

DISTRICT SALES OFFICES...All Divisions

ATLANTA, GEORGIA 30326

Lenox Towers West,
3390 Peachtree Rd. N.E.
Tel. (404) 231-4320

BOSTON, MASSACHUSETTS 02149

Everett Station
Tel. (617) Dunkirk 7-5010

CHICAGO, ILLINOIS

3158 Des Plaines Ave.
Des Plaines, Illinois 60018
Tel. (312) 296-6688

CINCINNATI, OHIO 45206

2330 Victory Parkway
Tel. (513) 751-6707

CLEVELAND, OHIO 44122

3645 Warrensville Center Rd.
Tel. (216) 991-5400

DETROIT, MICHIGAN 48235

500 Northland Towers
Tel. (313) 357-0910

HOUSTON, TEXAS 77002

1300 Main Street
Tel. (713) Capitol 3-4011

LOS ANGELES, CALIFORNIA 90022

6670 E. Flotilla St.
Tel. (213) Raymond 3-2492

MINNEAPOLIS, MINNESOTA 55402

912 Northstar Center 110 S. Seventh St.
Tel. (612) Federal 9-4651

NEW YORK, NEW YORK 10017

277 Park Avenue
Tel. (212) 922-4111

PITTSBURGH, PENNSYLVANIA 15222

No. 4 Gateway Center Bldg. Room 1406
Tel. (412) 261-2156

ST. LOUIS, MISSOURI 63166

800 N. Lindbergh Blvd.
Tel. (314) Wydown 3-1000

SAN FRANCISCO BAY AREA

2710 Lafayette, Santa Clara, Calif. 95052
Tel. (408) 243-0414

SEATTLE, WASHINGTON 98104

911 Western Avenue
Tel. (206) Main 2-4203

SPRINGFIELD, MASSACHUSETTS 01102

912 Monsanto Ave.
Tel. (413) 788-6911

WILMINGTON, DELAWARE 19803

2005 Concord Pike, Fairfax
Tel. (302) Olympia 8-6531

*Additional District Offices
are maintained by:*

Agricultural Division

EL DORADO, ARKANSAS 71731
Smackover Highway
P. O. Box 231
Tel. (501) Union 3-3151

LULING, LOUISIANA 70070
P. O. Box 174
Tel. (504) 784-2911

PLAINVIEW, TEXAS 79073
P. O. Box 196/
Tel. (806) Capital 4-2759

Building Products Department

ST. LOUIS, MISSOURI 63166
800 N. Lindbergh Blvd.
Tel. (314) Wydown 3-1000

LOS ANGELES, CALIFORNIA 90066
814 San Fernando Road
Tel. (213) CA. 2-9111

Chemstrand Company Division

AKRON, OHIO 44313
3030 West Market St.
Tel. (216) Temple 6-7941

CHARLOTTE, NORTH CAROLINA 28202
Wachovia Bank Building
129 West Trade St.
Tel. (704) 376-9871

NEW YORK, NEW YORK 10001
350 Fifth Ave.
Tel. (212) 556-5100

Hydrocarbons & Polymers Division Lion Oil

EL DORADO, ARKANSAS 71730
Lion Oil Building
Tel. (501) Un on 3-3111

JACKSON, MISSISSIPPI 39201
950 Milner Building
210 South Lamar St.
Tel. (601) Fleetwood 2-3648

LITTLE ROCK, ARKANSAS 72203
1515 West Seventh St.
Tel. (501) Franklin 6-2437

MEMPHIS, TENNESSEE 38101
1023 Riverside Drive
P. O. Box 252
Tel. (901) Whitenall 8-4461

Organic Chemicals Division (Rubber Industry)

AKRON, OHIO 44311
920 Brown Street
P. O. Box 2307
Tel. (216) Hemlock 4-1921

MONSANTO, 800 N. LINDBERGH BLVD., ST. LOUIS, MISSOURI 63166

0557343

TOWOLDMON0041077