bcc: G. F. Fague - Monsanto Detroit
J. R. Fallon Monsanto Detroit
R. Davis/R. A. Garcia/D. F. Smith - G.O

February 13, 1968

Mr. Ray Reed
Director of Safety
General Motors Corporation
Chevrolet Division
Metal Fabricating Plant
2238 West Bristol Road
Flint, Michigan

Dear Mr. Reed:

Mr. Fague of our Detroit office has asked me to forward toxicity and safe handling information on our fire resistant hydraulic fluid, Pydraul 312.

I have enclosed a copy of our bulletin entitled, "Toxicity and Safe Handling of Pydraul 312." In addition, I thought you might be interested in the more detailed data discussed below.

The oral toxicity of this product shows an LD_{50} to rats of 6500 mg/kg and it is classified as "practically non-toxic" from the acute oral point of view.

When applied to the skin undiluted and allowed to remain overnight, a barely perceptible redness occurred, giving a maximum score of 1.3/8.0, which was classed as a slight irritant. The material proved capable of being absorbed through the skin in high doses when allowed to remain on the rabbit under a cuff. The minimum lethal dose was somewhere over 2000 and under 3000 mg/kg. This would fall into the "slightly toxic" range.

The material is a slight eye irritant when applied undiluted to the rabbits' eyes and there was mild discomfort and slight redness. The maximum score was 13/110 and the eye had returned to normal within three days.

Rats survived six-hour inhalation exposure to the vapors evolved at ambient temperatures following the passage of air through the material. No systemic effects were noted.

DSW 018633

STLCOPCB4005177

Clinically, we have had no cases of illness occurring in our employees during the manufacture and distribution of this material, nor have we had reports of injuries from the field.

However, there is no question but that a potential of injury could occur should the fumes evolved at elevated temperatures be breathed for long periods of time or repeatedly. Likewise, the action of the material on the skin causes defatting but, even more so, repeated or continuous skin contact must be avoided to prevent absorption of the material with systemic effects. I repeat, however, these conditions have not come to my attention.

If you have any further questions, please write directly to me.

Sincerely,

R. Emmet Kelly, M. D.
Medical Director

REK:cjs

Enclosure

bcc: Vincent Castrop

P.S. I don't know if you have received any inquiries from Mr. Reed of your Chevrolet Division at Flint but thought you would be interested in the above letter which was sent to him following a telephone request from our Sales Department

Elmer P. Wheeler

DSW 018634

STLCOPCB4005178