

FILE NAME: Marley (MAR)

DATE: 1959 Aug

DOC#: MAR001

DOCUMENT DESCRIPTION: Advertisement

You can't buy any other tower with the **SERVICE LIFE OF A MARLEY CLASS 600 DOUBLE-FLOW**

Years . . . many more years than those now considered usual service life of cooling towers . . . are engineered into every Marley Class 600 Cross-Flow. Years of full performance; years of low maintenance; years for longer amortization. By incorporating (after comprehensive research) modern inert materials and protective processes throughout Class 600 design, Marley engineers have achieved an over-all durability that prolongs tower life expectancy beyond any current norm.

GLASS FIBER REINFORCED POLYESTER

—steel-strong and impervious to corrosion—makes many components invulnerable to corrosion and decay; GRP molded **Fan Blades** are shatter-proof, shock resistant and completely unaffected by moisture or corrosive atmosphere. **GRP Fill Support Grids** position fill bars perfectly and permanently—no nails needed. **GRP Timber Connectors, GRP Retaining Rings** and **GRP Fan Cylinder Positioning** cannot corrode nor are they subject to oxidation that encourages decay in contacted lumber . . . they add vitality to critical areas, as do **Ceramic Timber Ring Connectors** and **Louver Supports** molded of rigid linear polyethylene.

ASBESTOS CEMENT BOARD—fire-safe and wear-proof—forms casing walls and wide, functional louvers that characterize Class 600's.

MARLITH PRESERVATIVE TREATMENT is life-insurance for tower lumber. Applied after fabrication, every piece of wood is deeply and thoroughly impregnated with toxic, proven protection against rot and decay.



The Marley Company