

The Hazards of Asbestos for Brake Mechanics

198

BARRY CASTLEMAN, LUCILLE A. CAMAROTA, ALBERT J. FRITSCH,
SUSAN MAZZOCCHI, and ROBERT G. CRAWLEY

ASBESTOS is the generic name of a group of hydrated magnesium silicate mineral fibers. There are two groups of these minerals—serpentine (chrysotile) and amphibole (amosite, crocidolite, anthophyllite, tremolite, and actinolite). Ninety-five percent of the world's asbestos production is chrysotile.

Reports of epidemiologic and pathological studies (1-4) reveal that occupational exposure to commercial asbestos minerals enhances the likelihood of a number of diseases—asbestosis and cancers of the lung, pleura, peritoneum, larynx, and gastrointestinal tract. The time from onset of exposure to the time of clinically apparent disease is usually more than 20 years. Cancer from asbestos is not limited to workers who handle the material. There are also reports of pleural and peritoneal mesothelioma (tumors rarely seen in the general population) in persons with family, or neighborhood, or indirect occupational exposure to asbestos (4-7).

Mesothelioma was the cause of death of a man who had regularly sanded vinyl asbestos floor tile (8). Under simulated conditions of this man's work, a maximum asbestos dust concentration of 1.3 fibers per ml (fibers longer than 5 microns) was found in air samples passed through membrane filters worn by a person sanding vinyl asbestos (8). The type of asbestos now used in domestic floor tile is chrysotile—the same as that used in brake friction materials, according to the Asbestos Information Association. A case of mesothelioma in a brake mechanic has been reported (9).

Commercial friction materials used in the United States for braking passenger cars and trucks contain an average composition of 50 percent chrysotile by weight (10). Asbestos has been used for brake drum linings,

disk pads, and clutch facings for the past 50 years. Jacko and DuCharme (11) estimated that the United States annually uses 103 million pounds of asbestos for brake friction materials and 4.5 million pounds in automotive clutch friction materials.

In 1968 Lynch reported that because of the heat of friction caused by braking, almost all of the asbestos in brake linings is transformed to a nonfibrous mineral, and a small fraction of asbestos escapes as free fiber (12). Jacko and co-workers determined that vehicles in this country emit 158,000 pounds of asbestos per year, of which 11.2 percent is retained in the brake and disposed of during service (13).

Brake mechanics have low and intermittent exposure to asbestos. This exposure has been reported to be 0.79 fiber per ml time-weighted average (fibers longer than 5 microns), with peaks up to 7 fibers per ml when brake parts are being cleaned (14). The standard method for removing dust from brake parts is to blow it out with a

□ Mr. Castleman, an environmental engineer, was with the Center for Science in the Public Interest when this paper was prepared; he is now with the Maryland Public Interest Research Group. Dr. Fritsch is director of the Center for Science in the Public Interest. Ms. Camarota is an occupational health nurse, District of Columbia Department of Human Resources. Ms. Mazzocchi was a research associate, Environmental Cancer Research Project, Environmental Sciences Laboratory, Mount Sinai School of Medicine, New York City. Mr. Crawley is a sanitarian, Baltimore County Department of Health.

Teasheet requests to Barry Castleman, Maryland Public Interest Research Group, 3110 New Main Dining Hall, University of Maryland, College Park, Md. 20742.

