

DATE: _____ LOT A2K20

() YE-735-D (M) FWP 10/08/81

() ()
() ()

ESTIMATED WEIGHT: 3819* LBS.

COMTYP JOB NAME: 01YE735DMM

EQUIP MENT	NAME: MOLYBDATE ORANGE	USE LBS	N-CODE	ACCT LBS
PREP	1. OBTAIN FOR S-34	315	4-A	315
1	2. OBTAIN FOR S-23	42	108-A	42
	3. OBTAIN FOR S-38	105	3-A	105
	4. OBTAIN FOR S-40	58	32-D	58
	5. OBTAIN FOR S-43	47	3-A	47
	6. DISSOLVE IN 30 G WATER AT 100-120°F IN DRUM FOR S-47	17	765-A	17
	7. DISSOLVE IN 30 G WATER AT 100-120°F IN DRUM FOR S-51	60	994-A	60
351 2	8. WEIGH IN OPTR _____, MK <u>9</u> , <u>38.67</u> % <u>3688</u>		10-D	1426
	OPTR _____, MK _____, _____%			
359 3	9. WEIGH IN. OPTR _____, MK <u>114</u> , T- <u>360</u> , <u>36.59</u> % <u>618</u>		423-D	226
	OPTR _____, MK _____, T-_____, _____%			
SV 4	10. FLUSH DISTRIBUTOR LINES UNTIL WATER COMES OUT ALL JETS RECORD: _____ (OK)			
	11. RUN IN 40" (1992 G) WATER			
	12. RUN IN FROM V-354. OPTR <u>52</u> , MK _____, <u>42</u> *F <u>13153</u>		41-D	3800
	PH <u>1.19</u> (2.8-3.7) G/ML <u>1.317</u> (1.270-1.328)			
	<u>38.89</u> % SEE SUPV IF NOT IN RANGE.			
	13. ADJ TO 3350 GAL AT 67-69°F. RECORD: <u>68</u> *F		57-A	
	(37" IN V-240 & 246; 68" IN V-241, 242, 245)			
	14. STIR 5MIN. & RECORD: PH <u>2.4</u> (2.8-3.6)			
	15. IF NECESSARY, ADJ TO PH 3.8-3.9 ASSUME 32%		28-D	
	& RECORD: PH <u>3.9</u> (3.8-3.9) ASSUME 50%	<u>2</u>	7-D	<u>1</u>
	NOTE: DILUTE N-7-D 10:1 WITH WATER BEFORE ADDING			
	16. RECORD: <u>1.112</u> G/ML (1.116-1.118)			
	NOTE: IF G/ML OUT OF LIMITS, FILL OUT CHECK LIST & ATTACH.			
	17. STIR AT 67-69°F FOR S-28. TAKE 1 QT SAMPLE.			
358 5	18. RUN 2" (110 G) WATER INTO V-358			
	19. RUN V-359 INTO V-351			
	20. PUMP V-351 INTO V-358			
	21. TURN ON AGITATOR			
	22. SETT IN N-108-A FROM S-2			
	23. ADJUST TO 68" (3216 G) AT 67-69°F			
	RECORD: <u>67</u> *F			
	24. STIR 3 MIN. & RECORD: PH <u>8.9</u> (9.0-9.5)		28-D	
	25. IF NECESSARY, ADJ. TO PH 9.0-9.5 ASSUME 32%			
	& RECORD: PH <u>9.2</u> ASSUME 50%		7-D	
	26. RECORD: G/ML <u>1.059</u> (1.059-1.060)			
	NOTE: G/ML OUT OF LIMITS FILL OUT CHECK LIST & ATTACH			
	27. STIR AT 67-69°F FOR S-28. TAKE 1 QT SAMPLE.			

PUNCHED & CHECKED

JAN 27 1982

