

b) The limitations of Section 215.204(j) shall not apply to the Waukegan, Illinois, facilities of the Outboard Marine Corporation, so long as the emissions of volatile organic material related to the surface coating of miscellaneous metal parts and products at those facilities do not exceed 35 tons per year.

c) Notwithstanding the limitations of Section 215.204(k)(2), the John Deere Harvester-Moline Works of Deere and Company, Moline, Illinois, shall not cause or permit the emission of volatile organic material from its existing green and yellow flocoating operations to exceed a weekly average of 6.2 lb/gal.

(Source: Amended 12 Ill. Reg. 20133, effective November 21, 1988)

Section 215.207 Compliance by Aggregation of Emission Sources

a) Owners or operators of coating lines subject to Section 215.204 may comply with this Section rather than with Section 215.204. The methods or procedures used to determine emissions of volatile organic material under this Section shall be approved by the Agency in accordance with 35 Ill. Adm. Code 201. Emissions of volatile organic material from sources subject to Section 215.204 are allowable, notwithstanding the limitations in Section 215.204, if the combined actual emissions from selected coating lines at the coating plant, but not including coating lines or other emission sources constructed or modified after July 1, 1979, is less than or equal to the combined allowable emissions as determined by the following equations:

$$E_{ALL} = \sum_{j=1}^m \sum_{i=1}^n (A_i B_i),$$

$$E_{ACT} = \sum_{j=1}^m \sum_{i=1}^n (C_i B_i (1 - D_i)),$$

b) A_i shall be determined by the following formula:

$$A_i = \frac{R_i}{1 - \frac{R_i}{S_i}}$$

c) As used in subsection (a) and (b), symbols mean the following:

E_{ALL} = the allowable volatile organic material emissions from the coating plant in kg/day (lb/day)...

A_i = the allowable emission limit for a coating pursuant to Section 215.204 expressed in kg/l (lbs/gal) of coating solids.

B_i = the volume of coating solids in l/day (gal/day), in a coating as delivered to the coating line.

m = the number of coating lines included in the combined emission rate.

n = the number of different coatings delivered to a coating line.

E_{ACT} = the actual volatile organic material emissions from the coating plant in kg/day (lbs/day).

C_i = the weight of volatile organic material per volume of solids in kg/l (lb/gal) for a coating.

D_i = the control efficiency by which emissions of volatile organic material from a coating are reduced through the use of control equipment.

R_i = the applicable volatile organic material emission limit pursuant to Section 215.204, for a coating in kg/l (lb/gal).

S_i = the density of the volatile organic material in a coating in kg/l (lb/gal).

d) The owner or operator of the coating plant shall maintain records of the density of the volatile organic material in each coating, the quantity and volatile organic material and solids content of each coating applied and the line to which coating is applied, in such a manner so as to demonstrate continuing compliance with the combined allowable emissions.

e) Except for emission sources subject to Section 215.301 or 215.302, credits from emission sources at the coating plant that are subject to this Part, other than coating lines, may be given, to the extent that emissions are reduced from the allowable emission limits for such emission sources contained in either this Part, or any existing operating permit, whichever limit is less.

(Source: Amended at 12 Ill. Reg. 815, effective December 24, 1987)

Section 215.208 Testing Methods for Solvent Content

a) The following methods of analyzing the solvent content of coatings, as revised from time to time, or any other equivalent procedure approved by the Agency, shall be used as applicable:

1) ASTM D 1644-59 Method A

2) ASTM D 1475-60

3) ASTM D 2369-73

4) Federal Standard 141a, Method 4082.1