


1449

SHERWIN-WILLIAMS

ONE GALLON

U. S. STANDARD MEASURE



SEMI-LUSTRE

Satin Finish for Walls and Woodwork

210 WHITE

SHERWIN-WILLIAMS	
Color Name	210 WHITE
Quantity	1 GALLON
Weight	12.5 LBS.
Volume	12.5 LBS.
Volume of Paint by Volume	12.5 LBS.
Volume of Paint by Weight	12.5 LBS.
Volume of Paint by Volume	12.5 LBS.
Volume of Paint by Weight	12.5 LBS.
Volume of Paint by Volume	12.5 LBS.
Volume of Paint by Weight	12.5 LBS.

SEMI-LUSTRE
What It Is—
 An exceptional, washable finish for interior walls and woodwork.
Type of Finish—
 Semi-gloss or satin sheen.
Where to Use It—
 Bedrooms, bathrooms, libraries, recreation rooms, etc.
Best Care for Long Wear—
 Dirt, grease, ink, crayon, nail and medicine stains can be readily removed with S.W. Flaxol or other mild soaps or cleansers. Avoid harsh, abrasive cleaners.
Tools Needed with—
 A brush and roller or a brush for walls and a brush for woodwork. Wall Flaxol for walls—first coat on porous walls.

WILLIAMS

SHERWIN-WILLIAMS

U. S. STANDARD MEASURE

SEMI-LUSTRE

Wall II—An exceptionally wearable finish for interior walls and woodwork.

Where to Use It—

Kitchens, bathrooms, laundry, recreation rooms, etc.

Best Care for Longer Wear—

Dirt, grease, ink, crayon, fruit and moderate stains wash off with warm water and soap or other mild soap or cleanser. Avoid harsh, abrasive cleaners.

How to Apply—

A clean 3 1/4" or 4" brush for walls and a 1 1/4" or 2" brush for woodwork. Wall Primer and Sealer—first coat on porous walls—first coat on porous

IMPORTANT—Follow directions for thinning and use thoroughly. If pigment has settled, pour liquid into a clean vessel. Stir, then remove the brush in slowly to wet mass with a brush. Then use the brush in slowly to wet mass.

Shervin-Williams Semi-Lustre is a durable, washable finish. It is recommended for use on walls, woodwork, trim, composition boards and wood trim. The following directions are recommended for best results:

NEW WORK—First Coat—Porous surfaces must be thoroughly sealed to prevent spotting caused by the paint penetrating the pores. Wall Primer and Sealer should be applied to the surface. Wall Primer and Sealer is available in two colors: *Flat Wall Primer* and *Flat Wall Sealer*. Both are available in a suitable first coat or undercoat for Semi-Lustre.

Second Coat—Apply Semi-Lustre as it comes from the package.

Third Coat—(If desired)—Apply Semi-Lustre as it comes from the package.

NOTE—Whether used "as it comes from the package" or reduced, the paint must be thoroughly mixed.

OLD WORK—First Coat—The surface must be free from dirt, grease and loose paint, in short—a clean surface. Water, paint or Kalamazoo should be washed off and the wall allowed to dry completely—then proceed with the application of the paint. The paint should be applied in two coats. The first coat should be applied in a thin layer and the second coat should be applied in a thicker layer. The paint should be applied in a thin layer and the second coat should be applied in a thicker layer.

Second Coat—Apply Semi-Lustre as it comes from the package.

NEW INTERIOR WOOD TRIM

First Coat—Apply Semi-Lustre, each gallon reduced with one pint Enkment or turpentine.

Second Coat—Apply Semi-Lustre as it comes from the package.

Third Coat—(If desired)—Apply as it comes from the package.

PREVIOUSLY FINISHED INTERIOR TRIM

The surface to be finished shall be thoroughly cleaned, preferably with Sherwin-Williams Flaxol (pure linseed oil soap) and warm water. When dry, sand just enough to remove gloss from the old finish.

First Coat—Apply Semi-Lustre as it comes from the package.

Second Coat—(If desired)—Apply Semi-Lustre as it comes from the package.

NOTE—Should thinning be necessary use Enkment or turpentine.

CAUTION—Keep away from fire. Use in a well ventilated place. Cleanliness and sanitary precautions should be observed.

THE SHERWIN-WILLIAMS CO.

JOHN W. WILLIAMS, JR., PRESIDENT
OFFICES, FACTORIES AND WAREHOUSES IN ALL MAJOR CITIES
MADE IN U. S. A.