

STYLE 1160 HTCR* SHEET PACKING

HTCR is an elastomeric system based on Aflas Fluororubber, a copolymer of tetrafluoroethylene and propylene.

HTCR has excellent resistance to a wide variety of chemical environments. It is thermally stable for continuous use in temperatures of 450°F, and depending on the specific application, has serviceability in environments up to 550°F.

Availability: 1/16" and 1/8" immediate delivery. Other thicknesses from 1/64" to 3/16" available on special order. Standard sheet width is 36".

Approximate weight: 1/16" -- 5 lbs. per yard. Other thicknesses in proportion.

Services. Inorganic acids, alkalis, high temperature steam, oxidizing agents, polar solvents, organic bases, hydrocarbon oils, amines and amine corrosion inhibitor systems, and hydrogen sulfide bearing media.

*HTCR is a Registered Trademark of Utex Industries
Aflas is a Registered Trademark of Ashai Glass Co Ltd.

STYLE 1152 EPDM SHEET

A general service ethylene-propylene sheet that is strong, stretchy, highly resistant to ozone and heat aging. Black in color with smooth finish. Meets specification ASTM D-2000, Type BA.

Availability: Standard in 1/16" and 1/8" thicknesses in continuous rolls 36" wide, 60 durometer. Other thickness on special order.

Approximate weight; 1/8" -- 6.2 lbs. per square yard. Other thicknesses in proportion.

Service: Weathering, ozone, acids and alkalis, steam, esters and alcohols.

STYLE 1125 NON-ASBESTOS COMPRESSED SHEET

A high quality non-asbestos material that will seal as effectively as compressed asbestos in most applications. Style 1125 is composed of high chemical and heat resistant fibres bonded with nitrile rubber. It has outstanding creep resistance at high temperatures (up to 750°F) and high pressures.

Availability: Sheet size 60" x 60" in thicknesses of 1/64", 1/32", 1/16", 3/32" and 1/8".

Approximate weight: 60" x 60" x 1/16" -- 12 lbs. Other thicknesses in proportion.

Services. Gases, water, steam, inorganic salt solutions, organic acids, alkalis, hydrocarbons, oils and greases, heat transfer oils, refrigerants, aliphatic alcohols, esters and ketones.

NOTE: Style 1126 wire inserted non-asbestos sheet is also available upon request.

STYLE 1155 SILICONE SHEET

A general service silicone material, red in color with a smooth, plate finish. Meets specifications ZZ-R-765, Class IIA & IIB, GR.50. AMS 3302 and ASTM D-2000 GE-507.

Availability: Standard 1/32", 1/16" and 1/8" thicknesses in continuous rolls 36" wide, 50 durometer.

Approximate weight: 1/16" -- 4 lbs. per square yard. Other thicknesses in proportion.

Services: Air, acetic acid, asphalt, diluted and concentrated nitric acid, ozone, potassium chloride, hydroxide and sulphate, soda ash, cold sulphuric acid, water.

METALS

Utex maintains stocks of various metals suitable for gasket applications. Aluminum, copper, super-soft steel, long term steel, stainless steel are available for gasket fabrication or bulk shipment. Also, brass, copper and stainless steel shim stock in standard widths and thicknesses are available.

UTEX 000257