

"Petroleum Liquid": crude oil, condensate or any finished or intermediate product manufactured at a petroleum refinery, but not including Numbers 2 through 6 fuel oils as specified in ASTM D-396-69, gas turbine fuel oils Numbers 2-GT through 4-GT as specified in ASTM D-2880-71 or diesel fuel oils Numbers 2-D and 4-D, as specified in ASTM D-975-68.

"Petroleum Refinery": any facility engaged in producing gasoline, kerosene, distillate fuel oils, residual fuel oils, lubricants, or other products through distillation, cracking, extraction or reforming of unfinished petroleum derivatives.

"Pharmaceutical": any compound or mixture, other than food, used in the prevention, diagnosis, alleviation, treatment or cure of disease in man and animal.

"Photochemically Reactive Material": any organic material with an aggregate of more than 20 percent of its total volume composed of the chemical compounds classified below or the composition of which exceeds any of the following individual percentage composition limitations. Whenever any photochemically reactive material or any constituent of any organic material may be classified from its chemical structure into more than one of the following groups of organic materials it shall be considered as a member of the most reactive group, that is, the group having the least allowable percent of the total organic materials.

A combination of hydrocarbons, alcohols, aldehydes, esters, ethers or ketones having an olefinic or cyclo-olefinic types of unsaturation: 5 percent. This definition does not apply to perchloroethylene or trichloroethylene.

A combination of aromatic compounds with eight or more carbon atoms to the molecule except ethylbenzene: 8 percent.

A combination of ethylbenzene, ketones having branched hydrocarbon structures or toluene: 20 percent.

"Pneumatic Rubber Tire Manufacture": the production of pneumatic rubber tires with a bead diameter up to but not including 20.0 inches and cross section dimension up to 12.8 inches, but not including specialty tires for antique or other vehicles when produced on equipment separate from normal production lines for passenger or truck type tires.

"Polybasic Organic Acid Partial Oxidation Manufacturing Process": any process involving partial oxidation of hydrocarbons with air to manufacture polybasic acids or their anhydrides, such as maleic anhydride, phthalic anhydride, terephthalic acid, isophthalic acid, trimellitic anhydride.

"Portable Grain-Handling Equipment": any equipment (excluding portable grain dryers) that is designed and maintained to be movable, primarily for use in a non-continuous operation for loading and unloading one-turn storage

space, and is not physically connected to the grain elevator, provided that the manufacturer's rated capacity of the equipment does not exceed 10,000 bushels per hour.

"Portland Cement Process": any facility manufacturing portland cement by either the wet or dry process.

"Power Driven Fastener Coating": the coating of nail, staple, brad and finish nail fasteners where such fasteners are fabricated from wire or rod of 0.0254 inch diameter or greater, where such fasteners are bonded into coils or strips, such coils and strips containing a number of such fasteners, which fasteners are manufactured for use in power tools, and which fasteners must conform with formal standards for specific uses established by various federal and national organizations including Federal Specification FF-N-105b of the General Services Administration dated August 23, 1977 (does not include any later amendments or editions; U.S. Army Armament Research and Development Command, Attn: DRDAR-TST, Rock Island, IL 61201); Bulletin UM-25d of the U.S. Department of Housing and Urban Development - Federal Housing Administration dated September 5, 1973 (does not include any later amendments or editions; Department of HUD, 547 W. Jackson Blvd., Room 1005, Chicago, IL 60606); and the Model Building Code of the Council of American Building Officials, and similar standards. For the purposes of this definition, the terms "brad" and "finish nail" refer to single leg fasteners fabricated in the same manner as staples. The application of coatings to staple, brad, and finish nail fasteners may be associated with the incremental forming of such fasteners in a cyclic or repetitious manner (incremental fabrication) or with the forming of strips of such fasteners as a unit from a band of wires (unit fabrication).

"PPH (Vol.) (Parts per Million) (Volume)": a volume/volume ratio which expresses the volumetric concentration of gaseous air contaminant in a million-unit volumes of gas.

"Pressure Tank": a tank in which fluids are stored at a pressure greater than atmospheric pressure.

"Prime Coat": the first film of coating material applied in a multiple coat operation.

"Prime Surfacer Coat": a film of coating material that touches up areas on the surface not adequately covered by the prime coat before application of the top coat.

"Process": any stationary emission source other than a fuel combustion emission source or an incinerator.

"Process Weight Rate": the actual weight or engineering approximation thereof of all materials except liquid and gaseous fuels and combustion air, introduced into any process per hour. For a cyclical or batch operation, the process weight rate shall be determined by dividing such actual weight or engineering approximation thereof by the number of hours of