

FORMULA NO. **Y-2024** U

GOODS Endurance 1st 1200

~~T.M.S.~~

LABORATORY NO.

CONSISTENCY

COST CLASS.

DATE 12/18/60

FOR USE ONLY

STRAINER

GRIND 3 5

CUSTOMER

ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED

WT OR RE 14.5

[illegible]

N12402

GLD060543

FORMULA RECORD

Formula No. 7 1804A

Date 10-5-49 / Laboratory No

Cost Classification

GLD060544

W-47 5-4 3-42 PRINTED IN U. S. A. B

COST DEPARTMENT RECORD

Revision #1

Classified Formula No. **Y-1804-L**

Goods **Endurance Shade White Base**

Laboratory Formula No.

Consistency **Liquid**

Date **3-31-43**

Factory Letter No.

For Use on **Exteriors**

Production No. **903-784**

Customer **Paint Shop**

Cost Classification

Ingredient Code Number	Lab'ty Formula	Large Batch		Do not write in these columns For Cost Department Use Only					Manufacturing Specifications
		Pounds	Gallons						
W-104	1125 #								Grind 24 hrs
W-33	1110 #								Kind of Mill pebbles
W-69	480 #								Strainer coarse
W-18	240 #								Weight per Gallon 16.2
W-11	240 #								Light Baume Temp.
									Heavy Baume Temp.
Q-1	101-1/4 gal								Viscosity Temp.
D-286	60 #								Viscosimeter
D-13	15 #								Flash Point
E-43	45-3/4 #								Is Agitator Required
S-48	15 #								
67-T-9	3 #								Formulator
Yield									

GLD060546

4024-1A 2N 4579 3 43 36401 21

Classified Formula No. Y-1804-N

Lat. Formula No.

Cost Classification

Standard Formula.
Not to be taken
from File

GLD060551

1004

Formula No.

Date 5-21-46

Laboratory No. 7-1804

Cost Classification

Standard Formula.
Not to be taken
from F.C.

GLD060553

A-222 624

Formula Y-1804-C

Date 5-1-1926. Old No.

Classification

GLD060555

FORMULA RECORD		Formula No.	Date	Old No.		
Formula Name: <u>Fluorinated Hydrocarbon Solvent</u>		<u>7-1014-2</u>	<u>6/5/50</u>	<u>Old No.</u>		
Formula Description: <u>Fluorinated Hydrocarbon Solvent</u>		Unit Classification				
Code Number	1	5	M Bbl	R Bbl	S Bbl	Manufacturing Specifications
<u>0-100</u>				<u>20 Gals</u>		<u>Grid</u>
<u>0-100</u>				<u>10 Gals</u>		<u>Grid of MIB</u>
<u>0-100</u>				<u>20 Gals</u>		<u>Base per ft.</u>
<u>0-100</u>				<u>3 Gals.</u>		<u>Scrubber</u>
<u>0-100</u>				<u>2 1/2 Gals.</u>		<u>Wash per 100 lbs</u>
<u>0-100</u>				<u>5 Gals.</u>		<u>Light Burner</u>
<u>0-100</u>				<u>3/8 Gals.</u>		<u>Heavy Burner</u>
<u>0-100</u>				<u>3/8 Gals.</u>		<u>Wash</u>
<u>0-100</u>				<u>500 lbs.</u>		<u>Mix of Viscosity</u>
<u>0-100</u>				<u>200 lbs.</u>		<u>Black Paint</u>
<u>0-100</u>				<u>100 lbs.</u>		<u>In Airplane Fuelage Required</u>
<u>0-100</u>				<u>80 lbs.</u>		<u>Reserve</u>

GLD060557

A 480 B 2m 11-45 Printed in U. S. A.

FORMULA RECORD

Goods

End. Shade White Paste

Formula No.

218047

Consistency

Date *1/18/52*

Old No.

For Use on

Cost Classification

Code Number	1	5	1/2 Bbl.	Bbl.	2 Bbl.	Manufacturing Specifications	
<i>03</i>	<i>12 gal</i>		<i>12 gal</i>		<i>12 gal</i>	Grind	
<i>04</i>	<i>20 "</i>		<i>"</i>			Kind of Mill	<i>Stone</i>
<i>01</i>	<i>33 "</i>		<i>53 "</i>			Rate per hr.	
<i>064</i>	<i>2 "</i>		<i>2 "</i>			Strainer	
<i>* V 715</i>	<i>1 1/2 "</i>		<i>1/2 "</i>			Weight per Gallon	<i>15 1/4 #</i>
<i>210</i>	<i>5 "</i>		<i>5 "</i>			Light Baumé	Temp.
<i>843</i>	<i>3 1/2 "</i>		<i>3 1/2 "</i>			Heavy Baumé	Temp.
<i>6779</i>	<i>3 "</i>		<i>3 "</i>			Viscosity	Temp.
						Make of Viscosimeter	
<i>W 77</i>	<i>270 #</i>					Flash Point	
<i>W 6</i>	<i>510 #</i>					Is Agitator Package Required	
<i>W 10</i>	<i>110 #</i>					Remarks	
<i>W 11</i>	<i>100 #</i>						<i>P. 3004</i>
<i>* Note: Add V 715 only if needed for Body.</i>							<i>1st Grade Paint</i>
Yield							

GLD060559

440

FORMULA RECORD

Goods

THREE WHITE BUTTE

TORONTO

Consistency

Date 2-15-1904

For Use on

Classification No.

Material	Code	1	2	Bbl.	Manufacturing Specifications
Raw Oil	01			48 gals	Grind
Hy Oil	02			6 "	Kind of Mill
TEXACO	03			1 1/2 "	Rate per hr.
KINGSLEY	04			3 3/4 "	Wt. per gal. Burnt
WATER	05			3/4 "	Strainer Viscosity
					Flash Point
THREE LEAD	06			135 "	Testing Requirements
THREE LEAD	07			495 "	Reduce with
THREE LEAD	08			135 "	Amount
THREE LEAD	09			35 "	Apply by
THREE LEAD	10			100 "	Surface
					Drying time
					Baking time
					Match for
					Std. Yield.

GLD060560

FORMULA RECORD

Formula No. 24 18046

Date 2/7/67 Lab. No.

Cost Classification

GLD060561

FORMULA RECORD

Formula No. 21804H

Date 7/20/43 Lab. No. 100

Cost Classification

GLD060562

FORMULA RECORD

Goods *Endurance Tint Base*
 Consistency *Liquid*
 For Use on

Formula No. *Y1804-0*
 Date *11-25-46* Laboratory No.
 Cost Classification

Code Number	One Gallon Batch			Gallon Batch			Gallon Batch			Manufacturing Specifications
	Pints	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	
<i>W-104</i>		<i>2</i>	<i>3</i>					<i>175</i>		Grind <i>L-2</i>
<i>W-6</i>		<i>7</i>	<i>2</i>					<i>570</i>		Kind of Mill <i>Pebble</i>
<i>W-69</i>		<i>2</i>						<i>160</i>		Strainer <i>Hi-R</i>
<i>W-46</i>		<i>1</i>						<i>80</i>		Weight per Gallon <i>15.84</i>
<i>W-11</i>		<i>1</i>						<i>80</i>		Light Baume Temp.
										Heavy Baume Temp.
<i>0-5</i>	<i>1 1/6</i>							<i>10</i>		Viscosity <i>85-90</i> Temp. <i>H.U.</i>
<i>0-1</i>	<i>1 1/6</i>							<i>15 1/2</i>		Viscosimeter
<i>0-286</i>	<i>2 1/2</i>							<i>20</i>		Flash Point
<i>D-15</i>	<i>3 1/6</i>							<i>5 1/2</i>		Is Agitator Required
<i>S-43</i>	<i>1 1/2</i>							<i>18 1/4</i>		Remarks <i>Hayward</i>
<i>S-148</i>	<i>2 1/2</i>							<i>5</i>		
<i>67-T-9</i>								<i>5 1/2</i>		

Standard Formula
 Not to be taken
 from File

12oz oz.
Reformulated to replace 1 Pint 0-1 with 0-5.

Yield

FORMULA RECORD

Goods: *Endurance Tint Base*Formula No. *Y 1804-1*Consistency *Liquid*Date *3-12-47*

Laboratory No.

For Use on *1*

Cost Classification

Code Number	One Gallon Batch			Gallon Batch			Gallon Batch			Manufacturing Specifications
	Pints	Lbs.	Oz.	Gals.	Lbs.	Oz.	Gals.	Lbs.	Oz.	
<i>W-104</i>		<i>4</i>	<i>11</i>					<i>375</i>		Grind <i>1-2</i>
<i>W-33</i>		<i>4</i>	<i>10</i>					<i>370</i>		Kind of Mill <i>W-33</i>
<i>W-69</i>		<i>2</i>						<i>160</i>		Strainer
<i>W-16</i>		<i>1</i>						<i>80</i>		Weight per Gallon <i>15.85</i>
<i>W-11</i>		<i>1</i>						<i>80</i>		Light Baume Temp.
										Heavy Baume Temp.
<i>0-5</i>	<i>1</i>						<i>10</i>			Viscosity <i>85-90</i> Temp. <i>70</i>
<i>0-1</i>	<i>1 1/2</i>						<i>15 1/2</i>			Viscosimeter
<i>0-286</i>	<i>2 1/2</i>						<i>25</i>			Flash Point <i>119</i>
<i>1-15</i>	<i>3 1/2</i>						<i>5 1/2</i>			Is Agitator Required
<i>5-43</i>	<i>1 1/2</i>						<i>18 1/2</i>			Remarks <i>Haywood</i>
<i>5-148</i>	<i>1 1/2</i>						<i>5</i>			
<i>67-7-7</i>			<i>1 1/2</i>				<i>5 1/2</i>			
<i>Formula changed to conserve W-6</i>										
<i>U.S. 2 1/2 15.24 (1) 15.24 2 1/2 15.24</i>										
Yield										

GLD060566

FORMULA RECORD

SHADE WHITE BASE

Formula No. Y1804 K

Consistency	Liquid
-------------	--------

Date 6-5-41 Laboratory No.

For Use on

Cost Classification

[illegible]

GLD060567

Goods *Crabapple Shad White Bay*
Consistency _____ Date *3/19*
For Use on _____

Formula No. 418041
Laboratory No. _____
Cost Classification _____

Code Number	One Gallon Batch			Gallon Batch			Gallon Batch			Manufacturing Specifications
	Pints	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	
W 114					375					Grind
W 35					370					Kind of Mill
W 59					160					Strainer
W 16					80					Weight per Gallon 16.2 #
W 11					80					Light Baume Temp.
										Heavy Baume Temp.
01				33 3/4						Viscosity Temp.
0286				20						Viscosimeter
D 15				5						Flash Point
S 43				15 1/4						Is Agitator Required
S 142				5						Remarks
6779				1						

Standard Formula.
Not to be taken
from File.

W. J. Ward

Residue to conserve linseed oil

Yield

FORMULA RECORD

Goods *Emulsion Tint Base*

Formula No. *Y 1804-P*

Consistency *Liquid*

Date *4-21-47*

Laboratory No.

For Use on

Cost Classification

Code Number	One Gallon Batch			Gallon Batch			Gallon Batch			Manufacturing Specifications
	Pints	Lbs.	Ozs.	Gals.	Ozs.	Gals.	Lbs.	Ozs.		
70% Finest Zinc Oxide		6	12				540		Grind 1-2	
									Kind of Mill <i>Wet Process</i>	
									Strainer	
W-33		2					205		Weight per Gallon 15.84	
W-69		2					160		Light Baume Temp.	
W-16		1					80		Heavy Baume Temp.	
W-11		1					80		Viscosity 85-90 Temp. 60-70	
									Viscosimeter	
0-5	1					10			Flash Point	
0-1	1 1/2					15 1/2			Is Agitator Required	
0-286	2 1/2					25			Remarks H.G.H.	
D-15	3 1/2					55 1/2			Formula for use to Conserve W-6	
S-43	1 1/2					18 3/4			This base to be used in place of tint due to account of the color of the 70 tinted	
S-148	1/2					5				
W-79						2 1/2				
Yield										

GLD060572

FORMULA RECORD

alternate

Formula No. *Y1804-P*

Consistency

Date *7-11-49*

Laboratory No.

For Use on

Cost Classification

Code Number	One Gallon Batch			Gallon Batch			Gallon Batch			Manufacturing Specifications
	Pints	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	
<i>W-104</i>		<i>4</i>	<i>3</i>							Grind <i>1-2</i>
<i>10% Leaded Zinc Ox</i>		<i>5</i>	<i>2</i>							Kind of Mill <i>W-8 or</i>
<i>W-69</i>		<i>2</i>								Strainer <i>Pebble</i>
<i>W-16</i>		<i>1</i>								Weight per Gallon <i>15.8#</i>
<i>W-11</i>		<i>1</i>								Light Baume Temp.
										Heavy Baume Temp.
<i>0-5</i>	<i>1</i>									Viscosity <i>85-90</i> Temp. <i>Kill</i>
<i>0-1</i>	<i>1 1/2</i>									Viscosimeter
<i>0-236</i>	<i>2 1/2</i>									Flash Point <i>119F</i>
<i>V-15</i>	<i>2 1/6</i>									Is Agitator Required
<i>S-148</i>	<i>1/2</i>									Remarks <i>Hayward</i>
<i>S-43</i>	<i>1 1/8</i>									<i>Discontinued</i>
<i>67T9</i>										
Yield	<i>alternate formula to use 10% Leaded Zinc</i>									

GLD060573

FORMULA RECORD

Grade *Endurance Shade White Base*

Formula No. *Y-1804*

Consistency *Squad*

Laboratory No.

For use on

Cost Class.

Date *8-*

Customer

Strainer

Grind

Mill *Roller & H-1*

Code Number	One Gallon Batch			Large Batch		Is agitator required	
	Pints	Lbs.	Ozs.	Gals.	Lbs.	Wt. or Be	Temp.
<i>W-69</i>		<i>3</i>	<i>10</i>		<i>290</i>	<i>15.7</i>	<i>Temp. KU</i>
<i>W-6</i>		<i>6</i>	<i>14</i>		<i>550</i>	<i>5-90</i>	<i>Temp. KU</i>
<i>W-10</i>			<i>12</i>		<i>60</i>	<i>Viscosimeter</i>	
<i>W-11</i>		<i>2</i>	<i>1</i>		<i>165</i>	<i>Color White</i>	<i>Sheen</i>
						<i>Non Vol. 15</i>	<i>Flash Pt. 105</i>
						<i>Watch for 15</i>	
<i>D-1</i>	<i>3</i>			<i>30</i>			
<i>D-5</i>	<i>1</i>			<i>10</i>		<i>Reducer</i>	
<i>D-286</i>	<i>1 1/2</i>			<i>15</i>		<i>Amt. for brushing F.B.</i>	
<i>D-15</i>	<i>2 1/6</i>			<i>5 5/8</i>		<i>Spraying</i>	<i>Tumbling</i>
<i>S-43</i>	<i>1 15/16</i>			<i>19 3/8</i>		<i>Dipping</i>	<i>Drip time</i>
						<i>Bake</i>	<i>Temp.</i>
						<i>Air dries in</i>	
						<i>A. D. to recoat in</i>	<i>72 hrs</i>
<i>Changed to ease brushing</i>						Standard Formula. Not to be taken from File.	
<i>10% oil</i>						Formulator <i>H.G.H.</i>	
<i>-1 54.5</i>							
<i>-5 18.1</i>							
<i>-286 27.74</i>							
<i>Yield</i>							

GLD060574

SLIGHTLY REDUCED PRINTED IN U.S.A. PRINT

GOODS: **Endurance 1804 Tinting White**

FORMULA RECORD

FORMULA NO. **Y-1804-R**

CONSISTENCY: **Liquid**

LABORATORY NO.

FOR USE ON

COST CLASS.

DATE **8/1/50**

CUSTOMER

STRAINER

GRIND **2-3**

MILL **Pebble**

WT. OR SS **15.5**

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH			IS AGITATOR REQUIRED	
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.	VISC. F.B.	TEMP.
W-62		2	14		230		85-90KU	
W-35		5	3		415			
W-1		2			160			
W-10			12		60			
W-11		2	13		225			
Q-1	2 7/8			28 3/4				
Q-5	1 1/4			12 1/2				
Q-286	3/4			7 1/2				
WVR 149098	3/4			7 1/2				
OR Q-315								
S-13	1 3/4			17 1/2				
D-15	5/8			6 1/4				
W-25			2 loz/gal					
* Add if needed to bring viscosity up to standard							REMARKS: Use this formula until	
as Driscy W-0-315 can be used to replace W-149098							W-170 can be obtained in	
							sufficient quantity then new	
							formula will be issued.	
YIELD 2 1/4							FORMULATOR J. Langstoss 13H	
							26-1-6	

Standard Formula
Not to be taken
from file

GLD060575

COST DEPARTMENT RECORD

Goods

*Endurance Shade White Base*Formula No. *V18045 Ten*

Consistency

Date *5/16/49*

Laboratory No.

For Use on

Cost Classification

Code Number	One Gallon Batch			Gallon Batch			Gallon Batch			Manufacturing Specifications
	Pints	Lbs.	Oz.	Gals.	Lbs.	Oz.	Gals.	Lbs.	Oz.	
<i>W69</i>		<i>2</i>	<i>13</i>							Grind <i>1-2</i>
<i>W35</i>		<i>5</i>								Kind of Mill <i>Pebble</i>
<i>W104</i>		<i>1</i>	<i>14</i>							Strainer
<i>W-11</i>		<i>3</i>	<i>7</i>							Weight per Gallon <i>15.5</i>
<i>01</i>	<i>2 1/16</i>									Light Baume Temp.
<i>05</i>	<i>1 7/16</i>									Heavy Baume Temp.
<i>0286</i>	<i>1 7/8</i>									Viscosity <i>85-90</i>
<i>D15</i>	<i>1/2</i>									Viscosimeter <i>Krebs</i>
<i>543</i>	<i>1 3/4</i>									Flash Point
<i>add. Pin</i>										Is Agitator Required
<i>LEG 0183</i>										Remarks
<i>gh 1/4</i>										<i>A.S. 72 hrs</i>
<i>M25</i>		<i>as needed</i>								
<i>Wool</i>	<i>40-50</i>	<i>43</i>	<i>33%</i>							<i>J. Wangane</i>
	<i>40-50</i>	<i>23</i>	<i>33%</i>							<i>J. Lab</i>
Yield	<i>40-50</i>	<i>33</i>	<i>33%</i>							

GLD060576

Endurance #1804 Tinting White

FORMULA NO. Y-1804-S

GOODS Liquid

LABORATORY NO.

CONSISTENCY

COST CLASS.

DATE 6/19/52

FOR USE ON

STRAINER

GRIND 2-3

CUSTOMER

MILL Pebble

WT. OR BE 24.7

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH			IS AGITATOR REQUIRED
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.	
W-35		3	15		315		VISC. F. 105-145" TEMP. 80°
W-1		1	9		145		VISC. 85-90 KU TEMP. 80°
W-170		1	8		140		VISCOSIMETER #4 F.C. & Stormer
W-10		1	8		140		COLOR SHEEN 65°
W-11		3	11				NON VOL. FLASH PT.
							MATCH FOR Lab. Std.
O-1	2-7/8			18 3/4			REDUCER
O-5	1-1/4			17 1/2			AMT. FOR BRUSHING
O-286	3/4			7 1/2			SPRAYING TIMELING
VR-49098	3/4			7 1/2			DIPPING DRIP TIME
S-43	1-3/4			17 1/2			BAKE TEMP.
D-15	5/8			6 1/2			
S-14			1			30	AIR DRIES IN Overnight
#O-325			1			80	A. D. TO RECOAT IN 72 hrs.
							REMARKS:
	*Hold to adjust body.						
	Changed to improve hiding & tint retention.						
YIELD							FORMULATOR H.G. Hayward H. 25-8-4

Standard formula
 Not to be taken
 from file

COST	DATE	ANALYSIS	CUSTOMERS
		PIGMENT 61.8 %	V-1804-S 6/19/52
		VEHICLE 38.2 %	Endurance House Paint #1804 Tinting White <i>All Plants 6-27-52</i>
		100.0 %	
		PIGMENT	
		10% Leaded Zinc Oxide 52.3%	
		Basic Sulphate White Lead 12.8	
		Titanium Oxide 12.3	
		Barium Sulphate 12.3	
		Magnesium Silicate 30.3	
		100.0 %	
		VEHICLE	
		Linseed Oil 47.2%	
		Treated Soya Oil 26.0	
		Mineral Spirits 19.2	
		Liquid Drier 7.6	
		100.0 %	
		V-1804	256

GLD060578

FORMULA RECORD

FORMULA NO. Y-1804-T

Endurance #1804 Tinting White

LABORATORY NO.

WY-100 Liquid

COST CLASS. DATE 8/3/53

FOR USE ON

STRAINER : GRIND 2-3

CUSTOMER

MILL Pebbles or WT. OR BE 14.7#

[illegible]

GLD060579

PRINTED IN U.S.A. FRONT

FORMULA RECORD

FORMULA NO. **W-1804 Emergency**

GOODS **Endurance - Tint Base**

LAST MODIFIED **Temporary**

CONSISTENCY **Liquid**

COST CLASS. DATE **7/11/55**

FOR USE ON

STRAINER GRIND **3-4**

Q. NUMBER

MILL **Pebble or** WT. OR SS **13.45**

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH		
	PYTS	LBS.	OZS.	GALS.	LBS.	OZS.
W-180		4	12			
W-35		3	11			
W-63		2	12			
CH-185			1/2			
O-286	1-1/2					
O-1	3-1/8					
O-9	1					
S-43	2-3/8					
VM-432			2	oz.		
VM-433			1/4			
* O-325			2			

Standard Formula.
Not to be taken
from file.

IS AGITATOR REQUIRED **HI R**
VISC. F.D. **85-90 KU** TEMP. **74.5**
VISC. RED. TEMP. **Extra**
VISCOMETER **Stormer**
COLOR **White** SHEEN **cap**
NON VOL. FLASH PT.
WATCH FOR
REDUCER **S-43**
AIR. FOR BRUSHING **FB**
SPRAYING TUBING
DIPPING DRIP TIME
BAKE TEMP.
AIR DRIES IN **O.N.**
A. D. TO RECOAT IN **72 hrs.**

REMARKS:
* Use only if necessary for body. Sample of every batch to be sent to H. Homans.
** Use only in absolute emergency when all efforts to obtain W-170 have been exhausted- Must not be made for stock.
Approved in emergency per Mr. Mutersbaughs' FORMULATOR **H. Homans**
YIELD **1.39 Gal.) (letter of 7/11/55.** PCH **28-8-8**

GLD060581

GLD060582 PRINTED IN U.S.A. FRONT

FORMULA RECORD

FORMULA NO. **W-1804 Emergency**

CODES **Endurance - Tint Base**

UNEMPLOYMENT & Temporary

CONSISTENCY **Liquid**

COST CLASS.

DATE **7/11/55**

FOR USE ON

STRAINER

GRIND **3-4**

CUSTOMER

MILL **Pebble** or wt. or cc **13.45**

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH			IS AGITATED VISC. F.B.	TEMP.
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.		
W-180		4	12				85-90	KU
W-53		3	11				Stormer	
W-63		2	12				White	SHEN
CH-185			1/2				FLASH PT.	
Q-286	1-1/2			Reissued 8/24/55 to add analysis.			REDUCER	S-43
Q-1	3-1/8						AMT. FOR BRUSHING	FB
Q-9	1						SPRAYING	FLABLING
S-43	2-3/8						DIPPING	DRIP TIME
VM-432			2	Loz.			DATE	TEMP.
VM-433			1/4				AIR DRIES IN	O.N.
* O-325			2				A. D. TO RECOAT IN	72 hrs.

**Standard Formula
Not to be taken
from File.**

*** Use only if necessary for body.**

**Sample of every batch
to be sent to H. Homans.**

****Use only in absolute emergency when all efforts
to obtain W-170 have been exhausted-Must not be
made for stock.**

Approved in emergency per Mr. Mutersbaughs' letter to H. Homans

YIELD 1.39 gal.)

(of 7/11/55/

28-8-8

GLD060582

GLIDDEN 1951-11 PRINTED IN U.S.A. FRONT

FORMULA RECORD

FORMULA NO. Y-1804-U

GOODS Endurance Tint Base

LABORATORY NO.

CONSISTENCY Liquid

COST CLASS. DATE 9/4/56

FOR USE ON

STRAINER GRIND 3-4

CUSTOMER

Wt. OF BE 13.6#

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH			IS AGITATOR REQUIRED Hy-R
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.	
W-180		5			350		VISC. F.D. 85-90 KUW.P.
W-33		3	11		260		VISC. RED. TEMP.
W-63		2	12		195		VISCOSMETER Stormer
W-195			1		4-1/2		COLOR GREEN
							NON VOL. FLASH PT.
O-286	1-1/2			13			WATCH FOR
O-62	1/4			2-1/4			REDUCER S-43
O-1	4-1/2			40			WATER FOR BRUSHING as needed
S-43	1-1/2			13			SPRAYING TUMBLING
S-148	1/2			4-1/2			DIPPING DRIP TIME
							BAKE TEMP.
VM-432		2 Loz.	1-1/8				AIR DRIES IN O.N.
VM-523		1 Loz.	1/2				S. D. TO RECOAT IN 72 hrs.
VM-433		5/16 Loz.			22 Loz.		REMARKS:
S-72		1/2 Loz.			35 Loz.		
APA Advance Puffing Agent if needed.				1/8 or 1/4 Gal. / 100 Gals.			
YIELD 1.42 100 FORMULATOR J.E. Southwick 28-8-8							

Standard Formula
Not to be used
from this

GLD060584

[illegible]

GLD060585

GLD060586 PRINTED IN U.S.A. FRONT

FORMULA RECORD

FORMULA NO. Y-1804 SF & Tor.

GOODS Alkyd House Paint - Tint Base

LABORATORY NO.

CONSISTENCY

COST CLASS.

DATE 6/10/60

FOR USE ON in V-1856, Y-1857, Y-1859, Y-1886, Y-1887

STRAINER

GRIND 6

CUSTOMER TORONTO + SAN FRANCISCO & Y-1888

MILL Pebble

WT. OR BE 9.5#

CODE NUMBER	ONE GALLON BATCH			ONLY LARGE BATCH			IS AGITATOR REQUIRED	
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.	VISC. F.B.	TEMP.
W-170 or W-208				(4.15)	145		VISC. RED	TEMP.
W-188				(2.31)	55		VISCOSIMETER	Stormer
W-154				(2.44)	55		COLOR	SHEEN N1-Gloss
CH-185				(.26)	2.3		NON VOL.	FLASH PT.
W-218	Premix before			(.4)	6		MATCH FOR	
S-72	adding to mill			.46	(3)		REDUCER	S-43
V-869				62.7	(492)		AMT. FOR BRUSHING	F.B.
O-265				14.0	(108)		SPRAYING	TUMBLING
S-43	Standard Formula			9.5	(62)		DIPPING	DRIP TIME
VM-523	Not to be taken from File.			5	(4)		BAKE	TEMP.
VM-433				.25	(2)		AIR DRIES IN	O.N.
VM-432				.63	(6)		A. D. TO RECOAT IN	48 hrs.
D-83				.58	(4)		REMARKS:	
CH-359				.70	(1.5)		CAUTION: WHEN DETERMINING VISCOSITY-MATERIAL IS THIXOTROPIC.	
VM-559				.8	(6.4)			
*Jelomer	903(W-486)			.28	(2.0)			
*Alkydol	Labs. Inc.						FORMULATOR	J.E. Southwick
YIELD				99.4	954.2			

GLD060586

[illegible]

GLD004 (REV. 11-54) PRINTED IN U.S.A. FRONT

FORMULA RECORD

FORMULA NO. Y-1804 SF & Tor.

GOODS Alkyd House Paint - Tint Base

LABORATORY NO.

CONSISTENCY

COST CLASS.

DATE 1/20/60**

FOR USE IN Y-1856, Y-1857, Y-1859, Y-1886, Y-1887

STRAINER

GRIND 6

CUSTOMER TARRANTS & SONS FROM L.L.C. & Y-1888

MILL Pebble

WT. OR BE 9.5#

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH			IS AGITATOR REQUIRED
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.	
W-170 or W-205				14.15	145		VISC. F. 38-82 KU TEMP.
W-188				12.31	55		VISC. RED. TEMP.
W-154				12.44	55		VISCOSIMETER Storrer
W-185				.26	2.3		COLOR SHEEN-11008
W-218) Premix before				.4	6		NON VOL. FLASH PT.
S-72) adding to mill				.46	(3)		WATCH FOR
Y-809				62.7	(492)		REDUCER S-43
Y-205				14.0	(108)		AMT. FOR BRUSHING F.B.
S-43				9.5	(62)		SPRAYING TACKLING
VM-523				.5	(4)		DIPPING DRIP TIME
VM-433				.25	(2)		BAKE TEMP.
VM-432				.63	(6)		AIR DRIES IN O.N.
D-83				.58	(4)		A. D. TO RECOAT IN 48 hrs.
VM-359				.20	(1.5)		REMARKS:
VM-659				.8	(6.4)		
Sealumar 903(M-486)				.28	(2.0)		CAUTION: WHEN DETERMINING VISCOSITY-MATERIAL IS THIXOTROPIC.
Alkydol Labs, Inc.							FORMULATOR J.E. Southwick
**REISSUED TO SHOW CORRECTION.							
DESTROY COPY DATED 6/10/60							
YIELD				98.4	554.2		

GLD060588

Endurance Flint Base

U.S. RECORD
DISCONTINUED

LABORATORY NO.

CONSISTENT

COST CLASS.

DATE _____

FOR USE ON

Destroy formula dated 9/4/55.

STRAINER

GRIND

CUSTOMER

70 - K - 6 - rubble or

NET 09 55

135

CODE NUMBER	ONE GALLON BATCH			LARGE BATCH			IS AS BATCH REQUIRED	
	PINTS	LBS.	OZS.	GALS.	LBS.	OZS.	VISC. F.B.	TEMP.
W-180		5			350		VISC. RED.	TEMP.
W-35		3	11		260		VISCOSIMETER	Stormer
W-63		2	12		195		COLOR	SHEEN
W-195			1		4-1/2		NEW VOL.	FLASH PT.
							MATCH FOR	
W-286	1-1/2			13			REDUCER	8-43
W-62	1/4			2-1/4			INT. FOR BRUSHING	As needed
W-1	4-3/8			38-1/2			SPRAYING	TUMBLING
W-43	1-3/8			12			RIPPING	DRIP TIME
W-148	1/2			4-1/2			WAX	TEMP.
VM-432		2 Loz.		1-1/8			AIR DRIES IN	O.N.
VM-523		1 Loz.		1/2			A. D. TO RECOAT IN	72 hrs.
VM-433		5/16 Loz.			22 Loz.		REMARKS:	Changed for lower cost.
W-72 or W-91		1/2 Loz.			35 Loz.			
APA Puffing Agent (hold) as needed.				1/8 or 1/4 gals./100 gals.				
YIELD	1.42			100			FORMULATOR	J.E. Southwick 26-8-8

[illegible]

FORMULA RECORD

FORMULA NO. Y-1804-U

goods	Endurance Tint Base
-------	---------------------

LABORATORY NO.

CONSISTENCY

COST CLASS

DATE 4-17-59

FOR USE ON

STRAINER

GRIND

CUSTOMER

HELL

WT, OR BE

CODE	NUMBER
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

ONE GALLON BATCH

LARGE BATCH

IS AGITATOR REQUIRED

PINTS

195.

025.

GALS.

LBS.

025

YISC-F.B.I.

TOP

YISC. RED.

134

VISCOMETER

COLLEGE

SHEEN

INEN VOL.

FLASH PT.

MATCH FOR

REDUCER

ART. FOR DRUSHING

SPRAYING

TUMBLING

DIPPING

DRIP TIME

BAKE

12-4

AIR DRIES IN

A. D. TO RECOAT IN

REMARKS:

FORMULATOR

YIELD

~~Standard Formula
Not to be taken
from File~~

GLD060592

[illegible]

GLD060593