


OC 42-2

OWENS CORNING
FIBERGLAS

INTRA-COMPANY CORRESPONDENCE



To Mr. A. S. Kevlin - New York
From F. H. Edwards - Toledo
Subject BATH IRON WORKS

Date August 9, 1966

The subject company is pursuing the best course of action to solve their problems by hiring the Harvard School of Public Health as consultants. They will determine the degree of exposure and recommend methods of bringing it to acceptable levels.

The American Conference of Governmental Industrial Hygienists has established a threshold limit value (sometimes referred to as maximum allowable concentration) for air-borne asbestos particles at 5 million particles per cubic foot of air. ~~However, dusts in the air should not exceed this value which is an average figure over an 8-hour working day.~~ However, exposures may be considered excessive if massive exposures occur at certain times of the work period even though the computed average is within the limit value. *Asbestos fiber*

The extent of air contamination is determined by the air sampling unit - a Konimeter in this case. In order to avoid expense and work, the hygienist may assume that the collected aggregate consists only of the hazardous material. ~~This is seldom the case as~~ many other dusts are air-borne in the industrial atmosphere and, of course, are collected by the sampling unit. I am sure that Harvard will analyze the samples for asbestos fiber. As an example, our Kaylo products are composed primarily of calcium silicate which is not considered a health hazard. Intermixed in the calcium silicate is approximately 15% of asbestos fiber. Obviously, the dust created in the cutting or sawing of Kaylo should contain about this same percent of asbestos.

It is possible that Harvard may not agree with the limit value of the A.C.G.I.H. and may suggest a lower limit. If such is the case, they, no doubt, have data to support it.

Because of Bath Iron's unfortunate experience, I am sure that they will want to take drastic measures to prevent future problems. They have two alternatives with a hazardous material: (1) provide ventilation adequate to maintain dust levels within the recommended limits, or (2) provide suitable, approved respirators for workmen if ventilating equipment cannot be adapted to the operation. The former method is the best because workers will remove the masks whenever supervision is looking the other way.

~~Asbestos can cause asbestosis, a serious lung disease, after 12 years or more of exposure. Consequently, an enlightened company will provide protection and we should endorse adequate health and safety programs.~~ As you know, many companies are handling asbestos without health problems and they are doing it by means of good protective measures.

FHE:JSC

F. H. Edwards

01 039 147