NEG. NO. AK-11

TRADEMARK FILE INFORMATION

Trademark:	Alco
Trademark Owner:	National Varnish Co.
Last Assignee:	None
Date of First Use in Commerce:	April, 1956
Registration No.:	1,194,940
Date Trademark Registered:	May 11, 1982
Size of Label in Trademark File:	N/A

Receipt of Pictured Label by Patent Office:



FOUNDATION MASTIC

ALCO Foundation Mastic is a ready to use asphalt base mastic containing the highest grade of short, Canadian asbestos fiber suitable for brush and/or spray application. If spraying is desired, a heavy duty spray apparatus must be used. Foundation Mastic is similar to Tri-County (Trowel-On) except for the short fibers which allow for spraying.

Apply directly from the container without heating or thinning. For ease of application, material should be at room temperature when applied. Like any foundation coating, apply only to a clean, dry surface free from all foreign matter. This will ensure a good bond to the surface.

For dampproofing foundation surfaces, apply heavily with a brush or spray. Allow material to set for 12 hours. For best results, a second coat is recommended. Allow second coat to set for 24 hours. Allow at least 48 hours before backfilling.

PLASTIC SEALER

ALCO Plastic Sealer is a trowel-on foundation mastic. It can be used efficiently for repairing and plugging cracks and holes in basement walls.

Meets or exceeds Federal Spec. SS-C-153, Type I.

WARRANTY



Foundation Coating
Tri-County (Brush-On)
Tri-County (Trowel-On)
Foundation Mastic
Plastic Sealer
Melnar

DAMPPROOFING

NATIONAL VARNISH CO.