REGISTERED

REG'N. No. 78131

DATE 5-13-

O'BRIEN

"SEVENTY-FIVE"®

Low Lustre

HOUSE PAINT

SUNCREST

ONE GALLON

49 TOC 001710

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001750

O'BRIEN

"SEVENTY-FIVE"®

Low Lustre

HOUSE PAINT

SIERRA SLATE

ONE GA

49 TOC 001751

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001752

REGISTERED
REG'N. No. 751313
DATE 5-13-68

O'BRIEN

"SEVENTY-FIVE"®
Low Lustre
HOUSE PAINT

OLIVE

ONE GALLON

49 TOC 001753

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001754

O'BRIEN

"SEVENTY-FIVE"®

Low Lustre

HOUSE PAINT

GREEN BALSAM

ONE GAL

49 TOC 001755

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL GREEN BALSAM

Pigment	39.57%
18% Leaded Zinc Oxide	25.43%
Chromium Oxide	24.71%
Carbon Black	1.94%
Phthalocyanine Green	.45%
Silicates	47.47%
	100.00%
Vehicle	60.43%
Modified Soya Alkyd Resin	5.56%
Heat Processed Linseed Oil	29.35%
Aromatic Hydrocarbons	9.71%
Mineral Spirits & Driers	55.38%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001756

REGISTERED
REG'N. No. 75131³
DATE 5-13-68

O'BRIEN

"SEVENTY-FIVE"®
Low Lustre
HOUSE PAINT

BUD GREEN

ONE GALLON

49 TOC 001757

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT

(FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. — (PYOW)

CAUTION! COMBUSTIBLE!
CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" EGGSHELL – BUD GREEN

Pigment	47.18%
Titanium Dioxide	7.77%
18% Leaded Zinc Oxide	27.28%
Chromium Oxide	11.55%
C. P. Red Iron Oxide	.66%
Silicates	52.74%
	100.00%
Vehicle	52.82%
Raw Linseed Oil	11.45%
Heat Treated Linseed Oil	21.52%
Modified Soya Alkyd Resin	5.46%
Aromatic Solvent	10.88%
Mineral Spirits & Drier	50.69%
	100.00%

SINCE O'BRIEN 1875

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND IND • BALTIMORE MD • OKLAHOMA CITY OKLA • LOS ANGELES CAL • BRUNSWICK GA

49 TOC 001758