

bec C. Eaton/J. J. Roder
1800 D. R. Hansen
5120 J. A. Kriss

October 26, 1971

Mr. R. Courtney
Ridgeway Lithograph
4111 195th Ave. N.E.
Redmond, Wash. 98052

Dear Mr. Courtney:

This letter concerns the conversion of your heat transfer unit from Therminol FR to Therminol 55

Literature on Therminol 55 is enclosed. We are arranging for two drums of Therminol 55 to be sent to your attention at no charge. You should drain the Therminol FR from your system thoroughly -- this means removing all of the FR fluid. Therminol 55 can then be added and operation of the system resumed.

We would like to remind you that Therminol 55 is not classified as a fire resistant heat transfer fluid. Consequently, you may wish to consider the use of protective devices to minimize any added fire risks. We suggest that you consult with the insurer of your property relative to this matter.

Also enclosed are labels to be placed on the containers of drained FR fluid for return to the address shown. We will pay the return freight.

Your cooperation is appreciated.

Sincerely,

D. E. Roush
Product Specialist
Heat Transfer Fluids

cc
Enclosures

Note to bec: Application is pattern waxer for margarine boxes. Initially used Pydraul, but switched to FR-1 because of sludge problems.

DSW 435313

STLCOPCB4088374