

Title 40 - Protection of Environment
CHAPTER I - ENVIRONMENTAL PROTECTION AGENCY
SUBCHAPTER C - AIR PROGRAMS
PART 61 - NATIONAL EMISSION STANDARDS FOR
HAZARDOUS AIR POLLUTANTS
STANDARD FOR VINYL CHLORIDE

1976

On December 24, 1975, under section 112 of the Clean Air Act, as amended (42 U.S.C. 1857), the Environmental Protection Agency (EPA) added vinyl chloride to the list of hazardous air pollutants (40 FR 59477) and proposed a national emission standard for it (40 FR 59532). The standard covers plants which manufacture ethylene dichloride, vinyl chloride, and/or polyvinyl chloride.

EPA decided to regulate vinyl chloride because it has been implicated as the causal agent of angiosarcoma and other serious disorders, both carcinogenic and noncarcinogenic, in people with occupational exposure and in animals with experimental exposure to vinyl chloride. Reasonable extrapolations from these findings cause concern that vinyl chloride may cause or contribute to the same or similar disorders at present ambient air levels. The purpose of the standard is to minimize vinyl chloride emissions from all known process and fugitive emission sources in ethylene dichloride-vinyl chloride and polyvinyl chloride plants to the level attainable with best available control technology. This will have the effect of furthering the protection of public health by minimizing the health risks to the people living in the vicinity of these plants and to any additional people who are exposed as a result of new construction.

Interested parties participated in the rulemaking by sending comments to EPA. The comments have been carefully considered, and where determined by the Administrator to be appropriate, changes have been made to the regulation as promulgated.

Summary of the Standard

In ethylene dichloride-vinyl chloride plants, the standard limits vinyl chloride emissions from the ethylene dichloride and vinyl chloride formation and purification processes to 10 ppm. For the oxychlorination process, vinyl chloride emissions are limited to 0.2 g/kg of ethylene dichloride product.

In polyvinyl chloride plants, the standard limits vinyl chloride emissions from equipment preceding and including the stripper in the plant process flow to 10 ppm. Emissions from equipment following the stripper are to be controlled by stripping dispersion resins to 2000 ppm and other resins to 400 ppm, or by using equivalent controls. Vinyl chloride emissions from reactor opening are to be reduced to 0.02 g/kg polyvinyl chloride product.

In both ethylene dichloride-vinyl chloride and polyvinyl chloride plants, relief valve discharges and manual venting of gases are prohibited except under emergency conditions. Fugitive emissions are required to be captured and controlled.

Health and Environmental Impacts

EPA prepared a document entitled the Quantitative Risk Assessment for Community Exposure to Vinyl Chloride which estimates the risk from vinyl chloride exposure to populations living in the

vicinity of vinyl chloride-emitting plants before and after implementation of controls to meet the standard. There are no dose-response data for the concentrations of vinyl chloride found in the ambient air. Therefore assessments of risk at ambient levels of exposure were extrapolated from dose-response data from higher levels of exposure using both a linear model and a log-probit model. Extrapolations made with each of these models entailed making assumptions. Because different assumptions can be made in extrapolating to low doses, the health risks are reported in ranges.

It was estimated that 4.6 million people live within 5 miles of ethylene dichloride-vinyl chloride and polyvinyl chloride plants and that the average exposure around these plants before installation of controls to meet the standard is 17 parts per billion. The exposure levels for uncontrolled plants were calculated based on 1974 emission levels. Using the linear dose-response model, EPA found that the rate of initiation of liver angiosarcoma among people living around uncontrolled plants is expected to range from less than one to ten cases of liver angiosarcoma per year of exposure to vinyl chloride. The log-probit model gave predictions that are 0.1 to 0.01 times this rate. This wide range is an indication of the uncertainties in extrapolation to low doses. The cases initiated by exposure this year will not be diagnosed until 1991 or 1995. Vinyl chloride is also expected to produce an equal number of primary cancers at other sites, for a total of somewhere between less than one and twenty cases of cancer per year of exposure among residents around

plants. The number of these effects is expected to be reduced in proportion to the reduction in the ambient annual average vinyl chloride concentration, which is expected to be 5 percent of the uncontrolled levels after the standard is implemented.

Changes in the standard since proposal do not affect the level of control required. Thus, the environmental impact of the promulgated standard is, with one exception, the same as that described in Chapter 6 of Volume I of the Standard Support and Environmental Impact Statement. Based on data submitted by the Society of Plastics Industry, Inc. (SPI), the impact on water consumption in the draft environmental impact statement was overstated. In estimating the impact on water consumption, EPA based its estimates on worst case conditions. That is, EPA assumed that those control systems with the greatest water usage would be employed and that there would be no recycling of water. There is no regulation which would require water recycling. According to SPI, the control system utilizing the most water will not be used generally by the industry and economics will cause plants to recycle much of the water. Therefore, the impact of the standard on water consumption will be negligible.

A summary of the environmental impact of the promulgated standard is as follows: The primary environmental impacts of the

standard are beneficial and will consist of vinyl chloride emission reductions of approximately 94 percent at ethylene dichloride-vinyl chloride plants and 95 percent at polyvinyl chloride plants. Percentage numbers for both source categories are based on an estimated 90 percent reduction in fugitive emissions and 1974 emission levels.

The potential secondary environmental impacts of the standard are either insignificant or will be minimized without additional action, except for one adverse impact. Hydrogen chloride is already emitted by process equipment at ethylene dichloride-vinyl chloride plants and by other petrochemical plants in the complexes where ethylene dichloride-vinyl chloride plants are typically located. An incinerator used to attain the standard at an ethylene dichloride-vinyl chloride plant could increase hydrogen chloride emissions by several fold. Typically, however, due to the corrosion problems which would otherwise occur both on plant property and in the community, plants use scrubbers to control already existing hydrogen chloride emissions. Hydrogen chloride emissions resulting from control of vinyl chloride emissions are expected to also be controlled for the same reason. If even a moderately efficient scrubber (98 percent control) were used to control the hydrogen chloride emissions resulting from incineration of vinyl chloride emissions, the increase in hydrogen chloride emissions from a typical ethylene dichloride-vinyl chloride plant due to the standard would be reduced to 35 percent. However, EPA plans to further evaluate the need to control hydrogen chloride emissions, since diffusion model results indicate that under "worst-case" meteorological conditions, the

hydrogen chloride emissions from the process equipment and the incinerator combined would cause maximum ambient concentrations of hydrogen chloride in the vicinity of ethylene dichloride-vinyl chloride plants to be in the same range of somewhat higher than existing foreign standards and National Academy of Sciences (NAS) guidelines for public exposure.

Economic Impact

In accordance with Executive Order 11821 and OMB circular A-107, EPA carefully evaluated the economic and inflationary impact of the proposed standard and alternative control levels and certified this in the preamble to the proposed standard. These impacts are discussed in Chapter 7 of Volume I of the Standard Support and Environmental Impact Statement. Comments on the proposed standard have resulted in only one major change in the economic impact analysis. EPA estimated that there would be four plant closures as a result of the promulgated standard. Of the four plants identified as possible closure candidates, one has given notice that it no longer produces polyvinyl chloride and the other three have indicated that they do not intend to close as a result of the standard.

A summary of the economic impact of the promulgated standard is as follows: The total capital cost for existing plants to meet the standard is estimated to be \$198 million, of which \$15 million is for ethylene dichloride-vinyl chloride plants and \$183 million is for polyvinyl chloride plants. EPA estimates that these plants will have to spend \$70 million per year to maintain the required emission levels. In addition, total capital cost for existing plants to meet the EPA's 1973 water effluent guideline limitations is \$83 million and the total annualized operation cost is \$17 million. The costs to the industry of meeting the OSHA standard cannot be quantified

at this time, but they are expected to overlap to some degree with the costs to meet EPA's fugitive emission regulations. The costs of meeting the fugitive emission regulations are included in the total costs cited above for meeting the promulgated regulation. Broken out separately, the capital cost of meeting the fugitive emission regulations is \$37 million and the annualized cost is \$25 million.

The standard is not expected to deter construction of new ethylene dichloride-vinyl chloride plants or most types of new polyvinyl chloride plants. For one type of polyvinyl chloride plant (dispersion process) that represents 13 percent of the industry production, the standard would significantly deter the construction of smaller plants.

It is estimated that the price of polyvinyl chloride resins will rise by approximately 7.3 percent in order to maintain precontrol profitability and also to recover the total annualized control costs necessitated by the standard at ethylene dichloride-vinyl chloride plants and polyvinyl chloride plants. This increase is estimated to translate into a maximum consumer price increase in goods fabricated from polyvinyl chloride resins of approximately 3.5 percent. Recovery of effluent annualized costs plus maintenance of precontrol profitability is estimated to add approximately 2 percent to polyvinyl chloride resin prices and result in an additional maximum consumer price increase of 1 percent.

Public Participation

During the public comment period, 50 comment letters on the proposed standard were received. There were 24 from industry; 3 from environmental groups, 15 from Federal, State, and local agencies; and 8 from individual citizens. As required by section 112(b)(1)(B) of the Act, a public hearing was held on the proposed standard on February 3, 1976, in Washington, D. C. Presentations were made by the Environmental Defense Fund, the Society of the Plastics Industry, Inc., Dow Chemical Company, Diamond Shamrock Corporation, and Air Products and Chemicals, Inc. Copies of the comment letters received, the public hearing record, and a summary of the comments with EPA's responses are available for public inspection and copying at the EPA Public Information Reference Unit, Room 2922 (EPA Library), 401 M Street, S. W., Washington, D. C. In addition, copies of the comment summary and Agency responses may be obtained upon written request from the Public Information Center (PM-215), Environmental Protection Agency, 401 M Street, S.W., Washington, D. C. 20460 (specify Standard Support and Environmental Impact Statement, Emission Standard for Vinyl Chloride, Volume II).

Significant Comments and Changes to the

Proposed Regulation

(1) Decision to List Vinyl Chloride as a Hazardous Air Pollutant.

Only three commenters (two companies and one Federal agency) argued that available data are not sufficient to justify regulating vinyl chloride under section 112. The Act specifies that EPA could remove

vinyl chloride from the list of hazardous air pollutants only if information were presented to EPA that shows that it is clearly not a hazardous air pollutant. The commenters did not provide conclusive evidence that vinyl chloride does not cause or contribute to death or serious illness.

Several other commenters agreed with EPA's decision to list vinyl chloride as a hazardous air pollutant, but argued that EPA had overstated the health problem, the emission levels, and the projected ambient air concentrations around uncontrolled plants. With regard to the alleged overstated health problem, the commenters stated, for example, that the U. S. worker EPA discussed as having been exposed to vinyl chloride levels lower than those usually encountered in polyvinyl chloride production has been dropped from the National Institute of Occupational Safety and Health's listing of workers with angiosarcoma. EPA agrees that there are questions concerning the level of exposure of those cases not involved directly in polyvinyl chloride and vinyl chloride production, and in some cases the pathology. These uncertainties are stated in the appropriate footnotes of the Scientific and Technical Assessment Report on Vinyl Chloride and Polyvinyl Chloride (STAR) where the angiosarcoma cases are listed. However, in spite of these uncertainties, in view of the possible exposure patterns, these cases cannot be ignored in the evaluation of the potential public health problems.

With regard to the alleged overstated emission levels, the uncontrolled emission levels reported by EPA were based on 1974 data.

This qualification was stated wherever emission data were presented. EPA recognizes that emissions have been reduced since that time, and stated this in the preamble to the proposed standard. EPA decided not to gather more recent data on emission levels, because these emission levels are expected to change, and gathering the data would take considerable time both on the part of EPA and on the part of industry. Since the purpose of the standard is to minimize emissions, these more current data would not affect the standard itself. The 1974 emission levels were also used in diffusion modeling to project maximum ambient air concentrations around uncontrolled plants. These maximum air concentrations would probably be lower if 1976 emission levels were used. This would reduce the relative impact of the standard below that described in the Standard Support and Environmental Impact Statement, but should not affect the basis of the standard itself.

(2) Approach for Regulating Vinyl Chloride Under Section 112. Two approaches other than using best available control technology were suggested by the commenters for regulating vinyl chloride under section 112. The first was to ban polyvinyl chloride products for which substitutes are currently available and to gradually phase out other polyvinyl chloride products as substitutes are developed.

In the preamble to the proposed standard EPA named its reasons for not setting a zero emission limit for vinyl chloride, as follows: (1) There are beneficial uses of vinyl chloride products for which desirable substitutes are not readily available; (2) there are potentially adverse health and environmental impacts from

substitutes which have not been thoroughly studied; (3) there are a number of employees, particularly in the fabrication industries, who would become at least temporarily unemployed; and (4) control technology is available which is capable of substantially reducing emissions of vinyl chloride into the atmosphere.

EPA agrees that substitutes do exist or could be manufactured for most polyvinyl chloride uses. However, in general, these substitutes do not have some of the more desirable characteristics of polyvinyl chloride, such as nonflammability. If vinyl chloride and polyvinyl chloride were banned, other substitutes with these more desirable characteristics would likely be developed. EPA presently has no direct control over which substitutes are developed or used. There is a risk that these substitutes would also have adverse health or environmental effects. Since control measures are available which can reduce vinyl chloride emissions by 90 percent or more, it does not seem prudent to reduce emissions by the remaining percentage and take the risk of introducing new untested chemicals into the environment.

Another approach suggested by the commenters was to base the standard for each individual emission point on cost versus benefit. Several of the fugitive emission sources were named specifically as ones for which the costs of control were substantially higher than the benefits. Although EPA did determine a cost-effectiveness ratio for the controls required for a number of emission points, EPA does not favor using cost-effectiveness ratio as the basis of the standard. Section 111 of the Clean Air Act provides for the

development of standards based on best control technology (considering costs). In developing standards under section 111, standards are not based on a fine balancing of costs versus benefits. Instead a study is conducted to determine the affordability of the control technology required to achieve a given emission level and to determine the impact of a control level on the viability of the industry. Section 112 does not even provide for consideration of costs, so it does not seem appropriate to consider costs to a greater extent under section 112 than would be done under section 111. In developing standards under section 112 based on the best control technology, EPA felt that it was necessary to place some type of limit on the technology required. Otherwise, there are all types of theoretical controls which could be required. One limit placed on best control technology was that the costs of the technology not be grossly disproportionate to the amount of emission reduction achieved. In comparison with other emission points, the costs of controlling the fugitive emission sources mentioned by the commentators are relatively small compared with the amount of emission reduction achieved.

(3) Selection of Source Categories. In the preamble to the proposed standard EPA recognized that some small research and development facilities may exist where the emissions of vinyl chloride are insignificant and covering these facilities under the standard would be unnecessary and inappropriate. However, EPA did not have sufficient information available to clearly define which facilities should be excluded from the standard, and encouraged interested parties to submit

such information during the comment period. Based on the information submitted, EPA decided to exempt polyvinyl chloride reactors and associated equipment from applicability of the standard if the reactors are used in research and development and have a capacity of no more than 0.19 m^3 (50 gal). Reactors in this size range can generally be found in a laboratory, whereas the larger reactors are typically pilot scale facilities. Emissions from laboratory scale equipment are relatively small, and application of the controls required by the standard would be expensive and impractical. EPA also decided to require research and development facilities containing reactors greater than 0.19 m^3 (50 gal) and no more than 4.07 m^3 (1100 gal) in capacity to meet the 10 ppm limit for reactors, strippers, monomer recovery systems, and mixing, weighing and holding containers. EPA decided not to require these facilities to meet other parts of the standard because of the technical problems involved in doing so. For example, the standard for reactor opening is based in part on reducing the frequency of opening the reactor. Research and development reactors have to be opened after every batch for thorough cleaning. Also, stripping technology is developed individually for each resin in research and development equipment. Therefore, attainment of the stripping limitations in the research and development equipment would not always be possible. The 4.07 m^3 (1100 gal) figure was selected as an upper cut-off point because there are no commercial reactors smaller than this.

(4) Emission Limits. The only major change in the emission limits between proposal and promulgation is the addition of a provision for emergency manual venting of vinyl chloride from reactors to the atmosphere. The proposed standard prohibited all manual venting to the atmosphere. In the preamble to the proposed standard, EPA invited interested persons to comment on whether permitting manual venting to the atmosphere could result in overall lower emissions. There are several methods available for preventing relief discharges from reactors, one of which is manual venting of part of the reactor contents for purposes of cooling and reduction in pressure within the reactor. The higher the temperature and pressure within the reactor, the greater the amount of vinyl chloride which has to be removed to bring the reactor under control. Manual venting can be done at a lower pressure than the pressure required to open the relief valve. For this reason manual venting can result in lower emissions than would occur by allowing the reactor to discharge through the relief valve. Furthermore, a manual vent valve is under the control of an operator and can be closed. A relief valve may become clogged with resin and not close so that all the reactor contents are lost.

The contents of a reactor can be manually vented to a gasholder or other holding vessel. However, in some cases, such as during severe weather conditions, several reactors may be out of control at one time. There would be insufficient holding capacity under these conditions to manually vent the contents of all the reactors to a gasholder. Therefore, when all other measures to prevent relief valve discharges have been exhausted, manual venting will be permitted as a last resort before the relief valve opens. The same notification procedures are required for manual venting to the atmosphere as are required for relief discharges.

There are several changes in the numerical emission limits in the promulgated standard. Except for the standard for reactor opening loss, these changes simply involve conversion to the International System of Units (SI). There was an error involved in the original calculation used to derive the standard for reactor opening. Correcting this error doubles the allowable emissions. It is emphasized that the change in this standard is a correction, and not a change in the intent for the degree of control required.

The proposed standard required the installation of a rupture disc beneath each relief valve to prevent leakage from the relief valve. A provision has been added to the promulgated standard so that a rupture disc is not required if the relief valve is tied into a process line or recovery system. In this case, any leakage from the relief valve would be contained.

The regulation for obtaining vinyl chloride samples has been changed to an operating procedure. The proposed standard stated that there were to be no emissions from taking the samples. Several commenters pointed out that the use of the word "no" would make this regulation impractical to enforce. Therefore, the promulgated standard specifies the operating procedure which EPA originally intended to be used to control this source. This revision is only a change in wording and does not represent a change in the level of the standard.

The regulation for taking samples has also been revised to apply only to samples containing at least 10 percent by weight vinyl chloride. This is consistent with the other parts of the standard which apply to equipment "in vinyl chloride service." "In vinyl chloride service" distinguishes between situations where vinyl chloride is clearly involved and situations where vinyl chloride is a minor component or contaminant, and as defined in promulgated §61.61(1) means that a piece of equipment contains or contacts either a liquid that is at least 10 percent by weight vinyl chloride or a gas that is at least 10 percent by volume vinyl chloride.

The proposed standard required a vinyl chloride monitoring system for continuously measuring vinyl chloride levels both within the plant (for leak detection) and within stacks. The proposed standard did not outline required specifications for the monitoring system, except it was to analyze the samples with gas chromatography. It required that each plant submit a description of its monitoring system to EPA, so that EPA could determine whether it was acceptable or not. Comments

were received indicating a need for EPA to specify some criteria for judging the acceptability of monitoring systems. The accuracy of the monitoring system would be related to the frequency of calibration. EPA is currently developing criteria for judging the adequacy of each plant's calibration and maintenance schedule for the instrument. These are included in an enforcement guidelines document prepared by EPA.

The portable hydrocarbon detector required by the proposed standard was required to have a sensitivity of 5 ppm. Comments were received indicating that instruments in this sensitivity range are delicate and require continuing maintenance. The portable hydrocarbon detector is required for leak detection and for measuring vinyl chloride concentrations inside the equipment before opening it. A 5 ppm sensitivity is not needed in either case, and has been changed to 10 ppm in the promulgated standard.

The proposed standard contained a single regulation for compressors. The promulgated standard has separate regulations for rotating and reciprocating compressors. This is consistent with having separate regulations for rotating and reciprocating pumps in both the proposed and promulgated standards.

Section 61.66 of the proposed standard provided for the use of equivalent methods of control which have been approved by EPA. The promulgated standard requires that the plant owner or operator who submits a request for determination of equivalency within 60 days of the promulgation date. This is intended to provide time for EPA to evaluate the method before the plant has to be in compliance. EPA also suggests that this request for determination of equivalency be accompanied by a

request for waiver of compliance until EPA does determine whether the method is equivalent. The request for a waiver of compliance should provide for the case where EPA determines that a method is not equivalent and the plant needs to purchase other equipment. In no case will the waiver of compliance be extended beyond two years from the date of promulgation.

There are several wording clarifications which have been made in the promulgated standard. The definition for "in vinyl chloride service" [§60.61(1)] has been clarified by stating that it means equipment that contacts vinyl chloride as well as equipment that contains vinyl chloride. This would include such equipment as agitators.

Words have been added in §§61.62, 61.63, and 61.64 to clarify that the 10 ppm emission limits do not have to be met when equipment has already been opened in compliance with the regulation for opening of equipment. Equipment that has met the opening of equipment regulation can contain more than 10 ppm vinyl chloride and would be in violation of the standard if this statement were not included.

The requirements for stripping polyvinyl chloride resins to specified levels have been revised in §§61.64(e), 61.67(a)(2)(ii), and 61.70(c)(2) so that measurement of the vinyl chloride levels in the resins is to be made immediately after stripping is completed rather than as the resin is being transferred out of the stripper. This allows a plant to carry out operations in a stripper after stripping has been completed but before it is transferred out of the stripper. This is consistent with the original intent of the standard.

proposed standard takes into consideration that some resins are more difficult to strip than others by providing for averaging among different resins.

(5) Testing, Reporting, and Recordkeeping. There are several relatively minor changes in the testing, reporting, and recordkeeping requirements. A provision has been added to §61.67 which requires that stack gas samples taken with Test Method 106 are to be analyzed within 24 hours. This is consistent with the requirements in the proposed Test Method 106. The promulgated standard also specifies that in averaging the results of the three runs required by Test Method 106, a time-weighted average is to be used.

One commenter requested that the oxygen content and moisture content be specified for the 10 ppm concentration standards. The proposed standard specified that the vinyl chloride concentration is to be corrected to 10 percent oxygen (wet basis) if combustion is used as the control measure. In the promulgated standard, this requirement has been expanded to all control measures.

A provision has been added to the promulgated standard which states that if a reactor is also used as a stripper, the reactor opening emissions may be determined immediately following the stripping operation. If a reactor is also used as a stripper, the resin is in the reactor when it is opened. This means that vinyl chloride in the resin which has already been stripped to acceptable levels can escape from the resin and become part of the reactor opening loss. It is FPA's intent that once a resin has been stripped to the

required levels, that additional controls are not required. Under the new provision, vinyl chloride escaping from the resin after it has been stripped to acceptable levels is not counted as part of the reactor opening loss.

A section requiring continuous monitoring of stack emissions has been added to the promulgated standard. The continuous monitoring of stack emissions was required in the proposed standard. The addition of a specific paragraph for emission monitoring serves only to clarify the requirement.

The standard has been revised so that the initial report requires a "description" rather than a "detailed description" of the equipment used to control fugitive emissions. Several commenters pointed out that a detailed description would contain proprietary information. EPA agrees that a detailed description in the initial report is unnecessary. If additional information is needed, EPA can obtain it under section 114 of the Act and the plant can request that the information be handled confidentially.

The proposed standard required that a semiannual report be submitted every 180 days. The promulgated standard specifies dates for the submittal of the reports. It also specifies that the first semiannual report does not have to be submitted until at least six months after the initial report is submitted.

The standard has been revised to eliminate the requirement to record the cause of any leak detected by the vinyl chloride detector, the action taken to repair the leak, and the amount of time required

to repair the leak. EPA is concerned only that leaks are detected and repaired. That this has been done can be established by looking at the strip chart record of measurements made by the vinyl chloride detector. These records are still required for the portable hydrocarbon detector, however.

Several commenters recommended that the companies be allowed an extra two weeks to submit to EPA data from the initial performance test. They also recommended that they submit the data by regular mail rather than certified mail. EPA has not adopted either of these recommendations. A source is supposed to be in compliance with the standard within 90 days of the promulgation of the standard. The standard requires that the emission tests be done within the 90 day period, and permits an extra 30 days for determination of results. The purpose of using registered mail is to document the fact that emission data have been sent and received. This way if the results are lost in the mail, there will be no question that they were sent.

(6) Test Method. Test Method 106 has been changed to recognize that the acetaldehyde peak on a gas chromatograph interferes with the vinyl chloride peak. When a sample is expected to contain acetaldehyde, mass spectroscopy or another absolute analytical technique is required to be used to confirm the vinyl chloride peak obtained with the gas chromatograph.

In section 5.1.3 of Test Method 106 the requirement to use "oxygen gas" has been replaced with "oxygen gas or air, as required by the detector." Several commenters stated that most gas chromatographs are designed to use hydrogen and air for their

flame detectors. When used in this way, they are capable of detecting 0.5 ppm vinyl chloride in air. This is sensitive enough for monitoring the 10 ppm emission limits stipulated in the standard.

In section 6.4 of Test Method 106 the requirement for an automatic integrator has been replaced with a requirement for a disc integrator for measuring peak area. This change is in response to a comment which states that automatic integrators are unnecessarily elaborate and expensive when peak height, triangulation and disc integrators are sufficiently accurate for this use.

A new section 6.5 has been added to Test Method 106 which requires determination of the water vapor content of the sampling bag by measuring the ambient temperature and pressure near the bag. A provision for checking the rigid container for leaks has been added to section 7.4 of Test Method 106.

The only change in Test Method 107 is the provision in Section 5.3.2 for use of Carbopak C as well as Carbopak A.

AUTHORITY: Section 112 of the Clean Air Act as amended by sec. 4(a) of Pub. L. 91-604, 84 Stat. 1685 (42 U.S.C. 1857c-7; Section 114 of the Clean Air Act, as amended by sec. 4(a) of Pub. L. 91-604, 84 Stat. 1687, and by Pub. L. 93-319, sec. 6(a)(4), 88 Stat. 259 (42 U.S.C. 1857c-9); Section 301(a) of the Clean Air Act, as amended by sec. 15(c)(2) of Pub. L. 91-604, 84 Stat. 1713 (42 U.S.C. 1857g(a)).

Date

Administrator

Part 61 of Chapter I, Title 40 of the Code of Federal Regulations is amended as follows:

1. The table of sections for Part 61 is amended by adding a list of sections for Subpart F as follows:

* * * * *

Subpart F - National Emission Standard for Vinyl Chloride

Sec.

61.60 Applicability.

61.61 Definitions.

61.62 Emission standard for ethylene dichloride plants.

61.63 Emission standard for vinyl chloride plants.

61.64 Emission standard for polyvinyl chloride plants.

61.65 Emission standard for ethylene dichloride, vinyl chloride and polyvinyl chloride plants.

61.66 Equivalent equipment and procedures.

61.67 Emission tests.

61.68 Emission monitoring.

61.69 Initial report.

61.70 Semiannual report.

61.71 Recordkeeping.

2. The authority for Part 61 is revised as follows:

AUTHORITY: Section 112 of the Clean Air Act as amended by sec. 4(a) of Pub. L. 91-604, 84 Stat. 1685 (42 U.S.C. 1857c-7); Section 114 of the Clean Air Act, as amended by sec. 4(a) of Pub. L. 91-604, 84 Stat. 1687, and by Pub. L. 93-319, sec. 6(a)(4), 88 Stat. 259 (42 U.S.C. 1857c-9); Section 301(a) of the Clean Air Act, as amended by sec. 15(c)(2) of Pub. L. 91-604, 84 Stat. 1713 (42 U.S.C. 1857g(a)).

3. Part 61 is amended by adding Subpart F as follows:

Subpart F—National Emission Standard for
Vinyl Chloride

§ 61.60 Applicability.

- ✓ This subpart applies to plants which produce: (a)
- (1) ethylene dichloride by reaction of oxygen and hydrogen chloride with ethylene. (1)
 - (2) vinyl chloride by any process. (2)
 - and/or
 - (3) one or more polymers containing any fraction of polymerized vinyl chloride. (3)

(b) This subpart does not apply to equipment used in research and development if the reactor used to polymerize the vinyl chloride processed in the equipment has a capacity of no more than 0.19 m³ (50 gal) and the product is not sold.

(c) Sections of this subpart other than §§61.64(a)(1), (b), (c), and (d) do not apply to equipment used in research and development if the reactor used to polymerize the vinyl chloride processed in the equipment has a capacity of greater than 0.19 m³ (50 gal) and no more than 4.07 m³ (1100 gal), and the product is not sold.

§ 61.61 Definitions.

Terms used in this subpart are defined in the Act, in subpart A of this part, or in this section as follows:

(a) "Ethylene dichloride plant" includes any plant which produces ethylene dichloride by reaction of oxygen and hydrogen chloride with ethylene.

(b) "Vinyl chloride plant" includes any plant which produces vinyl chloride by any process.

(c) "Polyvinyl chloride plant" includes any plant where vinyl chloride alone or in combination with other materials is polymerized.

(d) "Slip gauge" means a gauge which has a probe that moves through the gas/liquid interface in a storage or transfer vessel and indicates the level of vinyl chloride in the vessel by the physical state of the material the gauge discharges.

(e) "Type of resin" means the broad classification of resin referring to the basic manufacturing process for producing that resin, including, but not limited to, the suspension, dispersion, latex, bulk, and solution processes.

(f) "Grade of resin" means the subdivision of resin classification which describes it as a unique resin, i.e., the most exact description of a resin with no further subdivision.

(g) "Dispersion resin" means a resin manufactured in such a way as to form fluid dispersions when dispersed in a plasticizer or plasticizer/diluent mixtures.

(h) "Latex resin" means a resin which is produced by a polymerization process which initiates from free radical catalyst sites and is sold undried.

(i) "Bulk resin" means a resin which is produced by a polymerization process in which no water is used.

(j) "Inprocess wastewater" means any water which, during manufacturing or processing, comes into direct contact with vinyl chloride or polyvinyl chloride or results from the production or use of any raw material, intermediate product, finished product, by-product, or waste product containing vinyl chloride or polyvinyl chloride but which has not been discharged to a wastewater treatment process or discharged untreated as wastewater.

(k) "Wastewater treatment process" includes any process which modifies characteristics such as BOD, COD, TSS, and pH, usually for the purpose of meeting effluent guidelines and standards; it does not include any process the purpose of which is to remove vinyl chloride from water to meet requirements of this subpart.

(l) "In vinyl chloride service" means that a piece of equipment contains either a liquid that is at least 10 percent by weight vinyl chloride or a gas that is at least 10 percent by volume vinyl chloride.

or contacts

(m) "Vinyl chloride detector" means a device which obtains air samples from one or more points on a continuous sequential basis and analyzes the samples with gas chromatography or, if the owner or operator assumes that all hydrocarbons measured are vinyl chloride, with infrared spectrophotometry, flame ion detection, or an equivalent or alternative method.

monitoring system"

(n) "Portable hydrocarbon detector" means a device which measures hydrocarbons with a sensitivity of at least 5 ppm and is of such design and size that it can be used to measure emissions from localized points.

delete

(o) "Standard operating procedure" means a formal written procedure officially adopted by the plant owner or operator and available on a routine basis to those persons responsible for carrying out the procedure.

(p) "Run" means the net period of time during which an emission sample is collected.

(q) "Ethylene dichloride purification" includes any part of the process of ethylene dichloride production which follows ethylene dichloride formation and in which finished ethylene dichloride is produced.

(r) "Vinyl chloride purification" includes any part of the process of vinyl chloride production which follows vinyl chloride formation and in which finished vinyl chloride is produced.

(s) "Reactor" includes any vessel in which vinyl chloride is partially or totally polymerized into polyvinyl chloride.

(t) "Reactor opening loss" means the emissions of vinyl chloride occurring when a reactor is vented to the atmosphere for any purpose other than an emergency relief discharge as defined in § 61.65(a).

(u) "Stripper" includes any vessel in which residual vinyl chloride is removed from polyvinyl chloride resin, except bulk resin, in the slurry form by the use of heat and/or vacuum. In the case of bulk resin, stripper includes any vessel which is used to remove residual vinyl chloride from polyvinyl chloride resin immediately following the polymerization step in the plant process flow.

§ 61.62 Emission standard for ethylene dichloride plants.

An owner or operator of an ethylene dichloride plant shall comply with the requirements of this section and § 61.65.

(a) Ethylene dichloride purification: The concentration of vinyl chloride in

all exhaust gases discharged to the atmosphere from any equipment used in ethylene dichloride purification is not to exceed 10 ppm, except as provided in § 61.65(a). This requirement does not apply to equipment that ~~is opened and meets the requirement in § 61.65(b) (6)~~ (1).

has been opened, is out of operation, and met before being opened.

(b) Oxychlorination reactor: Except as provided in § 61.65(a), emissions of vinyl chloride to the atmosphere from each oxychlorination reactor are not to exceed ~~0.2 g/kg (0.002 lb/100 lb)~~ of the 100 percent ethylene dichloride product from the oxychlorination process.

0.2 g/kg (0.002 lb/100 lb)

§ 61.63 Emission standard for vinyl chloride plants.

An owner or operator of a vinyl chloride plant shall comply with the requirements of this section and § 61.65.

(a) Vinyl chloride formation and purification: The concentration of vinyl chloride in all exhaust gases discharged to the atmosphere from any equipment used in vinyl chloride formation and/or purification is not to exceed 10 ppm, except as provided in § 61.65(a). This requirement does not apply to equipment that ~~is opened and meets the requirement in § 61.65(b) (6) (1)~~.

has been opened, is out of operation, and met before being opened.

§ 61.64 Emission standard for polyvinyl chloride plants.

An owner or operator of a polyvinyl chloride plant shall comply with the requirements of this section and § 61.65.

(a) Reactor: The following requirements apply to reactors:

(1) The concentration of vinyl chloride in all exhaust gases discharged to the atmosphere from each reactor is not to exceed 10 ppm, except as provided in paragraph (a) (2) of this section and § 61.65(a).

(2) The reactor opening loss from each reactor is not to exceed ~~0.2 g/kg (0.002 lb/100 lb)~~ of polyvinyl chloride product, with the product determined on a dry solids basis. This requirement applies to any vessel which is used as a reactor or as both a reactor and a stripper. In the bulk process, the product means the gross product of prepolymerization and postpolymerization.

0.2 g/kg vinyl chloride/kg

(0.0002 lb vinyl chloride/lb)

(3) Manual vent valve discharge: Except for an emergency manual vent valve discharge, there is to be no discharge to the atmosphere from any manual vent valve or any reactor in vinyl chloride service. An emergency manual vent valve discharge means a discharge to the atmosphere which could not have been avoided by taking measures to prevent the discharge. Within 10 days of any discharge to the atmosphere from any manual vent valve, the owner or operator of the source from which the discharge occurs shall submit to the Administrator a report in writing containing information on the source, nature and cause of the discharge, the date and time of the discharge, the approximate total vinyl chloride loss during the discharge, the method used for determining the vinyl chloride loss, the action that was taken to prevent the discharge, and measures adopted to prevent future discharges.

(b) Stripper: The concentration of vinyl chloride in all exhaust gases discharged to the atmosphere from each stripper is not to exceed 10 ppm, except as provided in § 61.65(a). This requirement does not apply to equipment that ~~is opened and meets the requirement in § 61.65(b)(6)(i)~~

has been opened, is out of operation, and met before being opened.

(c) Mixing, weighing, and holding containers: The concentration of vinyl chloride in all exhaust gases discharged to the atmosphere from each mixing, weighing, or holding container in vinyl chloride service which precedes the stripper (or the reactor if the plant has no stripper) in the plant process flow is not to exceed 10 ppm, except as provided in § 61.65(a). This requirement does not apply to equipment that ~~is opened and meets the requirement in § 61.65(b)(6)(i)~~

has been opened, is out of operation, and met before being opened.

(d) Monomer recovery system. The concentration of vinyl chloride in all exhaust gases discharged to the atmosphere from each monomer recovery system is not to exceed 10 ppm, except as provided in § 61.65(a). This requirement does not apply to equipment that ~~is opened and meets the requirement in § 61.65(b)(6)(i)~~

has been opened, is out of operation, and met before being opened.

(e) Sources following the stripper(s): The following requirements apply to emissions of vinyl chloride to the atmosphere from the combination of all sources following the stripper(s) [or the reactor(s) if the plant has no stripper(s)] in the plant process flow, including but not limited to, centrifuges, concentrators, blend tanks, filters, dryers, conveyor air discharges, baggers, storage containers, and inprocess wastewater:

(1) In polyvinyl chloride plants using stripping technology to control vinyl chloride emissions, the weighted average residual vinyl chloride concentration in all grades of polyvinyl chloride resin processed through the stripping operation on each calendar day, measured ~~as the resin leaves the stripper~~, may not exceed:

immediately after the stripping operation is completed, chloride

(i) 2000 ppm for polyvinyl dispersion resins, excluding latex resins;

(ii) 400 ppm for all other polyvinyl chloride resins, including latex resins, averaged separately for each type of resin; or

(2) In polyvinyl chloride plants controlling vinyl chloride emissions with technology other than stripping or in addition to stripping, emissions of vinyl chloride to the atmosphere may not exceed:

(i) ~~0.20 kg/100 kg (0.20 lb/100 lb)~~ 2 g/kg (0.002 lb/lb) product from the stripper(s) [or reactor(s) if the plant has no stripper(s)] for dispersion polyvinyl chloride resins, excluding latex resins, with the product determined on a dry solids basis;

(1) ~~0.004 g/kg (0.0004 lb/lb)~~ 0.4 g/kg (0.0004 lb/lb)
product from the strippers for reactor(s) if the plant has no stripper(s); for all other polyvinyl chloride resins, including latex resins, with the product determined on a dry solids basis.

§ 61.65 Emission standard for ethylene dichloride, vinyl chloride and polyvinyl chloride plants.

An owner or operator of an ethylene dichloride, vinyl chloride, and/or polyvinyl chloride plant shall comply with the requirements of this section.

(a) Relief valve discharge: Except for an emergency relief discharge, there is to be no discharge to the atmosphere from any relief valve on any equipment in vinyl chloride service. An emergency relief discharge means a discharge which could not have been avoided by taking ~~reasonable~~ measures to prevent the discharge. Within 10 days of any relief valve discharge, the owner or operator of the source from which the relief valve discharge occurs shall submit to the Administrator a report in writing containing information on the source, nature and cause of the discharge, the date and time of the discharge, the approximate total vinyl chloride loss during the discharge, the method used for determining the vinyl chloride loss, ~~the action that~~ was taken to prevent the discharge, and measures adopted to prevent future discharges.

(b) Fugitive emission sources:

(1) Loading and unloading lines: Vinyl chloride emissions from loading and unloading lines ~~are to be minimized as follows:~~ which are opened to the atmosphere after each loading or unloading operation

(i) After each loading or unloading operation and before opening a loading or unloading line to the atmosphere, the quantity of vinyl chloride in all parts of each loading or unloading line that are to be opened to the atmosphere is to be reduced so that the parts combined contain no greater than ~~0.0038 m³ (0.13 ft³)~~ of vinyl chloride, ~~at standard temperature and pressure, and~~ at

(ii) Any vinyl chloride removed from a loading or unloading line in accordance with paragraph (b)(1)(i) of this section is to be ducted through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm, or equivalent as provided in § 61.66.

(2) Slip gauges: During loading or unloading operations, the vinyl chloride emissions from each slip gauge in vinyl chloride service are to be minimized by ducting any vinyl chloride discharged from the slip gauge through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm, or equivalent as provided in § 61.66.

(3) Leakage from pump, compressor, and agitator seals:

(i) Rotating pumps: Vinyl chloride emissions from seals on all rotating pumps in vinyl chloride service are to be minimized by installing sealless pumps, pumps with double mechanical seals, or equivalent as provided in § 61.66. If double mechanical seals are used, vinyl chloride emissions from the seals are to be minimized by maintaining the pres-

sure between the two seals so that any leak that occurs is into the pump; by ducting any vinyl chloride between the two seals through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm; or equivalent as provided in § 61.66.

(ii) Reciprocating pumps: Vinyl chloride emissions from seals on all reciprocating pumps in vinyl chloride service are to be minimized by installing double outboard seals, or equivalent as provided in § 61.66. If double outboard seals are used, vinyl chloride emissions from the seals are to be minimized by maintaining the pressure between the two seals so that any leak that occurs is into the pump; by ducting any vinyl chloride between the two seals through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm; or equivalent as provided in § 61.66.

Rotating

(iii) Compressor: Vinyl chloride emissions from seals on all compressors in vinyl chloride service are to be minimized by installing compressors with double mechanical seals, or equivalent as provided in § 61.66. If double mechanical seals are used, vinyl chloride emissions from the seals are to be minimized by maintaining the pressure between the two seals so that any leak that occurs is into the ~~compressor~~ by ducting any vinyl chloride between the two seals through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm; or equivalent as provided in § 61.66.

compressor

(iv) Reciprocating Compressors: Vinyl chloride emissions from seals on all reciprocating compressors in vinyl chloride service are to be minimized by installing double outboard seals, or equivalent as provided in § 61.66. If double outboard seals are used, vinyl chloride emissions from the seals are to be minimized by maintaining the pressure between the two seals so that any leak that occurs is into the compressor; by ducting any vinyl chloride between the two seals through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm; or equivalent as provided in § 61.66.

(v) Agitator: Vinyl chloride emissions from seals on all agitators in vinyl chloride service are to be minimized by installing agitators with double mechanical seals, or equivalent as provided in § 61.66. If double mechanical seals are used, vinyl chloride emissions from the seals are to be minimized by maintaining the pressure between the two seals so that any leak that occurs is into the ~~agitator~~ by ducting any vinyl chloride between the two seals through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm; or equivalent as provided in § 61.66.

(v)

— agitated vessel;

(vi) Leakage from relief valves: Vinyl chloride emissions due to leakage from each relief valve on equipment in vinyl chloride service are to be minimized by installing a rupture disk between the equipment and the relief valve, or equivalent as provided in § 61.66.

—, by connecting the relief valve discharge to a process line or recovery system,

(vii) Manual venting of gas: All gases which are manually vented from equipment in vinyl chloride service are to be ducted through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm; or equivalent as provided in § 61.66.

Except as provided in § 61.64(a)(3), all

(6) Opening of equipment: Vinyl chloride emissions from opening of equipment are to be minimized as follows:

(i) Before opening any equipment for any reason, the quantity of vinyl chloride is to be reduced so that the equipment contains no more than 2.0 percent by volume vinyl chloride or ~~25~~ (25 gal) of vinyl chloride, whichever is larger, at standard temperature and pressure; and

(ii) Any vinyl chloride removed from the equipment in accordance with paragraph (b)(6)(i) of this section is to be ducted through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm, or equivalent as provided in § 61.66.

~~(7) Sample leak: There are to be no vinyl chloride emissions to the atmosphere due to the vinyl chloride lost in any sample leak after an analysis is made or due to the vinyl chloride passed through any leak during sampling in order to obtain a representative sample.~~

(8) Leak detection and elimination: Vinyl chloride emissions due to leaks from equipment in vinyl chloride service are to be minimized by instituting and implementing a formal leak detection and elimination program. The owner or operator shall submit a description of the program to the Administrator for approval. The program is to be submitted within 45 days of the effective date of these regulations, unless a waiver of compliance is granted under § 61.11.

If a waiver of compliance is granted, the program is to be submitted on a date scheduled by the Administrator. Approval of a program will be granted by the Administrator provided he finds:

(i) It includes a reliable and accurate vinyl chloride detector for detection of major leaks and identification of the general area of the plant where a leak is located.

(ii) It includes a reliable and accurate portable hydrocarbon detector to be used routinely to find small leaks and to pinpoint the major leaks indicated by the vinyl chloride detector.

(iii) It provides for an acceptable calibration and maintenance schedule for the vinyl chloride detector and portable hydrocarbon detector.

(iv) The location and number of points to be monitored and the frequency of monitoring provided for in the program are acceptable when they are compared with the number of pieces of equipment in vinyl chloride service and the size and general layout of the plant.

(v) It contains an acceptable plan of action to be taken when a leak is detected, and

(vi) It contains a definition of leak which is acceptable when compared with the background concentrations of vinyl chloride in the areas of the plant to be monitored by the vinyl chloride detector. Measurements of background concentrations of vinyl chloride in the areas of

(including loading or unloading lines that are not opened to the atmosphere after each loading or unloading operation)

0.0950 m³

Samples: Unused portions of samples containing at least 10 percent by weight vinyl chloride are to be returned to the process, and sampling techniques are to be such that sample containers in vinyl chloride service are purged into a closed process system.

monitoring system

monitoring system

monitoring system

monitoring system

The portable hydrocarbon detector is to measure hydrocarbons with a sensitivity of at least 10 ppm.

the plant to be monitored by the vinyl chloride ~~detector~~ are to be included with the description of the program. The definition of leak for a given plant may vary among the different areas within the plant and is also to change over time as background concentrations in the plant are reduced.

(9) Inprocess wastewater: Vinyl chloride emissions to the atmosphere from inprocess wastewater are to be reduced as follows:

(i) The concentration of vinyl chloride in each inprocess wastewater stream, immediately as it leaves a piece of equipment and before being mixed with any other inprocess wastewater stream is to be reduced ~~to 10 ppm by weight before~~ being exposed to the atmosphere; ~~or before~~ being discharged to a wastewater treatment process; or discharged untreated as a wastewater. This paragraph does apply to water which is used to displace vinyl chloride from equipment before it is opened to the atmosphere in accordance with § 61.64(a)(2) or paragraph (b)(6) of this section, but does not apply to water which is used to wash out equipment after the equipment has already been opened to the atmosphere in accordance with § 61.64(a)(2) or paragraph (b)(6) of this section.

(ii) Any vinyl chloride removed from the inprocess wastewater in accordance with paragraph (b)(9)(i) of this section is to be ducted through a control system from which the concentration of vinyl chloride in the exhaust gases does not exceed 10 ppm, or equivalent as provided in § 61.66.

(c) The requirements in paragraphs (b)(1), (b)(2), (b)(5), (b)(6), (b)(7) and (b)(8) of this section are to be incorporated into a standard operating procedure, and made available upon request for inspection by the Administrator. The standard operating procedure is to include provisions for measuring the vinyl chloride in equipment ~~≥ 4.75 m³~~ (1250 gal) in volume for which an emission limit is prescribed in § 61.65(b)(6) (i) prior to opening the equipment and using Test Method 106, a portable hydrocarbon detector, or an equivalent or alternative method. The method of measurement is to meet the requirements in § 61.67(g)(5)(i)(A) or (g)(5)(i)(B).

§ 61.66 Equivalent equipment and procedure.

Upon written application from an owner or operator, the Administrator may approve use of equipment or procedures which have been demonstrated to his satisfaction to be equivalent in terms of reducing vinyl chloride emissions to the atmosphere to those prescribed for compliance with a specific paragraph of this subpart.

§ 61.67 Emission tests.

(a) Unless a waiver of emission testing is obtained under § 61.13, the owner or operator of a source to which this subpart applies shall test emissions from the source.

— monitoring system

— containing greater than 10 ppm vinyl chloride measured

to no more than

before being mixed with any other inprocess wastewater stream which contains less than 10ppm vinyl chloride;

4.75 m³

Requests for using equivalent methods as the initial measure of control are to be submitted to the Administrator within 60 days of the effective date.

(1) Within 90 days of the effective date in the case of an existing source or a new source which has an initial startup date preceding the effective date, or

(2) Within 90 days of startup in the case of a new source, initial startup of which occurs after the effective date.

(b) The owner or operator shall provide the Administrator at least 30 days prior notice of an emission test to afford the Administrator the opportunity to have an observer present during the test.

(c) Any emission test is to be conducted while the equipment being tested is operating at the maximum production rate at which the equipment will be operated and under other relevant conditions as may be specified by the Administrator based on representative performance of the source.

(d) Each emission test is to consist of three runs. For the purpose of determining emissions, the average of results of all runs is to apply.

(e) All samples are to be analyzed, and vinyl chloride emissions are to be determined within 30 days after the emission test. The owner or operator shall report the determinations to the Administrator by a registered letter dispatched before the close of the next business day following the determination.

(f) The owner or operator shall retain at the plant and make available, upon request, for inspection by the Administrator, for a minimum of 2 years records of emission test results and other data needed to determine emissions.

(g) Unless otherwise specified, the owner or operator shall use test methods in Appendix B to this part for each test as required by paragraphs (g)(1), (g)(2), (g)(3), (g)(4), and (g)(5) of this section, unless an equivalent method or an alternative method has been approved by the Administrator. If the Administrator finds reasonable grounds to dispute the results obtained by an equivalent or alternative method, he may require the use of a reference method. If the results of the reference and equivalent or alternative methods do not agree, the results obtained by the reference method prevail, and the Administrator may notify the owner or operator that approval of the method previously considered to be equivalent or alternative is withdrawn.

(1) Test Method 106 is to be used to determine the vinyl chloride emissions from any source for which an emission limit is prescribed in §§ 61.62(a) or (b) § 61.63(a), or §§ 61.64(a)(1), (b), (c), or (d), or from any control system to which reactor emissions are required to be ducted in § 61.64(a)(2) or to which fugitive emissions are required to be ducted in §§ 61.65(b)(1)(ii), (b)(2), (b)(5), (b)(6)(ii), or (b)(9)(ii).

(i) For each run, one sample is to be collected. The sampling site is to be at least two stack or duct diameters down-

The average is to be computed on a time weighted basis.

within 24 hours,

stream and one half diameter upstream from any flow disturbance such as a bend, expansion, contraction, or visible flame. For a rectangular cross section an equivalent diameter is to be determined from the following equation:

$$\text{equivalent diameter} = 2 \frac{(\text{length})(\text{width})}{\text{length} + \text{width}}$$

The sampling point in the duct is to be at the centroid of the cross section. The sample is to be extracted at a rate proportional to the gas velocity at the sampling point. The sample is to be taken over a minimum of one hour, and is to contain a minimum volume of 50 liters corrected to standard conditions.

(II) ~~For those emission sources where combustion is used to reduce vinyl chloride emissions, the concentration of vinyl chloride as determined by Test Method 106 is to be corrected to 10 percent oxygen ~~emissions~~ for determination of emissions by using the following equation:~~ delete

$$C_v(\text{corrected}) = C_v \frac{10.9}{20.9 - \text{percent } O_2}$$

where

$C_v(\text{corrected})$ = The concentration of vinyl chloride in the exhaust gases, corrected to 10 percent oxygen.

C_v = The concentration of vinyl chloride as measured by Test Method 106.

20.9 = Percent oxygen in the ambient air at standard conditions.

10.9 = Percent oxygen in the ambient air at standard conditions, minus the 10 percent oxygen to which the correction is being made.

Percent O_2 = Percent oxygen in the exhaust gas as measured by Reference Method 8 in Appendix A of Part 60 of this chapter.

(III) For those emission sources where the emission limit is prescribed in terms of mass rather than concentration, mass emissions in kg/100 kg product are to be determined by using the following equation:

$$C_{\text{em}} = \frac{C_v (2.60) Q (10^{-6}) (100)}{Z}$$

where

C_{em} = kg vinyl chloride/100 kg product

C_v = The concentration of vinyl chloride as measured by Test Method 106.

2.60 = Density of vinyl chloride at one atmosphere and 20°C in kg/m³.

Q = Volumetric flow rate in m³/hr as determined by Reference Method 2 of Appendix A, to Part 60 of this chapter.

10⁻⁶ = Conversion factor for ppm.

Z = Production rate (kg/hr).

(2) Test Method 107 is to be used to determine the concentration of vinyl chloride in each inprocess wastewater stream for which an emission limit is prescribed in § 61.65(b) (9) (i).

(3) Where a stripping operation is used to attain the emission limit in § 61.64(e), emissions are to be determined using Test Method 107 as follows:

(i) The number of strippers and samples and the types and grades of resin to be sampled are to be determined by the Administrator for each individual plant at the time of the test based on the plant's operation.

(ii) Each sample is to be taken immediately following the stripping operation, ~~as the resin is transferred out of the stripper~~ delete

(iii) The corresponding quantity of material processed by each stripper is to be determined on a dry solids basis and by a method submitted to and approved by the Administrator.

(iv) At the prior request of the Administrator, the owner or operator shall provide duplicates of the samples required in paragraph (g)(3)(i) of this section.

(4) Where control technology other than or in addition to a stripping operation is used to attain the emission limit in § 61.64(e), emissions are to be determined as follows:

(i) Test Method 106 is to be used to determine atmospheric emissions from all of the process equipment simultaneously. The requirements of paragraph (g)(1) of this section are to be met.

(ii) Test Method 107 is to be used to determine the concentration of vinyl chloride in each inprocess wastewater stream subject to the emission limit prescribed in § 61.64(e). The mass of vinyl chloride in kg/100 kg product in each in process wastewater stream is to be determined by using the following equation:

$$C_{\text{W}} = \frac{[C_d R 10^{-6}] (100)}{Z}$$

where

C_{W} = kg vinyl chloride/100 kg product

C_d = the concentration of vinyl chloride as measured by Test Method 107.

R = water flow rate in l/hr, determined in accordance with a method which has been submitted to and approved by the Administrator.

10^{-6} = Conversion factor for ppm.

Z = Production rate (kg/hr), determined in accordance with a method which has been submitted and approved by the Administrator.

(5) The reactor opening loss for which an emission limit is prescribed in § 61.64 (a)(2) is to be determined. The number of reactors for which the determination is to be made is to be specified by the Administrator for each individual plant at the time of the determination based on the plant's operation.

(i) Except as provided in paragraph (g)(5)(ii) of this section, the reactor opening loss is to be determined using the following equation:

$$C = \frac{W (2.60) (10^{-6}) (Cb)}{YZ}$$

where

C = kg vinyl chloride emissions/kg product.

W = Capacity of the reactor in m³.

2.60 = Density of vinyl chloride at one atmosphere and 20° C in kg/m³.

10^{-6} = Conversion factor for ppm.

C_b = ppm by volume vinyl chloride as determined by Test Method 106 or a portable hydrocarbon detector.

Y = Number of batches since the reactor was last opened to the atmosphere.

Z = Average kg of polyvinyl chloride produced per batch in the number of batches since the reactor was last opened to the atmosphere.

(A) If Method 106 is used to determine the concentration of vinyl chloride (C_b), the sample is to be withdrawn at a constant rate with a probe of sufficient length to reach the vessel bottom from the manhole. Samples are to be taken for 5 minutes within 6 inches of the vessel bottom, 5 minutes near the vessel center, and 5 minutes near the vessel top.

(B) If a portable hydrocarbon detector is used to determine the concentration of vinyl chloride (C_b), a probe of sufficient length to reach the vessel bottom from the manhole is to be used to make the measurements. One measurement will be made within 6 inches of the vessel bottom, one near the vessel center and one near the vessel top. Measurements are to be made at each location until the reading is stabilized. All hydrocarbons measured are to be assumed to be vinyl chloride.

For a reactor that is also used as a stripper, the determination may be made immediately following the stripping operation.

which measures hydrocarbons with a sensitivity of at least 10 ppm.

(C) The production rate of polyvinyl chloride (Z) is to be determined by a method submitted to and approved by the Administrator.

(d) A calculation based on the number of evacuations, the vacuum involved, and the volume of gas in the reactor is hereby approved by the Administrator as an alternative method for determining reactor opening loss for postpolymerization reactors in the manufacture of bulk resins.

§61.68 Emission monitoring.

(a) The vinyl chloride monitoring system required in §61.65(b)(8)(i), or equivalent as to be used to monitor on a continuous basis the emissions from these sources for which emission limits are prescribed in §61.62(a) and (b), §61.63(a), and §61.64(a)(1)(b), (c), and (d), and for any control system to which reactor emissions are required to be ducted in §61.64(a)(2) or to which fugitive emissions are required to be ducted in §61.65(b)(1)(ii), and (b)(2), (b)(5), (b)(6)(ii), and (b)(9)(ii).

§61.69 Initial report.

9

(a) An owner or operator of any source to which this subpart applies shall submit a statement in writing notifying the Administrator that the equipment and procedural specifications in §§ 61.65 (b) (1), (b) (2), (b) (3), (b) (4), (b) (5), (b) (6), (b) (7), and (b) (8) are being implemented.

(b)(1) In the case of an existing source or a new source which has an initial startup date preceding the effective date, the statement is to be submitted within 90 days of the effective date, unless a waiver of compliance is granted under § 61.11, along with the information required under § 61.10. If a waiver of compliance is granted, the statement is to be submitted on a date scheduled by the Administrator.

(2) In the case of a new source which did not have an initial startup date preceding the effective date, the statement is to be submitted within 90 days of the initial startup date.

(c) The statement is to contain the following information:

(1) A list of the equipment installed for compliance,

(2) A ~~detailed engineering description~~ of the physical and functional characteristics of each piece of equipment,

(3) A description of the methods which have been incorporated into the standard operating procedures for measuring or calculating the emissions for which emission limits are prescribed in §§ 61.65 (b) (1) (i) and (b) (6) (i),

(4) A statement that each piece of equipment is installed and that each piece of equipment and each procedure is being used.

delete

§ 61.69 Semiannual report.

70

(a) The owner or operator of any source to which this subpart applies shall submit to the Administrator on a ~~semi-annual basis each 180 days~~ a report in writing containing the information required by this section.

September 15 and March 15 of each year

(b)(1) In the case of an existing source or a new source which has an initial startup date preceding the effective date, the first report is to be submitted within 180 days of the effective date, unless a waiver of compliance is granted under § 61.11. If a waiver of compliance is granted, the first report is to be submitted on a date scheduled by the Administrator.

The first semi-annual report is to be submitted following the first full 6 month reporting period after the initial report is submitted.

(2) In the case of a new source which did not have an initial startup date preceding the effective date, the first report to be submitted within 180 days of the initial startup date.

(c) Unless otherwise specified, the owner or operator shall use the Test Methods in Appendix B to this part to conduct emission tests as required by paragraphs (c)(2) and (c)(3) of this section, unless an equivalent or an alternative method has been approved by the Administrator. If the Administrator finds reasonable grounds to dispute the results obtained by an equivalent or alternative method, he may require the use of a reference method. If the results of the reference and equivalent or alternative methods do not agree, the results obtained by the reference method prevail, and the Administrator may notify the owner or operator that approval of the method previously considered to be equivalent or alternative is withdrawn.

(1) The owner or operator shall include in the report a record of any emissions in excess of the emission limits prescribed in §§ 61.62(a) or (b), § 61.63(a), or § 61.64(a)(1), (b), (c), or (d), or for any control system to which reactor emissions are required to be ducted in § 61.64(a)(2) or to which fugitive emissions are required to be ducted in § 61.65(b)(1)(II), (b)(2), (b)(3), (b)(6)(II), or (b)(9)(II). The emissions are to be measured with a vinyl chloride detector.

(2) ~~The owner or operator shall include in the report a record of the quantity of emissions of vinyl chloride from the sources following the stripper(s) for the reactor(s). If the plant has no stripper(s) in polyvinyl chloride plants for which a stripping operation is used to attain the emission limit prescribed in § 61.64(e), Test Method 107 is to be used to determine emissions as follows:~~

(i) If batch stripping is used, one representative sample of polyvinyl chloride resin is to be taken from each batch of each grade of resin immediately following the completion of the stripping operation ~~as the resin is transferred out of the stripper~~, and identified by resin type and grade and the date and time the batch is completed. The corresponding quantity of material processed in each stripper batch is to be recorded and identified by resin type and grade and the date and time the batch is completed.

(ii) If continuous stripping is used, one representative sample of polyvinyl chloride resin is to be taken for each grade of resin processed or at intervals of 8 hours for each grade of resin which is being processed, whichever is more frequent. The sample is to be taken as the resin flows out of the stripper and identified by resin type and grade and the date and time the sample was taken. The corresponding quantity of material processed by each stripper over the time period represented by the sample during the eight hour period, is to be recorded and identified by resin type and grade and the date and time it represents.

(iii) The quantity of material processed by the stripper is to be determined on a dry solids basis and by a method submitted to and approved by the Administrator.

(iv) At the prior request of the Administrator, the owner or operator shall provide duplicates of the samples required in paragraphs (c)(2)(i) and (c)(2)(ii) of this section.

in accordance with §61.68.

In polyvinyl chloride plants for which a stripping operation is used to attain the emission level prescribed in §61.64(e),

content in the polyvinyl chloride resin.

vinyl chloride content

(v) The report to the Administrator by the owner or operator is to include the vinyl chloride content found in all the samples required in paragraphs (c) (2) (i) and (c) (2) (ii) of this section, averaged separately for each type of resin, over each calendar day and weighted according to the quantity of each grade of resin processed by the stripper(s) that calendar day, according to the following equation:

$$A_T = \frac{\sum_{i=1}^n P_i M_i}{Q_T} = \frac{P_1 M_1 + P_2 M_2 + \dots + P_n M_n}{Q_T}$$

A = 24-hour average concentration of type T, resin in ppm.
Q = Total production of type T, resin over the 24-hour period, in kg.
T_j = Type of resin, j = 1, 2, ..., n where n is total number of resin types produced during the 24-hour period.
M = Concentration of vinyl chloride in one sample of grade G, resin, in ppm.
P = Production of grade G_j resin represented by the sample, in kg.
G_j = Grade of resin, e.g., G₁, G₂, and G_n.
n = Total number of grades of resin produced during the 24-hour period.

(vi) The owner or operator shall retain at the source and make available for inspection by the Administrator for a minimum of 2 years records of all data needed to furnish the information required by paragraph (c) (2) (v) of this section. The records are to contain the following information:

(A) The vinyl chloride content found in all the samples required in paragraphs (c) (2) (i) and (c) (2) (ii) of this section, identified by the resin type and grade and the time and date of the sample, and

(B) The corresponding quantity of polyvinyl chloride resin processed by the stripper(s), identified by the resin type and grade and the time and date it represents.

(3) The owner or operator shall include in the report a record of the emissions from each reactor opening for which an emission limit is prescribed in § 61.64(a) (2). Emissions are to be determined in accordance with § 61.67(g) (5), except that emissions for each reactor are to be determined.

§ 61.7 Recordkeeping.

(a) The owner or operator of any source to which this subpart applies shall retain the following information at the source and make it available for inspection by the Administrator for a minimum of two years:

(1) A record of the leaks detected by the vinyl chloride detector and the action taken to repair the leaks, as required by § 61.65(b) (8), including the following information:

The concentrations of vinyl chloride as measured, analyzed, and recorded by the vinyl chloride detector, including the location of each measurement and the date and approximate time of each measurement.

For a reactor that is also used as a stripper, the determination may be made immediately following the stripping operation.

1
monitoring system

delete

measured in accordance with §61.68.

(3) A record of emissions from any source for which an emission limit is prescribed in 11.61.6(a), (b), 11.62 (a), or 11.61.61(a), (1), (2), (c), or (d), or from any control system to which reactor emissions are required to be ducted in 11.61.62(a), (b) or to which fugitive emissions are required to be ducted in 11.61.65(b), (1), (2), (b)(1), (b)(2), (b)(3), (b)(4), or (c), (d), (e).

(4) For the relief discharges from reactors subject to the provisions of § 61.85 (b), a daily operating record for each reactor, including pressures and temperatures.

4. Appendix E is amended by adding Test Methods 106 and 107 as follows:

METHOD 106--DETERMINATION OF VINYL CHLORIDE FROM STATIONARY SOURCES

INTRODUCTION

Performance of this method should not be attempted by persons unfamiliar with the operation of a gas chromatograph, nor by those who are unfamiliar with source sampling, as there are many details that are beyond the scope of this presentation. Care must be exercised to prevent exposure of sampling personnel to vinyl chloride, a carcinogen.

1. Principle and Applicability.

1.1 An integrated bag sample of stack gas containing vinyl chloride (chloroethylene) is subjected to chromatographic analysis, using a flame ionization detector.

1.2 The method is applicable to the measurement of vinyl chloride in stack gases from both vinyl chloride and polyvinyl chloride manufacturing processes, except where the vinyl chloride is contained in particulate matter.

2 Range and Sensitivity

The lower limit of detection will vary according to the chromatograph used. Values reported include 1×10^{-10} mg and 4×10^{-10} mg.

3. Interferences

is the course of a test to identify the interference potential of recent hydrocarbons associated with vinyl chloride. Some were found to prevent resolution of the vinyl chloride peak with the Chromosorb 102 Column However, if resolution of the vinyl chloride peak is not satisfactory for a particular sample, then chromatograph parameters may be altered with prior approval of the Administrator. It is reasonable to believe that some ~~hydrocarbons~~ with an identical retention time is present in the sample, then repetition of confirmation of the vinyl chloride peak through an absolute analytical technique such as mass spectrometry, should be performed.

2. The only compound which is known to co-elute with vinyl chloride is acetaldehyde.

acetaldehyde or

-- compound

~~—~~must.

• Mention of trade names on specific products does not constitute endorsement by the Environmental Protection Agency.

4. Apparatus.
 - 4.1. Sampling (Figure 1).
 - 4.1.1. Probe—Stainless steel, Pyrex glass, or Teflon tubing according to stack temperature, each equipped with a glass wool plug to remove particulate matter.
 - 4.1.2. Sample line—Teflon, 6.4 mm outside diameter, of sufficient length to connect probe to bag. A new unused piece is employed for each series of bag samples that constitutes an emission test.
 - 4.1.3. Male (2) and female (2) stainless steel quick-connects, with ball checks (one pair without) located as shown in Figure 1.
 - 4.1.4. Tedlar bags, 100 liter capacity—To contain sample.
 - 4.1.5. Rigid leakproof containers for 4.1.4, with covering to protect contents from sunlight.
 - 4.1.6. Needle valve—To adjust sample flow rate.
 - 4.1.7. Pump—Leak-free. Minimum capacity 2 liters per minute.
 - 4.1.8. Charcoal tube—To prevent admission of vinyl chloride to atmosphere in vicinity of samplers.
 - 4.1.9. Flow meter—For observing sample flow rate; capable of measuring a flow range from 0.10 to 1.00 liter per minute.
 - 4.1.10. Connecting tubing—Teflon, 6.4 mm outside diameter, to assemble sample train (Figure 1).
 - 4.1.11. Pitot tube—Type B (or equivalent), attached to the probe so that the sampling flow rate can be regulated proportional to the stack gas velocity.
 - 4.2. Sample recovery.
 - 4.2.1. Tubing—Teflon, 6.4 mm outside diameter, to connect bag to gas chromatograph sample loop. A new unused piece is employed for each series of bag samples that constitutes an emission test, and is to be discarded upon conclusion of analysis of those bags.
 - 4.3. Analysis.
 - 4.3.1. Gas chromatograph—With flame ionization detector, potentiometric strip chart recorder and 1.0 to 5.0 ml heated sampling loop in automatic sample valve.
 - 4.3.2. Chromatographic column—Stainless steel, 2.5 m x 3.2 mm, containing 80/100 mesh Chromosorb 102.
 - 4.3.3. Flow meters (2)—Rotameter type, 0 to 100 ml/min capacity, with flow control valves.
 - 4.3.4. Gas regulators—For required gas cylinder.
 - 4.3.5. Thermometer—Accurate to one degree centigrade, to measure temperature of heated sample loop at time of sample injection.
 - 4.3.6. Barometer—Accurate to 5 mm Hg, to measure atmospheric pressure around gas chromatograph during sample analysis.
 - 4.3.7. Pump—Leak-free. Minimum capacity, 100 ml/min.
 - 4.4. Calibration.
 - 4.4.1. Tubing—Teflon, 6.4 mm outside diameter, separate pieces marked for each calibration concentration.
 - 4.4.2. Tedlar bags—Sixteen-inch square size, separate bag marked for each calibration concentration.
 - 4.4.3. Syringe—0.5 ml, gas tight.
 - 4.4.4. Syringe—50 μ l, gas tight.
 - 4.4.5. Flow meter—Rotameter type, 0 to 1000 ml/min range accurate to $\pm 1\%$, to meter nitrogen in preparation of standard gas mixtures.
 - 4.4.6. Stop watch—Of known accuracy, to time gas flow in preparation of standard gas mixtures.

5. Reagents. It is necessary that all reagents be of chromatographic grade.

5.1. Analysis.

5.1.1. Helium gas or nitrogen gas—Zero grade, for chromatographic carrier gas.

5.1.2. Hydrogen gas—Zero grade.

5.1.3. Oxygen gas—Zero grade.

5.2. Calibration.

5.2.1. Vinyl chloride, 99.9+ %—For preparation of standard gas mixtures.

5.2.2. Calibration cylinders (3), optional—One each of 80, 10 and 5 ppm vinyl chloride in nitrogen with certified analysis.

5.2.3. Nitrogen gas—Zero grade, for preparation of standard gas mixtures.

6. Procedure.

6.1. Sampling. Assemble the sample train as in Figure 106-1. Perform a bag leak check according to Section 7.4. Observe that all connections between the bag and the probe are tight. Place the end of the probe at the centroid of the stack and start the pump with the needle valve adjusted to yield a flow of 0.5 lpm. After a period of time sufficient to purge the line several times has elapsed, connect the vacuum line to the bag and evacuate the bag until the rotameter indicates no flow. Then reposition the sample and vacuum lines and begin the actual sampling, keeping the rate proportional to the stack velocity. Direct the gas entering the rotameter away from sampling personnel. At the end of the sample period, shut off the pump, disconnect the sample line from the bag, and disconnect the vacuum line from the bag container. Protect the bag container from sunlight.

, or Air, as required by the detector.

exiting
stack

6.2. Sample storage. Sample bags must be kept out of direct sunlight. When at all possible, analysis is to be performed within 24 hours of sample collection.

6.3. Sample recovery. With a piece of Teflon tubing identified for that bag, connect a bag inlet valve to the gas chromatograph sample valve. Switch the valve to withdraw gas from the bag through the sample loop. Plumb the equipment so the sample gas passes from the sample valve to the leak-free pump, and then to a charcoal tube, followed by a 0-100 ml/min rotameter with flow control valve.

6.4. Analysis. Set the column temperature to 155° C, the detector temperature to 225° C, and the sample loop temperature to 70° C. When optimum hydrogen and oxygen flow rates have been determined, verify and maintain these flow rates during all chromatograph operations. Using zero helium or nitrogen as the carrier gas, establish a flow rate in the range consistent with the manufacturer's requirements for satisfactory detector operation. A flow rate of approximately 15 ml/min should produce adequate separations. Observe the base line periodically and determine that the noise level has stabilized and that base line drift has ceased. Purge the sample loop for thirty seconds at the rate of 100 ml/min, then activate the sample valve. Record the injection time (the position of the pen on the chart at the time of sample injection), the sample number, the sample loop temperature, the column temperature, carrier gas flow rate, chart speed and the attenuator setting. Record the laboratory pressure. From the chart, select the peak having the retention time corresponding to vinyl chloride, as determined in Section 7.2. Measure the peak area, A_m , by use of the automatic integrator. Record A_m and the retention time. Repeat the injection at least two times or until two consecutive vinyl chloride peaks do not vary in area more than 5%. The average value for these two areas will be used to compute the bag concentration.

determined

a disc

6.5 Measure the ambient temperature and barometric pressure near the bag. From a water saturation vapor pressure table, determine and record the water vapor content of the bag.

7. Calibration and Standards.

7.1 Preparation of vinyl chloride standard gas mixtures. Evacuate a sixteen-inch square Tedlar bag that has passed a leak check (described in Section 7.4) and meter M 5.0 in liters of nitrogen. While the bag is filling, use the 0.5 ml syringe to inject 250 μ l of 99.9+ % vinyl chloride through the wall of the bag. Upon withdrawing the syringe needle, immediately cover the resulting hole with a piece of adhesive tape. This gives a concentration of 80 ppm of vinyl chloride. In a like manner use the other syringe to prepare dilutions having 10 and 5 ppm vinyl chloride concentrations. Place each bag on a smooth surface and alternately depress opposite sides of the bag 80 times to further mix the gases.

7.2 Determination of vinyl chloride retention time. This section can be performed simultaneously with Section 7.3. Establish chromatograph conditions identical with those in Section 6.3, above. Set attenuator to X 1 position. Flush the sampling loop with zero helium or nitrogen and activate the sample valve. Record the injection time, the sample loop temperature, the column temperature, the carrier gas flow rate, the chart speed and the attenuator setting. Record peaks and detector responses that occur in the absence of vinyl chloride. Maintain conditions. With the equipment plumbing arranged identically to Section 6.3, flush the sample loop for 30 seconds at the rate of 100 ml/min with one of the vinyl chloride calibration mixtures and activate the sample valve. Record the injection time. Select the peak that corresponds to vinyl chloride. Measure the distance on the chart from the injection time to the time at which the peak maximum occurs. This quantity, divided by the chart speed, is defined as the retention time. Record.

7.3 Preparation of chromatograph calibration curve. Make a gas chromatographic measurement of each standard gas mixture (described in Section 7.1) using conditions identical with those listed in Section 6.3 above. Flush the sampling loop for 30 seconds at the rate of 100 ml/min with each standard gas mixture and activate the sample valve. Record C_i , the concentrations of vinyl chloride injected, the attenuator setting, chart speed, peak area, sample loop temperature, column temperature, carrier gas flow rate, and retention time. Record the laboratory pressure. Calculate A_i , the peak area multiplied by the attenuator setting. Repeat until two injection areas are within 5%, then plot those points vs C_i . When the other concentrations have been plotted, draw a smooth curve through the points. Perform calibration daily, or before and after each set of bag samples, whichever is more frequent.

7.4 Tedlar bag leak checks. Before each use, make sure a bag is leak-free by checking it for leaks. To leak check, connect a water manometer and pressurize the bag to 5-10 cm H_2O (2-4 in. H_2O). Allow to stand for 10 minutes. Any displacement in the water manometer indicates a leak.

Check the rigid container for leaks in this manner.

(NOTE: An alternative leak check method is to pressurize the bag to 5-10 cm H₂O or 2-4 in. H₂O and allow to stand overnight. A deflated bag indicates a leak.)

8. Calculations.

8.1 Determine the sample peak area as follows:

$$A_i = A_m A_f$$

Equation 100-1

where:

A_i = The sample peak area.
 A_m = The measured peak area.
 A_f = The attenuation factor.

8.2 Vinyl chloride concentrations. From the calibration curve described in Section 7.3, above, select the value of C_i that corresponds to A_i , the sample peak area. Calculate C_b as follows:

$$C_b = \frac{C_i P_i T_i}{P_r T_r} \frac{1}{(1 - B_{wb})}$$

Equation 106-2

where:

C_i = The concentration of vinyl chloride in the bag sample in ppm.
 C_b = The concentration of vinyl chloride indicated by the gas chromatograph, in ppm.
 P_i = The reference pressure, the laboratory pressure recorded during calibration, mm Hg.
 T_i = The sample loop temperature on the absolute scale at the time of analysis, °K.
 P_r = The laboratory pressure at time of analysis, mm Hg.
 T_r = The reference temperature, the sample loop temperature recorded during calibration, °K.

9. References

1. Brown, D. W., Loy, E. W. and Stephenson, M. H. "Vinyl Chloride Monitoring Near the E. F. Goodrich Chemical Company in Louisville, Kentucky." Region IV, U.S. Environmental Protection Agency, Surveillance and Analysis Division, Athens, Georgia, June 24, 1974.

2. "Evaluation of A Collection and Analytical Procedure for Vinyl Chloride in Air," by G. D. Clayton and Associates, December 13, 1974. EPA Contract No. 68-02-1408, Task Order No. 2. EPA Report on 75-VCL-1.

After placing a bag in its rigid container, place a rotameter in-line between the bag and the pump inlet. Evacuate the bag. Failure of the rotameter to register zero flow when the bag appears to be empty indicates a leak.

$(1 - B_{wb})$

B_{wb} = The water vapor content of the bag sample, as analyzed.




Figure 106-1. Integrated bag sampling train.

(C) Notice of trade names on specific products does not constitute endorsement by the Environmental Protection Agency.

METHOD 107—DETERMINATION OF VINYL CHLORIDE CONTENT OF INPROCESS WASTEWATER SAMPLES, AND VINYL CHLORIDE CONTENT OF POLYVINYL CHLORIDE RESIN, SLURRY, WET CAKE, AND LATEX SAMPLES

INTRODUCTION

Performance of this method should not be attempted by persons unfamiliar with the operation of a gas chromatograph, nor by those who are unfamiliar with sampling, as there are many details that are beyond the scope of this presentation. Care must be exercised to prevent exposure of sampling personnel to vinyl chloride, a carcinogen.

1. Principle and Applicability.

1.1 The basis for this method relates to the vapor equilibrium which is established between RVCM, PVC, resin, water, and air in a closed system. It has been demonstrated that the RVCM in a PVC resin will equilibrate in a closed vessel quite rapidly, provided that the temperature of the PVC resin is maintained above the glass transition temperature of that specific resin.

1.2 This procedure is suitable for determining the vinyl chloride monomer (VCM) content of inprocess wastewater samples, and the residual vinyl chloride monomer (RVCM) content of polyvinyl chloride (PVC) resins, wet cake, slurry, and latex samples. It cannot be used for polymer in fused form, such as sheet or cubes. If a resolution of the vinyl chloride peak is not satisfactory for a particular sample, then chromatograph parameters may be altered with prior approval of the Administrator. If there is reason to believe that some other hydrocarbon with an identical retention time is present in the sample, then supplemental confirmation of the vinyl chloride peak through an absolute analytical technique, such as mass spectroscopy, should be performed.

2. Range and Sensitivity.

The lower limit of detection of vinyl chloride will vary according to the chromatograph used. Values reported include 1×10^{-7} mg and 4×10^{-7} mg. With proper calibration, the upper limit may be extended as needed.

3. Precision and Reproducibility.

An interlaboratory comparison between seven laboratories of three resin samples, each split into three parts, yielded a standard deviation of 2.63% for a sample with a mean of 2.09 ppm, 4.16% for a sample with a mean of 1.66 ppm, and 5.29% for a sample with a mean of 62.66 ppm.

4. Safety.

Do not release vinyl chloride to the laboratory atmosphere during preparation of standards. Venting or purging with VCM/air mixtures must be held to a minimum. When they are required, the vapor must be routed to outside air. Vinyl chloride, even at low ppm levels, must never be vented inside the laboratory. After vials have been analyzed, the pressure within the vial must be vented prior to removal from the instrument turntable. Vials must be vented into an activated charcoal tube using a hypodermic needle to prevent release of vinyl chloride into the laboratory atmosphere. The charcoal must be replaced prior to vinyl chloride breakthrough.

5. Apparatus.

5.1 Sampling.

5.1.1 Bottles—60 ml (2 oz), with waxed lined screw on tops, for PVC samples.

5.1.2 Vials—50 ml Hypo-vials,¹ sealed with Teflon faced Tuf-Bond discs for water samples.

¹ Mention of trade names on specific products does not constitute endorsement by the Environmental Protection Agency.

yielded

5.1.3 Electrical tape—or equivalent, to prevent loosening of bottle top.

5.2 Sample recovery.

5.2.1 Vials—With seals and caps, Perkin-Elmer Corporation No. 105-0118, or equivalent.

5.2.2 Analytical balance—Capable of weighing to ± 0.001 gram.

5.2.3 Syringe, 100 μ l—Precision Series "A" No. 010025, or equivalent.

5.2.4 Vial Sealer, Perkin-Elmer No. 105-0106 or equivalent.

5.3 Analysis.

5.3.1 Gas chromatograph—Perkin-Elmer Corporation Model F-40 head-space analyzer, No. 104-0001, or equivalent.

5.3.2 Chromatographic column—Stainless steel, 2 m $\times$ 3.2 mm, containing 0.4% Carbowax 1500 on Carbowax A, Perkin-Elmer Corporation No. 105-0133, or equivalent.

5.3.3 Thermometer—0 to 100° C, accurate to ± 0.1 ° C, Perkin-Elmer No. 105-0109 or equivalent.

5.3.4 Sample tray thermostat system—Perkin-Elmer No. 105-0103, or equivalent.

5.3.5 Septa—Sandwich type, for automatic dosing, 13 mm, Perkin-Elmer No. 105-1098, or equivalent.

5.3.6 Integrator - recorder — Hewlett - Packard Model 5380A, or equivalent.

5.3.7 Filter drier assembly (3)—Perkin-Elmer No. 2236117, or equivalent.

5.3.8 Soap film flowmeter—Hewlett Packard No. 0101-0113, or equivalent.

5.4 Calibration.

5.4.1 Regulators—for required gas cylinders.

6. Reagents.

6.1 Analysis.

6.1.1 Hydrogen gas—zero grade.

6.1.2 Nitrogen gas—zero grade.

6.1.3 Air—zero grade.

6.2 Calibration.

6.2.1 Standard cylinders (4)—one each of 50, 500, 2000, and 4000 ppm vinyl chloride in nitrogen, with certified analysis.

7. Procedure.

7.1 Sampling.

7.1.1 PVC sampling—Allow the resin or slurry to flow from a tap on the tank or silo until the tap line has been well purged. Extend a 60 ml sample bottle under the tap, fill, and immediately tightly cap the bottle. Wrap electrical tape around the cap and bottle to prevent the top from loosening. Place an identifying label on each bottle, and record the date, time, and sample location both on the bottles and in a log book.

7.1.2 Water sampling—Prior to use, the 60 ml vials (without the discs) must be capped with aluminum foil and muffled at 400°C for at least one hour to destroy or remove any organic matter that could interfere with analysis. At the sampling location fill the vials bubble-free, to overflowing so that a convex meniscus forms at the top. The excess water is displaced as the sealing disc is carefully placed, Teflon side down, on the opening of the vial. Place the aluminum seal over the disc and the neck of the vial and crimp into place. Affix an identifying label on the bottle, and record the date, time, and sample location both on the vials and in a log book. All samples must be kept refrigerated until analyzed.

7.2 Sample recovery. Samples must be run within 24 hours.

7.2.1 Resin samples—The weight of the resin used must be between 0.1 and 4.5 grams. An exact weight must be obtained (± 0.001 gram) for each sample. In the case of suspension resins a volumetric cup can be prepared which will hold the required amount of sample. The sample bottle is opened, and the cup volume of resin is added to the tared sample vial (including septum and aluminum cap). The vial is immediately sealed and the exact sample weight is then obtained. Report this value on the data sheet as it is

Carbopak C can be used in place of Carbopak A.

required for calculation of RVC. In the case of relatively dry resin samples (water content <0.3 weight %), 100 μ l of distilled water must be injected into the vial, after sealing and weighing, using a 100 μ l syringe. In the case of dispersion resins, the cup cannot be used. The sample is instead weighed approximately in an aluminum dish, transferred to the tared vial and weighed accurately in the vial. The sample is then placed in the Perkin-Elmer head space analyzer (or equivalent) and conditioned for one hour at 90°C.

Note: Some aluminum vial caps have a center section which must be removed prior to placing into sample tray. If not removed, serious damage to the injection needle will occur.

7.2.2 Suspension resin slurry and wet cake samples.—Slurry must be filtered using a small Buchner funnel with vacuum to yield wet cake. The filtering process must be continued only as long as a steady stream of water is exiting from the funnel. Excessive filtration time could result in some loss of VCM. The wet cake sample (0.10 to 4.5 grams) is added to a tared vial (including septum and aluminum cap) and immediately sealed. Sample weight is then determined to 3 decimal places. The sample is then placed in the Perkin-Elmer head space analyzer (or equivalent) and conditioned for one hour at 90°C. A sample of wet cake is used to determine

TS (total solids). This is required for calculating the RVC.

7.2.3 Dispersion resin slurry samples.—This material should not be filtered. Sample must be thoroughly mixed. Using a tared vial (including septum and aluminum cap) add approximately 8 drops (0.35 to 0.35 grams) of slurry or latex using a medicine dropper. This should be done immediately after mixing. Seal the vial as soon as possible. Determine sample weight accurate to 0.001 grams. Total sample weight must not exceed 0.50 grams. Condition the vial for one hour at 90°C in the analyzer. Determine the TS on the slurry sample (Section 7.3.5).

7.2.4 Inprocess wastewater samples.—Using a tared vial (including septum and aluminum cap) quickly add approximately 1 cc of water using a medicine dropper. Seal the vial as soon as possible. Determine sample weight accurate to 0.001 gram. Condition the vial for two hours at 90°C in the analyzer.

7.3 Analysis.

7.3.1 Preparation of gas chromatograph.—Install the chromatographic column and condition overnight at 150°C. Do not connect the exit end of the column to the detector while conditioning.

7.3.1.1 Flow rate adjustments.—Adjust flow rates as follows:

a. Nitrogen carrier gas—Set regulator on cylinder to read 50 psig. Set regulator on chromatograph to 1.3 kg/cm². Normal flows at this pressure should be 25 to 40 cc/minute. Check with bubble flow meter.

b. Burner air supply—Set regulator on cylinder to read 50 psig. Set regulator on chromatograph to supply air to burner at a rate between 250 and 300 cc/minute. Check with bubble flowmeter.

c. Hydrogen supply—Set regulator on cylinder to read 30 psig. Set regulator on chromatograph to supply approximately 35 $\pm$ 5 cc/minute. Optimize hydrogen flow to yield the most sensitive detector response without extinguishing the flame. Check flow with bubble meter and record this flow.

7.3.1.2 Temperature adjustments.—Set temperatures as follows:

a. Oven (chromatographic column), 50°C

b. Dosing line, 140°C.

c. Injection block, 140°C.

d. Sample chamber, water temperature, 90°C $\pm$ 1.0°C.

7.3.1.3 Ignition of flame ionization detector.—Ignite the detector according to the manufacturer's instructions.

7.3.1.4 Amplifier balance.—Balance the amplifier according to the manufacturer's instructions.

7.3.2 Programming the chromatograph.—Program the chromatograph as follows:

a. I—Dosing time—The normal setting is 2 seconds.

b. A—Analysis time—The normal setting is 8 minutes. Certain types of samples contain high boiling materials which can cause interference with the vinyl chloride peak on subsequent analyses. In these cases the analysis time must be adjusted to eliminate the interference. An automated backflush system can also be used to solve this problem.

c. B—Flushing—The normal setting is 0.2 minutes.

d. W—Stabilization time—The normal setting is 0.2 minutes.

e. X—Number of analyses per sample—The normal setting is 1.

7.3.3 Preparation of sample turntable.—Before placing any sample into turntable, be certain that the center section of the aluminum cap has been removed. The numbered sample bottles should be placed in the corresponding numbered positions in the turntable. Insert samples in the following order:

Positions 1 & 2—Old 2000 ppm standards for conditioning. These are necessary only after the analyzer has not been used for 24 hours or longer.

Position 3—50 ppm standard, freshly prepared.

Position 4—500 ppm standard, freshly prepared.

Position 5—2000 ppm standard, freshly prepared.

Position 6—4000 ppm standard, freshly prepared.

Position 7—Sample No. 7 (This is the first sample of the day, but is given as 7 to be consistent with the turntable and the integrator printout.)

After all samples have been positioned, insert the second set of 50, 500, 2000, and 4000 ppm standards. Samples, including standards must be conditioned in the bath of 90° C for 1 hour (not to exceed 5 hours).

7.3.4 Start chromatograph program—When all samples, including standards, have been conditioned at 90° C for 1 hour, start the analysis program according to the manufacturer's instructions. These instructions must be carefully followed when starting and stopping program to prevent damage to the dosing assembly.

7.3.5 Determination of total solids (TS).

For wet cake, slurry, resin solution, and PVC latex samples, determine TS for each sample by accurately weighing approximately 3 to 4 grams of sample in an aluminum pan before and after placing in a draft oven (105 to 110° C). Samples must be dried to constant weight. After first weighing return the pan to the oven for a short period of time and then reweigh to verify complete dryness. TS is then calculated as the final sample weight divided by initial sample weight.

8 Calibration

Calibration is to be performed each eight-hour period when the instrument is used. Each day, prior to running samples, the column should be conditioned by running two of the previous days 2000 ppm standards.

8.1 Preparation of Standards

Calibration standards are prepared by filling the vials with the vinyl chloride/nitrogen standards, rapidly seating the septum and sealing with the aluminum cap. Use a stainless steel line from the cylinder to the vial. Do not use rubber or tygon tubing. The sample line from the cylinder must be

purged (into hood) for several minutes prior to filling vials. After purging, reduce the flow rate to approximately 500-1000 cc/min. Place end of tubing into vial (near bottom) and after one minute slowly remove tubing. Place septum in vial as soon as possible to minimize mixing air with sample. After the standard vials are sealed, inject 100 µl of distilled water.

8.2 Preparation of chromatograph calibration curve

Prepare two 50 ppm, two 500 ppm, two 2000 ppm, and two 4000 ppm standard samples. Run the calibration samples in exactly the same manner as regular samples. Plot A_i , the integrator area counts for each standard sample vs C_i , the concentration of vinyl chloride in each standard sample. Draw a line of best fit through the points.

9 Calculations

9.1 Response factor

From the calibration curve described in Section 8.2, above, select the value of C_i that corresponds to A_i for each sample. Compute the response factor, R_i , for each sample, as follows:

$$R_i = \frac{A_i}{C_i} \quad \text{Equation 107-1}$$

9.2 Residual vinyl chloride monomer concentration, or vinyl chloride monomer concentration

Calculate C_{res} as follows:

$$C_{res} = \frac{A_i P_o}{R_i T_i} \left(\frac{M_i V_i}{m_i R} + K T_i \right)$$

Equation 107-2

where:

C_i = Concentration of vinyl chloride in the sample, in ppm.

P_o = Laboratory atmosphere pressure, mm Hg.

T_i = Room temperature, °K.

M_i = Molecular weight of VCM (62.5).

V_i = Volume of vapor phase (vial volume less sample volume).

m_i = Weight of sample, grams.

R = Gas constant (62.360).

K = Henry's Law constant for VCM in PVC at 90° C, $K = 6.52 \times 10^{-4} = K_o$, for VCM in 1 cc (approximate) wastewater sample at 90° C, $K = 5.0 \times 10^{-4} = K_o$.

T_i = Equilibration temperature, °K.

If the following conditions are met, Equation 107-2 can be simplified as follows:

1. $T_i = 22^\circ \text{C} (295^\circ \text{K})$.

2. $T_i = 90^\circ \text{C} (363^\circ \text{K})$.

3. $P_o = 756 \text{ mm Hg}$.

$$4. V_i - V_o = \frac{m_i}{1.4} = 23.5 - \frac{m_i}{1.4}$$

where

V_o = Vial volume, cc (23.5).

5. Sample contains less than 0.5% water.

$$C_{res} = \frac{A_i}{R_i} \left(4.197 \times 10^{-3} + \frac{5.988 \times 10^{-3}}{m_i} \right)$$

Equation 107-3

The following general equation can be used for any sample which contains VCM, PVC and/or water.

$$C_{res} = \frac{A_i P_o}{R_i T_i} \times \left[\frac{M_i V_i}{R m_i} + K_i (TS) T_i + K_o (1 - TS) T_i \right]$$

Equation 107-4

where:

T_i = Total solids.

Note: K_o must be determined.

For a 1 cc (approximate) wastewater sample, Equation 107-4 can be simplified to the following:

$$C_{res} = \frac{A_i}{R_i} \left[\frac{5.988 \times 10^{-3}}{m_i} + (2.066 \times 10^{-3}) \right]$$

Equation 107-5

Results calculated using Equation 107-4 can represent concentration based on the total sample. To obtain results based on dry PVC content, divide by TS.

10 References

1. Residual Vinyl Chloride Monomer Content of Polyvinyl Chloride Resins and Wet Cake Samples, B. F. Goodrich Chemical Co. Standard Test Procedure No. 1005-T. B. F. Goodrich Technical Center, Avon Lake, Ohio, January 30, 1975.

2. Berens, A. R., "The Solubility of Vinyl Chloride in Polyvinyl Chloride," ACS-Division of Polymer Chemistry, Polymer Preprints 15 (2): 197, 1974.

3. Berens, A. R., "The Diffusion of Vinyl Chloride in Polyvinyl Chloride," ACS-Division of Polymer Chemistry, Polymer Preprints 15 (2): 203, 1974.

4. Berens, A. R., L. B. Crider, C. J. Tomasek and J. M. Whitney, Analysis for Vinyl Chloride in PVC Powders by Head-Space Gas Chromatography, to be published.

[FR Doc. 75-34513 Filed 12-23-75; 8:45 am]

(Note)

AUTHORITY: Section 112 of the Clean Air Act as amended by sec. 4(a) of Pub. L. 91-604, 84 Stat. 1685 (42 U.S.C. 1857c-7); section 114 of the Clean Air Act, as amended by sec. 4(a) of Pub. L. 91-604, 84 Stat. 1687, and by Pub. L. 93-319, sec. 6(a)(4), 88 Stat. 259 (42 U.S.C. 1857c-9); Section 301(a) of the Clean Air Act, as amended by sec. 15(c)(2) of Pub. L. 91-604, 84 Stat. 1713 (42 U.S.C. 1857g(a)).