



STANDARD MAINTENANCE FINISHES

NET PRICE LIST

No. MW8

EFFECTIVE JANUARY 10, 1951

Subject to change without notice



THE GLIDDEN COMPANY

NATIONAL HEADQUARTERS • CLEVELAND 2, OHIO

Factories from Coast to Coast

Branches in Principal Cities

INDEX (Itemized)

Product	Page	Product	Page	Product	Page
A					
Ad-El-ite P&V. Remover.....	14-15	General Purpose Varnish.....	9	Rapidcote Spar Varnish.....	8
Aluminum Asphalt Roof Paint	13	General Purpose Varnish Stain	8	Romark.....	11
Aluminum Paints.....	13	Gliddencoat.....	4	Roof Paint.....	13
Asphalt Products.....	12	Gliddite Galvanized Iron Primer	8	Rust Inhibiting Oil.....	15
B					
Barn, Tool Shed, Wood		Gym Floor Varnish.....	9	S	
Building Paints.....	10	I		Sealette.....	5
Black Board Slating.....	11	Interior Wall Finishes.....	5	Semi-Gloss Interior Wall Finish.....	5
C					
Cement Coating—Exterior.....	9	L		Smoke Stack Black.....	14
Cement Coating Mixing Liquid.....	9	Line Marking Paints.....	11	Spred Flat.....	5
Chromatized Metal Primer.....	3	Liquid Cement Coating.....	9	Spred Luster.....	6
D					
Dado Enamels.....	6	M		Spred Satin.....	6
Driwal.....	8	Machinery Enamels.....	10	Spred Vapor Barrier.....	6
E					
Enamels.....	3-6-7-8-10	Masticrete.....	12	Stain.....	8
Exterior Base Coat.....	4	Masticrete Primer.....	12	Surfacene.....	11
Exterior Fume-Proof Paint.....	4	Metal Paints.....	8	Synthetic One Coat Enamel.....	8
Exterior Wood Building Finishes.....	7	N		Synthetic Tank Paint.....	7
E-Z-C Machinery Enamels.....	10	Nev-A-Rot.....	12	T	
E-Z-C Pipe Identification Enamels	10	O		Tank Finishes.....	7
E-Z-C Safety Enamels.....	10	One Coat Enamel.....	8	Tinners' Paints.....	4
F					
Flat Wall Finish.....	4	P		U	
Floor & Dado Enamels.....	6	Paints Varnish Remover.....	14-15	Undercoats.....	4
Floor Enamels.....	7	Penetrex.....	9	V	
Foundation Coating.....	12	Pli-Namel.....	7	Varnishes.....	8-9
Fume-Proof Paint.....	4	Primers.....	3-4	Vismatic Green Chalkboard Coating.....	11
		Protective Metal Paint.....	8	W	
				Wall Finishes.....	5-6
				Water Tank Finishes.....	7
				Wood Bleach.....	14
				Wood Building Paint.....	7

See separate list for prices on Spray-Day-Lite and Related Products.

SPRAY-DAY-LITE

THE LARGEST SELLING MAINTENANCE FINISH IN AMERICA

It is a top quality oil enamel especially developed for maximum light reflection and diffusion. It is the idea wall finish for industrial and commercial building interiors. A coat of Spray-Day-Lite has stepped up lighting efficiency as much as 102%.

One coat equals conventional two coat results permitting a saving of from 40 to 50% in maintenance painting cost. Spray-Day-Lite provides smooth covering over grimy, dirty and badly discolored surfaces of concrete, tile, masonry, plaster, steel, stucco and wood. It produces very little fog or mist when sprayed. Spray-Day-Lite will withstand repeated washings and give from three to eight years' service.

Spray-Day-Lite is made in Eggshell finish in White and ten beautiful Colors for both brush and spray application. Also furnished in White Semi-Gloss, Gloss, High Gloss, Wet Wall and Fume Resistant.

A Glidden representative will gladly call to recommend the proper Spray-Day-Lite materials to fit your requirements and give you an actual demonstration. He will suggest and help you make color selections for walls, ceilings, dados and floors by rooms or departments. Just drop us a line. There will be no obligation.



PROTECTIVE METAL PAINT

Type of Product—An exceptional product for efficient protection of metal surfaces against weather and temperature changes. It is water-resistant and also resists acid and alkali fumes. It contains rust inhibitive pigments and requires no primer, although it is very often used in conjunction with Liquid Red Lead Modified.

Drying Time—18-24 hours—48 or more for recoating.

Coverage—550-600 square feet per gallon—one coat.

Application—Stir well before using. Surfaces to be finished should be scraped or wire brushed free from all rust, scale and loose paint. Also be sure to remove all dust, dirt, grease and oil by washing if necessary. Be sure surface is dry before painting. Two coats are recommended, allowing twenty-four hours drying time between coats. If thinning is deemed necessary add a small amount of boiled linseed oil.

	1's each
Gray, Briar Green.....	\$5.41
Red, Black, Graphite.....	5.41

CHROMATIZED METAL PRIMER

Type of Product—A scientific combination of rust inhibitive pigments in a water-resisting vehicle. Better than Red Lead for either interior or exterior surfaces but not effective on galvanized metal surfaces. For both new work and touching up of bare spots when repainting.

Drying Time—18 hours—36 or more for recoating.

Coverage—550-600 square feet per gallon—one coat.

Application—The surface to be primed must be dry, free from dirt, dust and grease and foreign matter. Apply full body for brushing and reduce with turpentine or mineral spirits for spraying. Allow to dry hard before re-coating, which, under normal drying conditions or temperatures of 70°, will require approximately 18 hours.

	1's each
Red 560.....	\$6.06

GLIDTITE GALVANIZED IRON PRIMER

Type of Product—A superior first coat for all galvanized metal, plymetal, galvaneal, or treated metal surfaces that possess better adhesion for these surfaces than any other primer. Metal requires no previous etching with acid and eliminates the peeling experienced with ordinary materials. Dries hard for re-coating overnight. Adhesion is better if application is in thin rather than heavy coats.

Drying Time—Overnight—24 hours or more for recoating.

Coverage—550-600 square feet per gallon.

Application—It is recommended the surface be first washed with a dilute muriatic acid solution and then rinsed thoroughly with clean water. Allow the surface to weather as long as is practical. Apply one coat of Glidrite Galvanized Iron Primer full body as received. Apply paint selected for finishing not more than 72 hours after the Glidrite Galvanized Iron Primer has been applied.

	1's each
White.....	\$4.18

SYNTHETIC ONE COAT ENAMEL

Type of Product—A high grade gloss enamel for interior or exterior use. Recommended for pipe identification, machinery, concrete, brick, wood, trucks, tractors, etc.

Drying Time—4-6 hours — 24 for recoating.

Coverage—400-500 square feet per gallon—one coat.

Application—Old Painted Surfaces—Remove all loose paint, rust and other irregularities. Clean surface with soap and water. Wipe dry and allow sufficient time for moisture to thoroughly evaporate. One coat will be found sufficient where conditions are normal, though two coats produce a beautiful gloss and depth of finish.

New Unpainted Surfaces—All surfaces should be dry and clean and should be sanded to a smooth surface.

See directions for New Unpainted Surfaces under Gliddencost.

	1's each
Colors — Black and White.....	\$5.77

Deduct 10 cents from 1-gallon price for 5's and barrels



GLIDDENCOAT

Type of Product—Because of its quick drying properties, it is a truly economical enamel undercoater. It dries to recoat in 24 hours, possesses unusual opacity, works easily under the brush, flows out free from all brush marks and requires but a very light sanding. Because of its unusual sealing properties there is no absorption of succeeding coats of enamel and they stand out with a maximum of luster and depth of gloss. It can be water sanded to a beautiful eggshell.

Drying Time—12-18 hours—24 for recoating.

Coverage—500-600 square feet per gallon.

Application—Stir well before using.

Old Painted Surfaces—Gliddencoat is required only on enamel jobs calling for a distinct color change from dark to lighter shades. Apply one or two coats as may be required to produce necessary opaqueness. Allow twelve hours drying time. Sand last coat lightly before applying enamel.

New Unpainted Surfaces—Apply two coats to new wood that is properly sanded and perfectly dry. The first coat should be reduced about 10% with turpentine, allowed to dry overnight, then follow with a second coat applied full body. Second coat should dry about 12 hours then apply enamel in color selected. Sand lightly between coats.

Gliddencoat..... 1's each \$4.18

EXTERIOR FUME-PROOF PAINT

Type of Product—A high quality paint ready to use for exterior surfaces. The ingredients are the finest in pigment and oil combination to produce self cleaning properties and durability. Made in White, Cream, Tobacco Brown, Light Gray, Medium Gray.

Drying Time—24 hours—48 hours for recoating.

Coverage—Approximately 700 to 750 square feet per gallon—one coat.

Application—Stir thoroughly before using.

Old Painted Surfaces—Remove loose paint, scales, blisters and dirt. Surface must be dry. All bare wood should receive a coat of Glidden Exterior Base Coat, or paint reduced as for new surfaces.

Second Coat—Add small amount of turpentine.

Third Coat—Apply paint as received, full body.

New Unpainted Surfaces—Use Glidden Exterior Base Coat for priming. If not available proceed as follows: For yellow pine or cypress, add 1 pint raw linseed oil and two pints turpentine to a gallon of paint. For white pine, fir and soft woods, add 1 quart raw linseed oil and 1 pint turpentine to a gallon of paint. Allow to dry three days or longer.

Second Coat—Add one pint turpentine to a gallon of paint. Allow to dry three days or longer.

Third Coat—Use paint as received, if too heavy, add equal amounts of linseed oil and turpentine to produce desired body.

Mineral Spirits may be used in place of turpentine.

Colors and White..... 1's each \$5.00

EXTERIOR BASE COAT

Type of Product—A scientifically correct primer and first coater for both new and old work. Made from specially prepared oils to produce the elasticity, the adhesion, and control penetration that is so necessary to exterior paint jobs. Also an excellent primer for asbestos wall sidings, or porous masonry surfaces.

Drying Time—18 to 24 hours—48 or more for recoating.

Coverage—550 to 600 square feet per gallon—one coat.

Application—Stir the paint thoroughly with a lifting motion. All surfaces should be perfectly dry and free from all foreign matter. Under normal conditions, Base Coat should be applied without reduction although thinning 10% with turpentine improves working conditions during extremely hot weather.

Old Painted Surfaces—Remove loose paint by scraping, wire brushing or burning off where necessary. Be sure the surface is perfectly dry. Apply Base Coat to all sections that have become bared by blistering, scaling or peeling and to the entire surface if the old paint is porous, chalking and badly weathered.

New Unpainted Surfaces—Use Base Coat full body, without adding any liquid.

Exterior Base Coat..... 1's each \$5.00

TINNERS' PAINTS

Type of Product—For use primarily on metal roofs, flashings, gutters, downspouts and for work inside tin shops but equally satisfactory for surfaces of wood and brick, etc. Permanent in color and waterproof, they dry to be handled in a few hours and hard overnight. They are sufficiently elastic not to chip or crack even on bending the metal on which applied. Furnished only in a low gloss so that they will not intensify irregularities in the metal.

Drying Time—Overnight—36 hours for recoating.

Coverage—450-500 square feet per gallon—one coat.

Application—Stir paint well before using. Apply with a metal bound brush. Before application on any surface be sure that all rust, scale, grease, dirt, etc. are removed and that the surface is clean. One coat is all that is required. Material is ready for use, but for greater workability material may be reduced slightly with pure boiled linseed oil.

620 Light Red..... 1's each \$3.47
623 Light Green..... 5.36

Deduct 10 cents from 1-gallon price for 5's and barrels



SEMI-GLOSS INTERIOR WALL FINISH

Type of Product—A type of wall finish embodying quick drying properties without sacrificing any of the easy working and flowing qualities essential to a perfect job. It dries with a beautiful semi-gloss and is as satisfactory for woodwork and furniture as for wall decoration. Its hard, closely knit film permits easy and repeated washing, while its soft pleasing gloss imparts no strong light reflections or glare.

Drying Time—18 hours—24 or more for recoating.

Coverage—500-550 square feet per gallon—one coat.

Application—Stir thoroughly with a lifting motion.

On Plaster Surfaces—Be sure surface is dry and free from dirt, grease and loose particles. All new plaster or cement walls that show indication of alkali or active lime after testing with Phenolphthaleine should be given a wash coat of Zinc Sulphate solution (two pounds of Commercial Zinc Sulphate dissolved in one gallon water).

Old Painted Surfaces—Walls—If old paint has become porous and worn with age and repeated washings, apply a coat of Glidden Interior Base Coat and then proceed as recommended for New Unpainted Surfaces. If old paint is in good condition, one coat of Semi-gloss is often sufficient. If two coats are considered necessary, apply a first coat of Semi-gloss mixed with equal parts of Glidden Interior Base Coat. Allow this to dry then apply a coat of Semi-gloss as it comes from the can. On woodwork in place of Base Coat use Gliddencoat (Enamel Undercoater).

New Unpainted Surfaces—On unpainted walls make sure that wash coat of Zinc Sulphate solution has dried out. For first coat apply Glidden Interior Base Coat. Allow to dry overnight then apply a mixture of one half Semi-Gloss and one half of Glidden Interior Base Coat. After this has dried 24 hours apply a finishing coat of Semi-gloss as it comes from the can. On woodwork use Gliddencoat (Enamel Undercoater) in place of Base Coat.

Colors and White..... 1's each
\$4.41

FLAT WALL FINISH

Type of Product—The finest Flat Wall Finish possible to produce. Heavily bodied, this paint flows freely and is self-leveling. Remarkable hiding power alone places it far above ordinary wall finishes. Proper blending and the select grade of ingredients, account for the extra long wearing quality and unusual hiding power and covering capacity.

This paint dries to a beautiful smooth finish. Viewed toward light there is a slight sheen—desirable because it permits easy washing, but with no more sheen than is permissible in the best Flat Wall Paint. In addition to the popular White there is a wide selection of delicate and rich shades suitable for the most artistic decoration of walls and ceilings.

Drying Time—18 hours—24 for recoating.

Coverage—400-450 square feet per gallon—one coat.

Application—Stir thoroughly with a lifting motion.

On Plaster Surfaces—Be sure surface is dry and free from dirt, grease and loose particles. All new plaster or cement walls that show indication of alkali or active lime after testing with Phenolphthaleine should be given a wash coat of Zinc Sulphate solution (two pounds of Commercial Zinc Sulphate dissolved in one gallon water).

Old Painted Surfaces—Walls—If old paint has become porous and worn with age and repeated washings, apply a coat of Glidden Interior Base Coat and then proceed as recommended for New Unpainted Surfaces. If old paint is in good condition, one coat of Flat Wall Finish is often sufficient. If two coats are considered necessary, apply a first coat of Flat Wall Finish mixed with equal parts of Glidden Interior Base Coat. Allow this to dry then apply a coat of Flat Wall Finish as it comes from the can. On woodwork in place of Base Coat use Gliddencoat (Enamel Undercoater).

New Unpainted Surfaces—On unpainted walls make sure that wash coat of Zinc Sulphate solution has dried out. For first coat apply Glidden Interior Base Coat. Allow to dry overnight then apply a mixture of one half Flat Wall Finish and one half Glidden Interior Base Coat. After this has dried 24 hours apply a finishing coat of Flat Wall Finish as it comes from the can. On woodwork use Gliddencoat (Enamel Undercoater) in place of Base Coat.

White and Colors..... 1's each ¼'s each
\$3.41 \$1.05

SEALETTE

Type of Product—Sealette seals, primes and finishes in one operation. It can be applied over dry surfaces of casein, calcimine and texture paints. Also plaster wall board, wood previously painted, brick or cement surfaces or any other clean, dry and solid interior paintable surface.

Drying Time—18 hours.

Coverage—350 square feet, approximately.

Application—All surfaces must be clean and free from dust, dirt and grease. Loose and scaling surfaces should be wire brushed or scraped. Reduce Sealette Flat by adding two or three pints of Mineral Spirits or Turpentine to the gallon, depending on porosity of surface and method of application. Do not use Linseed Oil, Varnishes, or patented oils for reducing Sealette Flat for Finishing coats.

Sealette..... 1's each ¼'s each
\$3.12 \$.98

SPRED

SPRED FLAT

Type of Product—A washable, oil emulsion water-mix paint. Easily applied over any surface. Leaves a rich flat tone. An ideal finish over wallpaper, new or old plaster, wallboard, painted surfaces, cement and tile walls.

Drying Time—30 minutes to permit the use of the room when properly ventilated. 4 hours for recoating over wallpaper and at least 12 hours for recoating over plaster.

Coverage—500 to 650 square feet depending upon surface.

Application—Apply with a large brush. Apply generously and evenly; level off lightly with the tip of the brush. Keep brush well filled at all times. Do not work excessively or work out too thin.

Old Painted or Papered Surfaces—Remove all loose scale, grease, dirt, glue size, calcimine, and other water soluble compounds. Fill in holes and cracks with spackling compound. Paste all loose wallpaper securely. Be sure wallpaper colors are not water soluble, or bleeding will result. Test by rubbing surface with cloth wet with soapy water. Color should not show on cloth.

New Unpainted Surfaces—Need two coats for best results.

White and Tints..... 1's each ¼'s each
\$2.90 \$.92

Deduct 10 cents from 1-gallon price for 5's and barrels



SPRED LUSTER

Type of Product—A washable, durable, enamel-like finish, making it excellent for walls where a gloss finish is desired.
Drying Time—Dries to touch in one hour. Allow at least eight hours before recoating if a second coat is necessary. When used on wood, surface should be sanded between coats.
Coverage—Same as for Spred Flat.
Application—Same as for Spred Flat.

White and Tints.....	1's each \$4.24	1/4's each \$1.25
----------------------	--------------------	----------------------

SPRED SATIN

Type of Product—Spred Satin imparts to interior walls and woodwork a modern, glareless finish. Remarkable ease of application, excellent coverage, and durability make Spred Satin outstanding. Washes perfectly with mild soap and water after 30 days.
Drying Time—Dries to touch in 30 minutes, and a second coat may be applied after a drying period of 12 hours under proper ventilation and good drying conditions. Remove paint spatters promptly with a damp cloth.
Coverage—500-600 square feet depending upon the surface.
Application—Apply generously and evenly with a large flexible brush. Level off lightly with the tip of the brush. Keep brush well filled at all times. Do not brush excessively or brush out too thinly.
Old Painted or Prepared Surfaces—Remove all loose scale, dirt, grease, glue size, calcimine, and water soluble compounds. Patch holes and cracks with spatchling compound. Use metal primers over bare metal. Dull any glossy surface with steel wool or washing powder solution before painting. Do not use over wallpapers which will stain a white cloth wet with soap and water or which contain metallic colors (silver or gold).
New Unpainted Surfaces—Need two coats for best results.

White and Tints.....	1's each \$3.94	1/4's each \$1.18
Decorator Colors	3.94	1.18

PRIMER-SEALER

SPRED (VAPOR BARRIER)

Type of Product—An excellent primer and sealer for porous surfaces of dry-wall construction, cured plaster and masonry surfaces.
Drying Time—Dries to touch in 30 minutes—12 hours for recoating.
Coverage—400 square feet per gallon on plaster; 100 square feet per gallon on soft, porous wallboard.
Application—Surface Preparation—Remove all loose scale, dirt, grease, glue size, calcimine and water soluble compounds. Patch holes and cracks with spatchling compound.
Mixing—Spred Vapor Barrier is ready for use, no thinning required. Stir thoroughly. Avoid whipping or shaking. CAUTION: Do not add turpentine, other paint solvents or oils.
Application—Brushing—Use a large flexible brush—keep it well filled—apply generously and evenly in a continuous film. Do not brush excessively or brush out too thin. Thoroughly clean all brushes with soap and water before and after using.
Spraying—Apply full body. Thoroughly clean equipment with warm, soapy water immediately after using.

1's each \$3.71	1/4's each \$1.12
--------------------	----------------------

FLOOR AND DADO ENAMELS

Type of Product—For either inside or outside use. Should not be confused with the ordinary line of floor and dado enamels as it is distinctly different. It is especially adapted for finishing new or painted woodwork and cement.
Drying Time—12 hours—24 or more for recoating.
Coverage—500-600 square feet per gallon—one coat.
Application—Stir enamel well before using. Be sure surface is clean and dry. Remove polishes, wax or grease by washing with turpentine. When washing cement with Zinc-Sulphate, allow to dry thoroughly before painting.
Inside Floors and Dados—Reduce the first coat 10% with turpentine. Allow to dry overnight, then apply second coat as it comes from the can.
Cement Surfaces—If cement is new, wash with a solution of two pounds of zinc sulphate to a gallon of water to neutralize alkali in cement. Reduce first coat slightly with turpentine. Apply second coat as it comes from can.

All Colors.....	1's each \$4.65	1/4's each \$1.35
-----------------	--------------------	----------------------

Deduct 10 cents from 1-gallon price for 5's and barrels



PLI-NAMEL

Type of Product—A true plastic, the product of a chemical combination known as "Polymerization," which gives it outstanding performance. It is highly resistant to acids, alkali, moisture, severe fume conditions, oil and grease. It is the perfect finish for concrete floors and interior masonry surfaces. Pli-Namel resists water and the action of alkalies in the concrete. It has good resistance to abrasion, good adhesion and is sufficiently hard to resist wear. It is an anti-corrosive, and protects against the deterioration of metal.

Drying Time—Sets in 30 minutes and dries firm overnight.

Coverage—400-500 square feet per gallon—one coat.

Application—For Concrete—Remove oil and grease with alkaline cleanser or steam. Then etch with Sani Flush, applying powder to wet floor by shaking it directly from can; or, a solution of one quart muriatic acid and three quarts of water. Flush with clear water to remove any excess Sani Flush or acid. Thin first coat Pli-Namel 10% with pure turpentine to increase penetration. Apply second coat full body after first coat is thoroughly dried. Under good drying conditions allow second coat to dry 48 hours before the floor is subjected to severe wear.

For Metal—Surface must be clean and dry. Wire brush or chip corroded metal. Apply primer coat of No. 1525 Chromate Primer. This base coat will insure good adhesion; allow to dry before applying Pli-Namel. Then apply Pli-Namel full body. Do not use Pli-Namel on surfaces subjected to high heat. Cannot be tinted with Colors in Oil.

Newly Plastered or Damp Walls—Apply a prime coat of No. 6413 Alkali Resistant Primer, then first and succeeding coats as under concrete.

Regular Colors.....	1's each	1/4's each
White.....	\$5.41	\$1.54
Black.....	6.00	1.69
6413 Alkali Resistant Primer.....	4.53	1.33
1525 Chromate Primer.....	4.98	1.46
	6.18	1.97

EXTERIOR WOOD BUILDING FINISHES

Type of Product—A high quality paint ready to use for exterior. The ingredients are the finest in pigment and oil combination to produce self cleaning properties and durability. Made in White, Black, Beige, Cottage Brown, Cream White, Crylight Green, Shadow White.

Drying Time—24 hours—48 hours for recoating.

Coverage—Approximately 700 to 750 square feet per gallon—one coat.

Application—Stir thoroughly before using.

Old Painted Surfaces—Remove loose paint, scales, blisters and dirt. Surface must be dry. All bare wood should receive a coat of Glidden Exterior Base Coat, or paint reduced as for new surfaces.

Second Coat—Add small amount of turpentine.

Third Coat—Apply paint as received, full body.

New Unpainted Surfaces—Use Glidden Exterior Base Coat for priming. If not available proceed as follows: For yellow pine or cypress, add 1 pint raw linseed oil and two pints turpentine to a gallon of paint. For white pine, fir and soft woods, add 1 quart raw linseed oil and 1 pint turpentine to a gallon of paint. Allow to dry three days or longer.

Second Coat—Add one pint turpentine to a gallon of paint. Allow to dry three days or longer.

Third Coat—Use paint as received, if too heavy, add equal amounts of linseed oil and turpentine to produce desired body.

Mineral Spirits may be used in place of turpentine.

Colors and White.....	1's each
Crylight Green.....	\$5.00
	6.36

SYNTHETIC TANK PAINT

Type of Product—An exceptional product for efficient protection of metal surfaces against weather and temperature changes. It is water-resistant and also resists acid and alkali fumes. It contains rust inhibitive pigments and requires no primer, although it is very often used in conjunction with Liquid Red Lead Modified.

Drying Time—18-24 hours—48 or more for recoating.

Coverage—550-600 square feet per gallon—one coat.

Application—Stir well before using. Surfaces to be finished should be scraped or wire brushed free from all rust, scale and loose paint. Also be sure to remove all dust, dirt, grease and oil by washing if necessary. Be sure surface is dry before painting. Two coats are recommended, allowing twenty-four hours drying time between coats. If thinning is deemed necessary add a small amount of boiled linseed oil.

285 Red — 215 Black.....	1's each
385 Green — 185 Steel Gray.....	\$5.41
	5.41

WATER TANK FINISHES

Type of Product—A coating material for the protection of the inside surfaces of steel tanks for the storage of water. In a test including a large number of competitive products of every description it was given a rating of 100%. Satisfied users in all parts of the country, and its adoption as a standard by the country's largest builders of steel storage tanks proves its superiority.

Drying Time—8 hours. 24-48 for recoating.

Coverage—450-500 square feet per gallon—one coat.

Application—Brush or spray.

No. 1525 Chromate Primer.....	5's per gal.	1's each
No. 1777 Gray Synthetic Enamel.....	\$6.05	\$6.18
	6.90	7.00

Deduct 10 cents from 1-gallon price for 5's and barrels



DRIWAL

Type of Product—A damp-resisting and stain-resisting material designed for application to limestone, stucco, sandstone, concrete, brick and other porous surfaces. It penetrates the pores of the surface to which it is applied and lines them with an insoluble substance which makes them fully water-repellent. Does not change texture nor discolor the surface. Contains no paraffine.

Drying Time—About 2 hours.

Coverage—On cement, concrete, stucco and brick approximately 125 to 175 square feet per gallon for first application and from 175 to 225 square feet on second application. On stone—between 175 and 225 square feet per gallon for first application and from 225 to 275 square feet per gallon for the second application.

Application—Brush or Spray.

	5's per gal.	1's each
Clear.....	\$2.49	\$2.59
Heavy Body—Clear.....	2.84	2.94
White.....	4.84	4.94

ONE COAT ENAMEL

Type of Product—First quality gloss enamel for Trucks, Rigs, Engines, Pipe Lines. For all types of surfaces, interior or exterior, where a good gloss finish is desired.

Drying Time—4-6 hours—24 for recoating.

Coverage—400-500 square feet per gallon—one coat.

Application—Old Painted Surfaces—Remove all loose paint, rust and other irregularities. Clean surface with soap and water. Wipe dry and allow sufficient time for moisture to thoroughly evaporate. One coat of One Coat Enamel will be found sufficient where conditions are normal, though two coats produce a beautiful gloss and depth of finish.

New Unpainted Surfaces—All surfaces should be dry and clean and should be sandpapered to a smooth surface. Apply two or more coats reducing the first coat about 10% with turpentine. Sand lightly between coats.

102 Yellow — 6521 Red — 4521 Green — 6421 Blue.....	1's each
	\$5.77

GENERAL PURPOSE VARNISH STAIN

Type of Product—Stains and varnishes in one operation. For use on all interior surfaces, furniture, woodwork, and floors particularly. It is unusually waterproof, will not mar or scratch while on floor surfaces. Old pieces of furniture can be quickly transformed to the popular and modern Mahogany and Walnut. Varnish Stains dry with a rich deep gloss.

Drying Time—4-6 hours—24 hours for recoating.

Coverage—600 square feet per gallon—one coat.

Application—Shake the can well before removing cover, stir the contents thoroughly before applying.

Old Painted Surfaces—Carefully remove all blemishes and discolorations with sandpaper or steel wool, clean the surface with mild soap and water, then allow sufficient time for thoroughly drying. One coat will produce a satisfactory finish under any but unusual conditions. If two coats are considered desirable allow overnight for first coat to dry and sandpaper it lightly, then apply second coat.

New Unpainted Surfaces—Two coats are recommended, sanding lightly between coats. The first coat serves as a primer and sealer. If a third coat is considered advisable, apply full body after the preceding coat has dried overnight.

1200 Light Oak — 1201 Dark Oak — 1202 Walnut — 1203 Mahogany.....	1's each
	\$4.24

RAPIDCOTE

Spar Varnish

Type of Product—This product possesses quick drying qualities without sacrificing the elasticity, durability or wear-resisting qualities of the varnish. Can be used on floors, woodwork or furniture or on interiors, and, being unusually waterproof, is excellent for exterior use as well. The extreme paleness of this varnish makes it ideal for use on surfaces which are to retain the original color.

Drying Time—4-6 hours. 16 for recoating.

Coverage—600-700 square feet per gallon—one coat.

Application—Old Work—Remove all dirt and grease and sandpaper sufficiently to remove the gloss of the old varnish. If the surface is badly marred and checked, take off the old varnish with varnish remover or sandpaper. Where two or more coats are used, reduce the first coat of varnish 10% with turpentine. Allow to dry overnight for complete drying of each coat.

New Work—Open grained woods should first be filled with Paste Wood Filler following directions on the label and when dry apply Rapidcote Varnish. If two or more coats are used reduce the first coat about 10% with turpentine.

Do not use over shellac, liquid wood fillers, wax or lacquer on floors.

Rapidcote.....	1's each	1/2's each
	\$4.71	\$1.37

Deduct 10 cents from 1-gallon price for 5's and barrels



GENERAL PURPOSE VARNISH

Type of Product—A dependable varnish for floors and all interior trim. Ideal for use where a durable, high gloss finish is desired. Dries dust free in from 2-3 hours and hard enough to walk on overnight.

Drying Time—Overnight. 24 hours for recoating.

Coverage—600-700 square feet per gallon.

Application—On Old Work—Remove all dirt and grease. Sandpaper sufficiently to remove gloss of the old varnish. If surface is badly marred and checked take off old varnish by scraping or with varnish remover.

On New Work—Open grained wood should first be filled with Paste Wood Filler. Where two or more coats are to be used, the first coat may be thinned with one pint of Turpentine to a gallon of varnish.

For best results: Do not use over Shellac, Shellac Substitute, Liquid Wood Filler, Wax or Lacquer.

Painters' Floor Varnish.....	1's each \$3.51	1/2's each \$1.07
------------------------------	--------------------	----------------------

PENETREX—FOR GYM FLOORS

Type of Product—A penetrating type of finish for floors. It affords unusual protection against staining and discoloration as well as imparting wearing qualities. This product penetrates deeply and seals the pores of the wood. It is best applied by brushing on to the surface for more than 15 minutes. A wood surface should be carefully sanded and made smooth before applying the varnish and a light mousing with steel wool is advisable between coats.

Drying Time—Overnight. 24 hours for recoating.

Coverage—500-600 square feet per gallon.

Application—Shake well before applying and stir occasionally during use. Floor surfaces should be free from all foreign matter and sanded carefully to a smooth surface, after which all dust should be carefully removed. Apply Penetrex as it comes from the can by either mopping or brushing it on to the surface. The best drying conditions are in temperatures of 70° F. After 20 minutes any excess material that has not been absorbed by the wood should be wiped from the surface with clean rags and in another hour the entire floor surface should be buffed with a pad of No. 2 steel wool to remove any grain of the wood that is raised, any excess material, and to produce a uniform appearance. Where two coats are to be applied allow 12 hours for complete hardening of the first coat. Any excess material remaining on the surface 10 minutes after the second coat is applied should be removed and the entire surface buffed with steel wool as recommended in the first coat application. Open grain woods require no filler as the second coat will sufficiently fill the open grain. Old floors previously finished must be cleaned free from all paint, varnish or other finishing materials previously used with either sanding equipment or paint and varnish remover. Where paint and varnish remover is used wash the surface thoroughly with naphtha to remove wax deposits.

Caution—All wiping rags and steel wool should be burned immediately after use.

Penetrex.....	1's each \$3.88	1/2's each \$1.17
---------------	--------------------	----------------------

LIQUID CEMENT COATING

Type of Product—Used to make dampproof and uniform in color, exterior and interior surface of concrete, cement, stucco, unglazed tile, brick and stone, without changing surface texture. Produces a pleasing effect which, in 90 days dulls down and takes on the true appearance of cement and stucco surfaces.

Drying Time—18 to 24 hours—48 hours or more for recoating.

Coverage—400 to 600 square feet per gallon.

Application—Pour off one-third of the liquid and completely break up and put into thorough suspension the solid matter at the bottom of the package. Replace liquid, stir thoroughly before and during use.

Any surface which shows indications of alkali should receive a wash coat made by dissolving two pounds of zinc sulphate crystals into a gallon of water. Apply freely and allow to dry thoroughly.

Old Painted Surfaces—Remove loose paint, touch up bare spots as recommended for prime coat on new work, then apply one coat of liquid Cement Coating.

New Unpainted Surfaces—First Coat. To each gallon of Liquid Cement Coating add one quart of Cement Mixing Liquid. This should be applied liberally and brushed well into pores. Allow forty-eight hours to dry. Second coat: Any spots on surface that show flat, should receive a second coat. Allow these spots to dry then apply a finish coat of Liquid Cement Coating full body. Brush out evenly and uniformly.

Liquid Cement Coating.....	1's each \$5.30
----------------------------	--------------------

CEMENT COATING MIXING LIQUID

Type of Product—This material is a light colored, transparent drying liquid of about the same gravity as linseed oil and will work easily under the brush. When spread in an even thin layer on glass it dries in about eighteen hours, forming a tough, elastic film similar to a Spar Varnish. It is obvious that thinning vehicles such as turpentine or benzine are wholly unsuited for use where Glidden Mixing Liquid is specified.

Application—Glidden Mixing Liquid is used in conjunction with Glidden Liquid Cement Coating as a thinning vehicle where its need is indicated, such as first coat on woodwork; also for use as a priming coat, in conjunction with Glidden Liquid Cement Coating, on broken places, and uneven areas in cement surfaces, which are to be brought up to the general level with Glidden Concrete Patching Compound. For these purposes, it is mixed with equal parts of Glidden Liquid Cement Coating. To each gallon of the mixture add one pint of pure Spirits of Turpentine.

Mixing Liquid.....	1's each \$3.53
--------------------	--------------------

Deduct 10 cents from 1-gallon price for 5's and barrels



BARN, TOOL SHED, WOOD BUILDING PAINTS

Type of Product—Offers the best protection for outside surfaces to be found at such low cost. A dependable paint for exterior use, with easy working qualities and good hiding power. Spreads easily and smoothly, drying slowly to a tough, glossy surface. Greatly improves the appearance of barns, fences, warehouses, factories and other structures of this type. Excellent for metal roofs and brick surfaces. Application of this paint increases the value of the property and protects the investment—all at an unusually low price. Unpainted or poorly protected surfaces are an unnecessary liability when a reliable Barn Paint can be applied for such a small outlay. Prevents deterioration and high replacement or maintenance charges.

Drying Time—24 to 36 hours.

Coverage—400-540 square feet per gallon—one coat.

Application—Stir well before using. Apply with a large bristle brush working it into the seams and cracks.

Old Painted Surfaces—Should be scraped or wire brushed to remove loose particles. Two coats are recommended, but if the surface is in good condition one coat may be sufficient. The paint may be thinned with raw linseed oil to make it work properly over porous surface.

New Wood Surfaces—For first coat on new wood, add one-half gallon linseed oil to one gallon of paint. Second coat may be applied full body as it comes in the can.

New Metal Surfaces—Roofs, eaves and down spouts should be carefully scraped to remove all rust and scales after which two coats of barn paint should be applied.

For Brick or Concrete—The first coat of barn paint should be reduced with Cement Mixing Liquid and any spots that show unusual absorption should be given a second application. Allow surface to dry at least 3 days before the second coat is applied full body.

Red—500.....	1's each
Gray—501.....	\$2.77
	4.12

E-Z-C MACHINERY ENAMELS

Type of Product—These are synthetic, fast-drying enamels for machine tools and equipment. The film is extremely tough to insure long wear. Have excellent resistance to the softening and discoloring action of cutting oils and compounds. Will withstand heavy impact and abrasion. This line also includes vismatic colors for work areas and control points on machinery.

Drying Time—12 hours—24 or more for recoating.

Coverage—500 to 600 square feet per gallon—one coat.

Application—Stir enamel well before using. The parts to be painted should be cleaned thoroughly to remove all dirt and smudge. All surfaces that have been subjected to grease or oil should be washed off with naphtha to insure a suitable surface for the paint or enamel to adhere to. The old surface on machinery should be sanded to remove the luster and to smoothen the edges of any chipped paint. Other surfaces, if not too glossy, can be painted without being sanded. If the material to be applied is similar in color to the surface to be coated, one coat will generally be sufficient. If two coats are to be used, thin the first coat with turpentine or mineral spirits to a thin brushing consistency. Apply the second coat full body as received.

Regular Colors — White and Gray Primers.....	1's each	½'s each
Vismatic Orange—Cream—Surf Green—Bud Green.....	\$4.65	\$1.35
	5.77	1.64

E-Z-C SAFETY ENAMELS

Type of Product—A durable quick-drying gloss enamel particularly adapted for use in industrial plants. Recommended for application according to approved safety color codes to identify machinery and equipment parts, and point out hazards to safety. Can be used on wood, steel, plaster, masonry, or wall board.

Drying Time—4 to 6 hours—24 hours for recoating.

Coverage—400 to 500 square feet per gallon—one coat.

Application—Before applying, remove all dust, dirt, grease, wax, or other foreign matter by washing thoroughly with turpentine, or naphtha. For brush application, reduce first coat 10% with turpentine, or mineral spirits. Apply second coat full body.

Regular Colors.....	1's each	½'s each
Pilot White.....	\$5.77	\$1.64
	4.50	1.53

E-Z-C PIPE IDENTIFICATION ENAMELS

Type of Product—A quick-drying, long-lasting gloss enamel designed for application on pipe lines to identify their contents in accordance with approved color codes.

Drying Time—4 to 6 hours—24 hours for recoating.

Coverage—400 to 500 square feet per gallon—one coat.

Application—All loose paint and scale should be removed by scraping and wire brushing. Remove all dirt, grease, or oil by washing with turpentine, or naphtha. Reduce first coat 10% with turpentine, or mineral spirits. Apply second coat full body.

All Colors.....	1's each	½'s each
	\$5.77	\$1.64

Deduct 10 cents from 1-gallon price for 5's and barrels



BLACKBOARD SLATING

Type of Product—A tough, abrasion resisting finish drying with a semi-gloss. Covers solidly with one coat.

Drying Time—5-6 hours.

Coverage—600 square feet per gallon.

Application—The surface to be finished should be free from all foreign matter and perfectly dry. One coat will give a good wearing, smooth writing surface, but two coats will wear longer because of the heavier film that is developed.

Blackboard Slating.....	1's each \$3.00	1/4's each \$.94
-------------------------	--------------------	---------------------

VISMATIC GREEN CHALKBOARD COATING

Type of Product—A new type of chalkboard coating that is colored green to allow maximum light reflection and ease of cleaning.

Drying Time—Overnight dry between coats.

Coverage—Brushing—350-400 square feet. Spraying—slightly less.

Application—Brush Method—Brush evenly, using a soft, well broken-in 3-inch brush, extending strokes in all directions, using care to have brush fairly full at all times. Apply full body or reduce if necessary with 1/4 pint of mineral spirits per gallon. One coat is usually sufficient; however 2 coats will give longer wear. Allow overnight drying between coats.

Spray Method—Reduce Coating with 1 pint of V M & P Naphtha to the gallon. One coat will usually be sufficient.

Preparation—Chalkboard must be cleaned to a dust-free surface. Any wax crayon or grease must be removed with turpentine or mineral spirits. Unsealed surfaces must be sealed with Glidden Spred Primer-Sealer or Glidden Interior Base Coat, not necessary on slate surfaces. Surfaces with a sheen should be sanded prior to applying the Coating.

Conditioning Chalkboards for Use—After coating has dried for 48 hours, apply chalk, broadside, over entire surface. Use felt eraser to work chalk into surface and remove excess with clean eraser.

Cleaning Chalkboard—Avoid washing as much as possible; when necessary use a sponge-rubber eraser. The chalk treatment previously described should be repeated after washing. Dry cleaning may be done by wiping with a dry chamolts or soft dry rag. Oil treated rags should not be used.

Green Vismatic Chalkboard Coating.....	1's each \$5.83	1/4's each \$1.65
--	--------------------	----------------------

ROMARK NO. 1

Type of Product—Retards bleeding on an asphalt or tar base surface. Dries in from 4 to 15 minutes to a film that will not blister, flake, crack or wash off. Makes it excellent as a sealer and primer for succeeding coats of paint on that type surface. Stripes show a clean cut edge and it can be applied either with a brush or machine.

Drying Time—4 to 15 minutes.

Coverage—250-300 square feet per gallon.

Application—Apply with brush or spray unit. Can be thinned with alcohol.

	5's per gal.	1's each
Romark No. 1 White.....	\$4.50	\$4.60
Romark No. 1 Yellow.....	4.75	4.85

ROMARK NO. 2

Type of Product—A traffic paint of as great durability as No. 1 but not suitable for use on any surface of which asphalt is the base. Will last from 3 to 5 months under heavy traffic and from 5 to 8 months under moderate.

Drying Time—45 to 60 minutes.

Coverage—One gallon will paint a stripe 5 inches wide and 800 feet long.

Application—Use naphtha only to thin Romark No. 2.

Romark No. 2 should be reduced with Naphtha to a viscosity best suited to the spraying equipment in use. It works best with a forty-pound atomization pressure at the gun, and ten-pound pressure at the tank, through standard spraying equipment.

For brushing, apply Romark No. 2 just as it comes from the container. If it becomes heavy in body, due to evaporation, use Naphtha only for thinning.

	5's per gal.	1's each
Romark No. 2 White.....	\$3.80	\$3.90
Romark No. 2 Yellow.....	3.75	3.85

SURFACENE

Type of Product—A clear liquid which can be applied to an old surface to deaden the gloss and create a bond for a new finish coat. Surfacing acts as a cleaner and will dissolve wax, grease, or polish which can be removed from old surfaces by simply wiping them off with a clean cloth.

Application—This material can be brushed or applied with a cloth. For old surfaces that are fairly clean, Surfacing may be added to the paint to furnish a bond and anchor the new finish to the old without crawling. A quarter pint to a gallon of any paint is recommended.

	1's each \$2.18	1/4's each \$.74
--	--------------------	---------------------

Deduct 10 cents from 1-gallon price for 5's and barrels



NEVA-ROT

Type of Product—A new war-proven preservative for application on all wood, fabrics and ropes. It has many uses in the home, on the farm, and anywhere insects, molds or fungus are active. Neva-Rot is toxic to organisms that destroy cellulose; it prevents the action of termites. Formulated in green and clear solutions.

Coverage—One gallon of Neva-Rot will treat 200 square feet of an average surface. Very rough wood may require one gallon per 100 square feet of surface.

Application—Applied by brushing, spraying, dipping or swabbing. Neva-Rot Green is particularly desirable for fence posts and all wood that is to come into contact with soil. Neva-Rot Clear is recommended for all surfaces where the Green color is not desired.

	5's per gal.	1's each
Neva-Rot Clear.....	\$2.78	\$2.88
Neva-Rot Green.....	2.14	2.24

ASPHALT PRODUCTS

MASTICRETE

Type of Product—A permanent and efficient material for patching, repairing and resurfacing all types of traffic-bearing surfaces of concrete, wood, metal, tile, terrazzo, asphalt, composition, etc. Eliminates the need for chipping, chopping, or in any other way preparing the surface, other than cleaning free from dirt, grease, oil or paint. It prevents costly production losses because repairs can be completed overnight. It is mixed with common cement mortars and when so used results in a tough, resilient surface, having all the general characteristics and strength of concrete but unlike concrete, will not chip, crack, crumble or dust. The surface is slipproof, skidproof, noiseless, waterproof, sparkproof and will not sustain combustion. It improves with use and will resist the severe abuse of heavily loaded steel wheel trucking equipment. Supplied ready for use without heating or special equipment, it can be applied by any handy man. Contains no oils or solvents and therefore can be used in confined areas without endangering applicators or contaminating water or food.

Drying Time—24 to 36 hours before use.

Application—If grease, oil or paint is present use a good caustic cleaner to remove it. See that the surface is free from dirt and dust. Flush with clear water as the surface should be damp when Primer is applied. Any excess water should be removed.

Brush on two coats of Masticrete Primer, allowing sufficient time for thorough drying. For surfaces to stand trucking and heavy traffic we recommend one part Portland Cement, two parts clean sharp sand, three parts one-quarter inch stone or gravel and two parts of Masticrete. For foot traffic use one part Portland Cement, four parts clean sharp sand, two parts Masticrete. Water should be added to either mass in a quantity sufficient to produce a consistency resembling mortar.

All materials are to be measured by volume, not weight. Place the Masticrete in the hole and level off. After an initial set, smooth with a wood finishing float when the mixture is intended for heavy loads and with a steel trowel for foot traffic mixtures.

	5's per gal.	1's each
Masticrete.....	\$1.08	\$1.18

MASTICRETE PRIMER

Type of Product—This is the priming or bonding coat for succeeding coats of Masticrete.

Application—If grease, oil or paint is present on the surface to be patched use a good caustic cleaner to remove it. See that the surface is free from dirt and dust. Flush with clean water as the surface should be damp when the Masticrete Primer is applied. Any excess water that stands on the surface should be removed.

Masticrete Primer should be reduced 50% with clean water and stirred well until all lumps have become broken up and dissolved before it is applied. The Primer should be applied in two coats and the first coat allowed to dry thoroughly before application of the second coat. The second should also be allowed to dry thoroughly before any of the Masticrete Patching Compound is applied.

The space to be patched should be primed for a distance extending at least 2 inches beyond the edge of the patch.

	5's per gal.	1's each
Masticrete Primer.....	\$1.08	\$1.18

FOUNDATION COATING

Type of Product—A pure asphalt waterproofing that contains no oils or solvents and is supplied in a consistency suitable for application with brush, spray gun or trowel. Ideal for waterproofing concrete, brick, stone and other masonry surfaces below grade. Used for dampproofing plaster board on interior masonry surfaces above grade, prior to plastering, it eliminates the need for furring and lathing.

Application—For best results, it should be applied in two separate coats, the first coat reduced approximately 50% with water and applied after the surface has been wetted down with water and allowed to remain damp while the first coat is being applied. The second coat should be applied as received, without reductions after the first coat has become thoroughly dry.

	5's per gal.	1's each
Foundation Coating.....	\$1.08	\$1.18

Deduct 10 cents from 1-gallon price for 5's and barrels



ALUMINUM ASPHALT ROOF PAINT

Type of Product—No. 145 Aluminum Asphalt Roof Coating is made with selected asphalts, the finest grade of aluminum flakes and solvents. It is recommended for tar paper, composition, or asphalt roofs. It will rejuvenate weathered roofs and insulate with a silvery sheet of aluminum, all in one coat. It sharply reduces roof and inside building temperature in hot weather. It decreases heat losses in cold weather.

Coverage—Covers approximately 225 to 300 square feet to the gallon, depending on roughness and porosity of the surface.

Application—May be applied by brush or spray, and comes ready to use.

Before application, broom or hose off all loose material and imbedded dirt. When the surface is dry, coat badly worn spots with Asphalt Roof Coating No. 1420 and repair leaks. Allow two weeks Summer weathering of Asphalt Roof Coating before applying the Aluminum Asphalt. Coal tar coatings should be allowed to harden before applying Aluminum Asphalt.

Follow with No. 145 Aluminum Asphalt on the surface with only enough brushing to secure a uniform film. It should be kept away from sparks or flames until the solvent has evaporated. This material may be used on metal roofs previously primed with metallic primers.

Note: As a word of caution, we suggest that operators work with their backs to the sun to avoid sunburn, and wear dark glasses to avoid eye damage.

Aluminum Asphalt Roof Paint.....	5's per gal. \$3.25	1's each \$3.35
----------------------------------	------------------------	--------------------

METALLITE

CHROME ALUMINUM

For Interior Surfaces

Type of Product—An extremely smooth, chrome-like, aluminum finish for use on radiators, furnace jackets, airducts, hot water tanks and heaters, pipes and other interior surfaces. Not recommended for surfaces subjected to temperatures between 400° F. and 600° F. For these temperatures use Glidden Heat-Resisting Metallite. Will not tarnish under ordinary conditions.

Drying Time—8 to 12 hours; 24 to 36 for recoating.

Coverage—600 to 700 square feet per gallon in one coat.

Application—Stir well before using and occasionally during use. Surface to be coated must be dry and free from grease and dirt. Apply in one direction only using a soft brush. Keep brush well filled with the Chrome Aluminum to insure a constant flow. If the product becomes too heavy, thin with turpentine or mineral spirits.

Interior Metallite Ready Mixed.....	1's each \$4.30	½'s each \$1.27
-------------------------------------	--------------------	--------------------

EXTERIOR METALLITE

Ready-Mixed—Aluminum

Type of Product—Metallite produces a smooth, enamel-like, polished aluminum finish. It will retain its brilliance over a long period of time. Furnishes ideal protection to structural steel, metal roofs, low-temperature smokestacks, farm equipment, and outer surfaces of storage tanks. Retards evaporation loss in storage tanks and reduces temperatures in buildings because the aluminum reflects the heat waves of the sun.

Drying Time—Overnight; 48 hours for recoating.

Coverage—600 to 700 square feet per gallon—one coat.

Application—Stir well before using and occasionally during use. The surface must be dry, free from all loose particles, dirt, grease and other foreign matter. Apply with a soft-bristle brush, keeping the brush well filled with Metallite. Do not brush back and forth, apply in one direction to secure a smooth, bright surface. If thinning is found necessary, use small amount of turpentine or mineral spirits.

Exterior Metallite Ready Mixed.....	1's each \$4.65	½'s each \$1.35
-------------------------------------	--------------------	--------------------

HEAT RESISTING METALLITE

Ready-Mixed—Aluminum

Type of Product—As its name implies, this product is intended for metal surfaces subjected to heat. At low surface temperatures the product is baked onto the surface while at high surface temperatures the Aluminum is fused to the surface. Not recommended for use at bases of smokestacks where heat is intense.

Application—Stir well before using and occasionally during use. The surface must be dry, free from all loose particles, dirt, grease and other foreign matter. Apply with a soft-bristle brush, keeping the brush well filled with Metallite. Do not brush back and forth, apply in one direction. If thinning is found necessary, use small amount of turpentine or mineral spirits.

1's each \$4.30	½'s each \$1.27
--------------------	--------------------

Deduct 10 cents from 1-gallon price for 5's and barrels



SMOKE STACK BLACK

Type of Product—A high gloss black for smoke stacks and all other surfaces that require a heat-resisting finish. Not only will it withstand high degrees of heat but it is unusually weather-resistant as well. This material is made on a varnish and carbon black base and should not be confused with the many asphalt products offered. Should withstand heat to 800° F.

Drying Time—Overnight—36-48 hours for recoating.

Coverage—400-500 square feet per gallon—one coat.

Application—Stir paint thoroughly with lifting motion. Surface must be dry and free from dirt, grease, rust and other foreign matters. Apply one or two coats Smoke Stack Black as received in the container, allowing sufficient time to dry between coats.

Smoke Stack Black.....	5's per gal. \$3.43	1's each \$3.53
------------------------	------------------------	--------------------

WOOD BLEACH

Type of Product—Has the amazing properties of bleaching practically any type of wood from its original color to an almost natural white and without any deposit of a salt of any kind in the pores of the wood, necessary to the production of the blond effects so popular and modern as present.

Application—

1. Sand wood thoroughly and dust before applying Wood Bleach.
2. Apply a wet coat of Wood Bleach with a small mop, clean soft rag, cotton waste.
3. Dry first application 8 hours and repeat for whiter bleaching.
4. The strength of Wood Bleach may be controlled by adding Distilled Water to the final mixture.
5. Allow Wood Bleach to dry thoroughly (not less than 12 hours) sand lightly and follow with desired finish.

Remove all old finish from surface of wood with paint and varnish remover, making as many applications as are necessary to remove all traces of the old finish. Then wash with a water solution of trisodium phosphate or soda. Rinse thoroughly with clear water. Allow to dry overnight before applying Wood Bleach.

CAUTION!

In mixing Wood Bleach USE ONLY GLASS, ENAMEL WARE OR HARD RUBBER CONTAINERS. Add one part of No. 2 to four parts of No. 1. Stir with glass or wood rod. USE NO METAL FOR MIXING OR STIRRING.

DO NOT mix more Wood Bleach than can be used in three hours. DO NOT—Pour unused mixture into either No. 1 or No. 2 Solution. DO NOT—Keep mixed solution in closed container. DO NOT—Store Wood Bleach in warm places or direct sunlight. USE RUBBER GLOVES in mixing and applying Wood Bleach. If Wood Bleach gets on hands wash thoroughly with cold water and vinegar and apply Hand Lotion.

NOTICE: Sometimes there is a precipitation in Solution No. 2. This material quickly goes back into solution when warmed. Submerge the bottle in warm water or by standing it on a radiator. The cork of the bottle should be loosened to prevent gas formation.

Wood Bleach.....	Large Unit \$7.30	Small Unit \$2.83
------------------	----------------------	----------------------

AD-EL-ITE NON-INFLAMMABLE PAINT & VARNISH REMOVER

Type of Product—Advantages over ordinary removers for removing baked enamel, paint, varnish, shellac, etc.: (1) It is non-inflammable. (2) It has a heavy body and therefore has less tendency to run and sag on upright surfaces. (3) Water may be used to clean remover from metal surfaces, mineral spirits or turpentine for other type surfaces. (4) Stays wet longer which permits working on larger areas.

Application—Apply remover with paint brush. Usually from 5 to 20 minutes is sufficient to soften the finish, depending upon the hardness and nature of the old finish. Remove softened finish with a broad knife and follow above for final cleaning. Before refinishing be sure surface is thoroughly clean and dry.

Note—Paint and Varnish Removers irritate the skin of some people. Protect the skin by applying Vaseline. CAUTION: Contains Volatile Chlorinated Solvent. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not take internally.

1's each \$3.47	¼'s each \$1.06
--------------------	--------------------

Deduct 10 cents from 1-gallon price for 5's and barrels



AD-EL-ITE PAINT & VARNISH REMOVER

Type of Product—The highest grade, most satisfactory remover manufactured. Contains no alkalies, acids, oils or water. Does not raise the grain or discolor wood. Very slow in evaporating, consequently very effective on old paint, varnish, enamel, lacquer or baked japan.

Ad-El-Itc Paint & Varnish Remover.....	1's each \$1.82	1/4's each \$.65
--	--------------------	----------------------

NO. 100 RUST INHIBITING OIL

Type of Product—A rust inhibitive primer for application to rusty steel and iron. A clear oil liquid of low surface tension and great penetrating qualities. It arrests rusting which has already begun and acts as a foundation (primer) for top coats of paint or enamel.

Application—If rust is of a dry, dusty nature, brush off the loose, excess particles. Then prime with No. 100 Rust Inhibiting Oil. Hard, scaly rust must be removed. Apply No. 100 Rust Inhibiting Oil liberally so as to penetrate thoroughly through and beneath it. It will tend to loosen the scales and make them easier to remove. See directions on label for complete details.

No. 100 Rust Inhibiting Oil.....	5's per gal. \$2.70	1's each \$2.80
----------------------------------	------------------------	--------------------

See separate list for prices on Spray-Day-Life and Related products.

For a complete color analysis and recommendations to suit your individual requirements, we urge you to take advantage of the facilities of our nationally known Color Laboratory. This service is available to you without cost, or obligation. Write for details.

Deduct 10 cents from 1-gallon price for 5's and barrels

TERMS AND CONDITIONS

This price list supersedes all previous lists, terms and other arrangements granted prior to this date, all of which are hereby cancelled.

We reserve the right at any time to refuse any order for any reason and further to grant these new prices and discounts to only those accounts we select as authorized agents for regularly labeled products.

Any tax, custom, import or export duties, or any other governmental charge on the production, sale or shipment (or any combination of these several) of the products listed in this price list or upon the materials from which they are produced, and whether imposed by Federal, State, Municipal, or other governmental authorities, and hereafter becoming effective and which have an effect upon the cost of these products, shall be added to the prices printed herein.

Terms—Our terms on paints, varnishes, enamels, stains, lacquers, white lead, turpentine, linseed oil and sundries not manufactured by us, are 30 days net, 1 per cent discount for cash in 10 days from date of invoice.

All shipments of paint products are forwarded f.o.b. our factories or nearest distributing points.

Notes on Ordering—Always give post office address and shipping directions, naming the delivering railroad.

To insure prompt attention all orders should be addressed to the firm and not to a representative.

Shortages and Claims—Shortages or errors in packing or invoicing must be reported immediately upon receipt of goods to enable proper checking and adjustment.

All claims for losses and damage enroute must be filed by the customer with the carrier. Be sure to have a proper official of the transportation company inspect all instances where there is concealed damage and report to them promptly all shortages and goods received in damaged condition, obtaining their notation on the freight bill to avoid inconveniences and the making of affidavits at a later date.

The manufacture, sale and delivery of all products mentioned in our price lists are contingent upon strikes, fires, floods, the elements, explosion, war, riot, embargoes, insurrection, acts of God, or the public enemy, acts of governmental authorities, labor troubles, delays of vendors or in transportation, inability to obtain raw materials or containers or transportation facilities, or any other causes beyond our control and we may cancel orders for said products undelivered because of any said causes.

All prices, terms and conditions are subject to change without notice.

National Headquarters

THE GLIDDEN COMPANY

11001 Madison Ave., Cleveland 2, Ohio

FACTORIES

Cleveland 2, Ohio, 11001 Madison Ave.
Chicago 16, Ill., 1833 S. Normal St.
Chicago 39, Ill., 1856 No. Le Claire Ave.
Minneapolis 13, Minn., 1901 E. Hennepin Ave

Toronto 9, Ont., 351 Wallace Ave.

New Orleans 8, La., 424 Josephine St.
Reading, Pa., Third and Bern Sts.
St. Louis 2, Mo., Main and Gratiot Sts.
San Francisco 7, Calif., 1800 7th St.

BRANCHES AND DISTRIBUTING POINTS

Atlanta, Ga.
Baltimore, Md.
Billings, Mont.
Birmingham, Ala.
Buffalo, N. Y.
Cambridge, Mass.
Charlotte, N. C.
Chattanooga, Tenn.
Chicago, Ill.
Cleveland, Ohio
Columbus, Ohio
Dallas, Texas

Detroit, Mich.
Duluth, Minn.
El Paso, Texas
Evansville, Ind.
Honolulu, T. H.
Houston, Texas
Huntington Park, Calif.
Indianapolis, Ind.
Jacksonville, Fla.
Knoxville, Tenn.
Long Beach, Calif.
Louisville, Ky.
Los Angeles, Calif.
Memphis, Tenn.

Miami, Fla.
Minneapolis, Minn.
Mobile, Ala.
Montreal, Quebec, Canada.
Mt. Vernon, Ill.
New Orleans, La.
Norfolk, Va.
North Bergen, N. J.
Oklahoma City, Okla.
Omaha, Neb.
Orlando, Fla.
Philadelphia, Pa.
Portland, Ore.
Reading, Pa.

Richmond, Va.
St. Louis, Mo.
St. Petersburg, Fla.
San Antonio, Texas
San Diego, Calif.
San Francisco, Calif.
Scranton, Pa.
Sioux Falls, S. D.
Tampa, Fla.
Toledo, Ohio
Washington, D. C.
West Palm Beach, Fla.
Winnipeg, Man., Canada