 O'BRIEN[®]

REGISTERED

SS/3

10-12-65

"75"[®] HOUSE PAINT

FOR ANY EXTERIOR SURFACE

IVORY

MADE BY THE O'BRIEN CORPORATION

ONE GALLON

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES, CAL.

"75" HOUSE PAINT

White and Colors — A whiter white and standard colors formulated for longer life and better color retention in all climates.

Base No. 1 & No. 2 — Special white bases to be tinted with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. May be used for both body and trim.

"75" Trim & Tinting White — Non-chalking finish for body or trim. May be tinted.

"75" Priming White — Low-lustre primer for standard colors, bases, and for trim and tinting white. May be tinted.

"75" Trim White & Colors — Ready-mixed for trim use only. For new wood, first coat to be reduced with one pint of turpentine or mineral spirits per gallon (do not use other primers). Apply at package consistency over previous paint.

Preparation

Surface must be clean and dry. Remove chalk and loose paint. Repair flashings and provide adequate ventilation for trapped moisture. Sand and dull glossy areas under eaves and protected areas.

Priming

Spot prime previous paint as needed. Prime new wood, or previous paint in poor condition, with "75" Priming White. Tint primer toward topcoat with Tone-All, Oil Colors, or by mixing with finish coat for deeper colors. Prime new or bare metal with Flexico Metal Primer. Etch galvanized metal before priming.


Application

Stir well. Apply one or more coats as needed at temperature not less than 60° F. If thinning is desired, use turpentine or mineral spirits up to one-half pint per gallon. Allow 48 hours good drying weather between coats. Covers up to 500 sq. ft. per gallon.

CAUTION! COMBUSTIBLE!
CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" HOUSE PAINT TINT BASE	
Pigment	56.46%
Barium Sulfate	9.55%
Titanium Dioxide	22.95%
Lead Oxide	36.07%
Calcium Hydroxide	100.00%
Magnesium Silicate	100.00%
Vehicle	43.54%
Low Lustre Oil	41.69%
Thermallyzed Tung Oil	2.84%
Mineral Spirits and Driers	28.71%
Less Than 5% Tinting Colors Added	100.00%

"Be Sure The Paint You're Buyin' Is O'Brien"



O' B R I E N

"75"
HOUSE PAINT

FOR ANY EXTERIOR SURFACE

CREAM

MADE BY THE O'BRIEN CORPORATION

ONE GALLON

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES

"75" HOUSE PAINT

White and Colors — A whiter white and standard colors formulated for longer life and better color retention in all climates.

Base No. 1 & No. 2 — Special white bases to be tinted with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. May be used for both body and trim.

"75" Trim & Tinting White — Non-chalking finish for body or trim. May be tinted.

"75" Priming White — Low-lustre primer for standard colors, bases, and for trim and tinting white. May be tinted.

"75" Trim White & Colors — Ready-mixed for trim use only. For new wood, first coat to be reduced with one pint of turpentine or mineral spirits per gallon (do not use other primers). Apply at package consistency over previous paint.

Preparation

Surface must be clean and dry. Remove chalk and loose paint. Repair flashings and provide adequate ventilation for trapped moisture. Sand and dull glossy areas under eaves and protected areas.

Priming

Spot prime previous paint as needed. Prime new wood, or previous paint in poor condition, with "75" Priming White. Tint primer toward topcoat with Tone-All, Oil Colors, or by mixing with finish coat for deeper colors. Prime new or bare metal with Flexico Metal Primer. Etch galvanized metal before priming.

Application

Stir well. Apply one or more coats as needed at temperature not less than 60° F. If thinning is desired, use turpentine or mineral spirits up to one-half pint per gallon. Allow 48 hours good drying weather between coats. Covers up to 500 sq. ft. per gallon.

CAUTION! COMBUSTIBLE!
CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" HOUSE PAINT TINT BASE	
Pigment	56.46%
Barium Oxide	9.84%
Titanium Dioxide	12.75%
18% Treated Zinc Oxide	34.07%
Magnesium Silicate	31.14%
	100.00%
Vehicle	43.54%
Raw Unseed Oil	41.03%
Heat Treated Linseed Oil	26.84%
Mineral Spirits	28.75%
Mineral Spirits and Driers	28.75%
	100.00%
Less Than 2% Tinting Color Added	

"Be Sure The Paint You're Buyin' Is O'Brien"





O' B R I E N

"75"
HOUSE PAINT

FOR ANY EXTERIOR SURFACE

WHITE

WHITEST WHITE • 1 COAT HIDING

MADE BY THE O'BRIEN CORPORATION

ONE GALLON

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES

"75" HOUSE PAINT

White and Colors — A whiter white and standard colors formulated for longer life and better color retention in all climates.

Base No. 1 & No. 2 — Special white bases to be tinted with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. May be used for both body and trim.

"75" Trim & Tinting White — Non-chalking finish for body or trim. May be tinted.

"75" Priming White — Low-lustre primer for standard colors, bases, and for trim and tinting white. May be tinted.

"75" Trim White & Colors — Ready-mixed for trim use only. For new wood, first coat to be reduced with one pint of turpentine or mineral spirits per gallon (do not use other primers). Apply at package consistency over previous paint.

Preparation

Surface must be clean and dry. Remove chalk and loose paint. Repair flashings and provide adequate ventilation for trapped moisture. Sand and dull glossy areas under eaves and protected areas.

Priming

Spot prime previous paint as needed. Prime new wood, or previous paint in poor condition, with "75" Priming White. Tint primer toward topcoat with Tone-All, Oil Colors, or by mixing with finish coat for deeper colors. Prime new or bare metal with Flexico Metal Primer. Etch galvanized metal before priming.

Application

Stir well. Apply one or more coats as needed at temperature not less than 60° F. If thinning is desired, use turpentine or mineral spirits up to one-half pint per gallon. Allow 48 hours good drying weather between coats. Covers up to 500 sq. ft. per gallon.

CAUTION! COMBUSTIBLE!
CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**

"75" HOUSE PAINT — WHITE	
Pigment	59.99%
Barium Sulfate	16.37%
Basic Carbonate White Lead	2.43%
18% Lead Zinc Oxide	2.43%
Iron Oxide	2.43%
Amorphous Silicate	20.99%
	100.00%
Vehicle	40.01%
Raw Untreated Oil	19.68%
Thermally Treated Oil	2.82%
Thermally Treated Tung Oil	30.60%
Mineral Spirits & Driers	100.00%

"Be Sure The Paint You're Buyin' Is O'Brien"

