



DURABLE

Made for exterior use to with-
stand extremely severe weather
conditions.

Granits

LAB TESTED

barn & roof paint

RED

EASY TO USE

Brush or spray it on the surface.
To spray reduce 5% with paint
thinner or turpentine. Use 30-40
lbs. air pressure.

GLD018217

Satisfaction Guaranteed

Grants Barn & Roof Paint for application on barns, fences, out-buildings of wood, metal or concrete, and roofs of metal or wood shingles. Made from oxide pigments and treated oils to make it durable. Stir contents thoroughly before and occasionally while using. Apply with a wide brush, working the paint well into the surface.

On new wood surfaces thin first coat in proportion of 1 qt. of linseed oil to the gallon of paint. Allow 2 or 3 days drying time then apply a coat of paint full body. This same system may be followed for new masonry or metal surfaces.

On old painted surfaces, wire brush, scrape or sand surface to remove loose particles and all foreign matter. Apply one or two coats of paint.

WARNING — FLAMABLE — Keep away from heat, sparks and open flame. Use with adequate ventilation. Keep container closed when not in use. May contain lead compound. Avoid prolonged or repeated breathing of vapors, spray mist, and dust when wire brushing or sanding, also prolonged or repeated contact with skin. Do not take internally. Before smoking or eating and after using, cleanse hands thoroughly. Keep out of the reach of children.

CAUTION! COMBUSTIBLE — Keep from Heat and Open Flame. CONTAINS LEAD OR OTHER COMPOUNDS HARMFUL IF EATEN. Do not apply on interior surfaces of a dwelling or a place used for the care of children, or on windowsills, toys, cribs, and other furniture which might be chewed by children. Avoid breathing vapor, spray mist, or dust, if sanding, and prolonged contact with skin may cause skin irritation. Wash thoroughly after handling and before eating or smoking. Do not take internally. Keep container closed when not in use. Keep Out of the Reach of Children. Use with Adequate Ventilation. (IV-381)

W. T. GRANT CO.

NEW YORK 18, N. Y., U.S.A.

1 U. S. Gallon or 128 Liquid Ounces

Iron Oxide	13.0%	Silica and Silicates	1.6
Zinc Oxide	2.6	Treated Soya Oil Prepared Rosin	26.2
Calcium Carbonate	28.0	Mineral Spirits and Driers	27.8
Lead Oxide	.8		

More than 1% Lead — Flash Point over 80 deg. F. 100.0%

912810079

THE GLIDDEN COMPANY
900 Union Commerce Bldg.
Cleveland-14, Ohio

W. T. Grant Company
New York 18, New York

Grant's Lab-Tested Barn & Roof Paint - Red

Receipt not required
W.T.

ARMOUR T. HART
PRODUCTION REG. SUPER.
Virgin

612810079