

DIESEL TACHOMETERS

HIGHEST QUALITY PRECISION ELECTRIC TACHOMETERS FOR DIESEL TACH-GENERATOR SYSTEMS

ICC Regulations require large trucks to make an immediate stop and repair or replace inoperative tachometers.

Simplest tachometers to install — no make-or-break points in generator therefore longer, maintenance free life.


No batteries or relays to check or replace.

No battery replacement.


No maintenance care necessary — gives higher accuracy over longer periods.

Four shunts provided with Tach heads take care of ratio changes — no different power units to stock and handle.


**STANDARD
90° SCALE
HEAD**



**SWEEP SCALE
250°
HEAD**



**RUGGEDIZED
AND SEALED
HEAD**



Available in 4 RPM ranges and in three head styles.

(Wired for Illumination)

R.P.M. Range	Standard 90° Scale	Sweep Scale 250° Scale	Ruggedized and Sealed 90° Scale
0-2000	3-5700	3-5701	3-5702
0-2500	3-5703	3-5704	3-5705
0-3000	3-5706	3-5707	3-5708
0-4000	3-5709	3-5710	3-5711

Standard and Sweep Scales can be mounted in 3 3/8" dia., SAE Standard panel cut-out or may be mounted on column or above dash using Balkamp Chrome Housing 3-569.

Ruggedized and Sealed head is designed for severe environment and vibration. Meter movement internally suspended in shock mounts and entire head is hermetically sealed, mounts into 3 3/8" dia. panel cut-out. Non-illuminated.

NOTE: For specific Diesel Applications, see Balkamp Automotive Parts and Service Items Master Catalog.

DIESEL TACHOMETER GENERATOR 3-5730



A sealed unit rotating magnet, fixed coil, digital pulse type with no brushes or contacts. Equipped with unique spring drive tongs to fit standard round SAE drives and includes extra long tong for mating with the standard square SAE drive.

3-5731 GENERATOR EXTENSION provides clearance for certain Mack trucks.

OUR METERS

**Sealed-Water and Dust Proof
Heavy Bearings—Shockproof Odometer
High Voltage Insulation**

**3-9330
3-9331**

**Stirrup Mount
Screw Mount**

These fine hour meters are for all direct current applications within a range of 4-40 D.C. Fits all nominal electrical systems 6-12-24-36 volts. Has 2" metal dial in black plastic case. 3-9330 has chrome bezel and 3-9331 has a black one. Dials have white lettering; black numerals show total accumulated hours, while red numerals show tenths of hours. Has a total read out of 9999.9 then repeat automatically.

These meters can be used on portable air compressors, earth moving machine construction, farm tractors, truck fleets, cranes, dredges, shovels, power pumps, generator sets, boats, aircraft, trains, lift trucks. Contains necessary mounting hardware.



3-9331



3-9330