



ROCKBESTOS WIRE & CABLE CO.

DIVISION OF CERRO CORPORATION

NEW HAVEN · CONN 06534

September 26, 1966

TO ALL ROCKBESTOS PRICE SHEET HOLDERS:

SUBJECT: PRICE CHANGE

Earlier this year it was necessary for Rockbestos to apply a copper adder of 20¢ a lb., which reflected a part of the increment in our cost over the domestic producers' price level of 36¢ a lb. We are pleased to announce that as a result of some reduction in these premiums, it is possible for us to eliminate a part of this cost to you.

The attached sheets reflect an increase of approximately 5 percent in the prices previously published, but with the elimination of the copper adder will reflect, in most instances, a significant decrease in the billing prices.

Please replace your Rockbestos price sheets as follows:

CANCEL: Price Sheets dated Nov. 15, 1965

INSERT: Complete new schedule dated Sept. 26, 1966

Any requests for additional sheets or changes in mailing instructions should be sent to the Rockbestos branch office nearest you. The back of our price sheets includes the addresses of these offices.

Very truly yours,

A handwritten signature in dark ink, appearing to read "E. S. Reed".

E. S. REED
General Sales Manager

K.
Encl.

(Pricing Memo #63)

RBB 00564

INDEX OF WIRES AND CABLES
BY ROCKBESTOS TABLE LETTER

TABLE	DESCRIPTION	Page
A	600 Volt Rheostat Wire (Solid)	3
A-300	300 Volt Rheostat & Stave Wire (Solid)	3
ACM-313(108)	1000 Volt Switchboard Cable	23
B	600 Volt A.V.C. Switchboard Wire (Solid)	20
BS	600 Volt A.V.C. Switchboard Wire (Stranded)	20
BH	600 Volt A.V.C. Hinge Cable	20
C	600 Volt A.V.C. Lighting & Control Wire	7
CV	2/C 600 Volt A. V. C. Flexible Cord	4
E	600 Volt A.V.C. Power Cable (1/C)	7
EC	600 Volt A.V.C. Power Cable (3/C)	9
ECL	600 Volt A.V.C. Power Cable Lead (3/C)	9
EL	600 Volt A.V.C. Power Cable Lead (1/C)	9
EMA	1000 Volt Control & Switchboard Cable	23
E3AA	600 Volt Aluminum Armored Power Cable (3/C)	9
E3AS	600 Volt Steel Armored Power Cable (3/C)	9
FS	300 Volt Fixture Wire (Stranded)	5
FSB	300 Volt Fixture Wire (Stranded) plus cotton braid	5
L	600 Volt A.V.C. Motor Lead Cable	8
LH	120 Volt Heating Cable	25
LHV	440 Volt Heating Cable	25
MD	600 Volt A.V.C. Control Cable (#12 19/25)	13
ML	600 Volt Mining Cable	8
MT	600 Volt A.V.C. Control Cable (#9 19/22)	13
PMD, PMT	600 Volt PNR Control Cable (Sizes 12 - 9)	14
PMDAS	600 Volt PNR Armored Control Cable (Size 12)	18
PMDX, PMTX	600 Volt Special PNRX-90 Control Cable (Sizes 12 - 9)	17
PMF	600 Volt PNR Control Cable (Size 14)	15
PMFX	600 Volt Special PNRX-90 Control Cable (Size 14)	18
PMPH	600 Volt PNR Control Cable (Size 16)	16
PND, PNF, PNT	600 Volt 1/C PN Wire (Sizes 12 - 14 - 9)	15
PNDX, PNFX, PNTX	600 Volt Special 1/C PN Wire (Sizes 12 - 14 - 9)	15
ROCKZONE® I	600 Volt Control & Apparatus Lead Wire	26
ROCKZONE® II	Control & Apparatus Lead Wire	26
ROCKZONE® III	Control & Apparatus Lead Wire	26
ROCKZONE® I	600 Volt Power Cable	27
ROCKZONE® II	600 Volt Power Cable	28

Rockbestos Wire & Cable Co. - Div. of Cerro Corporation-New Haven, Conn.

RBB 00565

INDEX OF WIRES AND CABLES
BY ROCKBESTOS TABLE LETTER

TABLE	DESCRIPTION	Page
ROCKZONE® III	600 Volt Power Cable	29
X LINK	600 Volt 90°C Control Cable	30
X LINK	600 Volt 125°C Control Cable	31
X LINK	600 Volt 90°C 3/C Interlocked Armor Power Cable	32
R	600 Volt Rheostat Cable	3
RF	600 Volt Apparatus Cable	4
R-300	300 Volt Coarse Stranded Rheostat Cable	4
SIS	600 Volt X Linked Polyethylene Switchboard Wire, Solid	24
SISS	600 Volt X Linked Polyethylene Switchboard Cable, Coarse Stranded	24
SISF	600 Volt X Linked Polyethylene Hinge Cable, Flexible Stranded	24
SPB	600 Volt Thermoplastic Switchboard Wire (Sol)	22
SPBS	600 Volt Thermoplastic Switchboard Wire (Str)	22
SPBH	600 Volt Thermoplastic Hinge Cable	22
SR-AW	600 Volt Silicone Rubber Glass Appliance Wire	11
SR-C	600 Volt Silicone Rubber Glass Lighting Wire	10
SR-E	600 Volt Silicone Rubber Asbestos Power Cable	11
SR-H	5000 Volt Silicone Rubber Asbestos Power Cable	12
SR-HC	440 Volt Silicone Rubber Heating Cable	25
SR-FWC	600 Volt Silicone Rubber Fixture Wire (Type SF2)	6
SR-FWF	600 Volt Silicone Rubber Fixture Wire (Type SFF2)	6
SR-FWT	300 Volt Silicone Rubber Fixture Wire (Type SFF1)	6
SR-MD	600 Volt Silicone Rubber Control Cable Braided (#12 19/25)	19
SR-MF	600 Volt Silicone Rubber Control Cable Braided (#14 19/27)	19
SR-ML	600 Volt Silicone Rubber Glass Motor Lead Cable	10
SR-MLA	600 Volt Silicone Rubber Asbestos Motor Lead Cable	10
TC	Armored Thermostat Wire (Solid)	25
V (Type)	Varnished-Cambric Power Cable (600 - 5000 Volt)	9
W	300 Volt Apparatus Cable	4
WSC (F)	Appliance Lead Wire (Moistemp)	5
XBNF	Appliance Lead Wire Nickel Conductor (HiTemp)	5
XB	600 Volt Switchboard Wire (Thermoplastic & Asbestos) Solid	21
XBS	600 Volt Switchboard Wire (Thermoplastic & Asbestos) Coarse Str.	21
XBH	600 Volt Hinge Cable (Thermoplastic & Asbestos) Flex. Stranded	21
XSC (F)	Appliance Lead Wire (Hitemp)	5
ZM	1000 Volt Hookup Wire	23

ISSUE #10
SEPT. 26, 1966
Replaces Sheet
dated Nov. 15, 1965
Changes: Min. order value

ROCKBESTOS WIRE & CABLE CO.

Division of CERRO CORPORATION

Main Office and Works

NICOLL AND CANNER STS., NEW HAVEN 4, CONN., U. S. A.

TERMS and CONDITIONS OF SALE

QUOTATIONS AND PRICING OF ORDERS

1. Price in effect at time of shipment.
2. Minimum order value and quantity
 - a) Stock material: \$50.00 or (1) Standard package, whichever is higher.
 - b) Non stock materials: see each table.
3. Terms of payment: $\frac{1}{2}\%$ 10 days from date of invoice, net 30 days.
4. Special Taxes:
Special state or local taxes will be added to invoices on which they are applicable. Where the taxes do not apply, proper exemption certificates should be furnished.
5. Delivery Point:
On shipments of 500 lbs. or more, prices are f.o.b. factory or warehouse with lowest transportation costs allowed to destination in continental United States except Alaska (nearest freight station or common carrier delivery point). On shipments of less than 500 lbs., prices are f.o.b. point of shipment.
The term "Continental U.S." is defined and applied as follows:
 - A. Where shipment is made to Panama Canal Zone or Hawaii by boat from New York, it will be made f.o.b. factory with transportation charges prepaid or allowed to port of discharge provided the weight of the shipment is 500 lbs. or more.
 - B. Shipment from any point on the West Coast to any destination outside the United States mainland will be made f.o.b. the West Coast point with no transportation charges allowed.
 - C. All shipments to any point in Alaska will be made f.o.b. Seattle, Washington, transportation charges from Seattle to Alaska destination to be paid by purchaser. The transportation charges for shipments from factory or warehouse to Seattle to be charged or allowed as determined by weight of shipment.
6. Reels:
Returnable reels are not included in price of cable but shall be charged separately. If such reels are returned to point of origin, freight collect, within 12 months from date of shipment, credit will be allowed at prices charged less any reasonable repair charges.
7. Acceptance of Orders:
All orders or contracts are subject to written acceptance by the Rockbestos Wire & Cable Co. Division of Cerro Corporation. The mailing of our form acknowledgment sheet is deemed to be "written acceptance," and unless otherwise stated in writing, current terms and conditions of sale will apply.
8. Inspection Point:
Inspection point, on which customers' acceptance of material is based, is at the factory, New Haven, Connecticut. After material has been approved and released for shipment, further claims will be limited to provisions of Guarantee, Section 10.
9. Quantity Variation:
Quantity shipped against any item of an order is subject to variation of plus or minus 10 percent of the quantity ordered on that item.
10. Warranty:
The Rockbestos Wire & Cable Co. Division of Cerro Corporation warrants that the cable furnished is free from defects of material and workmanship, except such defects as are commercially acceptable and that such warranty shall be understood to be in lieu of and to exclude all other warranties expressed or implied by operation of law or otherwise.

RBB 00567

INDEX

N.E.C. Type	Rockbestos Table Letter	Description	Page
A	XSC(F)	300 Volt Appliance Lead Wire (Hitemp)	5
A	XBNF	300 Volt Appliance Lead Wire Nickel Conductor (Hitemp)	5
AA	A-300	300 Volt Rheostat & Stove Wire (Solid)	3
AA	R-300	300 Volt Rheostat Cable (Coarse Stranded)	4
AA	W	300 Volt Apparatus Cable	4
AF	FS	300 Volt Fixture Wire (Stranded)	5
AF	FSB	300 Volt Fixture Wire (Stranded) plus cotton braid	5
AI	WSC(F)	300 Volt Appliance Lead Wire (Moistemp)	5
AIA	A	600 Volt Rheostat Wire (Solid)	3
AIA	R	600 Volt Rheostat Cable (Stranded)	3
AIA	RF	600 Volt Apparatus Cable	4
AVA	C	600 Volt AVC Lighting & Control Wire	7
AVA	E	600 Volt AVC Power Cable	7
AVA	L	600 Volt AVC Motor Lead Cable	8
	E3AS	600 Volt AVC Steel Armored Power Cable (3/c)	9
	E3AA	600 Volt AVC Aluminum Armored Power Cable (3/c)	9
	EC	600 Volt AVC Power Cable (3-c) Braided	9
	MD	600 Volt AVC Control Cable (No. 12 19/25)	13
	MT	600 Volt AVC Control Cable (No. 9 19/22)	13
AVB	B	600 Volt AVC Switchboard Wire (Solid)	20
AVB	BS	600 Volt AVC Switchboard Wire (Stranded)	20
AVB	BH	600 Volt AVC Hinge Cable	20
	ECL	600 Volt AVC Power Cable Lead (3/c)	9
AVL	EL	600 Volt AVC Power Cable Lead (1/c)	9
SA	SR-E	600 Volt Silicone Rubber Asbestos Power Cable	11
SF-2	SR-FWC	600 Volt Silicone Rubber Fixture Wire	6
SFF-1	SR-FWT	300 Volt Silicone Rubber Fixture Wire	6
SFF-2	SR-FWF	600 Volt Silicone Rubber Fixture Wire	6
SIS	SIS	X Link polyethylene Switchboard Wire, 600 volt, Solid	24
SIS	SISS	X Link polyethylene Switchboard Cable, 600 volt, Coarse stranded	24
SIS	SISF	X Link polyethylene Hinge Cable, 600 volt, Flexible stranded	24
TA	XB	600 Volt Switchboard Wire (Thermoplastic and Asbestos) - Solid	21
TA	XBS	600 Volt Switchboard Wire (Thermoplastic and Asbestos) - Coarse Stranded	21
TA	XBH	600 Volt Hinge Cable (Thermoplastic and Asbestos) - Flexible Stranded	21
TBS	SPB	600 Volt Thermoplastic Switchboard Wire (Solid)	22
TBS	SPBS	600 Volt Thermoplastic Switchboard Wire (Stranded)	22
TBS	SPBH	600 Volt Thermoplastic Hinge Cable	22
V	V(Type)	Varnished Cambric Power Cable (600-5000 Volt)	9

I N D E X (Continued)

Rackbestos Table Letter	Description	Page
CV	2/C 600 Volt AVC Flexible Cord	4
EMA	1000 Volt ACA Control and Switchboard Cable	23
108	1000 Volt ACA Switchboard Cable	23
LH	120 Volt Heating Cable	25
LHV	440 Volt Heating Cable	25
ML	600 Volt AVC Mining Cable	8
PMD, PMT	600 Volt PNR Control Cable (sizes - 12 - 9)	14
PMDAS	600 Volt PNR Armored Control Cable (size - 12)	18
PMDX, PMTX	600 Volt Special PNRX-90 Control Cable (sizes - 12 - 9)	17
PMF	600 Volt PNR Control Cable (size 14)	15
PMFX	600 Volt Special PNRX-90 Control Cable (size 14)	18
PMPH	600 Volt PNR Control Cable (size 16)	16
PND, PNF, PNT	600 Volt 1/c PN Wire (sizes - 12 - 14 - 9)	15
PNDX, PNFX, PNTX	600 Volt Special 1/c PNX-90 Wire (sizes - 12 - 14 - 9)	15
ROCKZONE® I	600 Volt Control & Apparatus Lead Wire	26
ROCKZONE® II	Control & Apparatus Lead Wire	26
ROCKZONE® III	Control & Apparatus Lead Wire	26
ROCKZONE® I	600 Volt Power Cable	27
ROCKZONE® II	600 Volt Power Cable	28
ROCKZONE® III	600 Volt Power Cable	29
X LINK	600 Volt. 90°C Control Cable	30
X LINK	600 Volt. 125°C Control Cable	31
X LINK	600 Volt 90°C 3/C Interlocked Armor Power Cable	32
SR-AW	600 Volt Silicone Rubber Glass appliance Wire	11
SR-C	600 Volt Silicone Rubber Glass Lighting Wire	10
SR-H	5000 Volt Silicone Rubber Asbestos Power Cable	12
SR-HC	440 Volt Silicone Rubber Heating Cable	25
SR-MD	600 Volt Silicone Rubber Control Cable (No. 12-19/25)	19
SR-MF	600 Volt Silicone Rubber Control Cable (#14 19/27)	19
SR-ML	600 Volt Silicone Rubber Glass Motor Lead Cable	10
SR-MLA	600 Volt Silicone Rubber Asbestos Motor Lead Cable	10
TC	Armored Thermostat Wire (Solid)	25
ZM	1000 Volt ACA Hookup Wire	23

 Terms and Conditions of Sale
 Conduit Fill Weights and Diameters
 Offices

Front Cover
 33
 Back Cover

RBB 00569

TABLE A-
N.E.C. TYPE AIA
Rheostat Wire 600 Volt, Underwriters listed
Solid copper, all asbestos
125°C (257°F)

Size	Stranding	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M.Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
14	Solid	\$ 89.40	\$ 79.40	\$ 74.80	\$ 66.20	500'C	.204	32
12	"	104.00	91.80	86.40	76.50	500'C	.221	42
10	"	124.00	110.00	104.00	91.40	500'C	.242	55
8	"	169.00	150.00	142.00	125.00	500'C	.269	78
6	"	312.00	278.00	262.00	231.00	500'R	.322	122
4	"	411.00	365.00	344.00	304.00	500'R	.364	177
2	"	603.00	536.00	504.00	446.00	500'R	.418	259

Stock sizes: 12 thru 2 Black
Non Stock sizes: Prices on request
Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color 6 and smaller - 2500 ft; 4 and larger - 500 ft.

TABLE A-300
N.E.C. TYPE AA
Rheostat and Stave Wire, 300 Volt, Underwriters' listed
Solid copper, all asbestos
200°C (392°F)

Size	Stranding	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M.Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
14	Solid	\$ 89.40	\$ 79.40	\$ 74.80	\$ 66.20	500'C	.204	29
12	"	104.00	91.80	86.40	76.50	500'C	.221	38

Stock sizes: 14 and 12 White
Non Stock sizes: See prices on Table A above
Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 6 and smaller - 2500 ft; 4 and larger - 500 ft.

TABLE R
N.E.C. TYPE AIA
Rheostat Cable, 600 Volt, Underwriters listed
Coarse stranded copper, all asbestos
125°C (257°F)

Size	Stranding	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M.Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
14	7/.0242	\$ 116.00	\$ 103.00	\$ 96.80	\$ 85.70	500'C	.213	33
12	7/.0305	126.00	112.00	105.00	92.70	500'C	.252	47
10	7/.0385	145.00	129.00	121.00	107.00	500'C	.276	63
8	7/.0486	181.00	161.00	152.00	134.00	500'C	.306	89
6	7/.0612	369.00	328.00	309.00	273.00	500'R	.384	140
4	7/.0772	470.00	418.00	394.00	348.00	500'R	.432	199
2	7/.0974	735.00	653.00	615.00	544.00	500'R	.492	286

Stock sizes: 14 to 2 Black
Non Stock sizes: Prices on request
Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 2500 ft; 6 and larger - 500 ft.

ISSUE #10
SEPT. 26, 1966

Replaces Issue
dated Nov. 15, 1965

TABLE R-300

N.E.C. TYPE AA

Rheostat Cable, 300 Volt, Underwriters' listed
Coarse stranded copper, all asbestos
200°C (392°F)

Stock sizes: None. Prices on request (See table R)
Quantities of any item less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 2500 ft; 6 and larger - 500 ft.

TABLE RF

N.E.C. TYPE AIA

Apparatus Cable, 600 Volt, Underwriters' listed
Flexible stranded tinned copper, all asbestos
125°C (257°F)

Size	Stranding	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M. Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
12	65/.010	\$ 142.00	\$ 126.00	\$ 119.00	\$ 105.00	500'C	.255	48

Stock sizes: 12 Black
Non Stock sizes: Prices on request
Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 2500 ft; 6 and larger - 500 ft.

TABLE W

N.E.C. TYPE AA

Apparatus Cable, 300 Volt, Underwriters' listed
Extra Flexible stranded copper, all asbestos
150°C (302°F)

Size	Stranding	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M. Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
14	104/34	\$ 109.00	\$ 96.50	\$ 90.90	\$ 80.40	500'C	.217	31
12	259/36	124.00	111.00	104.00	91.80	500'C	.242	44
10	413/36	161.00	143.00	135.00	119.00	500'C	.270	59
8	665/36	250.00	222.00	210.00	185.00	500'C	.305	80
6	1050/36	319.00	284.00	267.00	236.00	500'R	.365	134
4	1666/36	531.00	472.00	445.00	393.00	500'R	.435	200
2	2646/36	854.00	759.00	715.00	632.00	500'R	.510	298
1	3332/36	1102.00	980.00	923.00	816.00	500'R	.600	368
1/0	4214/36	1190.00	1058.00	996.00	881.00	500'R	.640	488
2/0	5292/36	1604.00	1426.00	1343.00	1188.00	500'N/R	.700	578
4/0	8512/36	2337.00	2078.00	1957.00	1731.00	500'N/R	.840	916

Stock sizes: 14 thru 1 and 4/0
Non Stock sizes: Prices on request
Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 6 and smaller - 2000 ft; 4 and larger - 500 ft.

TABLE CV

2/C AVC FLEXIBLE CORD, 600 Volt

Tinned copper, asbestos, varnished cambric, asbestos insulation, asbestos braid overall.
110°C (230°F)

Size	Stranding	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M. Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000ft. and over			
16 2/C	26/.010	\$ 235.00	\$ 209.00	\$ 197.00	\$ 174.00	500'C	.420	75
14 2/C	41/.010	291.00	258.00	243.00	215.00	500'C	.450	91
12 2/C	65/.010	408.00	363.00	342.00	302.00	500'C	.485	116

Stock Sizes: None
Non Stock sizes: Prices on request
Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color: 18 - 2000 ft. 10 - 1000 ft.

ROCKBESTOS WIRE & CABLE CO.

Division of CERRO CORPORATION

New Haven 4, Conn.

RBB 00571

TABLE FS-
UNDERWRITERS TYPE AF
 Fixture Wire, 300 Volt, Underwriters' Listed
 Flexible stranded copper, plain asbestos
 150°C (302°F)

Size	Stranding	Prices Per 1000 ft.				M Ft.	
		Less than 500 ft.	500- 19,999 ft.	20,000- 49,999 ft.	50,000 ft. and over	Std. Pkg.	Ship. Weight
18	16/.010	\$ 18.60	\$ 16.60	\$ 15.60	\$ 13.80	500'S	.109
16	26/.010	21.60	19.20	18.10	16.00	500'S	.122
14	41/.010	27.80	24.70	23.30	20.60	500'S	.138
12	65/.010	44.10	39.20	37.00	32.70	500'S	.187
10	104/.010	57.60	51.20	48.30	42.70	500'S	.209

Stock sizes: 16, 12 - Black, White, Red; 14 - Blue also 18 Black - White
 Quantities of non stock sizes less than the following subject to
 factory acceptance: Size and/or color: 18 - 14 - 10,000 ft.
 12 - 10 - 5,000 ft.

TABLE FSB
UNDERWRITERS TYPE AF
 Fixture Wire, 300 Volt, Underwriters' Listed
 Ditto table FS (above) plus cotton braid
 150°C (302°F)

All sizes: Prices on request
 Quantities of any item less than the following, subject to
 factory acceptance: Size and/or color - 18 - 14 - 10,000 ft.)
 12 - 10 - 5,000 ft.) 2,000 ft. per color within size

TABLES WSC - WSCF
N.E.C. TYPE AI

Moistemp Appliance Lead Wire, 300 volt
 Solid or stranded copper, high dielectric tape and felted asbestos wall
 125°C (257°F)

TABLES XSC - XSCF
N.E.C. TYPE A

HiTemp Appliance Lead Wire, 300 volt
 200°C (392°F) - 150°C (302°F)

43 Mils - Sizes 8 to 12; 33 Mils - Sizes 14 to 18

Stock sizes: None
 Prices and other constructions: on request
 Quantities of any item less than the following, subject to
 factory acceptance: 18 to 8 - 10,000 ft.

TABLE XBNF
N.E.C. TYPE A
 Hi Temp Appliance Lead Wire, 300 Volt
 Flexible stranded nickel, 030" felted asbestos
 200°C (392°F)

Size	Stranding	Prices Per 1000 ft.				M Ft.	
		Less than 500 ft.	500- 19,999 ft.	20,000- 49,999 ft.	50,000 ft. and over	Std. Pkg.	Ship. Weight
18	16/.010	\$ 44.10	\$ 39.20	\$ 37.00	\$ 32.70	500'C	.105
16	26/.010	61.70	54.80	51.60	45.70	500'C	.119
14	41/.010	95.30	84.70	79.80	70.60	500'C	.135
12	65/.010	146.00	130.00	123.00	108.00	500'C	.155
10	104/.010	227.00	202.00	190.00	168.00	500'C	.180

Stock sizes: 16, 14, 12 White.
 Quantities of any non stock item less than the following subject to
 factory acceptance: 18 - 10,000 ft.
 10 - 2,000 ft.

ISSUE #10
SEPT. 26, 1966.

Replaces Issue
dated Nov. 15, 1965.

SF-2

TABLE SR-FWC

Fixture and/or Appliance Wire, 600 Volt, Underwriters' listed
Coarse stranded tinned copper, Silicone rubber insulation - Glass braid
200°C (392°F)

Size	Stranding	Insul. 64ths.	Braid Mils	Prices Per 1000 feet				M Ft.		
				Less than 500 ft.	500- 19,999 ft.	20,000- 49,999 ft.	50,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
18	7/.0152	2	9	\$ 66.60	\$ 59.20	\$ 55.70	\$ 49.30	500'S	.129	15
16	7/.0192	2	9	84.00	74.60	70.30	62.20	500'S	.141	20
14	7/.0242	2	9	104.00	92.30	86.90	76.90	500'S	.156	27
*12	19/.0185	2	9	129.00	114.00	108.00	95.00	500'S	.176	38
*10	19/.0234	3	9	262.00	233.00	220.00	194.00	500'C	.234	62

Stock sizes: 16, 14 - Black, White, Red

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to factory acceptance: Size and/or color: 18 - 14 - 5,000 ft; 12 - 10 - 3,000 ft.

All sizes listed are approved for internal wiring of appliances.

* Not N.E.C. Type SF-2

SFF-2

TABLE SR-FWF

Fixture and/or appliance wire, 600 Volt, Underwriters' listed
Flexible stranded tinned copper, Silicone rubber insulation - Glass braid
150°C (302°F)

Size	Stranding	Insul. 64ths.	Braid Mils	Prices Per 1000 feet				M Ft.		
				Less than 500 ft.	500- 19,999 ft.	20,000- 49,999 ft.	50,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
*22	7/.010	2	9	\$ 51.60	\$ 45.80	\$ 43.20	\$ 38.20	500'S	.113	10
*20	10/.010	2	9	59.90	53.30	50.20	44.40	500'S	.121	11
18	16/.010	2	9	68.70	61.10	57.50	50.90	500'S	.128	15
16	26/.010	2	9	85.10	75.60	71.20	63.00	500'S	.142	20
14	41/.010	2	9	106.00	93.40	87.90	77.80	500'S	.158	27
*12	65/.010	2	9	125.00	111.00	104.00	91.90	500'C	.178	38

Stock sizes: 12 - 14, Black, White, Red - 18 - 16, Black and White

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to factory acceptance: Size and/or color: 5,000 ft.

All sizes listed are approved for internal wiring of appliances

* Not N.E.C. Type SFF-2

SFF-1

TABLE SR-FWT

Fixture wire, 300 Volt, Underwriters' listed
Flexible stranded tinned copper, Silicone rubber insulation - Glass braid
150°C (302°F)

Size	Stranding	Insul. 64ths.	Braid Mils	Prices Per 1000 feet				M Ft.		
				Less than 500 ft.	500- 19,999 ft.	20,000- 49,999 ft.	50,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
18	16/.010	1	9	\$ 47.50	\$ 42.20	\$ 39.80	\$ 35.20	500'S	.097	12

Stock sizes: None

Quantities of any item less than the following, subject to factory acceptance: Size and/or color: 10,000 ft.

ROCKBESTOS WIRE & CABLE CO.

RBB 0057C

TABLE C
N.E.C. TYPE AVA
Control and Lighting Wire, 600 Volt, Underwriters' listed
Solid copper, Asbestos, Varnished Cambric, Asbestos braid
110°C (230°F)

Size	Stranding	Prices Per 1000 ft.				M Ft.		
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
14	Solid	\$ 116.00	\$ 103.00	\$ 96.60	\$ 85.50	500'C	.244	39
12	"	126.00	112.00	105.00	92.80	500'C	.261	50
10	"	141.00	125.00	118.00	104.00	500'C	.282	65
8	"	179.00	159.00	150.00	132.00	500'C	.309	89
6	"	350.00	311.00	293.00	259.00	500'R	.372	143
4	"	566.00	503.00	474.00	419.00	500'R	.414	198

Stock sizes: 14 and 12 - Black and White; 10 thru 6 - Black

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to:

factory acceptance: Size and/or color - 6 and smaller - 2,000 ft. 4 and larger - 500 ft.

TABLE E
N.E.C. TYPE AVA
Power Cable, 600 Volt, Underwriters' listed
Coarse stranded copper, Asbestos, Varnished Cambric, Asbestos braid
110°C (230°F)

Size	Stranding	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M Ft.		Conduit Size 3 Conds.
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000ft. and over			Ship. Weight	C.C.C.* 30°C	
14	7/.0242	\$ 167.00	\$ 148.00	\$ 139.00	\$ 123.00	500'C	.263	44	30	1/2"
12	7/.0305	176.00	156.00	147.00	130.00	500'C	.282	55	35	3/4"
10	7/.0385	207.00	184.00	173.00	153.00	500'C	.306	73	45	1"
8	7/.0486	269.00	239.00	225.00	199.00	500'C	.336	96	60	1 1/4"
6	7/.0612	378.00	336.00	317.00	280.00	500'R	.394	152	80	1 1/2"
4	7/.0772	601.00	534.00	503.00	445.00	500'R	.442	213	105	2"
2	7/.0974	851.00	756.00	712.00	630.00	500'R	.502	304	135	2 1/2"
1	19/.0664	982.00	873.00	822.00	727.00	500'R	.572	386	160	3"
1/0	19/.0745	1275.00	1133.00	1067.00	944.00	500'R	.613	465	190	3 1/2"
2/0	19/.0837	1407.00	1251.00	1178.00	1042.00	500'R	.659	562	215	4"
3/0	19/.0940	1564.00	1390.00	1309.00	1158.00	500'R	.710	797	245	4 1/2"
4/0	19/.1055	1745.00	1551.00	1460.00	1292.00	500'R	.768	870	275	5"
250	37/.0822	2183.00	1941.00	1828.00	1617.00	500'R	.865	1094	315	6"
300	37/.0900	2375.00	2111.00	1988.00	1759.00	500'R	.920	1263	345	6 1/2"
350	37/.0973	2583.00	2296.00	2162.00	1913.00	500'R	.971	1431	390	7"
400	37/.1040	2803.00	2492.00	2346.00	2076.00	500'R	1.018	1599	420	7 1/2"
500	37/.1162	3230.00	2871.00	2703.00	2392.00	500'R	1.103	1929	470	8"
750	61/.1109	4179.00	3714.00	3498.00	3095.00	500'R	1.298	2998	580	9"

Stock sizes: 14 to 12 - Black and White; 10 to 400, 500, 750 - Black

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to factory acceptance:

Size and/or color: - 8 and smaller - 2,000 ft; 6 and larger - 500 ft.

*Correction Factors: 40°C - .94 - 50°C - .87 - 60°C - .79

ISSUE #10

SEPT. 26, 1966

Replaces Issue

dated Nov. 15, 1965

TABLE ML

Mining Cable, 600 Volt

Flexible Stranded tinned copper, Asbestos, Varnished cambric, Asbestos braid
110°C (230°F)

Size	Stranding	Prices Per 1000 ft.				M Ft.		
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Max.* O.D.	Ship. Weight
14	41/.010	\$ 158.00	\$ 141.00	\$ 133.00	\$ 117.00	500'C	.273	40
12	65/.010	176.00	156.00	147.00	130.00	500'C	.294	50
10	104/.010	222.00	197.00	186.00	164.00	500'C	.309	68
8	133/.0111	397.00	353.00	333.00	294.00	500'C	.359	92
6	133/.0140	507.00	450.00	424.00	375.00	500'R	.405	140
4	133/.0177	724.00	644.00	606.00	536.00	500'R	.473	214
3	133/.0199	817.00	726.00	684.00	605.00	500'R	.506	254
2	133/.0223	1068.00	950.00	894.00	791.00	500'R	.546	304
1	259/.0180	1134.00	1008.00	950.00	840.00	500'R	.620	390
1/0	259/.0202	1557.00	1384.00	1303.00	1153.00	500'R	.669	474
2/0	259/.0227	1696.00	1508.00	1420.00	1256.00	500'R	.716	572
3/0	259/.0255	1904.00	1692.00	1594.00	1410.00	500'R	.779	718
4/0	259/.0286	2144.00	1906.00	1795.00	1588.00	500'R	.849	886

Stock sizes: 14 thru 4/0 - Black (except 3)

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 14 to 8 - 1,000 ft. - 6 and larger - 500 ft.

*NOTE: This is Max. O.D.

TABLE L

N.E.C. TYPE AVA

Motor lead cable, 600 Volt, Underwriters' listed

Flexible stranded tinned copper, Asbestos, Varnished cambric, Asbestos braid
110°C (230°F)

Size	Stranding	Prices Per 1000 ft.				M Ft.		
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Max. O.D.	Ship. Weight
14	41/.010	\$ 168.00	\$ 149.00	\$ 141.00	\$ 124.00	500'C	.265	46
12	65/.010	191.00	170.00	160.00	141.00	500'C	.285	57
10	104/.010	239.00	213.00	201.00	177.00	500'C	.310	76
8	133/.0111	419.00	372.00	351.00	310.00	500'C	.357	112
6	133/.0140	536.00	477.00	449.00	397.00	500'R	.420	160
4	133/.0177	771.00	686.00	646.00	571.00	500'R	.476	222
3	133/.0199	864.00	768.00	724.00	640.00	500'R	.509	263
2	133/.0223	1137.00	1011.00	952.00	842.00	500'R	.545	317
1	259/.0180	1207.00	1073.00	1011.00	894.00	500'R	.618	409
1/0	259/.0202	1653.00	1469.00	1384.00	1224.00	500'R	.664	490
2/0	259/.0227	1805.00	1605.00	1511.00	1337.00	500'R	.717	595
3/0	259/.0255	2008.00	1785.00	1681.00	1487.00	500'R	.776	754
4/0	259/.0286	2279.00	2026.00	1908.00	1688.00	500'R	.841	908
250MCM	427/.0242	2767.00	2459.00	2316.00	2049.00	500'R	.943	1142
350	427/.0286	3417.00	3038.00	2861.00	2531.00	500'R	1.062	1488
500	427/.0342	4195.00	3729.00	3511.00	3107.00	500'R	1.213	2247

Stock sizes: 14 to 500 MCM - Black as listed (Except 3 and 3/0)

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 2,000 ft. - 6 and larger - 500 ft.

TABLE E3AB

N.E.C. TYPE AVA

Power Cable, 600 Volt singles

3/C Coarse stranded copper, Cabled, Taped, Galvanized steel interlocked armor
110°C (230°F)

Size	Stranding	Prices Per 1000 ft.				Nominal O.D.		Weight		C.C.C.*	
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	under armor	over armor	Net M Ft.	Ship.	30°C	40°C
4/0	19/.1055	\$ 5742.00	\$ 5104.00	\$ 4806.00	\$ 4253.00	1.658	1.960	3298	4298	322	300
250MCM	37/.0822	6934.00	6164.00	5804.00	5136.00	1.868	2.168	3956	4506	358	334
300	37/.0900	7632.00	6784.00	6388.00	5653.00	1.987	2.290	4770	5560	402	375
350	37/.0973	8408.00	7474.00	7038.00	6228.00	2.097	2.400	5048	6348	440	411
500	37/.1162	10067.00	8949.00	8427.00	7457.00	2.382	2.680	6720	8020	554	517

Stock sizes: None

Other sizes: Prices on request

Quantities of any item less than the following subject to
factory acceptance: 250 ft.

* I. P. C. E. A. Recommendation - 40°C

TABLE E3AA

N.E.C. TYPE AVA

Ditto above (except Aluminum interlocked armor)

Size	Stranding	Prices Per 1000 ft.				Nominal O.D.		Weight		C.C.C.*	
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	under armor	over armor	Net M Ft.	Ship.	30°C	40°C
4/0	19/.1055	\$ 5881.00	\$ 5228.00	\$ 4923.00	\$ 4356.00	1.658	1.960	2675	3675	322	300
250MCM	37/.0822	7097.00	6309.00	5941.00	5257.00	1.868	2.168	3345	3895	358	334
300	37/.0900	7824.00	6954.00	6549.00	5795.00	1.987	2.290	3884	4674	402	375
350	37/.0973	8565.00	7613.00	7169.00	6344.00	2.097	2.400	4375	5675	440	411
500	37/.1162	10259.00	9119.00	8587.00	7599.00	2.382	2.680	5955	7255	554	517
750	61/.1109	14792.00	13149.00	12382.00	10957.00	2.803	3.105	8611	10741	706	658

Stock sizes: None

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to
factory acceptance: 250 ft.

* I. P. C. E. A. Recommendation - 40°C

TABLES EC AND EL 1/C and ECL 3/C

N.E.C. TYPES AVA AND AVL

Miscellaneous Power Cable

3/C AVA, 600 Volt braided - Table EC

3/C AVL, 600 Volt leaded - Table ECL

1000 to 5000 Volt AVA braided and/or
leaded, 1/C and 3/C constructions.

Stock sizes: None

Prices on request

Quantities of any item less than the following, subject to
factory acceptance: 8 and smaller - 1000 ft. - 6 and larger - 500 ft.

N.E.C. TYPE V

Varnished Cambric Power Cable

Braided, Leaded, Armored

600 to 5000 Volt Construction

Stock sizes: None

Prices and Manufacturing Quantities - Contact Factory.

ISSUE #10
SEPT. 26, 1966
Replaces Issue
dated Nov. 15, 1965

TABLE SR-MB

Motor lead Cable, 600 Volt

Flexible stranded tinned copper, Silicone rubber insulation, Glass braid
200°C (392°F) Class H (A. I. E. E.) Intermittent service

Size	Stranding	Insul. 64 ths.	Braid Mils	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M Ft.	
				Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000ft. and over			Ship. Weight	C.C.C. at 30°C*
18	16/.010	2	9	\$ 65.60	\$ 58.30	\$ 54.90	\$ 48.60	500'S	.127	13	24
16	26/.010	2	9	81.30	72.20	68.00	60.20	500'S	.141	17	30
14	41/.010	2	9	101.00	89.00	83.80	74.20	500'C&S	.157	23	40
12	65/.010	2	9	119.00	106.00	99.10	87.70	500'C&S	.177	33	55
10	104/.010	3	9	210.00	186.00	176.00	155.00	500'C&S	.236	55	82
8	133/.0111	4	9	334.00	297.00	280.00	247.00	500'C	.316	90	115
6	133/.0140	4	9	451.00	401.00	378.00	334.00	500'R	.362	141	154
4	133/.0177	4	9	609.00	542.00	510.00	451.00	500'R	.418	205	205
2	133/.0223	4	9	779.00	693.00	653.00	577.00	500'R	.487	301	280
1	259/.0180	5	20	1005.00	893.00	841.00	744.00	500'R	.586	402	325
1/0	259/.0202	5	20	1203.00	1070.00	1007.00	891.00	500'R	.632	482	385
2/0	259/.0227	5	20	1430.00	1271.00	1197.00	1059.00	500'R	.685	598	450
3/0	259/.0255	5	20	1708.00	1518.00	1430.00	1265.00	500'R	.744	764	520
4/0	259/.0286	5	20	2070.00	1840.00	1733.00	1533.00	500'R	.811	888	600

Stock sizes: 18 and 8 Black and White; 16 to 10 Black, White and Red; 14-12 also Green; 14 and 12 also Blue;

6 thru 4/0 Black only

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: - 8 and smaller - 5,000 ft.
6 - 4/0 - 1,000 ft.

*Correction factors: 40°C - .97 - 50°C - .94 - 60°C - .91

TABLE SR-MLA

Motor Lead Cable, 600 Volt

Flexible stranded tinned copper, Silicone rubber insulation, Asbestos braid
130°C (257°F) continuous service
200°C (392°F) Intermittent service

Size MCM	Stranding	Insul. 64 ths.	Braid Mils	Prices Per 1000 ft.				Std. Pkg.	Nom. O.D.	M Ft.	
				Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000ft. and over			Ship. Weight	
250	427/.0242	6	45	\$2698.00	\$2398.00	\$2258.00	\$1998.00	500'R	.912	1076	
300	427/.0265	6	45	3280.00	2915.00	2745.00	2429.00	500'R	.994	1316	
350	427/.0286	6	45	3681.00	3272.00	3081.00	2726.00	500'R	1.040	1491	
500	427/.0342	6	45	4140.00	3680.00	3465.00	3066.00	500'R	1.157	1965	

Stock sizes: 250 - 350 - 500

Quantities of any item less than the following, subject to
factory acceptance: Size and/or color: - 250 MCM and larger - 3,000 ft. (1000 ft. per color within size)

TABLE SR-C

Lighting Wire, 600 Volt

Solid tinned copper, Silicone rubber insulation, Glass braid
125°C (257°F)

Size	Insul. 64 ths.	Braid Mils	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft.		Conduit Size
			Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			Ship. Weight	C.C.C. 30°C*	
14	2	20	\$ 99.10	\$ 88.10	\$ 82.90	\$ 73.40	500'C	.172	26	27	1/2"
12	2	20	115.00	102.00	95.50	84.50	500'C	.189	36	35	3/4"
10	3	20	192.00	171.00	161.00	142.00	500'C	.244	57	48	1"
8	4	20	289.00	257.00	242.00	214.00	500'C	.304	91	64	1 1/2"

Stock sizes: None

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 5,000 ft.

*Correction factors: 40°C - .94 50°C - .89 60°C - .83

ROCKBESTOS WIRE & CABLE CO.

Division of CERRO CORPORATION

New Haven 4, Conn.

RBB 00577

TABLE SR-AW

Appliance Wire, 600 Volt, Underwriters' listed (Recommended in place of
Asbestos insulated nickel conductor appliance wire.)
Flexible stranded nickel plated copper, Silicone rubber insulation, Glass braid
200°C (392°F)

Size	Stranding	Insul. 64ths.	Braid Mils	Prices Per 1000 feet				M Ft.			
				Less than 500 ft.	500- 19999 ft.	20,000- 49,999 ft.	50,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight	C.C.C. at 30°C*
16	26/.010	2	9	\$112.00	\$98.80	\$93.00	\$82.30	500'S	.142	20	25
14	41/.010	2	9	146.00	130.00	123.00	108.00	500'S	.158	27	30
12	65/.010	2	9	189.00	168.00	159.00	140.00	500'S	.178	38	40

Stock sizes: 16, 14, 12 - White

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color; 5,000 ft.

* Correction factors: 50°C - .94 75°C - .86 100°C - .77 150°C - .54

TABLE SR-E

N.E.C. TYPE SA

Power Cable, 600 Volt

Coarse stranded tinned copper, Silicone rubber insulation, Asbestos braid
125°C (257°F)

Size	Stranding	Insul. 64ths.	Braid Mils	Prices Per 1000 feet				M Ft.			Candul Size 3 Candr
				Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Nom. O.D.	Ship. Weight	C.C.C.* 30°C	
14	7/.0242	3	40	\$208.00	\$185.00	\$175.00	\$154.00	.252	44	30	1/2"
12	7/.0305	3	40	241.00	214.00	202.00	178.00	.271	48	38	3/4"
10	7/.0385	3	40	276.00	245.00	231.00	204.00	.295	71	49	1"
8	7/.0486	4	45	397.00	353.00	333.00	294.00	.358	109	67	1 1/4"
6	7/.0612	4	45	566.00	503.00	474.00	419.00	.399	158	89	1 1/2"
4	7/.0772	4	45	647.00	575.00	542.00	479.00	.447	222	115	2"
2	7/.0974	4	45	877.00	779.00	734.00	649.00	.507	311	148	2 1/2"
1	19/.0664	5	45	1047.00	930.00	876.00	775.00	.577	391	173	3"
1/0	19/.0745	5	45	1323.00	1176.00	1108.00	980.00	.618	474	204	3 1/2"
2/0	19/.0837	5	45	1471.00	1307.00	1231.00	1089.00	.662	577	230	4"
3/0	19/.0940	5	45	1643.00	1461.00	1376.00	1217.00	.715	703	262	5"
4/0	19/.1055	5	45	1934.00	1719.00	1619.00	1432.00	.772	889	295	6"
MCM											
250	37/.0822	6	45	2516.00	2236.00	2106.00	1863.00	.849	1043	333	2 1/2"
300	37/.0900	6	45	3051.00	2712.00	2554.00	2260.00	.904	1276	385	3"
350	37/.0973	6	45	3362.00	2988.00	2814.00	2490.00	.954	1445	423	3 1/2"
500	37/.1162	6	45	3895.00	3462.00	3261.00	2885.00	1.085	1903	502	4"

Stock sizes: 12 Black and White; 14 to 250, 350 and 500 MCM Black (Except 3/0)

Non Stock sizes: Prices on request

Quantities of non stock sizes less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 3,000 ft;

6 - 4 - 500 ft.

2 and larger - 3,000 ft.

* Correction factors: 40°C - .94 50°C - .89 60°C - .83

TABLE SR-H
Power Cable 5,000 Volt
Coarse Stranded tinned copper, Silicone rubber insulation - Asbestos braid
125°C (257°F)

Size	Stranding	Insul. 64ths.	Braid Mils	Prices Per 1000 feet				M Ft.		Conduit	
				Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000ft. and over	Nom. O.D.	Ship. Weight	C.C.C. at 30°C*	Size 3 Can drs.
8	19/.0295	10	45	\$1179.00	\$1048.00	\$987.00	\$873.00	.560	200	73	1½"
6	19/.0372	10	45	1359.00	1208.00	1137.00	1006.00	.600	251	93	2"
4	19/.0469	10	45	1522.00	1353.00	1274.00	1127.00	.646	314	125	2"
2	19/.0591	10	45	1769.00	1572.00	1481.00	1310.00	.706	447	160	2"
1	37/.0476	10	45	1932.00	1718.00	1618.00	1431.00	.746	514	182	2"
1/0	37/.0534	10	45	2138.00	1900.00	1789.00	1583.00	.787	594	215	2½"
2/0	37/.0600	10	45	2402.00	2135.00	2011.00	1779.00	.833	727	244	2½"
3/0	37/.0673	10	45	2637.00	2344.00	2207.00	1953.00	.884	920	276	2½"
4/0	37/.0756	10	45	3069.00	2728.00	2569.00	2273.00	.928	1079	323	2½"
MCM											
250	61/.0640	11	45	3627.00	3224.00	3036.00	2686.00	1.021	1247	353	3"
300	61/.0701	11	45	4003.00	3558.00	3351.00	2965.00	1.060	1423	392	3"
350	61/.0757	11	45	4380.00	3893.00	3666.00	3244.00	1.100	1600	424	3"
500	61/.0950	11	45	5480.00	4871.00	4587.00	4059.00	1.259	2359	518	3½"

Stock sizes: None

Quantities of any item less than the following subject to
factory acceptance: Size and/or color (8, 6, 4 - 5,000 ft.) (2 and larger - 1,000 ft.)

* Correction factors: 40°C - .95 50°C - .89 60°C - .83

NOTE: Shielding should be used in all circuits operating above 2000 volts where
recommended by IPCEA. Refer to IPCEA Standard S-19-81, 4th Ed., Section 5
4.2.1 through 4.2.4.

TABLE MD
N.E.C. TYPE AVA
Control Cable, 600 Volt

SIZE 12 AWG

12 AWG 19/25 Tinned copper, each conductor Asbestos Varnished cambric cotton braid,
Cabled, Taped, Black Asbestos braid.
110°C (230°F)

No. of Conductors	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft. Ship. Weight
	Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
2	\$ 692.00	\$ 615.00	\$ 579.00	\$ 512.00	500'R	.534	158
3	981.00	872.00	821.00	726.00	500'R	.570	193
4	1114.00	990.00	933.00	825.00	500'R	.631	249
5	1296.00	1152.00	1085.00	960.00	500'R	.697	273
6	1473.00	1310.00	1233.00	1091.00	500'R	.767	370
7	1604.00	1426.00	1343.00	1188.00	500'R	.767	391
8	1711.00	1521.00	1432.00	1267.00	500'R	.837	443
9	1853.00	1647.00	1551.00	1372.00	500'R	.919	499
10	2034.00	1808.00	1702.00	1506.00	500'R	.986	595
11	2169.00	1928.00	1815.00	1606.00	500'R	.986	614
12	2301.00	2045.00	1926.00	1704.00	500'R	1.021	657

Stock sizes: None
Non Stock Combinations: Prices on request
Quantities of non stock combinations less than the following subject to
factory acceptance: 500 feet.

TABLE MT
N.E.C. TYPE AVA

SIZE 9 AWG

Control Cable, 600 Volt
9 AWG 19/22 Tinned copper, each conductor Asbestos Varnished Cambric cotton braid,
Cabled, Taped, Black Asbestos braid.
110°C (230°F)

No. of Conductors	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft. Ship. Weight
	Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
2	\$ 832.00	\$ 740.00	\$ 697.00	\$ 616.00	500'R	.643	249
3	1224.00	1088.00	1024.00	906.00	500'R	.648	285
4	1410.00	1253.00	1180.00	1044.00	500'R	.730	358
5	1616.00	1437.00	1353.00	1197.00	500'R	.831	473
6	1745.00	1551.00	1460.00	1292.00	500'R	.877	530
7	1842.00	1637.00	1542.00	1364.00	500'R	.877	654
8	2119.00	1883.00	1773.00	1569.00	500'R	.993	733
9	2371.00	2108.00	1985.00	1756.00	500'R	1.077	823
10	2619.00	2328.00	2193.00	1940.00	500'R	1.166	882
11	2811.00	2499.00	2353.00	2082.00	500'R	1.166	991
12	2975.00	2644.00	2490.00	2203.00	500'R	1.207	1080

Stock sizes: None
Other combinations: Prices on request
Quantities of any item less than the following, subject to
factory acceptance: 500 feet.

ISSUE #10

SEPT. 26, 1966

14

Replaces Issue
dated Nov. 15, 1965

TABLE PMT

SIZE 9 AWG

PNR Small Diameter Control Cable, 600 Volt

9 AWG 19/22 Copper, each conductor 16½ Mils Polyethylene, 4 Mils Nylon, Color coded,
Cabled, Taped, Rockhide (P. V. C.), Sheath overall.

75°C (167°F)

No. of Conductors	Prices Per 1000 feet				M Ft.			
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10000 ft. and over	Sheath Tkns.	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 359.00	\$ 319.00	\$ 225.00	\$ 199.00	3/64	1M'N/R	.445	148
3	463.00	412.00	291.00	257.00	3/64	1M'N/R	.472	193
4	641.00	570.00	403.00	356.00	3/64	1M'N/R	.516	250
5	746.00	663.00	468.00	414.00	4/64	1M'N/R	.602	333
6	845.00	751.00	530.00	469.00	4/64	1M'N/R	.652	382
7	929.00	826.00	584.00	516.00	4/64	1M'N/R	.652	417
8	1066.00	948.00	669.00	592.00	4/64	1M'N/R	.705	474
9	1196.00	1063.00	751.00	664.00	4/64	1M'N/R	.758	556
10	1377.00	1224.00	865.00	765.00	4/64	1M'N/R	.820	631
11	1467.00	1304.00	921.00	815.00	4/64	1M'N/R	.820	645
12	1579.00	1404.00	992.00	877.00	5/64	1M'N/R	.882	734
15	1820.00	1618.00	1143.00	1011.00	5/64	1M'N/R	.984	875
19	2268.00	2016.00	1424.00	1260.00	5/64	1M'N/R	1.027	1060

Stock sizes: Multi-Conductor: 2, 3, 4, 5, 7, 9, and 12 conductor - Other combinations: Prices on request

1/C Black - White, Red, Green, Orange, Blue

Quantities of any non stock items less than the following, subject to factory acceptance:

Size and/or color: multi-conductor - 1000 ft.

1/C - 5000 ft.

TABLE PMD

SIZE 12 AWG

PNR Small Diameter Control Cable, 600 Volt

12 AWG 19/25 Copper, each conductor 16½ Mils Polyethylene, 4 Mils Nylon,
Color coded, Cabled, Taped, Rockhide (P. V. C.) Sheath overall.

75°C (167°F)

No. of Conductors	Prices Per 1000 feet				M Ft.			
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10000 ft. and over	Sheath Tkns.	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 242.00	\$ 215.00	\$ 152.00	\$ 134.00	3/64	1M'N/R	.371	95
3	308.00	274.00	194.00	171.00	3/64	1M'N/R	.392	115
4	420.00	373.00	264.00	233.00	3/64	1M'N/R	.427	143
5	481.00	428.00	302.00	267.00	3/64	1M'N/R	.467	176
6	593.00	527.00	372.00	329.00	3/64	1M'N/R	.506	216
7	639.00	568.00	402.00	355.00	3/64	1M'N/R	.506	231
8	746.00	663.00	468.00	414.00	4/64	1M'N/R	.581	285
9	814.00	724.00	511.00	452.00	4/64	1M'N/R	.624	322
10	882.00	784.00	554.00	490.00	4/64	1M'N/R	.667	354
11	944.00	839.00	593.00	524.00	4/64	1M'N/R	.667	359
12	1008.00	896.00	633.00	560.00	4/64	1M'N/R	.695	385
15	1239.00	1101.00	778.00	688.00	4/64	1M'N/R	.751	492
19	1530.00	1360.00	961.00	850.00	4/64	1M'N/R	.809	587

Stock sizes: Multi-conductor: 2-10, 12, 15, 19/C. Other combinations: Prices on request

1/C - Black, White, Red, Green, Orange, Blue

Quantities of any Non Stock item less than the following, subject to

factory acceptance: Size and/or color: Multi-conductor - 1000 ft.

1/C - 5000 ft.

ROCKBESTOS WIRE & CABLE CO.

a division of CERRO CORPORATION

New Haven 4, Conn.

RBB 00581

TABLE PMF SIZE 14 AWG

PNR Small Diameter Control Cable, 600 Volt

14 AWG 19/27 Copper, each conductor 16½ Mils Polyethylene, 4 Mils nylon,
Color coded, Cabled, Taped, Rockhide (P.V.C.) Sheath overall.

75°C (167°F)

No. of Conductors	Prices Per 1000 feet				M Ft.			
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10,000 ft. and over	Sheath Tks.	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 211.00	\$ 188.00	\$ 133.00	\$ 117.00	3/64	1000'N/R	.335	69
3	260.00	231.00	163.00	144.00	3/64	1000'N/R	.353	84
4	366.00	325.00	230.00	203.00	3/64	1000'N/R	.383	105
5	432.00	384.00	272.00	240.00	3/64	1000'N/R	.418	124
6	477.00	424.00	300.00	265.00	3/64	1000'N/R	.452	146
7	519.00	461.00	326.00	288.00	3/64	1000'N/R	.452	155
8	591.00	525.00	371.00	328.00	3/64	1000'N/R	.489	193
9	674.00	599.00	423.00	374.00	3/64	1000'N/R	.525	212
10	756.00	672.00	475.00	420.00	4/64	1000'N/R	.595	263
11	810.00	720.00	509.00	450.00	4/64	1000'N/R	.605	266
12	857.00	762.00	538.00	476.00	4/64	1000'N/R	.620	281
15	1059.00	941.00	665.00	588.00	4/64	1000'N/R	.678	334
19	1323.00	1176.00	831.00	735.00	4/64	1000'N/R	.719	397

Stock sizes: Multi-conductor: 2 thru 10, 12 and 15C - Other combinations: Prices on request
1/C Black - White - Red - Green - Orange - Blue

Other sizes: Prices on request

Quantities of any Non Stock Item less than the following, subject to factory acceptance
Size and/or color: Multi-conductor - 1000 ft.

1/C PN Wire

Plain Copper Conductor 16½ Mils Polyethylene - 4 Mils Nylon - Tables - PNT - PND - PNF

Tinned Copper Conductor 26 Mils Linear Polyethylene - 4 Mils Nylon

TABLES - PNTX - PNDX - PNFX

Size	Stranding	Table	Prices per 1000 feet				M Ft.		
			Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
9	19/22	PNT	\$ 93.90	\$ 74.60	\$ 52.70	\$ 46.60	500'S	.171	46
12	19/25	PND	57.40	51.00	36.00	31.90	500'S	.134	22
14	19/27	PNF	44.60	39.70	28.00	24.80	500'S	.116	16
9	19/22	PNTX	101.00	89.40	63.20	55.90	500'S	.190	69
12	19/25	PNDX	68.60	61.00	43.10	38.10	500'S	.152	42
14	19/27	PNFX	53.50	47.50	33.60	29.70	500'S	.134	33

Stock sizes - Tables PNT - PND - PNF - Black - White - Red - Green - Orange - Blue

Tables PNTX - PNDX - PNFX - Same 6 colors

Quantities of any non stock item less than the following subject to
factory acceptance: 5,000 feet any color or stripes

ISSUE #10
SEPT. 26, 1966
Replaces Issue
dated Nov. 15, 1965

TABLE PMPH

SIZE 16 AWG

PNR Small diameter control cable, 600 volt

16 AWG 7/0192 copper, each conductor 16½ mils polyethylene, 4 mils nylon,
color coded, cabled, taped, Rockhide (P.V.C.) sheath overall.

75°C (167°F)

No. of Conductors	Prices Per 1000 feet							M Ft.
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10,000 ft. and over	Sheath Tlms.	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 200.00	\$ 178.00	\$ 126.00	\$ 111.00	3/64	1000'N/R	.305	59
3	247.00	220.00	155.00	137.00	3/64	1000'N/R	.321	84
4	281.00	250.00	177.00	156.00	3/64	1000'N/R	.349	87
5	319.00	284.00	201.00	177.00	3/64	1000'N/R	.379	103
6	362.00	322.00	228.00	201.00	3/64	1000'N/R	.409	124
7	404.00	359.00	254.00	224.00	3/64	1000'N/R	.409	139
8	450.00	400.00	283.00	250.00	3/64	1000'N/R	.440	154
9	510.00	453.00	320.00	283.00	3/64	1000'N/R	.472	172
10	573.00	509.00	360.00	318.00	3/64	1000'N/R	.507	198
11	614.00	546.00	386.00	341.00	3/64	1000'N/R	.507	214
12	675.00	600.00	424.00	375.00	4/64	1000'N/R	.560	229
15	839.00	746.00	527.00	466.00	4/64	1000'N/R	.603	276
19	1026.00	912.00	645.00	570.00	4/64	1000'N/R	.649	334

Stock sizes: None

Other combinations: Prices on request

Non stock items: Prices on request

Quantities on only non stock item less than the following subject to factory acceptance

Size and/or color: Multi-conductor - 1000 ft.

TABLE PMTX

SIZE 9 AWG

PNRX-90 Control Cable, 600 Volt

9 AWG 19/22 Tinned copper, 26 mils linear polyethylene, 4 mils nylon color coded, cabled, plastic fillers where necessary, taped, special Rockhide (P.V.C.) sheath overall.
90°C (194°F)

No. of Conductors	Prices Per 1000 feet				M Ft.			
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10,000 ft. and over	Sheath Tks.	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 452.00	\$ 402.00	\$ 284.00	\$ 251.00	3/64	1000'N/R	.480	179
3	522.00	464.00	328.00	290.00	4/64	1000'N/R	.515	216
4	726.00	645.00	456.00	403.00	4/64	1000'N/R	.595	322
5	845.00	751.00	530.00	469.00	4/64	1000'N/R	.650	366
6	956.00	850.00	601.00	531.00	4/64	1000'N/R	.705	438
7	1053.00	936.00	662.00	585.00	4/64	1000'N/R	.705	492
8	1208.00	1074.00	759.00	671.00	4/64	1000'N/R	.765	552
9	1350.00	1200.00	848.00	750.00	5/64	1000'N/R	.825	624
10	1556.00	1383.00	977.00	864.00	5/64	1000'N/R	.940	714
11	1662.00	1477.00	1043.00	923.00	5/64	1000'N/R	.940	756
12	1786.00	1588.00	1121.00	992.00	5/64	1000'N/R	.965	816
15	2060.00	1831.00	1293.00	1144.00	5/64	1000'N/R	1.045	992
19	2574.00	2288.00	1616.00	1430.00	5/64	1000'N/R	1.125	1224

Stock sizes: Multi-Conductor 2-3-4-5-7 - 1/C Black, White, Red, Green, Orange, Blue

Other combinations: Prices on request

Quantities of any item less than the following, subject to

factory acceptance: Multi-conductor - 2/C to 6/C - 5000 ft. - 7/C and more - 3000 ft.

TABLE PMDX

SIZE 12 AWG

PNRX-90 Control Cable 600 Volt

12 AWG 19/25 Tinned copper 26 mils linear polyethylene, 4 mils nylon color coded, cabled, plastic fillers where necessary, taped, special Rockhide (P.V.C.) sheath overall.
90°C (194°F)

No. of Conductors	Prices Per 1000 feet				M Ft.			
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10,000 ft. and over	Sheath Tks.	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 290.00	\$ 258.00	\$ 182.00	\$ 161.00	3/64	1000'N/R	.405	114
3	368.00	327.00	231.00	204.00	3/64	1000'N/R	.430	149
4	501.00	445.00	315.00	278.00	3/64	1000'N/R	.470	174
5	578.00	514.00	363.00	321.00	4/64	1000'N/R	.515	213
6	706.00	628.00	443.00	392.00	4/64	1000'N/R	.590	259
7	769.00	684.00	483.00	427.00	4/64	1000'N/R	.590	282
8	893.00	794.00	561.00	496.00	4/64	1000'N/R	.640	319
9	974.00	866.00	612.00	541.00	4/64	1000'N/R	.685	366
10	1055.00	938.00	663.00	586.00	4/64	1000'N/R	.735	396
11	1129.00	1004.00	709.00	627.00	4/64	1000'N/R	.735	420
12	1205.00	1071.00	756.00	669.00	5/64	1000'N/R	.765	450
14	1406.00	1250.00	883.00	781.00	5/64	1000'N/R	.805	526
15	1487.00	1322.00	934.00	826.00	5/64	1000'N/R	.830	564
19	1836.00	1632.00	1153.00	1020.00	5/64	1000'N/R	.935	708

Stock sizes: Multi-conductor: 2 thru 10, 12, 14, 15, 19/C - 1/C Black, White, Red, Green, Orange
Non stock sizes: Prices on request

Quantities of any non stock item less than the following subject to factory
acceptance: Size and/or color: Multi-conductor - 1000 ft. 1. C - 5,000 ft.

TABLE PMFX

SIZE 14 AWG

PNRX-90 Control Cable 600 Volt

14 AWG 19/27 Tinned copper 26 mils linear polyethylene, 4 mils nylon

Color coded, cabled, plastic fillers where necessary, taped, special Rockhide (P.V.C.)
sheath overall. 90°C (194°F)

No. of Conductors	Prices Per 1000 feet				M Ft.			
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10,000 ft. and over	Sheath Tks.	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 249.00	\$ 221.00	\$ 156.00	\$ 138.00	3/64	1000'N/R	.370	88
3	314.00	279.00	197.00	174.00	3/64	1000'N/R	.390	110
4	438.00	389.00	275.00	243.00	3/64	1000'N/R	.425	136
5	515.00	458.00	324.00	286.00	3/64	1000'N/R	.465	163
6	573.00	509.00	360.00	318.00	4/64	1000'N/R	.505	182
7	623.00	554.00	391.00	346.00	4/64	1000'N/R	.505	198
8	704.00	626.00	442.00	391.00	4/64	1000'N/R	.580	250
9	809.00	719.00	508.00	449.00	4/64	1000'N/R	.620	278
10	904.00	804.00	568.00	502.00	4/64	1000'N/R	.670	304
11	971.00	863.00	610.00	539.00	4/64	1000'N/R	.670	318
12	1030.00	916.00	647.00	572.00	4/64	1000'N/R	.690	342
13	1271.00	1130.00	798.00	706.00	4/64	1000'N/R	.745	414
19	1586.00	1410.00	996.00	881.00	5/64	1000'N/R	.805	504

Stock sizes: Multi-Conductor - 2 thru 10 and 12/C - 1/C Black, White, Red, Green, Orange, Blue
Other sizes: Prices on request

Quantities of any item less than the following, subject to factory
acceptance: Multi-conductor - 2/C to 6/C - 5000 ft. - 7/C and more - 3000 ft.

TABLE PMDAS

SIZE 12 AWG

PNR Armored Small Diameter Control Cable, 600 Volt

12 AWG 19/25 Copper, each conductor 16½ Mils polyethylene 4 Mils nylon,

Color Coded, Cabled, Taped, Rockhide (P.V.C.) Sheath, galvanized steel
interlocked armor overall.

No. of Conductors	Prices per 1000 feet				M Ft.		
	Less than 250 ft.	250- 999 ft.	1000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
2	\$ 548.00	\$ 487.00	\$ 344.00	\$ 304.00	1000'R	.671	121
3	614.00	546.00	386.00	341.00	1000'R	.692	141
4	728.00	647.00	457.00	404.00	1000'R	.727	167
5	803.00	714.00	504.00	446.00	1000'R	.767	227
6	929.00	826.00	584.00	516.00	1000'R	.806	255
7	980.00	871.00	615.00	544.00	1000'R	.806	270
8	1104.00	981.00	693.00	613.00	1000'R	.881	316
9	1187.00	1055.00	745.00	659.00	1000'R	.924	368
10	1268.00	1127.00	796.00	704.00	1000'R	.967	400
11	1323.00	1176.00	831.00	735.00	1000'R	.967	430
12	1395.00	1240.00	876.00	775.00	1000'R	.995	470
13	1727.00	1535.00	1084.00	959.00	500'R	1.051	557
19	2042.00	1815.00	1282.00	1134.00	500'R	1.109	652

Stock sizes: None

Quantities of any item less than the following, subject to
factory acceptance: 500 feet for all Multi-conductors listed as
stock items under Table PMD - 1000 feet for all other.

TABLE SR-MF

SIZE 14 AWG

Control Cable, 600 Volt

14 AWG 19/27 Tinned copper, each conductor 3/64" silicone rubber, Glass braid,
Color coded, conductors cabled, Taped, Black asbestos braid.
125°C (257°F)

No. of Conductors	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft. Ship. Weight
	Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
2	\$ 486.00	\$ 432.00	\$ 407.00	\$ 360.00	500 R	.444	119
3	694.00	617.00	581.00	514.00	500'R	.464	155
4	896.00	796.00	750.00	663.00	500'R	.512	187
5	1095.00	974.00	917.00	811.00	500'R	.563	238
6	1299.00	1155.00	1088.00	962.00	500'R	.618	278
7	1456.00	1294.00	1219.00	1078.00	500'R	.618	296
8	1625.00	1444.00	1360.00	1203.00	500'R	.673	344
9	1797.00	1598.00	1505.00	1331.00	500'R	.729	401
10	1966.00	1748.00	1646.00	1456.00	500'R	.790	418
11	2125.00	1889.00	1779.00	1574.00	500'R	.790	452
12	2287.00	2033.00	1915.00	1694.00	500'R	.818	467

Stock sizes: 2-3-4-5-7-8-12 Conductor

Quantities of any item less than the following, subject to
factory acceptance: 1000 feet.

TABLE SR-MD

SIZE 12 AWG

Control Cable, 600 Volt

12 AWG 19/25 Tinned copper, each conductor 3/64" Silicone rubber, Glass braid.
Color coded, conductors cabled, Taped, Black asbestos braid.
125°C (257°F)

No. of Conductors	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft. Ship. Weight
	Less than 250 ft.	250- 499 ft.	500- 1999 ft.	2000 ft. and over			
2	\$ 574.00	\$ 510.00	\$ 481.00	\$ 425.00	500'R	.485	141
3	821.00	730.00	688.00	608.00	500'R	.517	182
4	1059.00	941.00	886.00	784.00	500'R	.573	231
5	1296.00	1152.00	1085.00	960.00	500'R	.630	248
6	1542.00	1371.00	1291.00	1142.00	500'R	.693	331
7	1723.00	1532.00	1442.00	1276.00	500'R	.693	365
8	1924.00	1710.00	1611.00	1425.00	500'R	.755	427
9	2127.00	1890.00	1780.00	1575.00	500'R	.820	452
10	2325.00	2067.00	1946.00	1722.00	500'R	.888	592
11	2517.00	2237.00	2107.00	1864.00	500'R	.888	620
12	2710.00	2409.00	2268.00	2007.00	500'R	.919	690

Stock sizes: 2 thru 10 and 12 conductor

Non Stock combinations: Prices on request

Quantities of any non stock item less than the following subject to
factory acceptance: 1,000 feet.

ISSUE #10
SEPT. 26, 1966
Replaces Issue
dated Nov. 15, 1965

TABLE B
N.E.C. TYPE AVB

Switchboard wire, 600 volt, Underwriters' listed
Solid tinned copper, varnished cambric, asbestos insulation,
flameproof cotton braid. 90°C (194°F)

Size	Stranding	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
14	Solid	\$ 89.90	\$ 79.90	\$ 75.30	\$ 66.60	500'C	.200	32
12	"	99.40	88.30	83.20	73.60	500'C	.221	42
10	"	117.00	104.00	97.90	86.60	500'C	.242	57
8	"	158.00	141.00	133.00	117.00	500'C	.268	81
6	"	304.00	270.00	255.00	229.00	500'R	.336	130

Stock sizes: 14 to 8 - Gray

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color:

6 and smaller - 3,000 ft.

4 and larger - 500 ft.

TABLE BS
N.E.C. TYPE AVB

Switchboard cable, 600 volt, Underwriters' listed
Coarse stranded tinned copper, varnished cambric, asbestos insulation,
flameproof cotton braid. 90°C (194°F)

Size	Stranding	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
14	7/.0242	\$ 95.20	\$ 84.60	\$ 79.70	\$ 70.50	500'C	.210	34
12	7/.0305	104.00	92.30	86.90	76.90	500'C	.229	43
10	7/.0385	130.00	115.00	109.00	95.70	500'C	.255	59
8	7/.0486	187.00	166.00	156.00	138.00	500'C	.285	83
6	7/.0612	319.00	284.00	267.00	236.00	500'R	.363	144

Stock sizes: 14 to 8 - Gray

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color:

6 and smaller - 3,000 ft.

4 and larger - 500 ft.

TABLE BH
N.E.C. TYPE AVB

Hinge cable, 600 volt, Underwriters' listed
Flexible stranded tinned copper, asbestos, varnished cambric, asbestos insulation,
flameproof cotton braid. 90°C (194°F)

Size	Stranding	Prices Per 1000 feet				Std. Pkg.	Nom. O.D.	M Ft. Ship. Weight
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
14	41/.010	\$ 106.00	\$ 93.80	\$ 88.40	\$ 78.20	500'C	.217	35
12	65/.010	123.00	109.00	103.00	90.80	500'C	.239	46

Stock sizes: 14 and 12 - Gray

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color: 6 and smaller - 3,000 ft.
4 and larger - 500 ft.

TABLE XB

N.E.C. TYPE TA

Switchboard wire, 600 volt, Underwriters' listed
Solid tinned copper, thermoplastic and asbestos insulation,
flameproof cotton braid. 90°C (194°F)

Size	Stranding	Prices Per 1000 feet				M Ft.		
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
14	Solid	\$ 74.40	\$ 66.10	\$ 62.30	\$ 55.10	500'C	.183	30
12	"	83.70	74.40	70.10	62.00	500'C	.200	39

Stock sizes: None
Non Stock sizes: Prices on request
Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color:
8 and smaller - 5,000 ft.
6 and larger - 2,000 ft.

TABLE XBS

N.E.C. TYPE TA

Switchboard cable, 600 volt, Underwriters' listed
Coarse stranded tinned copper, thermoplastic and asbestos insulation,
flameproof cotton braid. 90°C (194°F)

Size	Stranding	Prices Per 1000 feet				M Ft.		
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
14	7/.0242	\$ 77.50	\$ 68.90	\$ 64.90	\$ 57.40	500'C	.192	31
12	7/.0305	88.60	78.70	74.10	65.60	500'C	.211	41
10	7/.0385	106.00	93.60	88.10	78.00	500'C	.240	63
8	7/.0486	125.00	111.00	105.00	92.10	500'C	.267	80
6	7/.0612	254.00	226.00	213.00	188.00	500'R	.340	156
4	7/.0772	380.00	338.00	318.00	281.00	500'R	.381	194
2	7/.0974	526.00	467.00	440.00	389.00	500'R	.447	288
1/0	19/.0745	666.00	592.00	558.00	493.00	500'R	.558	443
4/0	19/.1055	900.00	800.00	753.00	666.00	500'R	.713	813

Stock sizes: 14 thru 2 and 1/0, 4/0 - Gray
Non Stock sizes: Prices on request
Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color:
8 and smaller - 5,000 ft.
6 and larger - 2,000 ft.

TABLE XBH

N.E.C. TYPE TA

Hinge cable, 600 volt, Underwriters' listed
Flexible stranded tinned copper, thermoplastic and asbestos insulation,
flameproof cotton braid. 90°C (194°F)

Size	Stranding	Prices Per 1000 ft.				M Ft.		
		Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
14	41/.010	\$ 81.80	\$ 72.70	\$ 68.50	\$ 60.60	500'C	.194	31
12	65/.010	101.00	88.90	83.70	74.10	500'C	.214	41
10	104/.010	120.00	107.00	100.00	88.50	500'C	.241	57

Stock sizes: 14 thru 12 - Gray
Non Stock sizes: Prices on request
Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 5,000 ft.
6 and larger - 2,000 ft.

ROCKBESTOS WIRE & CABLE CO.

Division of CERRO CORPORATION

New Haven 4, Conn.

RBB 00588

ISSUE #10
SEPT. 26, 1966
Replaces Issue
dated Nov. 15, 1965

TABLE SPB

N.E.C. TYPE TBS

Switchboard wire, 600 volt, Underwriters' listed
Solid tinned copper, thermoplastic insulated, flameproof
cotton braid 90°C (194°F)

Size	Stranding	Insul. Mils	Braid Mils	Prices Per 1000 feet				M Ft.		
				Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
14	Solid	31	16	\$ 49.10	\$ 42.70	\$ 40.20	\$ 35.60	500'C	.163	26
12	"	31	16	53.50	47.50	44.70	39.60	500'C	.180	36
10	"	31	16	74.00	65.80	61.90	54.80	500'C	.201	50
8	"	47	17	99.20	88.20	83.10	73.50	500'C	.222	81
6	"	63	17	222.00	197.00	186.00	164.00	1000'N/R	.325	124

Stock sizes: None

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 5,000 ft.
6 and larger - 2,000 ft.

TABLE SPBS

N.E.C. TYPE TBS

Switchboard cable, 600 volt, Underwriters' listed
Coarse stranded tinned copper, thermoplastic insulated, flameproof
cotton braid. 90°C (194°F)

Size	Stranding	Insul. Mils	Braid Mils	Prices Per 1000 feet				M Ft.		
				Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
14	7/.0242	31	16	\$ 49.10	\$ 43.70	\$ 41.10	\$ 36.40	500'C	.172	28
12	7/.0305	31	16	58.70	52.20	49.20	43.50	500'C	.191	37
10	7/.0385	31	16	81.50	72.50	68.30	60.40	500'C	.215	52
8	7/.0486	47	17	107.00	94.90	89.40	79.10	500'C	.279	85
6	7/.0612	63	17	238.00	212.00	199.00	176.00	1000'N/R	.349	133

Stock sizes: 14 and 12 Gray

Non Stock sizes: Prices on request

Quantities of any non-stock item less than the following subject to
factory acceptance: Size and/or color: 8 and smaller - 5,000 ft.
6 and larger - 2,000 ft.

TABLE SPBH

N.E.C. TYPE TBS

Hinge cable, 600 volt, Underwriters' listed
Flexible stranded tinned copper, thermoplastic insulated, flameproof
cotton braid. 90°C (194°F)

Size	Stranding	Insul. Mils	Braid Mils	Prices Per 1000 feet				M Ft.		
				Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
18	16/.010	31	16	\$ 42.50	\$ 37.80	\$ 35.60	\$ 31.50	500'C	.144	17
14	41/.010	31	16	52.80	46.90	44.20	39.10	500'C	.174	28
12	65/.010	31	16	66.80	59.40	55.90	49.50	500'C	.194	38
10	104/.010	31	16	99.40	88.30	83.20	73.60	500'C	.219	53
8	133/.0111	47	17	179.00	159.00	150.00	132.00	500'C	.300	86
6	49/.0231	63	17	297.00	264.00	249.00	220.00	1000'N/R	.350	146

Stock sizes: 14 thru 12 Gray as listed

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject
to factory acceptance: Size and/or color: 8 and smaller - 5,000 ft.
6 and larger - 2,000 ft.

TABLE 108

ACA Switchboard Wire, 1000 Volt

Flexible stranded tinned copper, Synthetic tapes and Asbestos insulation, Flameproof cotton braid.
90°C (194°F)

Size	Stranding	Tape Mils	Asbestos Mils	Braid Mils	Prices Per 1000 feet				M Ft.		
					Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
20	10/.010	5	8.5	12.5	\$ 48.50	\$ 43.10	\$ 40.60	\$ 35.90	500'C	.090	10
18	16/.010	5	8.5	12.5	58.30	51.80	48.80	43.20	500'C	.100	11
16	26/.010	5	8.5	12.5	64.30	57.10	53.80	47.60	500'C	.114	15
14	41/.010	8	8.5	12.5	84.20	74.90	70.50	62.40	500'C	.137	21
12	65/.010	8	10	12.5	107.00	94.60	89.00	78.80	500'C	.160	31
10	104/.010	8	10	12.5	123.00	109.00	103.00	90.70	500'C	.185	48
8	133/.0111	12	10	12.5	262.00	233.00	220.00	194.00	500'C	.244	72
6	133/.0140	12	10	12.5	368.00	327.00	308.00	272.00	1M'N/R	.297	124
4	133/.0177	12	10	12.5	508.00	452.00	425.00	376.00	1M'N/R	.360	188
2	133/.0223	12	12	12.5	721.00	641.00	604.00	534.00	1M'N/R	.431	270

Stock sizes: 14 and 12 - Grey

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject
to factory acceptance: Size and/or color: 8 and smaller - 5,000 ft.
6 and larger - 1,000 ft.

TABLE EMA

ACA Control and Switchboard Cable, 1000 Volt

Stranded tinned copper, Synthetic tapes and Asbestos insulation, Lacquered cotton braid.
90°C (194°F)

Size	Stranding	Tape Mils	Asbestos Mils	Braid Mils	Prices Per 1000 feet				M Ft.		
					Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
14	19/.0142	10	20	12.5	\$ 77.10	\$ 68.50	\$ 64.50	\$ 57.10	500'C	.161	24
12	19/.0179	10	20	12.5	88.20	78.40	73.80	65.30.	500'C	.180	32

Stock sizes: 14 - Black, White, Red - 12 - Black and Red.

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject
to factory acceptance: Size and/or color: 8 and smaller - 5,000 ft.
6 and larger - 2,000 ft.

TABLE ZM

ACA Hookup Wire, 1000 Volt

Flexible tinned copper, synthetic tape, Felted asbestos, Lacquered glass braid overall.
125°C (257°F)

Size	Stranding	Tape Mils	Asbestos Mils	Braid Mils	Prices Per 1000 feet				M Ft.		
					Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship Weight
18	16/.010	5	8.5	16	\$ 52.80	\$ 46.90	\$ 44.20	\$ 39.10	500'S	.095	10
16	26/.010	5	8.5	16	57.90	51.50	48.50	42.90	500'S	.109	14
14	41/.010	8	8.5	16	76.00	67.60	63.60	56.30	500'S	.132	22
12	65/.010	8	10	16	91.50	81.40	76.60	67.80	500'S	.155	32

Stock sizes: 18 to 12 - White; - and 14 cotton braid - Red.

Non Stock sizes: Prices on request

Quantities of any non stock item less than the following subject
to factory acceptance: Size and/or color: 10 and smaller - 5,000 ft.)
8 and larger - 2,000 ft.)

ROCKBESTOS WIRE & CABLE CO.

ROCKBESTOS WIRE & CABLE CO.

NEW HAVEN, CT

RBB 00590

ISSUE #10
SEPT. 26, 1968
Replaces Issue
dated Nov. 15, 1965

TABLE SIS

X LINK polyethylene Switchboard Wire, 600 volt, Underwriters' listed
Solid tinned copper, cross-linked polyethylene insulation, Type SIS
90°C. (194°F.)

Size	Stranding	Insul. Mils	Prices Per 1000 ft.				Std. Pkg.	Nom. O. D.	M Ft. Ship. Weight
			Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
*18	Solid	31	\$ 32.30	\$ 28.70	\$ 27.00	\$ 23.90	500'C	.110	10
*16	"	31	35.10	31.20	29.40	26.00	500'C	.120	14
14	"	31	45.40	40.30	38.00	33.60	500'C	.130	19
12	"	31	50.80	45.10	42.50	37.60	500'C	.150	28
10	"	31	70.50	62.60	59.00	52.20	500'C	.170	41
8	"	47	94.60	84.10	79.20	70.10	500'C	.230	69
6	"	62	208.00	185.00	175.00	154.00	500'C	.300	110

Stock sizes: None

Min. Qty. for non Stock sizes: 5000 ft.

TABLE SISS

X LINK polyethylene Switchboard Cable, 600 volt, Underwriters' listed
Coarse stranded tinned copper, separator, cross-linked polyethylene
insulation, Type SIS. 90°C. (194°F.)

Size	Stranding	Insul. Mils	Prices Per 1000 ft.				Std. Pkg.	Nom. O. D.	M Ft. Ship. Weight
			Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
*18	7/.0152	31	\$ 33.20	\$ 29.50	\$ 27.80	\$ 24.60	500'C	.110	11
*16	7/.0192	31	35.90	31.90	30.10	26.60	500'C	.130	15
14	7/.0242	31	46.30	41.20	38.80	34.30	500'C	.140	20
12	7/.0305	31	55.90	49.70	46.80	41.40	500'C	.160	28
10	7/.0385	31	77.20	68.60	64.60	57.20	500'C	.180	42
8	7/.0486	47	102.00	90.50	85.20	75.40	500'C	.250	70
6	7/.0612	62	222.00	197.00	186.00	164.00	500'C	.320	113

Stock sizes: 16 thru 12 Grey

Min. Qty. for non Stock sizes: 5000 ft.

TABLE SISF

X LINK polyethylene Hinge Cable, 600 volt, Underwriters' listed
Flexible stranded tinned copper, separator, cross-linked polyethylene
insulation, Type SIS. 90°C. (194°F.)

Size	Stranding	Insul. Mils	Prices Per 1000 ft.				Std. Pkg.	Nom. O. D.	M Ft. Ship. Weight
			Less than 500 ft.	500- 1999 ft.	2000- 9999 ft.	10,000 ft. and over			
*18	16/.010	31	\$ 40.80	\$36.20	\$ 34.10	\$ 30.20	500'C	.110	11
*16	26/.010	31	43.30	38.50	36.30	32.10	500'C	.130	15
14	41/.010	31	50.00	44.40	41.80	37.00	500'C	.140	20
12	65/.010	31	63.00	56.00	52.80	46.70	500'C	.160	28
10	105/.010	31	93.80	83.40	78.50	69.50	500'C	.190	43
8	133/.0111	47	167.00	148.00	139.00	123.00	500'C	.270	75
6	133/.0140	62	307.00	273.00	257.00	227.00	500'C	.340	119

Stock sizes: 18 thru 6 Grey

Min. Qty. for non Stock sizes: 5000 ft.

*Not listed by Underwriters' Laboratories, Inc.

ROCKBESTOS WIRE & CABLE CO.
Division of CERRO CORPORATION

New Haven 4, Conn.

RBB 00591

TABLE TC

Armored Thermostat Wire

Solid enameled copper - each conductor 12½ Mils Felted Asbestos Wall, polarized, twisted, coated steel armor overall.

Size	No. of Conductors	Prices Per 1000 feet				M Ft.		
		Less than 500 ft.	500-1999 ft.	2000-9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
18	2/C	\$ 51.20	\$ 45.50	\$ 42.80	\$ 37.90	500'C	.153	25
18	3/C	65.20	58.00	54.60	48.30	500'C	.163	36

Stock sizes: 18 - 2 and 3/C

Non Stock sizes and combinations: Prices on request (Do not produce more than 3/C of any size)

Quantities of any non stock item less than the following subject to factory acceptance: Size or number of conductors: 5,000 feet.

TABLE LH

Heating Cable, 120 Volt (Maximum lead sheath temp. 350°F)

19 AWG Special alloy (max. resistance .5208 ohms/foot) 40 mils felted asbestos, 3/64" lead sheath. Recommended wattage - 7 watts/foot - 60 feet at 110 volts, 120 feet at 220 volts (Not to exceed 120 volts to ground).

Size	Prices Per 1000 feet				M Ft.		
	Less than 500 ft.	500-1999 ft.	2000-9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
19	\$ 157.00	\$ 140.00	\$ 132.00	\$ 116.00	1200'R	.210	178

Stock: 1200 ft. reels

TABLE LHV

Heating Cable, 440 Volt (Maximum lead sheath temp. 165°F)

19 AWG Special alloy (max. resistance .5208 ohms/foot) 31 mils felted asbestos, 21 mils varnished cambric, 3/64" lead sheath. Recommended wattage - 7 watts/foot - 60 ft. at 110 volts, 120 feet at 220 volts, 240 ft. at 440 volts.

Size	Prices Per 1000 feet				M Ft.		
	Less than 500 ft.	500-1999 ft.	2000-9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
19	\$ 168.00	\$ 149.00	\$ 141.00	\$ 124.00	1200'R	.240	192

Stock: 1200 ft. Reels

Underwriters' approved, by report, for pipe heating.

TABLE SR-HC

Silicone Rubber Heating Cable, 440 volt (Maximum operating temp. 200°C (392°F))

19 AWG Special alloy (max. resistance .5208 ohms/foot)
3/64" Silicone rubber-tinned copper braid shield. Recommended wattage - 10 watts/foot - 50 ft. at 115 volts, 100 ft. at 230 volts, 200 ft at 460 volts.

Size	Prices Per 1000 feet				M Ft.		
	Less than 500 ft.	500-1999 ft.	2000-9999 ft.	10,000 ft. and over	Std. Pkg.	Nom. O.D.	Ship. Weight
19	\$ 196.00	\$ 174.00	\$ 164.00	\$ 145.00	1200'R	.158	28

Stock: 1200 ft. reels

Minimum ordering quantity - 1200 ft. reel. We reserve the right to ship up to 20% of footage in two piece reels, with each piece 200 feet or multiple thereof.

ISSUE #10
SEPT. 26, 1966
Replaces Issue
dated Nov. 15, 1965

ROCKZONE® I**CONTROL & APPARATUS LEAD WIRE - 600 VOLT**

Stranded Tinned Copper, X Link® 90 Insulation, Rockcote®
Flame Retardant Coating
90°C - 194°F

Size	Strand	Ins.	Price Per 1000 Feet				O.D.	Wt. #/M'	Std. Package
			Less 500	500- 1999	2000- 9999	10,000 over			
14	19/.0142	.030"	\$ 45.80	\$ 40.70	\$ 38.30	\$ 33.90	.140	17	500°C
12	19/.0179	.030"	55.80	49.60	46.70	41.30	.160	26	500°C
9	19/.0254	.030"	85.10	75.60	71.20	63.00	.190	42	500°C

■ Stocked at New Haven-Black only
Other colors available

ROCKZONE® II**CONTROL & APPARATUS LEAD WIRE**

Stranded Tinned Copper, X Link® 90 Insulation,
Rockite® Jacket
90°C - 194°F

Size	Strand	Ins.	Jkt.	Price Per 1000 Feet				O.D.	Wt. #/M'	Std. Package
				Less 500	500- 1999	2000- 9999	10,000 over			
14	19/.0142	.030"	.015"	\$ 65.90	\$ 58.60	\$ 55.10	\$ 48.80	.170	22	500°C
12	19/.0179	.030"	.015"	84.10	74.80	70.40	62.30	.190	31	500°C
9	19/.0254	.030"	.015"	121.00	108.00	102.00	89.60	.225	53	500°C

■ Stocked at New Haven-Black only
Other colors available

ROCKZONE® III**CONTROL & APPARATUS LEAD WIRE**

Stranded Tinned Copper, X Link® 125 Insulation, Polyester Braid
with Heat Resistant Finish
125°C - 257°F

Size	Strand	Ins.	Braid	Price Per 1000 Feet				O.D.	Wt. #/M'	Std. Package
				Less 500	500- 1999	2000- 9999	10,000 over			
14	19/.0142	.030"	.010"	\$ 84.00	\$ 74.60	\$ 70.30	\$ 62.20	.155	22	500°C
12	19/.0179	.030"	.010"	91.40	81.20	76.50	67.70	.175	30	500°C
9	19/.0254	.030"	.010"	126.00	112.00	105.00	92.70	.210	55	500°C

■ Not Stocked

*Trademark

ROCKZONE®
POWER CABLE - 600 VOLT
Solid & Stranded Tinned Copper, X Link* 90 Insulation, Rockcote*
Flame Retardant Coating
90°C - 194°F

Size	Stranding	Insul. Mils	Price Per 1000 Feet				O.D.	Wt. #/M'	Std. Pkg.
			Less 500	500- 1999	2000- 9999	10,000 over			
14	Solid	.030"	\$ 38.30	\$ 34.10	\$ 32.10	\$ 28.40	.130	17	500'C
12	Solid	.030"	50.20	44.60	42.00	37.20	.150	26	500'C
10	Solid	.030"	58.30	51.80	48.80	43.20	.170	38	500'C
8	Solid	.045"	103.00	90.70	85.40	75.60	.220	63	500'C
14	7/.0242	.030"	44.70	39.70	37.40	33.10	.140	18	500'C
12	7/.0305	.030"	54.30	48.20	45.40	40.20	.160	27	500'C
10	7/.0385	.030"	74.00	65.80	61.90	54.80	.180	40	500'C
8	7/.0486	.045"	114.00	102.00	95.30	84.30	.240	67	500'C
6	7/.0612	.045"	164.00	146.00	137.00	121.00	.280	101	1000'R
4	7/.0772	.045"	212.00	189.00	178.00	157.00	.330	153	1000'R
2	7/.0974	.045"	326.00	290.00	273.00	241.00	.390	236	1000'R
1	19/.0664	.055"	478.00	425.00	401.00	354.00	.450	300	1000'R
1/0	19/.0745	.055"	535.00	476.00	448.00	396.00	.490	371	1000'R
2/0	19/.0837	.055"	623.00	554.00	521.00	461.00	.530	442	1000'R
3/0	19/.0940	.055"	740.00	658.00	620.00	548.00	.580	576	1000'R
4/0	19/.1055	.055"	956.00	850.00	801.00	708.00	.640	719	1000'R
250	37/.0822	.065"	1160.00	1031.00	971.00	859.00	.710	854	500'R
300	37/.0900	.065"	1337.00	1188.00	1119.00	990.00	.770	991	500'R
350	37/.0973	.065"	1494.00	1328.00	1250.00	1106.00	.820	1181	500'R
400	37/.1040	.065"	1664.00	1479.00	1393.00	1232.00	.870	1311	500'R
500	37/.1162	.065"	2016.00	1792.00	1688.00	1493.00	.850	1644	500'R
600	61/.0992	.080"	2579.00	2292.00	2159.00	1910.00	1.045	1970	500'R
750	61/.1109	.080"	3276.00	2912.00	2742.00	2426.00	1.170	2445	500'R
1000	61/.1280	.080"	4315.00	3836.00	3612.00	3196.00	1.325	3237	500'R

Stocked at New Haven - Sizes: 14 thru 8 solid - Black
14 thru 8 stranded - Black, White, Red
6 thru 500 and 750 Black (except 300 and 400)

*Trademark Other sizes - 1000' minimum order - Other colors available

ROCKZONE® II**POWER CABLE - 600 VOLT**

Solid or Stranded Tinned Copper, X Link* 90 Insulation

Rockite* Jacket

90°C - 194°F

Size	Stranding	Ins.	Jkt.	Price Per 1000 Feet				O.D.	Wt. #/M'	Std. Pkg.
				Less 500	500- 1999	2000- 9999	10,000 over			
14	Solid	.030"	.015"	\$ 57.80	\$ 51.40	\$ 48.40	\$ 42.80	.160	22	500'C
12	Solid	.030"	.015"	70.60	62.80	59.10	52.30	.180	31	500'C
10	Solid	.030"	.015"	89.10	79.20	74.60	66.00	.200	44	500'C
8	Solid	.045"	.015"	148.00	131.00	124.00	109.00	.255	71	500'C
14	7/.0242	.030"	.015"	64.40	57.20	53.90	47.70	.170	23	500'C
12	7/.0305	.030"	.015"	82.10	73.00	68.70	60.80	.190	32	500'C
10	7/.0385	.030"	.015"	102.00	90.00	84.80	75.00	.215	47	500'C
8	7/.0486	.045"	.015"	162.00	144.00	136.00	120.00	.275	75	500'C
6	7/.0612	.045"	.030"	223.00	198.00	187.00	165.00	.345	120	1000'R
4	7/.0772	.045"	.030"	291.00	258.00	243.00	215.00	.390	175	1000'R
2	7/.0974	.045"	.030"	418.00	371.00	350.00	309.00	.450	261	1000'R
1	19/.0664	.055"	.045"	538.00	478.00	450.00	398.00	.545	332	1000'R
1-0	19/.0745	.055"	.045"	576.00	512.00	482.00	426.00	.585	420	1000'R
2-0	19/.0837	.055"	.045"	704.00	626.00	589.00	521.00	.630	516	1000'R
3-0	19/.0940	.055"	.045"	836.00	743.00	700.00	619.00	.685	635	1000'R
4-0	19/.1055	.055"	.045"	1048.00	932.00	877.00	776.00	.740	782	1000'R
250	37/.0822	.065"	.045"	1398.00	1242.00	1170.00	1035.00	.850	956	500'R
300	37/.0900	.065"	.045"	1571.00	1396.00	1315.00	1163.00	.910	1103	500'R
350	37/.0973	.065"	.045"	1815.00	1613.00	1519.00	1344.00	.960	1299	500'R
400	37/.1040	.065"	.045"	2016.00	1792.00	1688.00	1493.00	1.010	1436	500'R
500	37/.1162	.065"	.045"	2421.00	2152.00	2027.00	1793.00	1.090	1799	500'R
600	61/.0992	.080"	.065"	2977.00	2646.00	2492.00	2205.00	1.205	2121	500'R
750	61/.1109	.080"	.065"	3771.00	3352.00	3157.00	2793.00	1.310	2610	500'R
1000	61/.1280	.080"	.065"	4962.00	4410.00	4153.00	3675.00	1.465	3422	500'R

Stocked at New Haven - sizes: 14 thru 8 stranded, Black, White Red
6 thru 500, except 300-400, Black

Other sizes - 1000' minimum order

Other colors available

*Trademark

ROCKZONE® III

POWER CABLE - 600 VOLT

Stranded Tinned Copper, X Link* 125 Insulation

Polyester Braid #2 & Smaller, Asbestos Braid #1 & Larger, Heat Resistant Finish

125°C - 257°F

Size	Strand	Ins.	Braid	Price Per 1000 Feet				O.D.	Wt. #/M'	Std. Pkg.
				Less 500	500- 1999	2000- 9999	10,000 over			
14	7/.0242	.030"	.010"	\$ 81.80	\$ 72.70	\$ 68.50	\$ 60.60	.155	22	500'C
12	7/.0305	.030"	.010"	89.10	79.20	74.60	66.00	.175	32	500'C
10	7/.0385	.030"	.010"	105.00	93.00	87.60	77.50	.200	46	500'C
8	7/.0486	.045"	.010"	173.00	154.00	145.00	128.00	.262	77	500'C
6	7/.0612	.045"	.010"	221.00	196.00	185.00	163.00	.300	115	1000'R
4	7/.0772	.045"	.010"	435.00	387.00	364.00	322.00	.350	169	1000'R
2	7/.0974	.045"	.010"	620.00	551.00	519.00	459.00	.410	254	1000'R
1	19/.0664	.055"	.045"	789.00	701.00	660.00	584.00	.530	345	1000'R
1/0	19/.0745	.055"	.045"	1026.00	912.00	859.00	760.00	.570	422	1000'R
2/0	19/.0837	.055"	.045"	1132.00	1006.00	947.00	838.00	.615	517	1000'R
3/0	19/.0940	.055"	.045"	1257.00	1118.00	1053.00	931.00	.670	635	1000'R
4/0	19/.1055	.055"	.045"	1403.00	1247.00	1175.00	1039.00	.725	785	1000'R
250	37/.0822	.065"	.045"	1753.00	1558.00	1467.00	1298.00	.795	924	500'R
300	37/.0900	.065"	.045"	1909.00	1697.00	1598.00	1414.00	.850	1065	500'R
350	37/.0973	.065"	.045"	2077.00	1846.00	1738.00	1538.00	.900	1261	500'R
400	37/.1040	.065"	.045"	2254.00	2003.00	1886.00	1669.00	.950	1395	500'R
500	37/.1162	.065"	.045"	2594.00	2306.00	2171.00	1921.00	1.030	1757	500'R
600	61/.0992	.080"	.045"	2989.00	2657.00	2502.00	2214.00	1.145	2073	500'R
750	61/.1109	.080"	.045"	3358.00	2985.00	2811.00	2487.00	1.250	2557	500'R
1000	61/.1280	.080"	.045"	4387.00	3899.00	3672.00	3249.00	1.405	3365	500'R

■ Not stocked

*Trademark

ISSUE #10
SEPT. 26, 1966
Replaces Issue
dated Nov. 15, 1965

X LINK* 90 CONTROL CABLE

600 VOLT. 90°C - 194°F

Stranded Tinned Copper, .030" X Link* 90 Insulation Color Coded Cabled

Fillers Where Necessary, Tape, 90°C Rockhide* Sheath

Number Of Cdrs	Price Per 1000 Feet							
	Less 500	500- 1999	2000- 9999	10,000 over	Jkt. Thick	O.D.	Wt. #/M'	Std. Pkg.
#14, 19/#27								
2	\$ 216.00	\$ 192.00	\$ 181.00	\$ 160.00	.045"	.360	63	1000'R
3	256.00	227.00	214.00	189.00	.045"	.380	83	1000'R
4	306.00	272.00	256.00	226.00	.045"	.415	107	1000'R
5	403.00	358.00	337.00	298.00	.045"	.456	128	1000'R
6	445.00	395.00	372.00	329.00	.045"	.495	146	1000'R
7	466.00	414.00	390.00	345.00	.045"	.495	163	1000'R
8	515.00	458.00	431.00	381.00	.060"	.567	188	1000'R
9	636.00	566.00	533.00	471.00	.060"	.609	210	1000'R
10	688.00	611.00	576.00	509.00	.060"	.664	255	1000'R
12	773.00	687.00	647.00	572.00	.060"	.680	275	1000'R
15	993.00	882.00	831.00	735.00	.060"	.721	338	1000'R
19	1229.00	1092.00	1029.00	910.00	.060"	.795	423	1000'R
#12, 19/#25								
2	262.00	233.00	220.00	194.00	.045"	.398	94	1000'R
3	322.00	286.00	269.00	238.00	.045"	.421	120	1000'R
4	420.00	374.00	352.00	311.00	.045"	.461	144	1000'R
5	480.00	426.00	402.00	355.00	.045"	.507	180	1000'R
6	547.00	486.00	458.00	405.00	.060"	.582	210	1000'R
7	581.00	516.00	486.00	430.00	.060"	.582	244	1000'R
8	686.00	610.00	575.00	508.00	.060"	.630	270	1000'R
9	751.00	668.00	629.00	556.00	.060"	.677	300	1000'R
10	851.00	756.00	712.00	630.00	.060"	.741	351	1000'R
12	943.00	838.00	789.00	698.00	.060"	.759	388	1000'R
15	1176.00	1046.00	985.00	871.00	.060"	.805	471	1000'R
19	1394.00	1239.00	1167.00	1032.00	.080"	.930	594	1000'R
#9, 19/#22								
2	389.00	346.00	326.00	288.00	.045"	.472	137	1000'R
3	449.00	399.00	376.00	332.00	.045"	.501	195	1000'R
4	621.00	552.00	520.00	460.00	.060"	.580	257	1000'R
5	721.00	641.00	604.00	534.00	.060"	.638	307	1000'R
6	819.00	728.00	685.00	606.00	.060"	.693	358	1000'R
7	902.00	802.00	755.00	668.00	.060"	.693	408	1000'R
8	1036.00	921.00	867.00	767.00	.060"	.752	459	1000'R
10	1332.00	1184.00	1115.00	986.00	.080"	.730	626	1000'R
12	1529.00	1359.00	1280.00	1132.00	.080"	.953	712	1000'R

■ Not stocked

*Trademark

ROCKBESTOS WIRE & CABLE CO.
Division of CERRO CORPORATION

New Haven 4, Conn.

RBB 00597

X LINK* 125 CONTROL CABLE
125°C - 257°F

Stranded Tinned Copper, .030" X Link* 125 Insulation, Color Coded,
Braid Lacquered, Cabled Asbestos Fillers, Tape, Asbestos Braid Overall

	Price Per 1000 Feet							
Number Of Cords	Less 500	500- 1999	2000- 9999	10,000 over	Jkt. Thick	O.D.	Wt. #/M'	Std. Pkg.
19/#27 (Approx. #14 AWG)								
2	\$ 497.00	\$ 442.00	\$ 416.00	\$ 368.00	.040"	.380	80	1000'R
3	636.00	566.00	533.00	471.00	.040"	.403	103	1000'R
4	701.00	623.00	587.00	519.00	.040"	.442	128	1000'R
5	794.00	706.00	665.00	588.00	.040"	.487	147	1000'R
6	887.00	789.00	743.00	657.00	.040"	.530	170	1000'R
7	951.00	845.00	796.00	704.00	.040"	.530	187	1000'R
8	1031.00	916.00	863.00	763.00	.040"	.577	215	1000'R
9	1116.00	992.00	934.00	826.00	.040"	.623	235	1000'R
10	1205.00	1071.00	1008.00	892.00	.040"	.685	255	1000'R
12	1341.00	1192.00	1123.00	993.00	.040"	.703	298	1000'R
15	1612.00	1433.00	1350.00	1194.00	.040"	.748	368	1000'R
19	1792.00	1593.00	1500.00	1327.00	.040"	.830	450	1000'R
19/#25 (Approx. #12 AWG)								
2	581.00	516.00	486.00	430.00	.040"	.418	126	1000'R
3	748.00	665.00	627.00	554.00	.040"	.443	150	1000'R
4	864.00	768.00	724.00	640.00	.040"	.487	174	1000'R
5	1002.00	891.00	839.00	742.00	.040"	.538	200	1000'R
6	1140.00	1013.00	954.00	844.00	.040"	.587	217	1000'R
7	1238.00	1101.00	1037.00	917.00	.040"	.587	251	1000'R
8	1340.00	1191.00	1121.00	992.00	.040"	.639	243	1000'R
9	1449.00	1288.00	1213.00	1073.00	.040"	.692	292	1000'R
10	1568.00	1394.00	1312.00	1161.00	.040"	.761	315	1000'R
12	1780.00	1582.00	1490.00	1318.00	.040"	.781	363	1000'R
15	2152.00	1913.00	1802.00	1594.00	.040"	.832	432	1000'R
19	2462.00	2188.00	2060.00	1823.00	.040"	.925	525	1000'R
19/#22 (Approx. #10 AWG)								
2	806.00	717.00	675.00	597.00	.040"	.492	168	1000'R
3	1085.00	964.00	908.00	803.00	.040"	.563	220	1000'R
4	1233.00	1096.00	1032.00	913.00	.040"	.576	271	1000'R
5	1377.00	1224.00	1153.00	1020.00	.040"	.638	327	1000'R
6	1600.00	1422.00	1340.00	1185.00	.040"	.698	375	1000'R
7	1750.00	1556.00	1465.00	1296.00	.040"	.698	427	1000'R
9	2042.00	1815.00	1709.00	1512.00	.040"	.826	535	1000'R
12	2532.00	2250.00	2119.00	1875.00	.040"	.935	690	1000'R

■ Not stocked

*Trademark

ISSUE #10
SEPT. 26, 1966.
Replaces Issue
dated June 3, 1966

**X LINK* 90 3/C INTERLOCKED ARMOR
POWER CABLE - 600 VOLT**

Stranded Tinned Copper, X Link* 90 Insulation, 3/C Cabled, Jute Fillers,
Tape, Interlocked Armor

			Price Per 1000 Feet				Nominal O.D.		
Size	Strand	Insul. Thick	Less 500	500- 1999	2000- 9999	10,000 over	Under Armor	Over Armor	Wt. #/M'
Aluminum Armor									
6	7/.0612	.045"	\$ 929.00	\$ 826.00	\$ 778.00	\$ 688.00	.602	.902	413
4	7/.0772	.045"	1282.00	1139.00	1073.00	949.00	.710	1.010	588
2	7/.0974	.045"	1629.00	1448.00	1363.00	1206.00	.839	1.139	857
1	19/.0664	.055"	2096.00	1863.00	1754.00	1552.00	.968	1.268	1079
1/0	19/.0745	.055"	2563.00	2278.00	2145.00	1898.00	1.054	1.354	1303
2/0	19/.0837	.055"	3030.00	2693.00	2536.00	2244.00	1.140	1.440	1595
3/0	19/.0940	.055"	3496.00	3107.00	2926.00	2589.00	1.247	1.547	1956
4/0	19/.1055	.055"	3930.00	3494.00	3290.00	2911.00	1.376	1.676	2412
250	37/.0822	.065"	5002.00	4446.00	4187.00	3705.00	1.527	1.827	2871
350	37/.0973	.065"	6073.00	5398.00	5083.00	4498.00	1.763	2.063	3905
500	37/.1162	.065"	7771.00	6908.00	6505.00	5756.00	1.828	2.128	5375
750	61/.1109	.080"	11340.00	0080.00	9492.00	8400.00	2.516	2.816	7859
Galvanized Steel Armor									
6	7/.0612	.045"	912.00	810.00	763.00	675.00	.602	.902	628
4	7/.0722	.045"	1256.00	1116.00	1051.00	930.00	.710	1.010	838
2	7/.0974	.045"	1596.00	1419.00	1336.00	1182.00	.839	1.139	1144
1	19/.0664	.055"	2054.00	1826.00	1719.00	1521.00	.968	1.268	1413
1/0	19/.0745	.055"	2511.00	2232.00	2102.00	1860.00	1.054	1.354	1664
2/0	19/.0837	.055"	2969.00	2639.00	2485.00	2199.00	1.140	1.440	1889
3/0	19/.0940	.055"	3425.00	3045.00	2867.00	2537.00	1.247	1.547	2383
4/0	19/.1055	.055"	3852.00	3424.00	3224.00	2853.00	1.376	1.676	2887
250	37/.0822	.065"	4901.00	4356.00	4102.00	3630.00	1.527	1.827	3372
350	37/.0973	.065"	5950.00	5289.00	4980.00	4407.00	1.763	2.063	4484
500	37/.1162	.065"	7614.00	6768.00	6374.00	5640.00	1.828	2.128	5970
750	61/.1109	.080"	11114.00	9879.00	9303.00	8232.00	2.516	2.816	8671

■ Not stocked

*Trademark

CONDUIT FILL WEIGHTS AND DIMENSIONS

TABLE 11

MAXIMUM CABLE DIAMETERS FOR PERMISSIBLE CONDUIT FILL

Conduit Size Inches	NOT LEAD COVERED No. Cables per Conduit				LEAD COVERED No. Cables per Conduit			
	1	2	3	4	1	2	3	4
1/2	.450	.243	.225	.195	.458	.239	.225	.190
3/4	.598	.323	.300	.260	.609	.318	.300	.253
1	.762	.412	.382	.331	.776	.405	.382	.322
1 1/4	1.000	.543	.505	.437	1.025	.535	.505	.426
1 1/2	1.170	.634	.588	.510	1.195	.624	.588	.496
2	1.505	.814	.755	.654	1.535	.801	.755	.637
2 1/2	1.795	.972	.902	.781	1.832	.956	.902	.761
3	2.232	1.206	1.120	.969	2.275	1.187	1.120	.945
3 1/2	2.585	1.398	1.295	1.123	2.635	1.375	1.295	1.094
4	2.930	1.585	1.470	1.273	2.985	1.559	1.470	1.240
4 1/2	3.281	1.776	1.646	1.425	3.345	1.745	1.646	1.389
5	3.675	1.987	1.843	1.596	3.745	1.955	1.843	1.555
6	4.415	2.390	2.215	1.920	4.500	2.350	2.215	1.870

TABLE 12

COMBINATIONS OF CONDUCTORS

Per Cent Area of Conduit or Tubing

TABLE NO. 3 NEC (See Sections 3466 and 3486 NEC)

	Number of Conductors				
	1	2	3	4	Over 4
Conductors (not lead covered)	53	31	40	40	40
Lead-Covered conductors	55	30	40	38	35

TABLE 13

ELECTRICAL METALLIC TUBING
WEIGHTS AND DIMENSIONS

Size, inches	Diameter inches		Approximate weight lbs. per 1000 feet
	Internal	External	
1/2	0.622	0.706	321
3/4	0.824	0.922	488
1	1.049	1.163	711
1 1/4	1.380	1.510	1000
1 1/2	1.610	1.740	1180
2	2.067	2.197	1500

TABLE 14

DIMENSIONS AND PERCENT AREA OF CONDUIT AND TUBING

Areas of Conduit or Tubing for the Combinations of Wires Permitted by Table 12

CONDUIT			PERMISSIBLE AREA—SQUARE INCHES							
Trade Size	Internal Diameter Inches	Total Area 100%	Not Lead Covered			Lead Covered				
			1 Cond. 53%	2 Cond. 31%	3 Cond. and Over 40%	1 Cond. 55%	2 Cond. 30%	3 Cond. 40%	4 Cond. 38%	Over 4 Cond. 35%
1/2	.622	.30	.16	.09	.12	.17	.09	.12	.11	.11
3/4	.824	.53	.28	.16	.21	.29	.16	.21	.20	.19
1	1.049	.86	.46	.27	.34	.47	.26	.34	.33	.30
1 1/4	1.380	1.50	.80	.47	.60	.83	.43	.60	.57	.53
1 1/2	1.610	2.04	1.08	.63	.82	1.12	.61	.82	.78	.71
2	2.067	3.36	1.78	1.04	1.34	1.85	1.01	1.34	1.28	1.18
2 1/2	2.469	4.79	2.54	1.48	1.92	2.63	1.44	1.92	1.82	1.68
3	3.068	7.38	3.91	2.29	2.95	4.06	2.21	2.95	2.80	2.58
3 1/2	3.548	9.90	5.25	3.07	3.96	5.44	2.97	3.96	3.76	3.47
4	4.026	12.72	6.74	3.94	5.09	7.00	3.82	5.09	4.83	4.45
5	5.047	20.00	10.60	6.20	8.00	11.00	6.00	8.00	7.60	7.00
6	6.065	28.89	15.31	8.96	11.56	15.89	8.67	11.56	10.98	10.11

From Chapter 9 NEC 1965

RBB 00600

MAIN OFFICE AND FACTORY

Nicoll and Canner Streets
New Haven, Conn. 06504
(203) 787-1141

(CHICAGO)*BELLWOOD, ILLINOIS 60104
2615 Grant Ave.
(312) 379-2265

*LOS ANGELES, CALIF. 90021
Rm. 201, 1807 E. Olympic Blvd.
(213) 627-2818

CLEVELAND, OHIO 44110
16601 St. Clair Ave.
(216) 481-3770

OAKLAND, CALIF. 94612
Suite 933-First Western Bldg.
1330 Broadway
(415) 452-4860

ELMHURST, NEW YORK 11373
91-31 Queens Blvd.
(212) 651-2500

ORLANDO, FLORIDA 32809
7040 Lake Ellenor Drive
(305) 855-7270

HARTFORD, CONN. 06103
119 Ann Street
(203) 747-7394

(PITTS)*CARNEGIE, PENNA. 15106
P. O. Box 490
(412) 923-2644

HOUSTON, TEXAS 77006
3407 Montrose Boulevard
(713) 523-6843

ST. LOUIS (CLAYTON), MO. 63105
200 S. Bemiston Ave.
(314) 721-2498

LATHRUP VILLAGE, MICHIGAN 48037
28660 Southfield Rd.
(313) 442-5833

VILLANOVA, PENNA. 19085
771 Lancaster Ave.
(215) 525-8434

* WAREHOUSES: Bellwood

Los Angeles

Pittsburgh

RBB 00601