

HARMFUL IF EATEN OR CHEWED

Do not apply on toys and other children's articles, furniture, or interior surfaces of any dwelling or facility which may be occupied or used by children. Do not apply on those exterior surfaces of dwelling units, such as window sills, porches, stairs, or railings, to which children may be commonly exposed. Keep away from heat and open flame. Avoid prolonged contact with skin and breathing of vapor or spray mist. Wash thoroughly after handling and before eating or smoking. Do not take internally. Close container after each use.

USE ONLY WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

CONTAINS TOLUOL

Keep away from heat, sparks and open flame. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Do not transfer contents to unlabeled bottles or other containers.

Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN. BA36

AVOLITE PROTECTIVE COATINGS

DIRECTIONS FOR USE

PREPARATION

General: Never paint a damp, dirty or greasy surface. Never paint during cold, frosty weather or when temperature is likely to drop to freezing. Avoid painting when surface is exposed to hot sun.

NEW OR WEATHERED STRUCTURAL STEEL: Remove mill scale by sandblasting or flame cleaning.

New Sheet Steel and Galvanized Metal: Remove grease and oil with Mineral Spirits. Remove rust spots with wire brush or sandpaper.

Old Painted Metal: Remove scale, rust and loose paint with a wire brush or coarse sandpaper. Clean rust spots down to bright metal.

APPLICATION

Stir thoroughly before use and occasionally during use. Apply as supplied by brush or spray. Roller application not recommended. Be sure each coat is dry before applying the next coat.

SPECIFICATIONS

Bare Metal: 1 coat KROMOX METAL PRIMER or a SYNTHEL FAST DRY PRIMER. On Galvanized metal, use AVOLITE GALVANIZED METAL PRIMER.

Old Work: Spot-prime bare spots. Apply 1 or preferably 2 coats of AVolite protective coating of type specified (KROMOX, SYNTHEL, ETC.)

COVERAGE

Up to 800 sq. ft. per U.S. gallon depending on the type and condition of surface.

CLEAN-UP

Use Mineral Spirits to clean brushes and equipment.

AVolitepaints
A Pratt & Lambert Co.
RICHMOND, VIRGINIA 23230

Mfd. in U.S.A.—77



DANGER!
FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED.
VAPOR HARMFUL.
See Other Cautions on Back Panel. PA56

WARNING!
CONTAINS LEAD
DRIED FILM OF THIS PAINT MAY BE
HARMFUL IF EATEN OR CHEWED
See Other Cautions on Back Panel. F73

FAST DRY PRIMER

RED NO. 5182

ONE GALLON