

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

MATERIAL SAFETY DATA SHEET

SECTION I	
MANUFACTURER'S NAME MONSANTO COMPANY	EMERGENCY TELEPHONE NO. (314) 694-1000
ADDRESS (Number, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166	
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS Inerteen 70-30
CHEMICAL FAMILY Chlorinated aromatic	FORMULA Mixture

SECTION II HAZARDOUS INGREDIENTS				
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%
PIGMENTS			BASE METAL	
CATALYST			ALLOYS	
VEHICLE			METALLIC COATINGS	
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX	
ADDITIVES			OTHERS	
OTHERS				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				% (Units)

SECTION III PHYSICAL DATA				
BOILING POINT (°F.)	760 mm	200-400°C	SPECIFIC GRAVITY (H ₂ O=1) (15.5/15.5°C)	1.523
VAPOR PRESSURE (mm Hg.)	Not Avail.		PERCENT VOLATILE BY VOLUME (%)	N.A.
VAPOR DENSITY (AIR=1)	Not Avail.		EVAPORATION RATE (BuAc = 1)	<1
SOLUBILITY IN WATER	20°C negligible	<0.01%		
APPEARANCE AND ODOR	colorless oil aromatic odor			

SECTION IV FIRE AND EXPLOSION HAZARD DATA				
FLASH POINT (Method used)	None	FLAMMABLE LIMITS	Lel	Uel
			N.A.	N.A.
EXTINGUISHING MEDIA				
SPECIAL FIRE FIGHTING PROCEDURES				
Respiratory protection when fighting fires where exposure to vapors or gases is possible.				
UNUSUAL FIRE AND EXPLOSION HAZARDS				
Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.				



00002137

Inerteen 70-30 SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	Not available.
EFFECTS OF OVEREXPOSURE	Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.
EMERGENCY AND FIRST AID PROCEDURES	Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO ₂ , smoke, soot, chlorides and chlorine			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.
WASTE DISPOSAL METHOD	Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Bureau of Mines approved respirator for organic vapors.			
VENTILATION	LOCAL EXHAUST	Yes - for vapors	SPECIAL vapors.
	MECHANICAL (General)		OTHER
PROTECTIVE GLOVES	rubber		EYE PROTECTION chemical goggles
OTHER PROTECTIVE EQUIPMENT			

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Avoid skin and eye contact. Avoid inhalation of vapors.
OTHER PRECAUTIONS	

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH;JTG:WBP

1/25/72