

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



TTY (As Used on Label and List)

SAND

Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Barry & Barry Sand Company, Inc.	Emergency Telephone Number 409-755-1528
Address (Number, Street, City, State, and ZIP Code) P.O. Box 9338	Telephone Number for Information 409 755-1528
Beaumont, Texas 77709	Date Prepared 9/20/89
	Signature of Preparer (optional)

PLAINTIFF'S EXHIBIT

H&G-8

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

Crystalline Silica - The current OSHA PEL for silicates containing
Crystalline Silica is 5mg/m³ for respirable dust and 15mg/m³ for total dust.
(Please see Section VI for applicable health hazard information)

Section III — Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	2.66
Vapor Pressure (mm Hg.)	N/A	Melting Point	3240 FAHR
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	insoluble in water		
Appearance and Odor	white to grayish in color, no odor		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media This material is non-combustible			
Special Fire Fighting Procedures Use extinguishing media appropriate to the surrounding area			
Unusual Fire and Explosion Hazards none known			

produce locally)

OSHA 174, Sept. 1985

NEG 0013692