

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

MATERIAL SAFETY DATA SHEET

81097-259
1-S.D. File
1-R. McCutchan

SECTION I						
MANUFACTURER'S NAME MONSANTO COMPANY			EMERGENCY TELEPHONE NO. (314) 694-1000			
ADDRESS (Number, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166						
CHEMICAL NAME AND SYNONYMS Mixture			TRADE NAME AND SYNONYMS Pyranol A13B3B			
CHEMICAL FAMILY Chlorinated aromatic			FORMULA Mixture			
SECTION II HAZARDOUS INGREDIENTS						
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)	
PIGMENTS			BASE METAL			
CATALYST			ALLOYS			
VEHICLE			METALLIC COATINGS			
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX			
ADDITIVES			OTHERS			
OTHERS						
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)	
SECTION III PHYSICAL DATA						
BOILING POINT (°F.)		760 mm	210-400°C	SPECIFIC GRAVITY (H ₂ O=1) (15.5/15.5°C)		1.567
VAPOR PRESSURE (mm Hg.)		Not Avail		PERCENT VOLATILE BY VOLUME (%)		N.A.
VAPOR DENSITY (AIR=1)		Not Avail		EVAPORATION RATE (BuAc = 1)		<1
SOLUBILITY IN WATER		20°C negligible				
APPEARANCE AND ODOR		colorless oil				aromatic odor
SECTION IV FIRE AND EXPLOSION HAZARD DATA						
FLASH POINT (Method used)		None		FLASH/LELE LIMITS		
				Lel		Uel
				N.A.		N.A.
EXTINGUISHING MEDIA						
SPECIAL FIRE FIGHTING PROCEDURES						
Respiratory protection when fighting fires where exposure to vapors or gases is possible.						
UNUSUAL FIRE AND EXPLOSION HAZARDS						
Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.						

DSW 267548

TOWOLDMON0011791

Pyranol A13B3B SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	Not available.
EFFECTS OF OVEREXPOSURE	Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.
EMERGENCY AND FIRST AID PROCEDURES	Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO2, smoke, soot, chlorides and chlorine			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.
WASTE DISPOSAL METHOD	Burn in approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)		
Bureau of Mines approved respirator for organic vapors.		
VENTILATION	LOCAL EXHAUST	Yes - for vapors.
	MECHANICAL (General)	
	SPECIAL	vapors.
	OTHER	
PROTECTIVE GLOVES	rubber	EYE PROTECTION
		chemical goggles
OTHER PROTECTIVE EQUIPMENT		

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Avoid skin and eye contact, avoid inhalation of vapors.
OTHER PRECAUTIONS	

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

1/26/72

DSW 267549

TOWOLDMON0011792