RENEWAL PARTS — Information Required

Parts CANNOT be sent promptly unless you include the FOLLOWING with your order: PUBLICATION NO. 10517, ITEM NO DESCRIPTION, PART NUMBER and NO. STAMPED ON THE BRAKE NAMEPLATE.

Item No.	Description of Part	4" Brake D-c 88-594-2 For 3 lbs-ft Torque 88-594-3 For 10 lbs-ft Torque 88-594-4 For 15 lbs-ft Torque		4" Brake A-c with Size "C" Solenoid 88-592-3 For 10 lbs-ft Torque 88-592-4 For 15 lbs-ft Torque		4" Brake A-c with Size "H" Solenoid 88-593-5 For 3 lbs-ft Torque	
		No. Req.	Part No.	No. Req.	Part No.	No. Req.	Part No.
1	Plunger	1	*51-110	1	51-97-4	1	51-82
2	Pin for plunger	1	*13-430	1	13-430	1	13-3196
	Washer	...	.....	...	.....	2	916-120
	Spring pin	...	.....	...	.....	2	13-3186
3	Lever	2	24-1389	2	24-1389	2	24-2678
4	Pin	1	13-433	1	13-433	1	13-433
5	Solenoid frame	1	*See Note	1	17-488	1	88-45-5
8	Coil	1	*See Note	1	◐	1	★
9	Base	1	17-474	1	17-474	1	17-2479
10	Spring for coil	...	.....	2	69-276	2	69-253
12	Link	...	.....	...	.....	1	61-837
13	Terminal cover	...	.....	1	47-828	1	47-762
14	Terminal case	...	.....	1	39-507	1	39-460
			69-578 For 3 lbs-ft Torque				
15	Spring Washer	1	69-702 For 10 lbs-ft Torque	1	69-702	1	69-270
			69-702 For 15 lbs-ft. Torque				
16	Adjusting screw nut	1	15-541	1	15-541	1	15-522
17	Spring gland	1	49-1978	1	14-1978	1	49-1874
18	Pivot block	1	17-473-2	1	17-473-2	1	17-473-3
			69-271 For 3 lbs-ft Torque		69-202 For 10 lbs-ft Torque		
19	Spring	1	69-202 For 10 lbs-ft Torque	1		1	69-271
			69-290 For 15 lbs-ft		69-290 For 15 lbs-ft		
20	Adj. screw assembly	1	14-272	1	14-272	1	14-272
21	Brake wheel	Give Cat. "H" No. when stamped on the wheel, or, if this No. does not appear on the wheel, give complete Brake Nameplate data, bore & keyway dimensions.					
22	Brake shoe assembly	2	48-306-3	2	48-306-3	2	48-510-3
23	Brake lining	...	48-80	2	48-80-2	2	48-80-2
24	Rivet for lining	8	813-158	8	813-158	8	813-158
25	Pin for brake shoe	2	13-431	2	13-431	2	13-431
29	Lock nut	1	15-292	1	15-292	1	15-292
30	Plunger guide	...	.....	2	54-300	2	54-273
31	Renewal set of linings (Consists of items 23 and 24)	1	6-166	1	6-166	1	6-166

*On these Brakes, items Nos. 5 and 8 are assembled as one part, and must be ordered as such. Give number stamped on outer shell of Solenoid.

★For Series Brakes supply the following: Plunger 51-347; Pin 13-1177; 2 Snap Rings 29-531.

◐ Give No. stamped on Coil.

CUTLER-HAMMER, Milwaukee, Wis.

Made in U.S.A.

GLEASON-000122