

(File 54251AA)

MATERIAL 54251AA, ARTU AC

COMPOUND, INSULATING, THERMAL AND SOUND DEADENING

CAUTION: THIS IS GROUP 2A FLAMMABLE LIQUID. KEEP SPARKS AND FLAMES AWAY. DO NOT BREATHE VAPOR OR SPRAY MISTS. AVOID PROLONGED OR REPEATED CONTACT WITH THE SKIN. SEE SPDS C-18.

FURNISHED BY -

(A) Jamestown Finishes, Inc, 52 Angove, Jamestown, NY

(B) M B Suydam Div, Pgh Plate Glass Co, Preble Ave, Pittsburgh, Pa

ORDER FROM SUPPLIER AS -

(A) Sound Deadener MS 1-3780 R-2

(B) Insulating Compound 10305-B S-16337 (2.2 gal) (2.60 gal)

CHARACTERISTICS - (54251AA) (Previous 4057-1) Canceled, obsolete.

(54251AB) (Previous 4057-2) Canceled, superseded by 46110B.

(54251AC) (Previous 4057-3) (User:PH) Heavy, brown insulating compound composed of inert fillers, asbestos fibers, and synthetic resin vehicle. Applied by spraying. It is nonflammable and has good heat resistance, sound deadening and insulating characteristics. INSULATION OF TURBINE ENCLOSURE

APPLICATION - Turbine lagging insulation

SPECIFY AS - COMPOUND 54251AA

Issued by Corporate Standards, R&D Center, Pgh 35, Pa  
Printed in U.S.A.

DOCUMENTS PRODUCED  
DALLAS COUNTY CASES



00006861