

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

MATERIAL SAFETY DATA SHEET

SECTION I						
MANUFACTURER'S NAME MONSANTO COMPANY			EMERGENCY TELEPHONE NO. (314) 694-1000			
ADDRESS (Number, Street, City, State, and Zip Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166						
CHEMICAL NAME AND SYNONYMS			TRADE NAME AND SYNONYMS Inertec 54201 cm (Aroclor 1248)			
CHEMICAL FAMILY Chlorinated aromatic			FORMULA Mixture			
SECTION II HAZARDOUS INGREDIENTS						
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)	
PIGMENTS			BASE METAL			
CATALYST			ALLOYS			
VEHICLE			METALLIC COATINGS			
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX			
ADDITIVES			OTHERS			
OTHERS						
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)	
SECTION III PHYSICAL DATA						
BOILING POINT (°F.)		760 mm	325-360°C		SPECIFIC GRAVITY (H ₂ O = 1) (25/25°C)	1.380
VAPOR PRESSURE (mm Hg.) (155-195°)		3 mm		PERCENT VOLATILE BY VOLUME (SI)		N.A.
VAPOR DENSITY (AIR = 1)				EVAPORATION RATE (B.P. vs. F.P.)		<1
SOLUBILITY IN WATER 20°C negligible		<0.02%				
APPEARANCE AND ODOR		colorless oil		AROMATIC OR NOT		
SECTION IV FIRE AND EXPLOSION HAZARD DATA						
FLASH POINT (Pensky-Martens)		C.O.C. 180°C		FLAMMABLE LIMITS		11.4% - 17.4%
EXTINGUISHING MEDIA Water foam, CO₂ or dry chemical						
SPECIAL FIRE FIGHTING PROCEDURES Respiratory protection when fighting fires where exposure to vapors or gases is possible.						
UNUSUAL FIRE AND EXPLOSION HAZARDS Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.						

DSW 267254

STLCOPCB4062667

Inerteen 54201 CM SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

Not available.

EFFECTS OF OVEREXPOSURE

Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain

EMERGENCY AND FIRST AID PROCEDURES

Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

CO, CO₂, smoke, soot, chlorides & chlorine

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Absorb on clay, sawdust or other absorbent material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.

WASTE DISPOSAL METHOD

Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

Bureau of Mines approved respirator for organic

VENTILATION	LOCAL EXHAUST	Yes - for vapors	SPECIAL	vapors.
	MECHANICAL (General)		OTHER	

PROTECTIVE GLOVES	rubber	EYE PROTECTION	chemical goggles
-------------------	--------	----------------	------------------

OTHER PROTECTIVE EQUIPMENT

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid skin and eye contact. Avoid inhalation of vapors

OTHER PRECAUTIONS

DSW 267255

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

1/26/72

STLCOPCB4062668