CG 20 CODE BP-366-D PKG ___ PROCESSES APPROVED BY

OCT 11 1982 K2K19 ( )BP-366-D (L) BBK 11/20/81

(DATE) (LOT NUMBER) (SIGNED) (~~DATE~~) 7 A.M.

TYPED BY: JMH

EST. WT. 2212* LBS.

PREPARATION NOTES: _____

EQUIP MENT		NAME: RAMAPO BLUE BF 2 PAGES	USE LBS	N-CODE	ACCT LBS
SV 1	1	RUN 2-3" (+/-200G) WATER INTO V- 200			
	2	USE STATION # 12, PRESET WATER METER PER CHART FOR WATER ADDITION TO FULL TOTES, USE MODE 3 FOR PUMPING FULL TOTES & MODE 2 FOR STUMPING TOTES. PUMP IN THRU 20 MESH SCREEN		8551-A	1750 ~~1750~~
		GALS OF WATER SEQUENCER STEPS			
		LOT 6 11 16 ÷100% %			
		643A 100 10 50 945 35.2	2682		
		641A 50 10 50 248 30.8	825		
		596 50 10 30 381 28.9	1319		
		647 25 10 50 360 20.0	180		
		627 10 10 50 90 8.34	1016		
		645 10 10 100 59 14.8	398		
		TOTAL 1759 ÷100%			
		AFTER LAST TOTE PUMPED RUN IN 100 GALS WATER & PUMP TO SV TO CLEAN SYSTEM			
313 2	4	RUN 44 ~~[illegible]~~ (660G) WATER INTO V-313 & HEAT TO 80-100 DEG F			
		NOTE : VENT ON SOD.DRESINATE TANK OR VAT USED FOR THIS SOL'N SHOULD BE CHECKED FOR DRAFT PRIOR TO DUMPING THE SOD.DRESINATE			
	5	TURN ON AGITATOR & ADD IN 10-12 MIN	600 ~~600~~	530-A	600 ~~600~~
	6	STIR 5 MIN & RECORD: PH 10.4 (10.0-10.5)			
	7	STIR 15 MIN OR LONGER TO DISSOLVE FOR S12			
		OCT 13 1982			
304 3	8	RUN 17 ~~[illegible]~~ (2076) WATER INTO V-304 & START AGITATOR			
	9	ADD IN 2-4 MIN & STIR TO DISSOLVE FOR S13	204 ~~204~~	20-A	204 ~~204~~
SV 4	10	START AGITATOR, STIR 5 MIN & RECORD: PH 10.0 (8.0-10.0)			
	11	IF NECESSARY ADJ TO PH 8.0-10.0 & RECORD PH_____ ASSUME 50%	_____	7-D	_____
		ASSUME 78%	_____	27-D	_____
	12	RUN IN V-313 THRU 20 MESH SCREEN & STIR 10 MIN.			

EQUIPMENT		PAGE 2 OF 2 CG 20 CODE BP-366-D (L)	USE LBS	N-CODE	ACCT LBS
SV 4 CONT	13	RUN IN V-304 IN 5-10 MIN & STIR 5 MIN	400	65-A	400
	14	ADD IN 8-10 MIN & STIR 15 MIN			
	15	FLOOD TO 72" & DO NOT STOP AGITATOR			

S15	200	202	204	210	213	261
IN	77	88	88	75	53	60
GAL	5205	5210	5174	5212	5252	5220

START	FIN	OPTR
115	330	282