

NEG. NO. AF-13

TRADEMARK FILE INFORMATION

Trademark:	Bercor
Trademark Owner:	G.W. Berkheimer Co., Inc.
Last Assignee:	None
Date of First Use in Commerce:	October, 1967
Registration No.:	1,068,874
Date Trademark Registered:	July 5, 1977
Size of Label in Trademark File:	N/A

Receipt of Pictured Label by Patent Office: N/A

ASPHALT ASBESTOS FIBRE ROOF COATING

A Combination of Pure Asphalt
and Long Fibred Asbestos
that Renews, Preserves and Protects
All Types of Roofing

For long lasting, waterproof, water tight service
on: Composition, Roll Roofing and Shingles. Can
be applied over Tar, Galvalume and Other Metals,
Wood, and Clay. Also in ideal coating for all
types of Rain-Guttering.

SUPERIOR FEATURES

It forms a seamless, asbestos-reinforced asphalt
coating over the roof, provides maximum resistance
to water, weather and corrosion, is acid and alkali
resistant. Expands and contracts with temperature
changes. Its superior coating that leads to rapid
renewal and repair. Solvent and sun-dried
waterproof. Seals roofing with penetrating asphaltic oil
to effectively roofing and protect in the prevents
penetration from roofing or hot weather. Gives an any
surface, finally with a 2-4 inch roofing brush or
roller.

AVOIDS BUYING AN EXPENSIVE NEW ROOF

When the roofing material is damaged beyond repair,
it can be renewed with this BERCOR 2287-A to give
your roof more years of good protection service. Thus
saving the much greater cost of a new roof.

DIRECTIONS

Roof Must Be Clean and Dry
Use a stiff broom to remove all loose debris and dirt.
Then use a hose to wash the roof clean. Do not
use any oil or grease on the roof. Do not use any
oil or grease on the roof. Do not use any oil or grease
on the roof. Do not use any oil or grease on the roof.
Do not use any oil or grease on the roof. Do not use
any oil or grease on the roof. Do not use any oil or
grease on the roof. Do not use any oil or grease on
the roof. Do not use any oil or grease on the roof.

After the roof is clean and dry, apply the BERCOR
2287-A to the roof. Apply the BERCOR 2287-A to the
roof. Apply the BERCOR 2287-A to the roof. Apply the
BERCOR 2287-A to the roof. Apply the BERCOR 2287-A
to the roof. Apply the BERCOR 2287-A to the roof.



Liquid Roof Coating

FIBRED

5 GALLONS (18.927 LITERS)



G. W. BERKHEIMER CO.

GARY, INDIANA 46405
INDIANAPOLIS CHICAGO SO. BEND FT. WAYNE

APPLICATION

Use this material as it comes. Apply with a 2-4 inch
brush, broom, or roller. After the roof is clean and dry,
material can be poured on and spread with a
squeegee.

WEATHER RESISTANT is the ideal time to apply roof
coating. In cold weather, keep this material in a
warm place and allow to get as warm as possible. If it gets
too heavy due to the cold, submerge this container in
hot water. DO NOT HEAT OVER 100° F.

COVERAGE

Composition and metal roofs: 1 to 1 1/2 gallons per 100
square feet. Paper and felt roofs: 1 to 1 1/2 gallons
per 100 square feet. Gravel and asphalt roofs: 1 to 1 1/2
to 4 gallons per 100 square feet, depending on the
roughness of the surface.

**FOR ALL TYPES OF ROOFING:
RENEWS! PRESERVES! PROTECTS!
ALSO IDEAL FOR RAIN GUTTERS!
(EASY TO APPLY!)**

CAUTION!
COMBUSTIBLE
See other cautions
on back panel

CAUTION!

Keep out of the reach of children. Harmful if swallowed.
Do not smoke, drink, or operate machinery while using.
If swallowed, call physician immediately. See physician if product
comes in contact with eyes. Avoid breathing con-
tact with skin, and breathing of vapor or dusts. Wash
face and hands after each use. Use with good
ventilation. Keep away from heat or open
flames. Wash hands thoroughly after handling and
before eating or drinking.