

TIME TESTED

PAINTS • VARNISHES • LACQUERS • ENAMELS

SHEEN SEMI-GLOSS

Recommended for walls, ceilings, furniture and in kitchens, bathrooms, breakfast nook, bedrooms, or any other room in the house where a velvet-like, washable finish is desired. Its ability to withstand repeated washing makes it ideal for hospitals, hotels, offices, schools.

DIRECTIONS

BUY THOROUGHLY WITH A LIFTING MALLOW.
ON PLASTER SURFACES.—Be sure surface is dry and free from dirt, grease and loose particles. All new plaster or cement walls that show indication of alkali or active moisture, or existing walls of composition should be given a wash coat of Zinc Subphosphate (Zinc Oxide and Phosphoric Acid) before painting. (See directions for use of Zinc Subphosphate on page 10.)
OLD PAINTED SURFACES.—WALLS.—If old paint has become brittle or worn with age and repeated washings, apply a coat of Interior Base Coat and then proceed as recommended for New Unpainted Surfaces. If old paint is in good condition, one coat of Sheen Semi-Gloss is often sufficient. If two coats are considered necessary, apply a first coat of Sheen Semi-Gloss mixed with equal parts of Interior Base Coat. Allow a few days for drying, then apply second coat. If color is desired, add color from the can. On woodwork in place of Base Coat use Under-Name! (Znate Undercoat).
NEW UNPAINTED SURFACE.—On unpainted walls make sure that all water resulting from washing has dried out. For first coat apply Interior Base Coat. Allow to dry overnight then apply a mixture of one-half Sheen Semi-Gloss and one-half of Interior Base Coat. After this has dried 24 hours apply a finishing coat of Sheen Semi-Gloss as it comes from the can. On woodwork use Under-Name! (Znate Undercoat) in place of Base Coat.

82

↑
 Pigment: 41.3% - Titanium Calcium 100%

GL031596

"DIXIE MADE FOR DIXIE TRADE"

Climatic

SHEEN

SEMI-GLOSS

4600 WHITE

THE AMERICAN PAINT WORKS

DIVISION

THE GLIDDEN COMPANY

★ NEW ORLEANS, LOUISIANA ★

GLD31597