

*	N510	10.41	386.7	29.26
*	R509	1.28	55.2	4.18
*	E118	0.35	5.2	0.39
	ZF74	34.67	304.4	23.03
H	F5161X	18.68	171.0	12.94
H	S416	10.66	77.1	5.83
H	S572	7.26	56.3	4.26
ADD AT SLOW SPEED-				
H	S572	7.26	56.3	4.26
	E214	0.66	5.2	0.39
*	N545	8.76	204.3	15.46

ALL EQUIPMENT USED MUST BE ABSOLUTELY CLEAN.

ZF74 IS EPI-REZ 202-CELANESE RESINS.

W. TOMC

NOV 3 1972

99.99 1321.7100.00

HOOD/SARRATT

WMT/STB

OK. *12-31-72*
add filling continuation.
check for residue - 12/31/72
pt can can
check for residue - 12/31/72
add filling
5 gal can - 4 gal 70 fl oz
1 gal can - 116 fl oz

Y5256C

REFORMULATION OF Y5256B TO REMOVE LEAD, TO CONFORM TO RULE 66, AND TO CHANGE FROM PEBBLE MILL TO COWLES DISPERSION.

0 112-122 KU 4C1A FLAT

NO SHADING

BAKER

SPRAY 7 MILS 4HRS-HNDL

01 COWLES

13.21 10-1

22F. -.06

NONE STEEL

Y5257A 44.9 46.27 4 HRS. 742.17

68.450 MESH

GLD012458