


- **Catalog number**

Maximum Volts	Horsepower Ratings			Mounting	Catalog Number		Price
	Polyphase		Single Phase		Sump Type	Tank Type	
	110-220 V.	440 V.	115-230 V.				
FLANGE MOUNTED—5 3/4" DIAMETER							
250	1	---	1	Top Side	10045- H20 H22	10045- H21 H23	\$36.50 36.50
PIPE PLUG MOUNTED							
250	1	---	1	Side Side	H11	H12	27.40
600	1	1	1		H13	H14	28.90

● Max. liquid temp. 250°F.—Max. internal tank pres. 50 psi.—Max. liquid level change—43/4".


APPROXIMATE DIMENSIONS AND SHIPPING WEIGHTS



1. Omit Float, deduct.....	\$4.50
2. Omit Rod, deduct.....	.70
3. Rubber Bushing for Conduit Hole (Part No. 29-885), add.....	.30

APPROXIMATE DIMENSIONS AND SHIPPING WEIGHTS

Volts	Horsepower Ratings		Catalog Number	Price
	Single Phase	D-c		
115-230	1/2	1/2	10059-H3 H4	\$3.70
	1/3	1/3		3.10



DISCOUNT SCHEDULE 2 CD

• **Catalog number**

—Kit contains 6 clips plus mounting hardware—For use with Cat. No. 9589, 9658, 9736 & 9739 combination starters.

Starter NEMA Size	Fuse Clip Rating		Fuse Clip Kit	
	Amps.	Volts	Cat. No.	Price
0	30	250	10982- H14 H15	\$1.00
	30	600		1.50
1	30	250	H14	1.00
	60	250	H15	1.50
	30	600	H15	1.50
	30	600	H15	1.50
2	60	250	H16	1.50
	100	250	H18	10.50
	60	600	H17	3.00
	100	600	H18	10.50

DISCOUNT SCHEDULE ICD