

USEPA at any time subsequent to the effective date of this Section, the owner or operator of an emission source located in that county or any county contiguous to that county who would otherwise be subject to the compliance date in subsection (b) shall comply with the requirements of Sections 215.601 through 215.603 within one year from the date of redesignation but in no case later than December 31, 1987.

(Source: Adopted at 7 Ill. Reg. 1244, effective January 21, 1983)

Section 215.605 Compliance Plan

- a) The owner or operator of an emission source subject to Section 215.604(a) shall submit to the Agency a compliance plan, pursuant to 35 Ill. Adm. Code 201, Subpart H, including a project completion schedule where applicable, no later than, for Section 215.601(a) and (b), April 21, 1983.
- b) The owner or operator of an emission source subject to Section 215.604(b) shall submit to the Agency a compliance plan, including a project completion schedule where applicable, no later than December 31, 1986.
- c) The owner or operator of an emission source subject to Section 215.604(c) shall submit a compliance plan, including a project completion schedule within 90 days after the date of redesignation, but in no case later than December 31, 1986.
- d) Unless the submitted compliance plan or schedule is disapproved by the Agency, the owner or operator of a facility or emission source subject to the rules specified in subsection (a), (b) or (c) may operate the emission source according to the plan and schedule as submitted.
- e) The plan and schedule shall meet the requirements of 35 Ill. Adm. Code 201, Subpart H, including specific interim dates as required in 35 Ill. Adm. Code 201.242.

(Source: Adopted at 7 Ill. Reg. 1244, effective January 21, 1983)

Section 215.606 Exception to Compliance Plan

Coin-operated dry cleaning operations and dry cleaning facilities consuming less than 30 gallons per month (360 gallons per year) of perchloroethylene are not required to submit or obtain an Agency approved compliance plan or project completion schedule.

(Source: Adopted at 7 Ill. Reg. 1244, effective January 21, 1983)

Section 215.607 Standards for Petroleum Solvent Dry Cleaners

- a) The owner or operator of a petroleum solvent dry cleaning dryer shall either:

- 1) Limit emissions of volatile organic material to the atmosphere to an average of 3.5 kilograms of volatile organic material per 100 kilograms dry weight of articles dry cleaned, or

- 2) Install and operate a solvent recovery dryer in a manner such that the dryer remains closed and the recovery phase continues until a final solvent flow rate of 50 milliliters per minute is attained.

b) The owner or operator of a petroleum solvent filtration system shall either:

- 1) Reduce the volatile organic material content in all filtration wastes to 1.0 kilogram or less per 100 kilograms dry weight of articles dry cleaned, before disposal, and exposure to the atmosphere, or

- 2) Install and operate a cartridge filtration system, and drain the filter cartridges in their sealed housings for 8 hours or more before their removal.

(Source: Added at 11 Reg. 7296, effective April 3, 1987)

Section 215.608 Operating Practices for Petroleum Solvent Dry Cleaners

In order to minimize fugitive solvent emissions, the owner or operator of a petroleum solvent dry cleaning facility shall employ good housekeeping practices including the following:

a) General Housekeeping Requirements

- 1) Equipment containing solvent (washers, dryers, extractors and filters) shall remain closed at all times except during load transfer and maintenance. lint filter and button trap covers shall remain closed except when solvent-laden material is being removed.

- 2) Cans, buckets, barrels and other containers of solvent or of solvent-laden material shall be covered except when in use.

- 3) Solvent-laden material shall be exposed to the atmosphere only for the minimum time necessary for load transfer.

b) Installation and operation of equipment:

- 1) All cartridge filters shall be enclosed and operated in accordance with the procedures and specifications recommended by the manufacturer for the cartridge filter. After installation, the cartridges shall be inspected, monitored and maintained in accordance with the manufacturer's recommendations; and

- 2) Vents on containers for new solvent and for solvent-containing waste shall be constructed and maintained so as to minimize solvent vapor emissions.