



GENERAL AUTOMATIC PRODUCTS CORP.

2300 Sinclair Lane Baltimore 13, Md.

FLOORLEVEL BASEBOARD HEATING

Manufacturers of a Complete Line of Residential Gas and Oil Heating Equipment and Summer Air Conditioning



RATINGS Reg. U. S. Pat. Off.	WATER		
	Average Water Temperature, F	Btu/hr per Linear Foot	
		500 lb/hr	3000 lb/hr
Floorlevel BR-2 1/2 A 3/4" Copper Tubing	165	430	450
Fins: Rectangular Aluminum 2 1/4" deep	170	470	500
× 2 1/4" high × 0.012, 54 fins per foot	175	500	540
	180	530	570
	185	570	610
	190	600	640
	195	630	690
	200	670	720
	205	700	760
	210	730	800
	215	770	840
	220	800	870

Floorlevel Model BR-2 1/2 A has been tested and approved by the Institute of Boiler and Radiator Manufacturers under the 3d edition of the I-B-R Rating Codes. Approval date June 10, 1958.

CARTON "A" contains: 10 ft of Floorlevel Baseboard complete with heating element and necessary brackets; 2 rubber grommets, 2 splice pieces. (Approximate shipping weight 25 lb.)

CARTON "B" contains: 10 ft of Floorlevel Baseboard complete with heating element and necessary brackets; 10 ft of extra enclosure only with necessary brackets, 4 splice pieces and 2 rubber grommets. (Approximate shipping weight 50 lb.)

CARTON "C" contains: 10 ft of Floorlevel Baseboard complete with heating element and necessary brackets; 3 inside corners, 1 outside corner, 4 right-hand corners, 4 left-hand corners, 1 wood block (used where wood baseboard meets enclosure), 2 rubber grommets, 2 splice pieces. (Approximate shipping weight 33 lb.)

CARTON "D" contains: two 10 ft sections of Floorlevel Baseboard complete with heating element and necessary brackets; 4 rubber grommets, 4 splice pieces. (Approximate shipping weight 55 lb.)

CARTON "E" contains: two 10 ft lengths of front and back panel, 10 brackets, 2 top moulding splice pieces, 2 front panel splice pieces. (Approximate shipping weight 44 lb.)



DUAL DE-AIRATOR TANK

A complete unit with feed and relief valve, for positive elimination of air in hot water heating systems; also acts as an expansion tank. Three sizes—500, 1,000 and 1,500 sq. ft.


SERIES "LG" GAS-FIRED BOILER-BURNER UNIT



Available for natural, manufactured, mixed or L.P. gas. All units only 31 in. high, completely assembled. Controls available to meet all local code requirements.

SPECIFICATIONS:

Model	Btu Input	Btu Output	Sq Ft Output
LG-4	84,000	67,200 to 168,000	448 to 1120
LG-10	210,000		



OIL-FIRED BOILER BURNER UNITS

"LO" is pre-wired and pre-assembled, complete with burner, 3 controls and circulator. Available in 3 sizes:

Model No.	Btu Input	Btu Output	Sq Ft Output
LO-6	140,000	112,000	560
LO-7	182,000	145,600	728

Series "T" Steel water-tube Boiler-Burner unit, constructed to ASME Code. Available in following sizes and ratings:

Model No.	Hot Water Sq Ft	Steam Sq Ft
T-16 to T-40	580 to 4500	230 to 3600

Also manufacturers of a complete line of summer and winter air-conditioning equipment.

KRITZER RADIANT COILS, Inc.


325 NORTH RIVER STREET • BATAVIA, ILLINOIS

"K" LINE Radiant Baseboard for RESIDENTIAL, COMMERCIAL, INDUSTRIAL and INSTITUTIONAL HEATING

Quick and easy to install with many KRITZER features (at no extra cost) such as Coil Support Brackets, Sliding Coil Shoes, and Thermovane Damper. Capacities shown below are representative of the wide selection available with KRITZER Radiant Baseboard.

Capacities per linear foot. Air at 65°F

Element Symbol	Cover Symbol	1 psi STEAM Sq Ft per Lin. Ft.	200°F Water Lin. Ft. (1 gpm)
STB-40A	E-1	3.50	840
STB-40	E-1	4.00	1050
STB-40	E-1	2.50	600
STB-40	E-1	2.50	600




Get BULLETIN 203 for complete information.

STB Radiant Baseboard for SCHOOLS, HOSPITALS, OFFICE BUILDINGS, INSTITUTIONS, and FACTORIES




Sturdy. Lifetime of efficient service. Has such KRITZER features (at no extra cost) as Adjustable Coil Support Brackets, Coil Shoe, and Damper and Control. Capacities shown below are but a few of the wide selection available with KRITZER STB Radiant Baseboard.

Capacities per linear foot. Air at 65°F

Element Symbol	Cover Symbol	1 psi STEAM Sq Ft per Lin. Ft.	200°F Water Lin. Ft. (1 gpm)
STB-40	E-1	5.1	1225
STB-40	E-1	6.7	1610
STB-40	E-1	6.3	1510
STB-40A	E-1	7.9	1895



4 in. minimum height from floor. Write for complete information.



Vertical

Horizontal

Cabinet Unit Heaters

Quiet, economical units used in areas calling for rapid concentration of heat such as meeting halls, churches, and large public recreation rooms.

- Six basic sizes. Standard or high capacity coils—500 to 1200 cfm. Up to 430 EDR.
- Floor, wall, inverted wall, or ceiling mounted.
- Only 32 in. high and 10 in. deep.
- 1050 rpm motors with permanently lubricated bearings.
- Trim strips, 3 or 4 sides, for full or partial recessing.
- 4 speed control available.
- All piping can be kept inside of cabinets.

Send for BULLETIN 1200-T

WE WELCOME YOUR INQUIRIES ON SPECIAL APPLICATIONS




"SPECIAL" Radiant Baseboard for HOMES, APARTMENTS, HOTELS, MOTELS, OFFICES


Low cost baseboard with many KRITZER quality features: Thermovane Damper, snap-in Coil Support Brackets, Sliding Coil Shoes, Built-in Air Diverter, packaged in convenient lengths. Capacities shown below are representative of wide selection available. BULLETIN 560.

Capacities per linear foot. Air at 65°F

Element Symbol	Cover Symbol	1 psi steam Sq ft per lin. ft.	200°F water lin. ft. (1 gpm)
175-50	SP	2.7	450
175-50A	SP	3.4	515
175-50	SPU	3.1	740
175-50A	SPU	3.9	600



Dual-Vectors Fan-coil units for heating and cooling with hot or chilled water. Two models: Free standing (DVF), and Semi-recessed (DV) which fits between standard studs. Optional outside air intake and dual room conditioning accessories. Sizes in 200, 300, 400, and 600 cfm. Write for BULLETIN 1001-T.



Converter-Radiators

Floor, wall hung and recessed models. Famous KRITZER coil construction for steam and hot water. Bronze headers. Heavy, reinforced steel cabinets. Full range of sizes. Chain or knob operated dampers. Cabinets phosphatized. Gray prime baked-on finish. Write for BULLETIN 600 and 601.