


The Waterman-Waterbury Co.

Minneapolis 13, Minnesota

Manufacturers of WATERBURY Coal, Oil and Gas
Fired Furnaces and Air Conditioning Equipment



WATERBURY GAS-TITE FURNACE A 100 Series


The welded steel furnace body keeps dust, smoke and fumes out of the air stream. A large combustion chamber and radiator with long fire travel insure efficiency and economy.

Also furnished in a complete home Air Conditioner.

Gravity Size	BTU/HR	Body Dia.	Body Hgt.	Round Galv. Dia.	Round Galv. Hgt.	Sq. In. Leader Pipe	Size Sq Casing	Size Sq Casing Outlet	Sq Casing Hgt.	Heating Surface Sq Ft	Smoke Pipe Dia.
A120	85,000	20	52	41	65	470	38x38	34x34	52	35.7	8"
A122	94,200	22	52	43	65	524	40x40	36x36	52	39.6	8"
A124	105,100	24	52	45	65	586	42x42	38x38	52	44.3	9"
A127	135,500	27	59	49	72	758	46x46	42x42	59	57.4	9"


Gasit Air Conditioner

Air Conditioner Size	Output BTU/HR	Width Casing	Length Casing	Height Casing	Size Outlet Opening	Size Inlet Opening	No. Filters	Size Each Filter	CFM Range
A120-9	95,400	38"	50"	52"	28x34	16x34	2	16x20	400-800
A120-10	95,400	38	50	52	28x34	16x34	2	16x20	600-1200
A122-9	105,800	40	54	52	28x36	20x36	2	20x25	400-800
A122-10	105,800	40	54	52	28x36	20x36	2	20x25	600-1200
A124-10	118,200	42	60	52	34x38	20x38	2	20x25	600-1200
A124-12	118,200	42	60	52	34x38	20x38	2	20x25	1000-2000
A127-12	153,000	46	62	59	34x42	22x42	2	20x25	1000-2000
A127-15	153,000	46	62	59	34x42	22x42	2	20x25	1800-2600



WATERBURY GAS FIRED AIR CONDITIONER

The latest achievement of Waterbury's engineers, designed specifically for gas. Completely automatic—filtered, humidified forced air—enclosed in a compact, baked enamel casing. Can also be furnished for Propane or Butane.




Size	Input Rating BTU Per Hr.	BTU Output	Blower CFM Range	Width	Length	Height Over-all	Size Outlet Opening	Size Return Inlet Opening	No. of Filters	Size each Filter	Flue Pipe Dia-meter	Size Gas Connection Required
6418A-9B	90,000	72,000	400 to 800	28"	59"	48"	24x23	24x16	2	16x25	5"	3/4"
6413A-9 HBB	90,000	72,000	400 to 800	28"	59"	48"	24x23	22x15	2	16x25	5"	3/4"
6415A-10B	120,000	97,000	600 to 1,200	28"	61"	53"	24x23	24x18	2	16x25	6"	3/4"
6415A-10 HB	120,000	97,000	600 to 1,200	30"	30"	76"	26x26	22x15	2	16x25	6"	3/4"
6418A-12B	150,000	120,000	1,000 to 2,000	34"	71"	53"	30x30	22x30	2	20x25	7"	1"
6418-12HB	150,000	120,000	1,000 to 2,000	34"	71"	53"	30x30	22x20	2	20x25	7"	1"
6426A-15B	180,000	144,000	1,300 to 2,600	50"	60"	50"	24x51	36x23	4	18x20	2-5 to 6	1 1/2"
6430A-18B	240,000	192,000	3,000 to 4,200	55"	60"	58"	24x51	36x28	4	16x20	2-6 to 7	1 1/2"

The Waterman-Waterbury Co.

Minneapolis 13
Minnesota

WATERBURY 6300 Series OIL FIRED AIR CONDITIONER

Completely automatic oil heat with forced, filtered, humidified air, all enclosed in one compact casing finished in baked enamel.



Size	Input Rating Gal. Oil per Hr.	Output Capacity Btu per Hr at Bonnet	Width Casing	Length Casing	Height Overall	Size Outlet Opening	Size Return Inlet	Opening Distance Between Opening	No. of Filters	Size each Filter	Diam. Smoke Pipe
6313A-9B	.75	75,000	28"	59"	48"	24x23	24x16	2 1/2"	2	16x25	6"
6315A-10B	1.00	100,000	28"	61"	53"	24x23	24x18	2 1/2"	2	16x25	7"
6313A-9HBB*	.75	75,000	28"	59"	48"	24x23	22x15	2 1/2"	2	16x25	6"
6315A-10HBB*	1.25	115,000	30"	76"	53"	26x26	22x15	2 1/2"	2	16x25	7"
6318-12B	1.35	135,000	34"	71"	53"	30x30	22x30	2"	2	20x25	7"
6318-12HBB*	1.35	135,000	34"	71"	53"	30x30	22x30	2"	2	20x25	7"

* HB indicates a Hi-boy model


WATERBURY GAS GRAVITY FURNACE

Size Furnace	Input Rating Btu per Hr	Output Rating Sq In. Warm Air Pipe	Width In.	Length In.	Height Overall In.	Size Outlet Opening	Rec. Flue Pipe Diam.	Size Gas Connection Required In.
6413A-G	80,000	60,000	28"	28"	48"	24x24	6"	3/4"
6415A-G	110,000	82,500	30"	30"	53"	26x26	6"	3/4"
6418A-G	130,000	97,500	40"	37"	53"	36x33	7"	3/4"



SEAMLESS OIL FIRED FURNACE BODY

Specially engineered for oil firing only, it may be used as a gravity circulating pipe furnace. It is the heating element of the Waterbury Oil Fired Air Conditioners.




Specifications Waterbury Oil Fired Air Conditioners

Size	Input Rating Gal. Oil per Hr.	BTU Output per Hr.	Width Less Front Hood†	Lgh Over-all	Height Over-all	Size Outlet Opening	Size Return Inlet Opening	No. of Filters	Size each Filter	Diam. Smoke Pipe	CFM Range
1322-12B	1.5	164,177	44"	66"	55"	40x40	18x24	2	16x25	8"	1000-2000
1322-15B	1.5	164,177	44"	80	55	40x40	28x36	4	20x20	8	1800-2600
1324-15B	2.0	218,903	48	80	55	44x44	28x36	4	20x20	8	1800-2600
1324-18B	2.0	218,903	48	80	55	44x44	28x36	4	20x20	8	3000-4200
1327-18B	2.5	273,609	52	84	55	48x48	28x36	4	20x20	9	3000-4200
1327-21	2.5	273,609	52	100	55	48x48	38x44	6	16x25	9	4600-6200
1330-21	3.0	328,354	56	104	62	52x52	38x44	6	16x25	9	4600-6200
1333-21	3.5	383,080	60	108	62	56x56	38x44	6	16x25	9	4600-6200
1336-34	4.0	437,805	66	116	72	62x62	46x48	6	20x25	9	5000-8000

† Burner hood all sizes is 24 in. wide, 10 in. deep.

GAS CONVERSION BURNER

A real gas burner, the same as used in the Gas Air Conditioner.



Number	Maximum Btu Input	Maximum Cubic Feet of Mixed Gas	Maximum Cubic Feet of Manuf'd Gas
G-200	200,000	250	360