






INDEX OF CHEMICAL MATERIALS AVAILABLE FROM NATIONAL LEAD COMPANY AND ITS DIVISIONS AND SUBSIDIARIES

CHEMICAL MATERIAL	DIVISION	PAGE NO.	CHEMICAL MATERIAL	DIVISION	PAGE NO.
ACETATES			CALCIUM ZIRCONATE	TAM	16
DIAMINES	BAROID	9	CALCIUM ZIRCONIUM SILICATE	TAM	16
ZIRCONIUM ACETATE SOLUTION	TAM	14			
ACETONATES			CHROMATES		
ZIRCONIUM ACETYLACETONATE	TAM	14	LEAD SILICO CHROMATE, BASIC	ONCOR	7
AMINES			LEAD SILICO CHROMATE, NORMAL	ONCOR	7
DIFATTY QUATERNARY	BAROID	9			
FATTY PRIMARY	BAROID	9	CLAY MINERALS		
FATTY SECONDARY	BAROID	9	ATTAPULGUS	BAROID	8
MONOFATTY TERTIARY	BAROID	9	BENEFICIATED CLAYS	CHEMICALS/ BAROID	6.8
MONOFATTY QUATERNARY	BAROID	9	BENTONITE	BAROID	8
MONOMETHYL TERTIARY	BAROID	9	HECTORITE	BAROID	8
PRIMARY, ACETATE	BAROID	9	MAGNESIUM SILICATE CLAY	BAROID	8
TRIFATTY TERTIARY	BAROID	9	ORGANOPHILIC CLAYS	CHEMICALS/ BAROID	6.8
QUATERNARY MIXTURES	BAROID	9			
AMINE-PHENOL COMPOUNDS	BAROID	9	CORROSION INHIBITORS	BAROID	8
ANTIMONY COMPOUNDS			DEMULSIFIERS	BAROID	9
ANTIMONY OXIDES	CHEMICALS	6			
REGULAR			DIAMINES		
RED STAR			ACETATE	BAROID	9
WHITE STAR GRADE M			ADIPATE	BAROID	9
GRADE 10			DIADIPATE	BAROID	9
ANTIMONY SILICO OXIDE	ONCOR/ CHEMICALS	6.7	DIOLEATE	BAROID	9
ATTAPULGITE	BAROID	8	MONOLEATE	BAROID	9
BARITE	BAROID	8			
BARIUM COMPOUNDS			DIATOMACEOUS CALCITE	DELORE	10
BARIUM-CADMIUM ORGANICS	CHEMICALS	4	DISPERSANTS	BAROID	8
(VINYL STABILIZERS)			FERROUS SULFATE	TPC	13
BARIUM CARBONATE	BAROID	9			
BARIUM SILICATE COMPLEX	CHEMICALS	4	HECTORITE		
(VINYL STABILIZER)			BENEFICIATED	CHEMICALS/ BAROID	6.8
BARIUM-SODIUM ORGANIC	CHEMICALS	4	MODIFIED	CHEMICALS/ BAROID	6.8
(VINYL STABILIZER)					
BARIUM STANNATE	TAM	16	LEAD COMPOUNDS		
BARIUM SULFATE	BAROID/ DELORE	8.10	LEAD-CALCIUM ORGANIC	CHEMICALS	4
BARIUM TITANATE	TAM	14	(VINYL STABILIZER)		
BARIUM ZIRCONATE	TAM	14	LEAD CHLOROSILICATE COMPLEX	CHEMICALS	4
BARIUM ZIRCONIUM SILICATE	TAM	16	(VINYL STABILIZER)		
BARYTES	DELORE	10	LEAD CHLOROSILICATE-SULFATE	CHEMICALS	4
BENTONITES			COMPLEX (VINYL STABILIZER)	CHEMICALS	4
CANADIAN	BAROID	8	LEAD 2-ETHYLHEXOATE	CHEMICALS	6
MODIFIED ORGANOPHILIC	CHEMICALS/ BAROID	6.8	LEAD FUMARATE, TETRABASIC	CHEMICALS	4
ORGANOPHILIC	CHEMICALS/ BAROID	6.8	LEAD MONOHYDROGEN PHOSPHATE	CHEMICALS	6
SOUTHERN	BAROID	8	LEAD MALEATE, TRIBASIC	CHEMICALS	4
TEXAS	BAROID	8	LEAD ORTHOSILICATE-SILICA GEL	CHEMICALS	4
WESTERN	BAROID	8	COPRECIPITATE (VINYL STABILIZERS)	CHEMICALS	4
CADMIUM COMPOUNDS			LEAD OXIDES		
BARIUM CADMIUM ORGANICS			LITHARGE	CHEMICALS	6
(VINYL STABILIZERS)	CHEMICALS	4	RED LEADS	CHEMICALS	6
CALCIUM COMPOUNDS			LEAD PHOSPHITE, DIBASIC	CHEMICALS/ ONCOR	4.7
CALCIUM CARBONATE	DELORE	10	LEAD PHTHALATE, DIBASIC	CHEMICALS	4
LEAD-CALCIUM ORGANIC	CHEMICALS	4	LEAD SALICYLATE, NORMAL	CHEMICALS	4
(VINYL STABILIZER)			LEAD SILICATE SULFATE, BASIC	CHEMICALS	4
CALCIUM STANNATE	TAM	16	LEAD SILICO CHROMATE, BASIC	ONCOR	7
CALCIUM TITANATE	TAM	16	LEAD SILICO CHROMATE, NORMAL	ONCOR	7

0000-NL-000019636

CHEMICAL MATERIAL	DIVISION	PAGE NO.	CHEMICAL MATERIAL	DIVISION	PAGE NO.
LEAD STEARATE, DIBASIC	CHEMICALS	4	SURFACTANT	BAROID	8
LEAD STEARATE, NORMAL	CHEMICALS	4	TIN COMPOUNDS		
LEAD SULFATE, TRIBASIC	CHEMICALS	4	BARIUM STANNATE	TAM	16
LEAD TITANATE	TAM	16	CALCIUM STANNATE	TAM	16
LEAD, WHITE, BASIC CARBONATE	CHEMICALS	6	CERIUM STANNATE	TAM	16
LEAD, WHITE, BASIC SILICATE	ONCOR	7	DIBUTYL TIN DILAUATE	CHEMICALS	6
LEAD ZIRCONATE	TAM	16	DIBUTYL TIN MALEATES	CHEMICALS	6
LEAD ZIRCONATE TITANATE	TAM	16	MAGNESIUM STANNATE	TAM	16
LITHARGE	CHEMICALS	6	STRONTIUM STANNATE	TAM	16
MAGNESIUM COMPOUNDS			TITANATES		
MAGNESIUM SILICATE CLAY	BAROID	8	BARIUM TITANATE	TAM	14
MAGNESIUM STANNATE	TAM	16	BISMUTH TITANATE	TAM	16
MAGNESIUM TITANATE "C"	TAM	16	CALCIUM TITANATE	TAM	16
MAGNESIUM ZIRCONATE	TAM	16	CERIUM TITANATE	TAM	16
MAGNESIUM ZIRCONIUM SILICATE	TAM	16	LEAD TITANATE	TAM	16
MAGNETITE	TPC	16	MAGNESIUM TITANATE	TAM	16
MALEATES			NICKEL TITANATE	TAM	16
LEAD MALEATE, TRIBASIC	CHEMICALS	4	POTASSIUM TITANATE	TAM	16
ORGANOPHILIC COLLOID	BAROID	8	SODIUM TITANATE	TAM	16
PARAFFIN TREATING COMPOUNDS	BAROID	9	STRONTIUM TITANATE (POWDER)	TAM	16
PHOSPHATES			TITANIUM OXIDE (HEAVY GRADE)	TAM	14
LEAD MONOHYDROGEN PHOSPHATE	CHEMICALS	6	ZINC TITANATE 'B'	TAM	16
PHOSPHITES			TITANIUM PIGMENTS		
LEAD PHOSPHITE, DIBASIC	ONCOR/ CHEMICALS	4,7	TITANIUM DIOXIDES	TPC	12,13
PHTHALATES			TiO ₂ -CaSO ₄ PIGMENTS	TPC	13
LEAD PHTHALATE, DIBASIC	CHEMICALS	4	TiO ₂ -NON-PIGMENTARY	TPC	13
POLYSACCHARIDE	BAROID	8	TITANIUM CHEMICALS (ENELCHEM)		
PRECIOUS METALS			FERROUS SULPHATE	TPC	13
SILVER, GOLD, PLATINUM (BASE CHEMICALS)	GOLDSMITH	11	MAGNETITE	TPC	13
RED LEADS	CHEMICALS	6	TITANIUM TETRACHLORIDE	TPC	13
SALICYLATES			STRONTIUM TITANATE CRYSTAL	TPC	13
LEAD SALICYLATE, NORMAL	CHEMICALS	4	TITANIUM CHEMICALS		
SCALE INHIBITORS & REMOVERS	BAROID	9	TITANIUM CARBIDE	TAM	16
SILICA			WHITE LEADS	CHEMICALS	
DIATOMACEOUS CALCITE	DELORE	10	ZIRCONIUM COMPOUNDS		
SILICATES			AMMONIUM ZIRCONYL CARBONATE	TAM	14
ANTIMONY SILICO OXIDE	ONCOR/ CHEMICALS	4,7	SOLUTION	TAM	14
BARIUM SILICATE COMPLEX (VINYL STABILIZER)	CHEMICALS	4	BARIUM ZIRCONATE	TAM	14
LEAD CHLOROSILICATE COMPLEX (VINYL STABILIZER)	CHEMICALS	4	BISMUTH ZIRCONATE	TAM	16
LEAD CHLOROSILICATE-SULFATE COMPLEX (VINYL STABILIZER)	CHEMICALS	4	CALCIUM ZIRCONATE	TAM	16
LEAD ORTHOSILICATE-SILICA GEL COPRECIPITATE (VINYL STABILIZER)	CHEMICALS	4	CERIUM ZIRCONATE	TAM	16
LEAD SILICATE SULFATE, BASIC	CHEMICALS	4	LEAD ZIRCONATE	TAM	16
LEAD SILICO CHROMATE, BASIC	ONCOR	7	MAGNESIUM ZIRCONATE	TAM	16
LEAD SILICO CHROMATE, NORMAL	ONCOR	7	SODIUM ZIRCONIUM SILICATE	TAM	16
STARCH, PREGELATINIZED	BAROID	8	SODIUM ZIRCONIUM SULFATE (TECHNICAL GRADE)	TAM	14
STEARATES			STRONTIUM ZIRCONATE	TAM	14
LEAD STEARATE, DIBASIC	CHEMICALS	4	ZIRCON G (MILLED OR GRANULAR)	TAM	14
LEAD STEARATE, NORMAL	CHEMICALS	4	ZIRCONIA, COLLOIDAL	TAM	16
SULFATES			ZIRCONIA, CARBONATED HYDROUS	TAM	14
BARIUM SULFATE	BAROID/ DELORE	8,10	ZIRCONIA (HYDROUS)	TAM	14
FERROUS SULFATE	TPC	13	ZIRCONIUM ACETATE SOLUTION	TAM	14
LEAD SILICATE SULFATE, BASIC	CHEMICALS	4	ZIRCONIUM HYDRIDE	TAM	14
LEAD SULFATE, TRIBASIC	CHEMICALS	4	ZIRCONIUM HYDROXYCHLORIDE SOLUTION	TAM	16
			ZIRCONIUM OXIDES	TAM	14
			ZIRCONIUM OXYCHLORIDE (TECHNICAL GRADE)	TAM	14
			ZIRCONIUM SILICATE	TAM	14
			ZIRCONIUM SULFATE (PULP)	TAM	14
			ZIRCONIUM TETRACHLORIDE	TAM	14
			ZIRCONYL NITRATE SOLUTION	TAM	14
			ZIRCONIUM SULPHATE PULP, BASIC	TAM	14

0000-NLI-000019637



Pigments & Chemicals Division

CHEMICALS

Vinyl Stabilizers (Lead)

PRODUCT	PRINCIPAL USE	COMPOSITION	Mol. Wt.	Color & Form	Fineness (Retained on No. 325 Mesh Sieve)	
TRIBASE ^{1,2}	Most basic of the lead sulphates. Used for electrical and other vinyl compounds requiring high heat stability.	Tribasic lead sulfate	991	Fine white powder	0.15% Max.	
TRIBASE-E ^{1,2}	For low volume cost vinyl electrical insulation.	Basic lead silicate sulfate		Fine white powder	0.1% Max.	
TRIBASE AG	High efficiency stabilizer for rigid vinyl compounds. Gives stability in molding and extrusion under extreme shear and high temperature conditions.	Modified tribasic lead sulfate		Off-white flakes		
DYTHAL ^{81,2}	Heat and light stabilizer for general vinyl use. Excellent for high temperature vinyl insulation and opaque film and sheeting.	Dibasic lead phthalate	818	Fluffy white crystalline powder	0.1% Max.	
DYPHOS ^{81,2}	Outstanding anti-oxidant; heat, light and weather stabilizer in opaque stocks including plastisols, organosols, chlorine-containing paints.	Dibasic lead phosphite	743	Fine white acicular crystals	0.3% Max.	
LECTRO "60" ^{81,2}	Economical stabilizer for vinyl electrical insulation and vinyl tapes.	Lead chlorosilicate complex		Fine white powder	0.1% Max.	
LECTRO ⁸ 78	Heat stabilizer for electrical grade plastisols, phonograph records and electrical insulation. Vulcanization agent for chlorosulfonated polyethylene.	Tetrabasic lead fumarate	1250	Fine creamy white powder	0.2% Max.	
LECTRO ⁸ 80	Multi-purpose stabilizer for all common classes of vinyl electrical insulation.	Basic lead chlorosilicate-sulfate complex		Fine white powder	0.1% Max.	
DS-207 ^{9,2}	Stabilizer-lubricant for vinyls. Excellent for vinyl records and as costabilizer in vinyl insulation.	Dibasic lead stearate	1221	Soft white unctuous powder	0.3% Max.	
PLUMB-O-SIL ⁸ B ² and C	For translucent and colored vinyl film, sheeting, and upholstery stocks.	Coprecipitates of lead orthosilicate and silica gel		Soft white powders	0.75% Max.	
NORMASAL ⁸	Stabilizer or costabilizer for flooring and other vinyl compounds requiring good light stability.	Normal lead salicylate	481	Soft, creamy white crystalline powder	0.2% Max.	
TRI-MAL ⁸	Vulcanizing agent for chlorosulfonated polyethylene. Highly basic stabilizer with high heat stability in vinyls.	Tribasic lead maleate	1008	Soft, yellowish white crystalline powder	0.2% Max.	
LEADSTAR ⁸	Lubricant and costabilizer for vinyl plastics.	Normal lead stearate	774	Fine white unctuous powder	See Remarks	
PLASTIFLOW TM LPC	Costabilizer and lubricant for rigid vinyl compounds. Does not retard compound fusion.	Lead-calcium soap of mixed organic acids		Off-white flakes		

1 Special XL Grade also available. Offers substantial improvements in heat stability, electrical properties, physical and mechanical properties, and color.

Vinyl Stabilizers (Non-Lead)

PROVINITE ⁸ A and B	Clear, heat and light stabilizer systems for vinyl film, sheeting, and dispersion resin systems.	Barium-cadmium organic		A Soft white powder	0.5% Max.	
				B Clear straw colored liquid		
CS-137 ⁸	Outstanding stabilizer for transparent organosols and solution coatings. Remarkable light and weathering resistance.	Barium-sodium organic		Creamy white paste		
BAROSIL ⁸	Supplementary stabilizer for barium-cadmium and/or zinc types. Especially useful in film, sheeting, extrusions and dispersion resin systems. Controls plating, hazing, crocking and fogging.	Complex barium silicate		Fine white powder	1.0% Max.	
TEMEX ⁸ 15 and 15-R	Clear heat stabilizers for vinyl phonograph record and other rigid stocks, based on vinyl copolymer resins. Offer excellent dispersion characteristics.	Barium-cadmium organics		Fine white powders	15-1.0% Max. 15-R-1.5% Max.	

0000-NLI-000019638

	Basic Lead Content % Total PbO	% Safely Reactive PbO (Average)	Specific Gravity	Refractive Index	Standard Package (Net. Wt.) Multiwall Paper Bags (except as noted)	REMARKS
	89	67.3	6.4	2.1	50 lbs.	Also supplied as a paste in DNODP plasticizer for ease in dispersion.
	68	50.8	4.9	2.1	50 lbs.	
	78	59	3.6		400 lbs. (fiberboard drum)	Very fine particle size lead stabilizer with special wax coating. Coating melts at 70°C.
	79.8	54.6	4.5	1.99 (av.)	50 lbs.	Also supplied as a paste in DNODP plasticizer for ease in dispersion.
	89	59	6.1	2.25	50 lbs.	Also supplied as a: (A) A paste in DNODP plasticizer for ease in dispersion (B) 50% Dyphos-50% CaCO ₃ as DYPHOS 50A
	47.5	36.1	3.9	2.1	50 lbs.	
	90	72.5	6.5	2.1	50 lbs.	
	55.5	44	3.6	2.1	50 lbs.	Surface treated to reduce dusting.
	55.3	36.5	2.0	1.60	50 lbs.	Non-melting at high temperatures.
	B 51 C 46	25.51 23.46	3.9 3.1	1.58-1.60 1.58	25 lbs. 25 lbs.	PLUMB-O-SIL C is specially treated for easy dispersion.
	46.5		2.3	1.78 (av.)	200 lbs. (fiberboard drum)	
	89	66.5	6.3	2.08	50 lbs.	
	29.5		1.4	1.58-1.60	50 lbs.	Melting point, 100°C-115°C. 1.2% max. retained on No. 100 Sieve.
	22.2		1.3		200 lbs. (fiberboard drum)	Melting point 69°C.

2 Also available in oiled grade — (Contains 5% of a colorless mineral oil)

			1.4	1.56 (Max.)	225 lbs. (fiberboard drum)	
			0.9	1.45	375 lbs. (55-gal. metal drum)	Supplied as a two package system— PROVINITE A and PROVINITE B.
			1.5	1.48	60 lbs. (5 gal. can)	Supplied only as a 70% solids content paste in DOP.
			2.5	1.50	70 lbs. (fiberboard drum)	
			1.3		100 lbs. (fiberboard drum)	

0000-NLI-000019639



Vinyl Stabilizers (Organotin)

PRODUCT AND PRINCIPAL USE	COMPOSITION	Color & Form	Tin Content, % Sn	Specific Gravity	Melting Point, °C.	Standard Package (Net Wt.) Steel Drums	Remarks
CLARITE® NS-1 High tin content heat and light stabilizer for clear vinyl compounds.	Modified dibutyl tin maleate	Light cream powder	32.1	1.5	65	225 lbs.	
CLARITE® NS-2 General purpose heat and light stabilizer for clear vinyl products.	Modified dibutyl tin maleate	Light yellow liquid	22.1	1.3	—	400 lbs.	Refractive index, 1.51
CLARITE® NS-3 Clear heat and light stabilizer for rigid vinyl blow molding applications.	Modified dibutyl tin maleate	Light yellow liquid	19.0	1.3	—	400 lbs.	Refractive index, 1.52
CLARITE® NS-4 Clear costabilizer-lubricant for rigid vinyl products.	Modified dibutyl tin maleate	Cream colored powder	11.9	1.1	50	225 lbs.	
CLARITE® NS-51 Heat and light stabilizer for high clarity flexible vinyl compounds.	Dibutyl tin diacetate	Colorless liquid	18.6	1.0	20	400 lbs.	Refractive index, 1.46

GELLING AND PIGMENT SUSPENDING AGENTS FOR VISCOSITY AND FLOW CONTROL, PIGMENT SUSPENSION

PRODUCT AND PRINCIPAL USE	COMPOSITION	Moisture	Particle Size* Max.	Sp. Gr.	Bulking Value	Standard Package Net Wt.
BENTONE® 38 Will efficiently thicken and gel solvents of both the intermediate and non-polar types as well as mixtures of low polarity organic liquids with ketones, alcohols and low molecular weight esters.	Organic derivatives of hydrous magnesium aluminum silicate minerals. For organic systems.	3.5% max.	less than 1 micron	1.8	15	50 lb. bags
BENTONE® 38 MASTERGEL Predispersed Masterbatch containing 15% BENTONE 38 thickening agent in odorless mineral spirits. Incorporates efficiently with high speed, low shear equipment during any stage of paint manufacturing to impart suspension, thixotropy, and viscosity increases which are stable and unaffected by temperature changes.		2.5% max.		.89	7.4	35 lb. pail
BENTONE® 34 Will thicken and gel straight non-polar solvents such as benzene, toluene, mineral spirits and naphtha as well as liquids of intermediate polarity such as vegetable oils, plasticizers, alkyds and other resins.		3.5% max.		1.8	15	50 lb. bags
BENTONE® 27 Bodies high polarity solvents such as diethylene glycol, ethyl acetate, methyl ethyl ketone and other lacquer solvents. Recommended for epoxy, polyester, lacquer and vinyl systems.		3.5% max.		1.7	14.2	50 lb. bags
BENTONE® 18-C For polar systems. Especially useful where pigment suspension is desired without strong thickening action, as in the case of aerosol paints.		3.5% max.		1.85	15.4	50 lb. bags
BENTONE® 11-N Suspending agent for use in organic systems. Prevents hard settling of pigments without producing a significant increase in viscosity.		7.0% max.	less than 5 microns	2.0	16.7	50 lb. bags
BENTONE® LT A highly efficient gellant for latex paints. Use results in stable, reproducible thixotropic consistencies. Improves "wet-edge" levelling and brushing properties. Acceptable in a wide range of latex paint systems.	Highly beneficiated hydrous magnesium silicates. For Aqueous Systems	6.0% max.	less than 1 micron	1.98	16.5	100 lb. fiber drums
BEN-A-GEL® BEN-A-GEL® EW		6% ± 2%		2.4	20	100 lb. fiber drums
BENAQUA® For thickening or gelling water systems and/or as suspension agents... emulsion stabilizers in oil-in-water emulsions. BEN-A-GEL requires high shear incorporation equipment. BEN-A-GEL EW and BENAQUA gel readily using low shear equipment.		4% ± 2%				
PROPALOID-T® Thickener for latex paints. Provides pigment suspension and good paint handling properties. Easily incorporated with low shear equipment.		4% ± 2%		2.2	18.3	50 lb. bags
MACALOID® Thickening and pigment suspending agent for water systems.		4% ± 2%		2.65	22.1	50 lb. bags

*Ultimate size when properly dispersed.

SPECIAL CHEMICALS

ONCOR® 23A

A pigment of low specific gravity composed of a surface layer of antimony oxide fused to a core of inert silica. It imparts flame resistance to paint and plastic compositions based on halogenated resins. In addition, it has low tinting strength and excellent dispersion characteristics.

L-26

The normal lead salt of 2-ethylhexoic acid. L-26 is a straw-colored viscous liquid characterized by its solubility in many common organic solvents and its stability at comparatively high temperatures. Used as a curing agent for silicone paints and insulating varnishes.

PEARLESCENT PIGMENT

This is lead monohydrogen phosphate, a soft white powder of fine plate-like crystals. Having excellent heat resistance, it imparts pearlescence, economically and directly, to flexible or rigid plastics. Used most effectively in polystyrene and casein.

ALSO AVAILABLE: WHITE LEAD • RED LEAD • LITHARGE • ANTIMONY OXIDES*

*National Lead Company offers four standard grades of Antimony Oxide: REGULAR, RED STAR, WHITE STAR GRADE M, AND GRADE 10. Each is a high quality, pigment grade, pure antimony trioxide.

0000-NL1-000019640



Pigments & Chemicals Division

ONCOR PIGMENTS

CHEMICAL MATERIAL	BRAND NAME	DESCRIPTION & APPLICATION
LEAD SILICO CHROMATE, NORMAL	ONCOR® Y47®	Intended for use in coatings, such as yellow traffic marking paints requiring a bright "alert" yellow color.
LEAD SILICO CHROMATE, BASIC	ONCOR® M50®	Corrosion inhibitive pigment for metal protective coatings, primers and finishes. Ideally suited for electrocoated primers.
LEAD SILICO CHROMATE, BASIC	ONCOR® F31	Similar to M50 but finer particle size. For use in electrocoating and dipping primers.
WHITE LEAD, BASIC SILICATE	ONCOR® 45X®	In multiple pigment exterior house paint coatings, both water and solvent base. Effective in controlling tannin staining of water base coatings.
ANTIMONY SILICO OXIDE	ONCOR® 23A	Flame retardant for halogenated paints and plastics.
DIBASIC LEAD PHOSPHITE	DYPHOS®	A white anticorrosive pigment for wood and metal coatings, both water and solvent base. Also effective for tannin stain control.

STANDARD PACKAGING: Net weight 50 lb. multi-wall paper bags.

Addresses

Pigments &
Chemicals
Division
GENERAL OFFICES
111 Broadway,
New York, N.Y. 10006

ATLANTA, GA. 30309
Box 7008, Station C
WESTWOOD, MASS. 02090
425 University Avenue
CHICAGO, ILL. 60680
P.O. Box 7000A
CINCINNATI, OHIO 45211
3670 Werk Road
CLEVELAND, OHIO 44113
1776 Columbus Road

DALLAS, TEXAS 75222
P.O. Box 5449
DEPEW, N. Y. 14043
3241 Walden Avenue
DETROIT, MICH. 48211
3501 Griffin Street
LOS ANGELES, CAL. 90023
P.O. Box 23396, Lugo Station
PHILADELPHIA, PA. 19125
2607 E. Cumberland Street

PITTSBURGH, PA. 15212
1376 River Avenue
OAKLAND, CALIF. 94601
4701 San Leandro Street
SEATTLE, WASH. 98134
1128 S.W. Spokane St.
ST. LOUIS, MO. 63177
P.O. Box 7109

IN CANADA
ENELCHEM PRODUCTS
Division of Canadian
Titanium Pigments, Ltd.
MONTREAL 110, QUEBEC
2140 Sun-Life Bldg.
TORONTO 1, ONTARIO
Terminal Bldg., Foot of York St.
VANCOUVER 5, B.C.
1575 W. Georgia Street

0000-NLI-000019641

NOTE: The foregoing recommendations, based on our research and that of others, are believed to be accurate. But no guarantee of accuracy is made. The products are sold without warranty, expressed or implied, and upon the condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes. Likewise, statements concerning the possible use of these products are not intended as recommendations to use these products in infringement of any patent.



Baroid Division

BRAND NAME	MATERIALS & APPLICATIONS	STD. PKG.
ALBERTABOND	High-yield Canadian bentonite for use as foundry sand binder, pelleted feed binder.	50 lb bag
AQUAGEL®	High-yield Western bentonite used primarily in well drilling muds.	100 lb bag
ANHYDROX®	Precipitated barium carbonate used to remove calcium sulfate from hard water, and anhydrite and gypsum from drilling muds.	100 lb bag
BARABOND®	Low-yield Southern bentonite for use as non-ferrous foundry sand binder.	50 lb bag
BARAGEL®	Chemically modified organophilic bentonite used as grease gelling agent.	50 lb bag
BARAWATE®	High density barite for making heavy concrete for use in atomic shielding and as pipeline coating.	100 lb bag
BAROCHEM™	Group of compounds for inhibiting corrosion and scale, and eliminating oxygen in cooling and boiler waters.	450-lb, fiber drum, 55-gal drum
BAROCO®	High-yield Southern bentonite used primarily in well drilling muds.	100 lb bag
BAROID®	Pulverized barite used primarily in well drilling mud.	100 lb bag
BARONITE®	Intimate mixture of bentonitic and water-soluble organic materials used as foundry sand binder.	50 lb bag
BD AMINES	A group of primary, secondary and tertiary ammonia derivatives used in corrosion inhibitors, textile finishing, rubber compounding and other uses.	55 gal drum
BD DIAMINES	A group of 1-3 propylene diamines used in petroleum additives, chemical formulations and other uses.	55 gal drum
BD QUATS	Alkyl ammonium chlorides used as corrosion inhibitors, fabric softeners, chemical intermediates, etc.	55 gal drum
BENTONE®	Chemically modified organophilic clay used as grease gelling agent.	25 lb bag
CARBONOX®	Alkaline soluble lignitic dispersant and thinning agent used primarily in well drilling muds.	50 lb bag
CC-16®	Solubilized alkaline lignitic thinner and dispersant used primarily in well drilling muds.	50 lb bag
CERCLAY	Medium yield Texas bentonite for use as non-ferrous foundry sand binder, pelleted feed binder.	50 lb bag
CLEAR	A group of surfactants for removal and prevention of paraffin deposition.	55 gal drum
COAGULOID	High-yield bentonitic clay for use in water clarification.	50 lb bag
COAT	A group of selected polar film-forming amine-salt corrosion inhibitors.	55 gal drum
DEXTRID®	Stabilized, partially dextrinized polysaccharide (toxic) flocculent, used primarily in drilling mud.	50 lb bag
DROP	A group of compounds for breaking water-in-oil emulsions.	55 gal drum
DURATONE®	Oil dispersible organophilic organic colloid for controlling filtration properties in oil drilling fluids.	50 lb bag
E Z MUL	Surfactant, emulsifier for water-in-oil emulsions.	55 gal drum
GELTONE®	Gel-forming organophilic clay that gives viscosity, gel strength and suspension properties to oil muds.	50 lb bag

BAROID DIVISION is one of the world's largest manufacturers and suppliers of natural and synthetic clays, amines, organic colloids, and chemicals made from these materials.

BRAND NAME	MATERIALS & APPLICATIONS	STD. PKG.
GROUND BARITE	Barium sulfate for use in industrial radioactive shielding.	100 lb bag
IMPERMEX®	Pregelatinized starch powder used for filtration control in drilling fluids.	50 lb bag
INVERMUL®	Emulsifier for water-in-oil emulsion drilling fluids.	50 lb bag
MACALOID®	Beneficiated hectorite for suspending, adsorbing, purifying, gelling.	25 lb bag
M H BENTONITE	Hectorite clay used in refractory linings.	50 lb bag
NATIONAL®	High-yield bentonite clay foundry sand binder, pelleted feed binder, pond and ditch sealer.	50 lb bag
NYKON®	Modified organophilic clay gelling agent for compounding non-corrosive greases.	50 lb bag
PETRO BOND®	Waterless foundry sand binder.	50 lb bag
PETROTONE®	Non-gelling organophilic clay that imparts suspension to oil with little effect on viscosity.	50 lb bag
PROPALOID®T	Chemically modified clay used as gelling agent in paint, pharmaceuticals, cosmetics.	25 lb bag
QUIK-GEL®	High-yield bentonite used in water well, mining and seismic drilling fluids.	50 lb bag
SF-100®	Mixed oleophilic oil mud additive used to free stuck drill pipe or for casing packs.	55 gal drum
SKOT FREE®	Selected, highly polar petroleum derivative used to free stuck drill pipe.	55 gal drum
SURFLO	Group of compounds for inhibiting scale deposition, hydration, and as bactericides.	55 gal drum
TANSUL®7	Beneficiated clay used as a precipitating and clarifying agent in brewing, paper manufacturing.	25 lb bag
TRIMULSO®	Non-ionic surfactant and emulsifier used in drilling fluids.	55 gal drum
TRIP-WATE	Coarse ground barite used to weight drilling fluid column temporarily.	100 lb bag
X-COR	Modified oil soluble, film forming corrosion inhibitor, used primarily in drilling fluids.	14 gal drum
ZEOGEL®	Attapulgate clay used as a viscosifier for salt water type mud systems.	100 lb bag

Addresses

Baroid Division

MAIN OFFICE

P.O. Box 1675,
2404 Southwest Freeway,
Houston, Texas 77001

BRANCH OFFICES

PACIFIC COAST AREA
19301 S. Santa Fe Avenue
Compton, California 90224

ROCKY MOUNTAIN AREA
290 Denver Club Building
Denver, Colorado 80202

WEST TEXAS AREA
118 Vaughn Building
Midland, Texas 79701

MID-CONTINENT AREA
412 Philtower Building
Tulsa, Oklahoma 74103

TEXAS GULF COAST AREA
300 Southwest Tower
Houston, Texas 77002

LOUISIANA GULF COAST AREA
1512 Pere Marquette Building
New Orleans, Louisiana 70112

IN CANADA

BAROID OF CANADA, LTD.
600 Humford Bldg.
608 7th St., S.W.
Calgary, Alberta, Canada

0000-NLI-000019643

DeLore Division

EXTENDER PIGMENTS



CHEMICAL MATERIAL	TRADE NAME	DESCRIPTION AND USE
BARIUM SULPHATE (BARYTES)	FOAM A®/BARYTA WHITE	A refined white waterground extender pigment of high specific gravity. Average particle size 6 microns.
BARIUM SULPHATE (BARYTES)	X10R	A microfine grade of white Barytes having excellent dispersing characteristics. Average particle size 3½ microns.
BARIUM SULPHATE (BARYTES)	X5R	A supermicrofine grade of white Barytes showing the ultimate in pigment dispersion. Average particle size 1¼ microns.
BARIUM SULPHATE (BARYTES)	PRIMEX	A waterground microfine grade of natural Barytes used extensively where color is unimportant but speed of dispersion is required. Average particle size 1¼ microns.
DIATOMACEOUS CALCITE	LORITE®	An ideal extender pigment for low sheen interior and exterior paints. Water base and oil base paints formulated with LORITE have excellent film characteristics because of its low binder demand. Acicular diatoms and calcium carbonate combine to promote stain removal, enamel holdout, scrub resistance, color retention and smoothness of film.
CALCIUM CARBONATE	CCO WHITE/VERA BLANC	A waterground amorphous type of calcium carbonate used primarily where high purity and uniformity is required. Used in conjunction with dry ground OOLITIC F and OOLITIC C for putty and caulking compounds.

STANDARD PACKAGING: Net weight 50 lb. multi-wall paper bags.

EXTENDER PIGMENTS FOR: URETHANE FOAMS, MIRROR BACKING FINISHES, VINYL COATINGS, SEALING COMPOUNDS, LET DOWN COLORS, RUBBER COMPOUNDING, PAINTS, BRAKE LINING.

Addresses

De Lore Division

MAIN OFFICE:
Mississippi River and
River Des Peres,
St. Louis, Mo. 63111
Tel. 314-638-0404

SALES REPRESENTATIVES

ATLANTA, GEORGIA
National Lead Company
404-876-7361

BOSTON, MASSACHUSETTS
National Lead Company
617-762-7400

CHICAGO AREA, ILLINOIS
The Cary Company
312-629-6600

CINCINNATI, OHIO
National Lead Company
513-922-4100

CLEVELAND, OHIO
Chem-Materials Co., Inc.
216-961-4400

DALLAS, TEXAS
Thompson-Hayward Chemical Co.
214-638-8034

DALTON, GEORGIA
Latex Filler & Chemical Co., Inc.
404-278-4998

DENVER, COLORADO
Herr-Hartnell Company
303-534-7350

DES MOINES, IOWA
Thompson-Hayward Chemical Co.
515-244-2281

DETROIT, MICHIGAN
Baker & Collinson, Inc.
313-366-2100

HOUSTON, TEXAS
Thompson-Hayward Chemical Co.
713-869-5801

KANSAS CITY, KANSAS
Thompson-Hayward Chemical Co.
913-342-6800

LOS ANGELES, CALIFORNIA
A. J. Lynch & Company
213-583-2271

LOUISVILLE, KENTUCKY
Wm. B. Tabler Company
502-634-0596

MINNEAPOLIS, MINNESOTA
Thompson-Hayward Chemical Co.
612-332-5394

NEW YORK, NEW YORK
Columbian Carbon Company
212-687-2300

PHILADELPHIA, PENNSYLVANIA
Dowdy Brothers
215-642-8663

PITTSBURGH, PENNSYLVANIA
Chem-Materials Co., Inc.
412-781-0523

SAN FRANCISCO AREA, CALIFORNIA
A. J. Lynch & Company
415-632-2520

SEATTLE, WASHINGTON
National Lead Company
206-622-1950

IN CANADA

ENELCHEM PRODUCTS
Division of Canadian
Titanium Pigments, Ltd.

MONTREAL, QUEBEC
514-866-6881

TORONTO, ONTARIO
416-363-2454

VANCOUVER, BRITISH COLUMBIA
604-685-0813

0000-NLI-000019644



Goldsmith Division

PRECIOUS METALS

Headquarters for silver chemicals, platinum group chemicals, gold chemicals and others, plus all precious metals.

Our new, fully equipped, expanded facilities utilize the most modern methods for processing metals, alloys and chemicals. And have enabled us to meet the demand for products providing higher and more predictable performance... of unquestioned quality, purity and uniformity. These not only include precious metals and their derivatives, but also silver brazing products.

Research

Goldsmith is an active participant in National Lead's metallurgical and chemical research and engineering programs.

Recovery

Goldsmith specializes in refining all forms of precious metal scrap. Our modern recovery processes provide total reclamation of all the gold, silver, platinum, etc., from your industrial wastes, solutions and residues. And you are assured of prompt reimbursement, according to the prevailing metal markets.

Silver Chemicals	SILVER NITRATE A high purity silver salt widely used in the manufacture of film, photographic and photocopy papers, mirrors and pharmaceuticals. SILVER ACETATE SILVER BROMATE SILVER BROMIDE SILVER CARBONATE SILVER CHROMATE SILVER CHLORIDE In powder, sheet, strip, blanks or preformed electrodes, this precision-rolled product affords high energy output, compactness and dependable performance in batteries. SILVER NITRITE SILVER OXIDE SILVER SULFATE SILVER SULFIDE SILVER SULFITE
Gold Chemicals	MONO GOLD CYANIDE (88%) POTASSIUM GOLD CYANIDE (41%) POTASSIUM GOLD CYANIDE (67%) POTASSIUM GOLD CYANIDE (68%) SODIUM GOLD CYANIDE (46%) SODIUM GOLD CYANIDE (72%) GOLD CHLORIDE - YELLOW (50%) GOLD CHLORIDE - BROWN (51%)
Platinum Group Chemicals	OSMIC ACID (OSMIUM TETROXIDE) PALLADIUM BLACK PALLADIUM CHLORIDE PLATINUM BLACK PLATINUM CHLORIDE PLATINUM DIOXIDE (ADAMS CATALYST) POTASSIUM PLATINIC CHLORIDE RHODIUM TRICHLORIDE RUTHENIUM TRICHLORIDE IRIDIUM SALTS

0000-NLI-000019645



Titanium Pigment Division

PHYSICAL PROPERTIES (Average Values)

	TITANOX GRADE	PER CENT TiO ₂ (min.)	SP. GRAV.	1 LB. BULKS (U.S. Gal.)	TINTING STRENGTH (Reynolds) (1)	TINTING STRENGTH (Latex) (2)	OIL ABSORPTION (3)	RESISTANCE TO CHALKING	MEETS SPECS. *
RUTILE	RA	97.0	4.20	0.0286	1700		19.5	NONE	B, G
	RA-44	80.0	3.66	0.0328		2150	50.0	MODERATE	
	RA-45	95.0	4.10	0.0293	1875		19.5	MODERATE	C, H
	RA-47	89.0	3.87	0.0310	1775	1875	36.0	MODERATE	C
	RA-48	84.0	3.82	0.0314		2025	45.0	MODERATE	
	RA-50	94.5	4.10	0.0293	1750		24.5	MODERATE	C, H
	RA-51	93.0	4.10	0.0293	1825	1675	26.5	MODERATE	C, H
	CL	94.0	4.10	0.0293	1875		18.5	MODERATE	C, H
	RANC	94.0	4.10	0.0293	1625		23.5	HIGH	D, H
	RANC-1	94.0	4.10	0.0293	1750		21.5	HIGH	D, H
	CL-NC	94.0	4.10	0.0293	1875		18.5	HIGHEST	C, H
	RA-10	98.0	4.20	0.0286	1625		19.0	NONE	B, G
	RA-30	95.0	4.10	0.0293	1875		19.5	MODERATE	C, H
	RA-40	97.0	4.20	0.0286	1900 ⁽⁵⁾		18.0	NONE	B, G
	RA-40-I	96.7	4.20	0.0286	1900 ⁽⁵⁾		16.5	NONE	B, H
	RA-41	97.0	4.20	0.0286	1930 ⁽⁵⁾		16.5	NONE	B, H
	RA-42	92.0	4.10	0.0293	1700		32.5	NONE	C, H
	RA-41-Z	95.1	4.00	0.0302	1880 ⁽⁵⁾		16.5	NONE	B, H
	PL	92.0	4.10	0.0293	1575		26.5	VERY HIGH	H
	CL-PL	91.0	4.10	0.0293	1725		22.5	VERY HIGH	H
	RCHT	29.5	3.25	0.0369	580		22.5	NONE	E, I
	RCHT-X	29.5	3.25	0.0369	590		21.0	NONE	E, I
	C-50	49.0	3.47	0.0345	975		21.0	NONE	I
	RC	29.5	3.25	0.0369	610		21.0	HIGH	E, I
ANATASE	A-MO	98.0	3.90	0.0308	1200		25.0	NONE	A, F
	A-MP	95.0	3.80	0.0316	1275		23.5	NONE	A, F
	A-WD	98.5	3.90	0.0308	1200		LOW WATER ABSORPTION	NONE	A, F
	A-CG	97.0	3.80	0.0316	1275		18.5	NONE	F
	PDA	72.0	2.15	0.0560					
NON- PIGMENTARY	GM	99.5							
	FMA	99.4	4.00	0.0334					
	TGA	99.0	3.90	0.0308	1200		25.0	NONE	NATIONAL FORMULARY

The following chemical products are also available:
 COPPERAS (IRON SULPHATE)
 MAGNETITE (Iron Ore)
 TITANIUM TETRACHLORIDE
 TITANYL SULPHATE CAKE
 TITANIUM HYDRATE PULP
 TITANYL SULFATE SOLUTION
 TITANYL CHLORIDE SOLUTION

COMMERCIAL CRYSTALS DEPT.

STRONTIUM TITANATE BOULE
 for gem, optical and
 scientific applications.
 TITANIA BOULE for various
 scientific applications.
 SPECIAL CRYSTALS can be
 made upon request.

(1) Tinting Strength: Reynolds constant volume method—0.5 grams std. TITANOX-A plus 1.25 gm. ultramarine blue (6 parts barytes, 1 part ultramarine blue) plus 0.515 ml. refined linseed oil has tinting strength 1250.

(2) Numbers are proportional to average brightness of comparable grey latex flats. Higher strength of TITANOX RA-44 is indicative of higher dry hiding at higher pvc levels.

(3) Oil Absorption: Spatula method expressed as lb. oil per 100 lb. pigment — determined in relation to standard sample under controlled conditions.

(4) Gradings are not absolute and should be compared only within one field of application. See product description sheets.

(5) Tinting Strength in Plastics: Plastic Reynolds Tinting Strength (PRTS) is the relative tinting strength of rutile TiO₂ in plastic at 5 PHR, based on T_xRA at 1700 RTS.

* SPECIFICATIONS

- A. Federal TT-P-442b, Type I
- B. Federal TT-P-442b, Type II
- C. Federal TT-P-442b, Type III
- D. Federal TT-P-442b, Type IV
- E. Maritime S2-MA-521b
Military MIL-T-15195a
- F. ASTM D476-68, Type I
- G. ASTM D476-68, Type II
- H. ASTM D476-68, Type III
- I. ASTM D476-68, Extended TiO₂

0000-NLI-000019646

A type to fit the manufacturing process and the properties of virtually any product that needs white pigment.

[illegible]**SALES OFFICES:**

Towson, Maryland 21204
724 York Road
301-828-8155

40 warehouses are strategically located throughout the country.

0000-NLI-000019647



Titanium Alloy Manufacturing Division

CLASSIFICATION AND COMMERCIAL APPLICATIONS	PRODUCT	
ZIRCONIUM CHEMICALS The number and variety of uses for these compounds is developing rapidly in such applications as: • a precipitant for acid and basic dyestuffs in preparing lakes and toners. • an active ingredient in metal soap type water repellents for textiles and leather. • a raw material in preparing zirconium metal, alloys and organic-zirconium complexes. • a catalyst for silicone type water repellent treatments of leather and textiles. • a strong chelating and coordinating reagent in pharmaceutical preparations. • an active ingredient of latex emulsion paints to improve scrub resistance. • improve bond between fillers and plastics. Plus other applications now in the research and testing stages of development.	ZIRCONIUM OXYCHLORIDE—TECHNICAL	
	ZIRCONIUM HYDROXYCHLORIDE SOLUTION	
	ZIRCONIUM TETRACHLORIDE	
	SODIUM ZIRCONIUM SILICATE	
	ZIRCONIUM ACETATE SOLUTION, 22% ZrO ₂	
	AMMONIUM ZIRCONYL CARBONATE SOLUTION	
	HYDROUS ZIRCONIA	
	HYDROUS ZIRCONIA (CARBONATED PHARMACEUTICAL or TECHNICAL GRADE)	
	SODIUM ZIRCONIUM SULFATE (WITH INSOLUBLE SILICA)	
	BASIC ZIRCONIUM SULFATE (CAKE)	
ZIRCONIUM OXIDE AND STABILIZED ZIRCONIUM OXIDE ZrO₂ is commercially important as an opacifier in ceramics where it imparts high opacity and color stability in glazes, enamels and ceramic pigments. In super refractories, it is used as the raw material for crucibles, rods, tubes and shapes... and for application in high temperature furnaces. C.P. Zirconium Oxide is used in the manufacture of Zirconium Metal and as a constituent in high dielectric ceramics. Another Zirconium Oxide finds increasing use in optical glass polishing. Stabilized Zirconia combines a high melting point with excellent thermal shock properties making it an outstanding refractory material for high temperature applications.	*ZIRCONYL NITRATE SOLUTION	
	ZIRCONIUM OXIDES OF VARIOUS PARTICLE SIZE AND PURITY AVAILABLE	
FILLERS FOR RESINS AND RUBBERS TAM produces Zirconium Silicates of various purities for a variety of applications. The use of Zirconium Silicate as a filler for various resins, plastics and synthetic rubbers increases their thermal stability, resistance to solvent and water absorption, and vapor transmission. The use of TAM Barium Titanate and Heavy Grade Titanium Dioxide improves the electrical properties of the various resins and rubbers. Barium Zirconate gives a white, easily colored silicone rubber compound that has good heat stability at temperatures up to 500°F.	EXCELOPAX®	
	SUPERPAX® A—SUPERPAX®	
	ZIRCOPAX® A—ZIRCOPAX®	
	G ZIRCON MILLED	
	G ZIRCON GRANULAR	
	TICON® B BARIUM TITANATE	
	TICON® HG HEAVY GRADE TiO ₂	
	TICON® BZ BARIUM ZIRCONATE	

*Available in developmental quantities.

0000-NLI-000019648

(approximate physical properties)
SOLUBILITY

STANDARD PKGS.

	EMPIRICAL FORMULA	Color	Wgt. Lbs./ Cu. Ft.	Melt Pt.	H ₂ O	Dil. Acids	Alkalis	Hot Conc. H ₂ SO ₄	HF	Paper Bags Lbs.	Drums or Bbls. Lbs.
	ZrOCl ₂ ·4H ₂ O	Light Yellow	44	Decomposes	Sol.	Sol	Ppt.	Sol			250
	ZrOOHCl	Clear			Sol.	Sol	Ppt.	Sol			500
	ZrCl ₄	Light Yellow		Sublimes at 330°C.	Sol. Decomposes	Sol Decomposes	Ppt. Decomposes	Sol Decomposes			250
	Na ₂ ZrSiO ₅	White		Decomposes	Ins.	Sol	Ins.	Sol		70	
	H ₂ ZrO ₂ (C ₂ H ₃ O ₂) ₂	Clear			Sol.	Sol	Ppt.	Decomposes			500
	(NH ₄) ₂ ZrOH· (CO ₃) ₂ ·2H ₂ O	Clear			Sol.	Decomposes	Decomposes	Decomposes			500
	ZrO ₂ ·xH ₂ O	White		Decomposes	Ins.	Sol	Ins.	Sol			250
	2ZrO ₂ ·CO ₂ ·xH ₂ O	White		Decomposes	Ins.	Sol	Ins.	Sol			250
	Na ₂ ZrO(SO ₄) ₂ ·2H ₂ O + SiO ₂	White	77	Decomposes	Pt. Sol.	Pt. Sol.	Decomposes	Pt. Sol.		100	
	5ZrO ₂ ·3SO ₃ ·15½H ₂ O	White		Decomposes	Ins.	Ins.	Decomposes	Sol.			400
	ZrO(NO ₃) ₂	Colorless		Decomposes	Sol.	Sol.	Ppt.	Decomposes			
	ZrO ₂	White to Salmon	72 to 205	4500°F to 4900°F	Ins.	Ins.	Ins.	Sol.	Sol.		
	ZrSiO ₄	White	65-70	Dissociate at approx. 3200°F	Ins.	Ins.	Ins.	Ins.	Sl. Sol.	50	400
	ZrSiO ₄	White	68		Ins.	Ins.	Ins.	Ins.	Sl. Sol.	50	400
	ZrSiO ₄	White	98		Ins.	Ins.	Ins.	Ins.	Sl. Sol.	80	500
	ZrSiO ₄	Gray-White	95		Ins.	Ins.	Ins.	Ins.	Sl. Sol.	100	500
	ZrSiO ₄	Gray-White	184		Ins.	Ins.	Ins.	Ins.	Sl. Sol.	100	500
	BaTiO ₃	Lt. Gray-Buff		3010°F	Ins.	Sl. Sol.	Ins.	Sol.	Sol.	100	100
	TiO ₂	Cream		3250°F	Ins.	Sl. Sol.	Ins.	Sol.	Sol.	100	100
	BaZrO ₃	Lt. Gray-Buff	140	4550°F	Ins.	Sl. Sol.	Ins.	Sl. Sol.	Sol.	100	100

TAM products continued on next page.

0000-NLI-000019649



Titanium Alloy Manufacturing Division

TITANIUM AND ZIRCONIUM PRODUCTS by TAM

Chemical, Ceramic, Electronic and Metallurgical

RUFLEX (Welding)

Ceramic Rutile
Frit Rutile
Potassium Titanate
Sodium Titanate
Treopax®
Alloys Milled

ELECTRONIC TITANATES

Barium Titanate
Bismuth Titanate
Calcium Titanate
Cerium Titanate
Magnesium Titanate
Nickel Titanate
Strontium Titanate
H. G. Titanium Oxide
Lead Titanate
Lead Zirconate Titanate
Zinc Titanate 'B'

ELECTRONIC STANNATES

Barium Stannate
Calcium Stannate
Cerium Stannate
Magnesium Stannate
Strontium Stannate

CERAMIC (Opacifiers)

Superpax®
Superpax®A
Zircopax®
Zircopax®A
Opax®
Excelopax®
Zirconium Silicates
Zirconium Double Silicates

CERAMIC CEMENTS

Zircon Cements
Zirconium Oxide Cements

METALLURGICAL

Zirconium Hydride
Titanium Carbide
Zirconites
Zirconia
Alloys
Fused Salts

ELECTRONIC ZIRCONATES

Barium Zirconate
Bismuth Zirconate
Calcium Zirconate
Cerium Zirconate
Lead Zirconate
Magnesium Zirconate
Strontium Zirconate

TAM SERVICE

In developing commercial application for the elements Titanium and Zirconium, TAM has also developed many benefits for the users of these products. An experienced technical staff and specialized research facilities are equipped to cope with problems peculiar to the variety of industrial applications for TAM products. By means of continuing research, products are being developed or adapted to meet changing demands. Extensive raw material deposits assure a continuous supply.

WHERE TO GET DETAILED DATA

The field engineer servicing your territory will be most willing to supply complete data. However, to obtain an immediate answer whether it concerns products, research developments, prices, engineering assistance or matters of similar nature, please contact our New York City Headquarters at 111 Broadway.

FIELD ENGINEERS

TAM resident development engineers are headquartered near key chemical centers to provide personal assistance when needed.

Addresses

Titanium Alloy
Manufacturing
Division

EXECUTIVE AND SALES OFFICES

Dept. CM, 111 Broadway, New York, N.Y. 10006

GENERAL OFFICES, WORKS AND RESEARCH LABORATORIES

Niagara Falls, N. Y.

Please direct inquiries to our New York City General Sales Office for prompt attention.

CANADIAN REPRESENTATIVES

ENELCHEM PRODUCTS, Division of Canadian Titanium Pigments Ltd.
2140 Sun-Life Bldg., Montreal 110, Que. • Terminal Warehouse, Toronto 1, Ont.
1575 W. Georgia St., Vancouver 5, B. C.