

Each employee has the duty to comply with these Safety & Health Standards , and all rules , regulations, and orders issued pursuant to these standards which are applicable to his own actions and conduct.

Results obtained from tests made by our environmental test center following the standard method prescribed by the Federal Register are:

Dept. 202 - Slitter	0.21, 0.31, 0.36, 0.205, 0.154
Square Shear	0.256, 0.41, 0.05, 0.31
Dept. 212 - Press # 12	0.36, 0.41, 0.41
#2255	0.15
# 10	0.21, 0.36
# 9	0.56, 1.79, 1.39, 0.72
Dept. 227 - Press #149	0.10, 0.26, 0.15
	0.36, 0.21

Although the exposure is well within the existing limits, and those limits effective July 1, 1976, we are taking additional precautions to reduce any possible hazard to our people.

- | | |
|----|--|
| 1. | All clean up of asbestos dust will be performed by <u>vacuum cleaning only</u> . No dry sweeping or blowing of asbestos dust from clothing, machinery will be permitted. |
| 2. | All visible amounts of asbestos dust must be <u>vacuumed</u> from each employees clothing upon completion of day's work. |
| 3. | Asbestos dust shall be vacuumed from equipment at the completion of each run and at completion of shift. |
| 4. | Asbestos waste and scrap shall be collected and placed in disposal containers. |
| 5. | <u>Liner bags shall be sealed and tagged before removal</u> from vacuum cleaner tank. Care must be taken to avoid breaking or tearing bag when removing it from vacuum cleaner tank and placing in gondola <u>CARDBOARD CARTON</u> <u>TO BE CAREFULLY DEPOSITED IN THE</u> <u>SCRAP GONDOLA R.R. CAR.</u> |