

MATERIAL SAFETY DATA SHEET

H+V

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)**SECTION I**

MANUFACTURER'S NAME Hollingsworth & Vose Company		EMERGENCY TELEPHONE NO. 617 668-0295
ADDRESS (Number, Street, City, State, and ZIP Code) 112 Washington St. East Walpole, MA 02032		
CHEMICAL NAME AND SYNONYMS Not applicable		TRADE NAME AND SYNONYMS Asbestopac 932 A.S.# 625
CHEMICAL FAMILY Article	FORMULA Not applicable	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Asbestos	78	2 f/cm ³
Carbon black	3	3.5 mg/M ³ ACCIH

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	1
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	Insignificant
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____=1)	N/A
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Gasketing paper		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	Not applicable	FLAMMABLE LIMITS	Not applicable	Lel	Uel
EXTINGUISHING MEDIA	Water, CO ₂				
SPECIAL FIRE FIGHTING PROCEDURES	Avoid breathing vapors				
UNUSUAL FIRE AND EXPLOSION HAZARDS	Toxic vapors may be released				