


THICK BLOKS and TAPERED BLOKS
Specifications Arranged by Width for Identifications.
Refer to Block Diagrams.



Pattern No.	Drum Diam.	W	X	Y	L	A	B	C	D	E	F	Counter-bore Angle	ABB-FMS Set No.
3-1/2" Width													
6	16 1/2	3 1/2	1 1/2	-	7 1/2	2.007	2.007	2.007	-	-	-	150°	4366AD
6	16 1/2	3 1/2	2 1/4	-	7 1/2	2.149	2.149	2.149	-	-	-	140°	4523D
6	7	3 1/2	1 3/70	-	11 1/4	2.585	4.724	2.585	-	-	-	82°	4214D
4" Width													
6	16	4	2 1/4	-	7 1/2	1 1/2	2 1/2	2	-	-	-	180°	4320AD
6	17 1/2	4	2 1/4	-	8	2.062	2.062	2.062	-	-	-	150°	4197AD
5" Width													
6	15	5	3 1/2	-	7 1/2	1.902	1.902	1.902	-	-	-	150°	4598D
6	16	5	2 1/4	-	7 1/2	1 1/2	2 1/2	2	-	-	-	180°	4321AD
6	16 1/2	5	2 1/4	-	15 1/2	5	3 1/2	5	-	-	-	82°	4232CD
6	16 1/2	5	3 1/2	-	7 1/2	2.007	2.007	2.007	-	-	-	150°	4312AD
6	16 1/2	5	3 1/2	-	8 1/2	2 1/4	2 1/4	2 1/4	-	-	-	140°	4498D
6	20	6	2 1/4	-	9 1/2	2.363	2.363	2.363	-	-	-	82°	4687AD
6	26	6	3 1/2	-	14 1/2	2.138	4.276	4.062	-	-	-	82°	4576D
6	24	5	2 1/4	-	11	2.880	2.880	2.880	-	-	-	180°	4589AD
6" Width													
6	15	6	4 1/2	-	7 1/2	1.802	1.802	1.802	-	-	-	150°	4594D
6	16	6	4 1/2	-	8 1/2	2 1/4	2 1/4	2	-	-	-	140°	4289AD
6	16	6	2 1/4	-	7 1/2	1 1/2	2 1/2	2	-	-	-	82°	4108AD
6	16 1/2	6	3 1/2	-	7 1/2	2.007	2.007	2.007	-	-	-	150°	43178D
6	16 1/2	6	3 1/2	-	8 1/2	2 1/4	2 1/4	2 1/4	-	-	-	140°	4364D
6 (4 pcs.)	16 1/2	6	4 1/2	-	8 1/2	2.094	2.062	1.898	-	-	-	140°	4376D
6 (4 pcs.)	16 1/2	6	4 1/2	-	8 1/2	1.963	2.062	2.193	-	-	-	140°	
6	16 1/2	6	4 1/2	-	8 1/2	1.963	2.094	2.094	-	-	-	180°	4378AD
6	17 1/2	6	2 1/4	-	8 1/2	2 1/2	2	2	-	-	-	180°	4277AD
6	16 1/2	6	3 1/2	-	7 1/2	982	2.029	2.094	-	-	-	120°	4557D
6-1/2" Width													
6	26	6 1/2	3 1/2	-	14 1/2	4.062	4.268	4.062	-	-	-	82°	4367D
7" Width													
6	15	7	4 1/2	-	7 1/2	1.902	1.902	1.902	-	-	-	150°	4595D
6	16 1/2	7	4 1/2	-	8 1/2	2 1/4	2 1/4	2 1/4	-	-	-	140°	4468AD
6	16 1/2	7	4 1/2	-	8 1/2	1.963	2.094	2.094	-	-	-	150°	44688D
6	18	7	3 1/2	-	8 1/2	1.584	3.168	1.584	-	-	-	82°	4527D
6	20	7	4 1/2	-	9 1/2	2.368	2.368	2.368	-	-	-	82°	4603AD
6	20	7	4 1/2	-	9 1/2	2.583	2.583	2.583	-	-	-	150°	4630D
8" Width													
6	19 1/2	8	5 1/2	-	9 1/2	2.230	2.230	2.230	-	-	-	82°	4178D
10" Width													
6	16 1/2	10	6	-	8 1/2	1.963	1.833	1.964	-	-	-	82°	4567AD