

Chicago Metal Hose Corporation

Maywood, Illinois

PLANTS
MAYWOOD and ELGIN, ILLINOIS

Distributors

HOUSTON, TEXAS.....	Peden Iron & Steel, Inc.
LOS ANGELES, CALIFORNIA.....	Los Angeles Rubber & Asbestos Works
NEW ORLEANS, LOUISIANA.....	Standard Supply & Hardware Company
PORTLAND, OREGON.....	Marshall-Wells Company
SAN FRANCISCO, CALIFORNIA.....	C. W. Marwedel
SEATTLE, WASHINGTON.....	Strehlow Supply Company

Rex Vibra-Sorbers Control Vibration and Noise



Rex Vibra-Sorbers are used to control vibration and reduce noise in refrigeration and air conditioning machinery. They are also available with male pipe thread fittings for use in connecting lines of pumps, turbines, and allied equipment.

Rex Vibra-Sorbers are pressure-tested to insure refrigerant-tightness, thus giving greater protection against leakage of valuable refrigerants. They are available in copper bearing alloy for Freon and Menthon, and steel for ammonia. Thus effective corrosion resistance is provided for all types of installations. C.M.H. engineers can help you solve your vibration problems. Write for information.

Specifications and List Prices

COPPER TUBE SIZE				Bursting Pressures Lbs. per Sq. in.	OVERALL LENGTHS		STOCK NUMBERS		UNIT LIST PRICES
Actual O.D.	Nominal I.D.	I.D. Flexible Hose	Length Flexible Hose		Standard Units with Female Sweat Fittings	Standard Units with Male Sweat Fittings	With Female Sweat Couplings	With Male Sweat Couplings	
1/4"	1/4"	1/4"	5 1/2"	3,000+	7"	7 1/2"	F-1	M-2	\$ 2.90
1/4"	1/4"	1/4"	5 1/2"	3,000+	7 1/2"	8 1/4"	F-3	M-4	3.00
1/4"	1/4"	1/4"	5 1/2"	3,000+	8 1/4"	9"	F-5	M-6	3.30
1/4"	1/4"	1/4"	6 1/2"	2,500+	9"	9 1/4"	F-7	M-8	3.60
1/4"	1/4"	1/4"	7"	2,500+	9 1/4"	10 1/4"	F-9	M-10	4.10
1/4"	1/4"	1/4"	7"	2,500+	10"	11"	F-11	M-12	4.10
1/4"	1/4"	1/4"	7 1/2"	2,000+	11 1/4"	12 1/4"	F-13	M-14	5.60
1/4"	1/4"	1/4"	7 1/2"	2,000+	11 1/4"	12 1/4"	F-15	M-16	5.60
1/4"	1/4"	1/4"	8 1/2"	1,500+	13"	14"	F-17	M-18	7.00
1/4"	1/4"	1/4"	9 1/2"	1,500+	14 1/4"	15 1/4"	F-19	M-20	10.00
1/4"	1/4"	1/4"	11"	1,500+	17"	17 1/2"	F-21	M-22	13.00
2 1/4"	2"	2"	13"	1,000+	20"	20 1/2"	F-23	M-24	18.00
2 1/4"	2 1/4"	2 1/4"	15 1/2"	1,000+	24"	24"	F-25	M-26	36.00
3 1/4"	3"	3"	17 1/2"	1,000+	27"	27"	F-27	M-28	46.00
3 1/4"	3 1/4"	3 1/4"	21 1/2"	1,000+	31 1/2"	31 1/2"	F-29	M-30	90.00
4 1/4"	4"	4"	21 1/2"	1,000+	32"	32"	F-31	M-32	120.00

* For convenience you need specify these numbers only when ordering.

NOTE: Flexible hose lengths listed above are for straight line installations only. Information on lengths for angle installations requiring bends and special units with elbows or threaded fittings is available on request.

All information on Rex Vibra-Sorbers is based on actual measurements and tests. However, due to manufacturing limitations and structural changes, this data must be regarded only as a general guide.

Seamlex Company, Inc.

Main Office and Factory

27-31 Jackson Ave., Long Island City 1, N. Y.

Since 1928—Specialists in the Manufacture of Flexible SEAMLESS All-Metal Hose

You are invited to submit your flexible tube problems to our engineers—without obligation on your part.

You May Obtain Catalog No. 45 Free of Charge

VIBRATION ELIMINATOR



Fig. 700
Seamlex with Sweat Fitting

FOR DOMESTIC OIL BURNERS



Fig. 82
Seamlex with Type "M" Fitting

FOR INDUSTRIAL OIL BURNERS



Fig. 87
Seamlex with Type "SBP" Fitting

FOR UNIVERSAL APPLICATIONS



Fig. 60
Seamlex with "DT" Fitting

FOR DIESEL EXHAUST from 2" I.D. to 24" I.D.




Fig. 90
Seamlex Welded Steel Hose

SEAMLEX

Bronze—Single Braided

STANDARD SIZES

I.D.	O.D.	Minimum Bending Radii for Flexing	Bursting Pressures Lbs./Sq. In.
1/4"	1/4"	4"	10,000
1/4"	1/4"	5"	7,500
1/4"	1/4"	6"	5,000
1/4"	1/4"	6"	4,000
1/4"	1/4"	6"	3,500
1/4"	1/4"	7"	3,000
1/2"	1/2"	8"	2,500
3/4"	3/4"	9"	2,000
1"	1 1/4"	10"	1,750
1 1/4"	2 1/4"	11"	1,500
1 1/2"	2 3/4"	12"	1,250
2"	3 1/4"	13"	1,000
2 1/2"	3 3/4"	18"	800
3"	4 1/4"	18"	675
3 1/2"	4 3/4"	22"	600
4"	5 1/4"	24"	500
4 1/2"	6"	26"	480
5"	6 1/4"	28"	440
6"	8"	30"	400

SEAMLEX Products Are Quality Products