


YOUNG Radiator Co.

Dept. 544, Racine, Wis.



Sales & Engineering Representatives in all Principal Cities
Heating, Cooling, Air Conditioning Products for Home and Industry, Heat Transfer Products for Automotive, Agricultural, Industrial, Gas and Diesel Engine Applications

CONVECTORS & UNIT HEATERS



Convectors are available from stock in six standard cabinet styles; also Institutional and bathroom models; for steam or hot water systems.



"Vertiflow" Unit Heaters are built in seven models; capacities from 52,600 to 552,000 Btu per hr; adjustable louvers, nozzles, diffusers, Anemostats.




Type "SH" Unit Heaters are built in 14 models; capacities from 19,000 to 325,000 Btu per hr; for steam and hot water systems.

Cabinet Type Unit Heaters are available in number of arrangements, wall hung, horizontally suspended, etc.; from 26,200 to 115,000 Btu per hr.



Type "BH" Blower Unit Heaters for floor, wall or ceiling mounting, designed to heat extra large industrial buildings, garages, etc.



Gas-Fired Unit Heaters are available in eight sizes ranging in capacities from 50,000 to 230,000 Btu/hr input. Have welded corrosion-resistant aluminized steel combustion chamber and heat exchanger; other important design features.



AIR CONDITIONING UNITS

Young "YAC" Air Conditioning Units provide year around service for cooling, heating, filtering, circulating, humidifying and dehumidifying in any combination. Units are available in eight sizes; capacities from 400 to 15,748 cfm; vertical (right) or horizontal types; for air conditioning stores, hotels, theaters, etc., and specialized industrial applications. Heating coils are furnished for either steam or hot water; cooling coils for water or direct expansion operation.

HEATING & COOLING COILS

Young manufactures a complete line of heating and cooling coils for central heating or cooling systems, etc.

Type "W" Water Coils—Serpentine tube construction with casing; for either cold water cooling or hot water heating systems.

Type "K" Water Coils—Cleanable tube type; used in either cold water cooling or hot water heating systems.

Type "S" Standard Heating Coils—Complete with casing; also available in





Type "HD" for heavy duty applications.

Type "SD" Steam Distributing Tube Heating Coils—Complete with casing; for heating, ventilating, and air conditioning systems.

Type "E" Evaporator Coils—For direct expansion cooling systems using Freon or Methyl Chloride.

Special Purpose Coils—Unencased and built in many sizes for use in factory-built air conditioning, heating, drying and special processing units.



ELECTROMODE CORPORATION


45 Crouch St.

Rochester 3, N.Y.

FOR HOME •


ELECTROMODE
All Electric HEATERS

INDUSTRY • FARM




BILT-IN-WALL Heaters for Homes and Offices

Using Electromode's Down-Flo principle, these heaters fan-circulate warm air at floor level for greater comfort and improved heating efficiency. Quick and easy to install. No duct work required. Famous cast-aluminum heating element eliminates all danger of fire, shock or burn. Capacities from 1500 to 4000 watts—with manual, wall thermostat or built-in thermostat control. All have thermal safety switches. Silver gray enamel finish.



BILT-IN-WALL BATHROOM Heater

Designed to build into the wall, this 110 volt, 1320 watt heater is designed for small rooms such as baths, bedrooms, kitchens, etc. Employs the famous cast-aluminum heating element that is completely safe. Available with or without built-in thermostat. Thermal cut-off prevents overheating. Two-way switch permits use of fan without heat. Available in white baked-on enamel or chrome.




UNIT HEATERS for Auxiliary Warmth

These fan-circulating units are used as auxiliaries to a main heating system or, where electric rates permit, as main heating sources. Require no plumbing or duct work—only circuit wiring. Employ the completely safe cast-aluminum heating element that has no exposed hot or glowing wires, gives high thermal conductivity and resists corrosion. Safety switch prevents overheating. Thermostat control available on all models.

Suspension Type (left) for wall or ceiling mounting in factories, stores, offices. 10,000 to 45,000 watts.

Combination Portable and Suspension Type plugs in where needed or mount permanently. 1500 to 7500 watts. Automatic thermostat control available on 1500 to 5000 watt models.



Explosion-Proof Heaters (left) for areas charged with inflammable vapors. Convection type. Entire electrical input provides useful heat. Three models range from 2000 to 6000 watts. Listed by Underwriters' Laboratories for Class 1-Group D Hazardous Industries.

Engineering help is at your disposal. For more information, see your supplier or write Dept. HVG-14, Electromode Corporation.

Electromodes are approved by Underwriters' Laboratories and are fully guaranteed.