# No. 82 T

EFFECTIVE SEPTEMBER 29, 1954
SUBJECT TO CHANGE WITHOUT NOTICE

*Suggested*

# RETAIL

## *PRICE LIST*

## Glidden Paints
## SPRED PRODUCTS

QUALITY PRODUCTS

THE GLIDDEN COMPANY, NATIONAL HEADQUARTERS, CLEVELAND 2, OHIO

GLD026241

# INDEX


| Product | Page |
|---|---|
| **A** | |
| Acrylic Sign Finishes | 24 |
| Ad-El-Ite Paint and Varnish Remover | 3 |
| Alkali-Resisting Primer No. 6419 | 3 |
| Alkyd Enamels | 3 |
| Aluminum Asphalt Roof Paint | 3 |
| Aluminum, Metallite | 17 |
| Spray Enamel, Japolac | 12 |
| Asbestos Shingle Paint | 3 |
| Asphalt Roof Coatings | 3 |
| **B** | |
| Bar Top Varnish, Glid-Tone Gloss | 10 |
| Barn Paint, Endurance | 5 |
| Basecoats: | |
| Endurance | 6 |
| Gliddencoat | 8 |
| Ripolin Undercoat | 20 |
| Speed-Wall, Interior | 21 |
| SPEED Primer-Sealer | 14 |
| Surface Bond | 15 |
| Basement Paints: | |
| Pli-Namel | 19 |
| Florenamel | 8 |
| SPEED Satin | 14 |
| SPEED Glide-On | 15 |
| Black Asphaltum | 3 |
| Blackboard Finishes, Vismetic Green | 23 |
| Bleach, Glid-Tone Wood Bleach | 10 |
| Blending Colors — Dromotone | 14 |
| Colors-in-Oil | 4 |
| Blending Liquid, Endurance Shingle and Shake Stain | 7 |
| Boat Varnish, Glid-Tone Spar Varnish | 10 |
| Brick Paint, SPEED Glide-On | 15 |
| Brilliant Colors | 26 |
| Brush Restorer, Glid-Strip | 9 |
| Brushes | 4 |
| Brushing Lacquer, Glid-Tone Crystalacq | 9 |
| Bulletin Colors | 25 |
| **C** | |
| Canvas Preservative, Nova-Sot | 18 |
| Caulking Compound | 4 |
| Calsyn | 24 |
| Cement and Stucco Paint: | |
| SPEED Glide-On | 15 |
| Cleaner, Glid-N Liquid | 9 |
| Colors-in-Oil | 4 |
| Concrete Paint: | |
| Pli-Namel | 19 |
| SPEED Glide-On | 15 |
| Crack and Crevice Filler, SPEED Patch | 16 |
| Surface Bond | 15 |
| Creosote Paint, Stock Farm White | 22 |
| Crystalacq, Glid-Tone | 9 |
| **D** | |
| Day-Lite Dado Enamel | 24 |
| Day-Lite White Fume-Resistant | 24 |
| Deck Paint, Florenamel | 8 |
| Deep Colors — SPEED Satin | 14 |
| Detergents, Glid-N Liquid Cleaner | 9 |
| Dromotone Tinting Colors | 14 |
| Drier, Japan | 12 |
| Driwel Clear, Silicone | 5 |
| Duo-Tex | 24 |
| **E** | |
| Enamel: | |
| Florenamel | 8 |
| Japolac | 11 |
| Japolac Spray | 12 |
| Pli-Namel | 19 |
| Ripolin | 20 |
| SPEED Lustre | 15 |
| Truck, Tractor & Machinery | 22 |
| Enamel Undercoater: | |
| Gliddencoat | 8 |
| Ripolin Undercoat | 20 |
| Endurance: | |
| Barn Paint | 5 |
| Basecoat | 6 |
| House Paint | 6 |
| Imperial | 6 |
| Mildew & Fume Resistant | 6 |
| Pastel Colors | 6 |
| Shingle & Shake Stain | 7 |
| Trim & Shutter Colors | 7 |
| Euston White Lead | 7 |
| Everon House Paint | 7 |
| Exterior Basecoat | 6 |
| E-Z-C Enamels | 24 |
| **F** | |
| Farm Building Paints: | |
| Endurance Paints | 5-7 |
| Maintenance Finishes | 24 |
| Metallite | 17 |
| SPEED Products | 14-16 |
| Stock Farm White | 22 |
| Fence Paints: | |
| Metallite | 17 |
| Nev-A-Rust | 18 |
| Stock Farm White | 22 |
| Filler, Glid-Tone | 11 |
| Florenamel | 8 |
| Floor Finishes: | |
| Florenamel | 8 |
| Glid-Tone Gloss Varnish | 10 |
| Penetrex | 19 |
| Pli-Namel | 19 |
| Floor Wax — Glid-N | 9 |
| Floor Enamel: Japolac | 11 |
| **G** | |
| Gliddex Paste Wax | 8 |
| Gliddencoat | 8 |
| Gliddenspar | 8 |
| Glid-N Floor Wax (Liquid) | 9 |
| Glid-N Liquid Cleaner (Detergent) | 9 |
| Glid Satin (Non-Flammable) | 9 |
| Glid-Tite Galvanized Iron Primer | 9 |
| Glid-Tone Gloss Varnish | 10 |
| Glid-Tone Products | 9-11 |
| Glid-Tone Satin-Sheen Varnish | 10 |
| Glid-Tone Spar Varnish | 10 |
| Glid-Tone Stains | 18 |
| Glid-Tone Wood Bleach | 10 |
| Glid-Tone Wood Filler | 11 |
| Glide-On, SPEED | 15 |
| Gloss Finishes: | |
| Florenamel | 8 |
| Japolac | 11 |
| Ripolin | 20 |
| Speed-Wall | 21 |
| Gold, Spray — Japolac | 12 |
| Granulate | 14 |
| Graphic Arts Finishes | 25-26 |
| Gymnasium Floor Finish | 24 |
| **H** | |
| Heat Resisting Aluminum | 17 |
| Heavy Duty Floor Finish | 24 |
| High Gloss Screen Process Colors | 25 |
| House Paint: | |
| Endurance | 6-7 |
| Everon | 7 |
| SPEED Glide-On | 15 |
| **I** | |
| Imperial House Paint | 6 |
| Interior Aluminum, Metallite | 17 |
| Interior Varnishes | 10, 20 |
| Iron Primer, Glid-Tite | 9 |
| **J** | |
| Japolac Enamel | 11 |
| Japolac Screen and Iron Enamel | 11 |
| Japolac Spray Enamel | 12 |
| Japolac Varnish Stain | 12 |
| Japan Drier | 12 |
| **L** | |
| Lacquer, Glid-Tone Crystalacq | 9 |
| Latex Paints | 14-16 |
| Linoleum Coating, Crystalacq | 9 |
| Linseed Oil | 12 |
| Liquid Cleaner Glid-N | 9 |
| Liquid Red Lead | 12 |
| Liquid Wax, Glid-N | 9 |
| **M** | |
| Machinery Enamels: | |
| Maintenance Finishes | 24 |
| Japolac | 11 |
| Truck, Tractor and Machinery | 22 |
| Masonry Finishes: | |
| Driwel | 5 |
| SPEED Glide-On | 15 |
| Mastic White Finish | 24 |
| Masticrete | 17 |
| Masticrete Primer | 17 |
| Metal Primers: | |
| Glid-Tite | 9 |
| Red Lead | 12 |
| Metal Protective Paints: | |
| Glid-Tite | 9 |
| Metallite | 17 |
| Nev-A-Rust | 18 |
| Red Lead | 12 |
| Metallite, Interior-Exterior | 17 |
| Mildew-Resisting Paints: | |
| Endurance | 6 |
| SPEED Glide-On | 15 |
| **N** | |
| Nova-Sot | 18 |
| Nev-A-Rust | 18 |
| **O** | |
| Oil Colors: | |
| Colors-in-Oil | 4 |
| One-Coat House Paint, Endurance Imperial | 6 |
| **P** | |
| Paint and Varnish Remover | 3, 9 |
| Paste Wood Filler, Glid-Tone | 11 |
| Pastel House Paint Colors | 6 |
| Patching Plaster, SPEED Patch | 16 |
| Penetrex | 19 |
| Plastic Roof Cement | 19 |
| Pli-Namel | 19 |
| Porch and Deck Enamel, Florenamel | 8 |
| Pastel Bulletin Colors | 25 |
| Primers and Sealers: | |
| Alkali-Resisting 6419 | 3 |
| Endurance Basecoat | 6 |
| Gliddencoat | 8 |
| Interior Basecoat | 21 |
| Ripolin Undercoat | 20 |
| SPEED Primer Sealer | 14 |
| Surface Bond | 15 |
| Professional Painter Finishes | 24 |
| Putty | 19 |
| **R** | |
| Red Lead | 12 |
| Redwood Finish | 19 |
| Ripolin Enamel | 20 |
| Ripolin Undercoat | 20 |
| Rockspar Varnish | 20 |
| Rosaprit | 24 |
| Roof Painter | |
| Aluminum Asphalt | 3 |
| Asphalt | 3 |
| Metallite | 17 |
| Nev-A-Rust | 18 |
| SPEED Glide-On | 15 |
| Rust Inhibiting Oil | 24 |
| **S** | |
| Semi-Gloss | 24 |
| Screen Enamel, Japolac | 11 |
| Semi-Gloss Enamels: | |
| Ripolin | 20 |
| Speed-Wall | 21 |
| SPEED Lustre | 15 |
| Shake Stain, Endurance | 7 |
| Shellac | 20 |
| Shingle Stain, Endurance | 7 |
| Sign Background Enamels | 25 |
| Sign Finishes | 25-26 |
| Silk Screen Process Inks | 25-26 |
| Smoke Stack Black | 24 |
| Spackling Compound, SPEED Patch | 16 |
| Spar Varnish, Gliddenspar | 8 |
| Glid-Tone Spar | 10 |
| Speed-Wall Alkyd Flat | 21 |
| Speed-Wall Alkyd Interior Basecoat | 21 |
| Speed-Wall Alkyd Semi-Gloss Enamel | 21 |
| Speed-Wall Gloss White Enamel | 21 |
| Spray-Day-Lite and Related Products | 24 |
| Spray Enamel, Japolac | 12 |
| SPEED Products | 14-16 |
| SPEED Flat | 16 |
| SPEED Glide-On | 15 |
| SPEED Granulate | 14 |
| SPEED Lustre | 15 |
| SPEED Patch | 16 |
| SPEED Primer-Sealer | 14 |
| SPEED Satin | 14 |
| SPEED Stipple Texture | 16 |
| SPEED Surfacene | 15 |
| SPEED Texture | 16 |
| Stains: | |
| Glid-Tone, Wood | 10 |
| Endurance, Shingle and Shake | 7 |
| Standard Screen Process Inks | 26 |
| Stipple Texture, SPEED | 15 |
| Stock Farm White Paint | 22 |
| Stove and Iron Enamel, Japolac | 11 |
| Suston Wiping Stain | 24 |
| Surface Bond | 15 |
| Surface Conditioner, SPEED Surfacene | 16 |
| Swimming Pool Finishes | 24 |
| **T** | |
| Table Top Varnish, Glid-Tone Gloss | 10 |
| Texture Paint, SPEED | 16 |
| Tile Roof Paint, SPEED Glide-On | 15 |
| Tinners' Paint | 22 |
| Tinting Colors | 4, 14 |
| Tinton-O-Zinc | 24 |
| Trim and Shutter Colors, Endurance | 7 |
| Truck, Tractor & Machinery Enamel | 22 |
| Tube Colors | 4, 14 |
| Turpentine | 22 |
| **U** | |
| Undercoaters: | |
| Endurance Exterior Basecoat | 6 |
| Gliddencoat | 8 |
| Ripolin Undercoat | 20 |
| Speed-Wall Interior Basecoat | 21 |
| SPEED Primer-Sealer | 14 |
| Surface Bond | 15 |
| **V** | |
| Vapor Barrier, SPEED Primer-Sealer | 14 |
| Varnishes: | |
| Glid-Tone Gloss | 10 |
| Glid-Tone Satin Sheen | 10 |
| Glid-Tone Spar | 10 |
| Japolac Clear Spray Finish | 12 |
| Rockspar | 20 |
| Varnish Remover | 3, 9 |
| Vinyl-Latex, SPEED Glide-On | 15 |
| Vismetic Green Chalkboard Coating | 23 |
| **W** | |
| Water Tank Finishes | 24 |
| Wax: | |
| Gliddex Paste Wax | 8 |
| Glid-N Floor Wax | 9 |
| White Lead | 23 |
| Wood Bleach | 10 |
| Wood Filler | 11 |
| Wood Finishes | 9-11, 19 |
| Wood Preservative, Nova-Sot | 18 |
| Wood Stain | 18 |
| **Z** | |
| Zinc Dust Paint | 24 |


GLD026242

Glidden QUALITY PRODUCTS

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| ***AD-EL-ITE PAINT AND VARNISH REMOVER**<br>A top-quality remover. Contains no alkalies, acids, oils or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked japan<br>APPLICATION—Brush | 3.36 | 1.29 | .85 | .65 |
| ***ALKALI-RESISTING PRIMER No. 6419**<br>An easy to apply masonry primer-sealer for interior newly plastered or damp walls, and exterior masonry, brick, stucco and concrete blocks, which are to be painted with synthetic rubber-base or oil base paints. Penetrates deeply into the pores and adheres firmly to the surface, to create perfect bond for finish coat. Resists moisture and alkali. Seals in active lime. Prevents fresh plaster from burning through and discoloring the finish coat<br>APPLICATION—Brush, Spray THINNER—Turpentine<br>DRYING TIME—16 hours Covers 350-400 Sq. Ft. per gal.<br>*(Also See SPRED Primer-Sealer Alkali-Resisting Primer)* | 7.96 | 2.45 | — | — |
| **ALKYD ENAMELS**<br>See: Speed-Wall Alkyd Flat and Semi-Gloss and Gloss White; Japalac; Florenamel; Nev-A-Rust; Ripolin; Speed-Wall Interior Basecoat; Spred Lustre | | | | |
| ***ALUMINUM ASPHALT ROOF PAINT**<br>Recommended for tar paper, composition and asphalt roofs. Will rejuvenate weathered roofs and insulate with a silvery sheet of aluminum, in one coat. Made with selected asphalts, finest grade aluminum flakes and solvents<br>APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turp.<br>DRYING TIME—10 hours Covers 275-400 Sq. Ft. per gal., depending on surface. | 5.36 | — | — | — |
| **ALUMINUM PAINTS**<br>See: Metallite; Japalac Spray Enamel, Aluminum | | | | |
| **ASBESTOS SHINGLE PAINT**<br>See: SPRED Glide-On | | | | |
| **ASPHALT ROOF COATINGS (Plain, Fibrated, Plastic)** | (PRICES UPON REQUEST) | | | |
| **ASPHALT ROOF PAINT**<br>See: SPRED Glide-On. | | | | |
| **BARN PAINT**<br>See: Endurance Barn Paint | | | | |
| **BASECOATS (Primers)**<br>For Exteriors—See: Endurance Exterior Basecoat; Surface Bond<br>For Interiors—See: Gliddencoat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Ripolin Undercoat | | | | |
| **BASEMENT PAINTS**<br>For Floors —See: Pli-Namel; Florenamel<br>For Walls —See: SPRED SATIN; SPRED Glide-On | | | | |
| ***BLACK ASPHALTUM**<br>A weather-resisting, quick-drying, gloss black asphaltum base paint. Recommended for exterior iron work, fences, metal sash and other exterior metal surfaces where an economical finish is desired<br>APPLICATION—Brush, Spray DRYING TIME—2 to 3 hours<br>THINNER—Mineral Spirits or Turp. Covers 400-500 Sq. Ft. per gal. | 3.26 | 1.19 | .83 | .65 |

* AVAILABLE IN 5-GAL. CANS AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



GLD026243

Glidden

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| **BLACKBOARD FINISHES** | | | | |
| See: Vismatic Green Chalkboard Coating | | | | |
| **BLEACH** | | | | |
| See: Glid-Tone Wood Bleach | | | | |
| **BLENDING COLORS** | | | | |
| See: SPRED Dramatone Tinting Colors; Colors-In-Oil | | | | |
| **BRICK PAINTS** | | | | |
| See: SPRED Glide-On. | | | | |
| **BRUSHES, ALL TYPES** | (PRICES UPON REQUEST) | | | |
| **BRUSHING LACQUER** | | | | |
| See: Glid-Tone Crystalacq | | | | |
| **BRUSH RESTORER** | | | | |
| See: Glid-Strip | | | | |
| **CANVAS PRESERVATIVE** | | | | |
| See: Neva-Rot | | | | |
| **CAULKING COMPOUND** | (PRICES UPON REQUEST) | | | |
| **CEMENT AND STUCCO PAINT** | | | | |
| See: SPRED Glide-On. | | | | |
| **CLEANER, LIQUID** | | | | |
| See: Glid-N Liquid Cleaner | | | | |

## COLORS-IN-OIL

Unexcelled for tinting flat wall paints, Semi-Gloss and Gloss enamels, glazing liquids, white lead and white paste paint. Ground extremely fine in special pale linseed oil for quick and positive dispersion. The finest pigments are used to develop perfect tone and strength of color. Not to be used in latex, emulsion paints or lacquer.

| | Gals. | Qts. | ½ Pts. | 1" x 5" Tubes 3 Per Box |
|---|---|---|---|---|
| Raw Umber, Burnt Umber | 7.92 | 2.45 | .94 | .40 |
| Raw Sienna, Burnt Sienna | 9.26 | 2.79 | 1.04 | .42 |
| Ivory Drop Black | — | 2.45 | .97 | .40 |
| Lamp Black | 6.92 | 2.18 | .92 | .40 |
| Prussian Blue | — | 2.89 | 1.05 | .45 |
| Ultramarine Blue (Interior Use Only) | — | — | 1.15 | .45 |
| Chrome Green, Light; Chrome Green, Medium | 11.92 | 3.49 | 1.24 | .47 |
| Perma-Green | — | 5.49 | 1.72 | .55 |
| Chrome Yellow, Light and Medium | — | 4.39 | 1.45 | .50 |
| Chrome Yellow, Dark | — | 5.35 | 1.68 | .55 |
| Yellow Ochre | 8.22 | 2.55 | .97 | .42 |
| Venetian Red | 7.26 | 2.25 | .93 | .42 |
| Rose Lake (Interior Use Only) | — | — | 1.45 | .52 |
| American Vermilion (Interior Use Only) | — | 4.49 | 1.48 | .52 |
| Perma Blue | — | 4.79 | 1.53 | .55 |

**CONCRETE PAINT**

See: SPRED Glide-On; Pli-Namel.

**CRACK AND CREVICE FILLER**

See: SPRED Patch; SPRED Stipple Texture

**CREOSOTE PAINT**

See: Stock Farm Paint



GLD026244

Glidden

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| **DECK PAINT** | | | | |
| See: Florenamel | | | | |
| **DEEP COLORS** | | | | |
| See: SPRED SATIN | | | | |
| **DETERGENTS** | | | | |
| See: Glid-N Liquid Cleaner | | | | |
| **DRAMATONE MULTI-PURPOSE TINTING COLORS** | | | | |
| See: SPRED Products Section | | | | |
| **DRIER** | | | | |
| See: Japan Drier | | | | |
| ***DRIWAL (Clear)** — A damp-resisting, stain-resisting material designed for application on limestone, stucco, sandstone, concrete and other porous surfaces of masonry. It penetrates pores of surface and coats them with an insoluble substance which makes them fully water-repellent. Does not change texture nor discolor surface. Contains no paraffine | 4.12 | — | — | — |
| APPLICATION—Brush, Spray<br>DRYING TIME—2 hours<br>THINNER—None Required<br>COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface | | | | |
| ***DRIWAL (Silicone)** — A transparent, water-repellent finish for exterior, above-ground brick, stone and masonry. Does the job in ONE COAT. Repels rain water from penetrating the pores. Resists efflorescence and staining. Masonry surfaces show no visible change in color or texture when treated with this material. Recommended for use on brick and mortar, concrete, cement-base paints, asbestos-cement combinations, sandstone, stucco and stones other than limestone. Not to be used on cinder block or other light weight aggregate concrete blocks with extremely porous surfaces. This invisible water-repellent coating contains silicone to combat masonry deterioration | 4.86 | — | — | — |
| APPLICATION—Brush, Spray<br>DRYING TIME—2 hours<br>THINNER—None Required<br>COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface | | | | |
| **ENAMELS** | | | | |
| See: Japalac; Ripolin; Speed-Wall Alkyd Flat; Speed-Wall Alkyd Semi-Gloss; Truck, Tractor and Machinery; Florenamel; Pli-Namel; SPRED Lustre | | | | |
| **ENAMEL UNDERCOATER** | | | | |
| See: Gliddencoat; Ripolin Undercoat | | | | |
| ***ENDURANCE BARN PAINT — No. 500 RED** — A new, highest quality paint with excellent hiding power. It dries to a tough glossy film that withstands the rigors of the roughest weather. Provides long-lasting protection for barns, sheds, granaries, silos, water tank exteriors, storehouses, fences, etc. Use it on exterior wood and metal | 4.65 | 1.59 | — | — |
| APPLICATION—Brush, Spray<br>DRYING TIME—Overnight; 36 hours for recoating<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—550 Sq. Ft. per gallon | | | | |

* AVAILABLE IN 5-GAL. CANS AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



GLD026245

Glidden

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|

## *ENDURANCE EXTERIOR BASECOAT

Exterior primer for new wood and previously painted wood that is badly weathered or chalked. Use it to spot-prime bare spots resulting from peeling and flaking. Made from specially prepared oils to produce the elasticity, adhesion and control penetration necessary for finest exterior paint jobs. Can be tinted with Colors-in-Oil or DRAMATONE Tinting Colors.

| | | | | |
|---|---|---|---|---|
| | — | — | — | — |

APPLICATION—Brush, Spray
DRYING TIME—48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—450 to 500 Sq. Ft. per gallon

## *ENDURANCE HOUSE PAINT

Contains more heavy-bodied, pure linseed oil per gallon for longer life; pure white lead for added strength, water-resistance and extra durability; titanium for whiteness and hiding; zinc oxide to combat mildew; magnesium silicate for protection against cracking and checking. The exclusive Glidden formula makes this the finest, longest-lasting, self-cleaning exterior house paint manufactured. May be tinted with DRAMATONE Tinting Colors.

| | | | | |
|---|---|---|---|---|
| Outside White No. 1800 | — | — | — | — |
| Tinting White No. 1804; Regular Colors and Black | — | — | — | — |
| Cryllght Green No. 1828 | — | — | — | — |

APPLICATION—Brush, Spray, Roller
DRYING TIME—16 hours; recoat in 72 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

## *ENDURANCE HOUSE PAINT

### MILDEW & FUME-RESISTANT

A deluxe, lead-free Super White House Paint—ideal for the finest homes. Excellent for exterior wood, masonry and metal in any climate. A Non-Staining House Paint that stays white and bright for years. Especially suited for industrial areas, where homes are subjected to chemical fumes, heavy smog and smoke. Its lead-free formulation makes it ideal for farm buildings and fences. Combats mold, mildew and the roughest year-round weather.

| | | | | |
|---|---|---|---|---|
| | — | — | — | — |

APPLICATION—Brush, Spray
DRYING TIME—16 hours; 72 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Up to 550 Sq. Ft. per gallon

## ENDURANCE HOUSE PAINT, PASTEL COLORS

Pastel colors are easily obtained by tinting existing colors of ENDURANCE HOUSE PAINT or ENDURANCE TINTING BASE WHITE No. 1804, with DRAMATONE Tinting Colors. See ENDURANCE HOUSE PAINT Color Card

## *ENDURANCE IMPERIAL ONE-COAT

### WHITE HOUSE PAINT (Alkyd Fortified)

Premium quality white exterior paint. Gives extra hiding and coverage with its built-in second coat. Has depth and richness of enamel. Easy brushing. Once over is enough with this amazing one-coat paint! Fortified with alkyds to give extra durability and lasting beauty.

| | | | | |
|---|---|---|---|---|
| | 9.06 | 2.75 | — | — |

APPLICATION—Brush, Spray
DRYING TIME—48 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

* AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.



GLD026246

## ENDURANCE SHINGLE AND SHAKE STAIN

ENDURANCE SHINGLE AND SHAKE STAIN colors are made by mixing two parts ENDURANCE HOUSE PAINT with one part BLENDING LIQUID. This combination makes an ideal finish for use on grained cedar shakes, wood shingles, rough surfaced cedar, redwood and fir—on porous, rough or hand-split siding, fences, barns, and rough structures that have weathered a long time. ENDURANCE SHINGLE AND SHAKE STAIN embodies the finest quality paint pigments dispersed and blended in a strong wood preservative liquid that holds color after long exposure. It also acts as a protective finish against dry rot, decay, moisture and insects. ENDURANCE SHINGLE AND SHAKE STAIN penetrates deeply into the wood to retard warping, curling and splitting. It combats the roughest weather for many years. For combination prices, SEE: ENDURANCE HOUSE PAINT AND BLENDING LIQUID.

APPLICATION—Brush, Dip, Spray
DRYING TIME—16 hours; 48 hours for recoating
COVERAGE—Approx. 300 Sq. Ft. per gallon depending on type of surface

### *BLENDING LIQUID

BLENDING LIQUID is a combination of treated oils and solvents specially formulated to be mixed with ENDURANCE HOUSE PAINT and TRIM AND SHUTTER COLORS. This combination produces ENDURANCE SHINGLE AND SHAKE STAIN, a quality preservative finish available in many modern colors.

| Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|
| 3.56 | 1.35 | — | — |

## ENDURANCE TRIM AND SHUTTER COLORS

Beautiful, deep, rich colors, designed to harmonize with ENDURANCE HOUSE PAINT colors. These colors hold their brilliance and weather-resisting luster on wood, metal, brick and concrete. Excellent also for use on store fronts, ornamental grill work, trellises, porch and lawn furniture, etc.

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| ‡Shutter Red No. 108. Deep Turquoise No. 150 | 13.16 | 3.79 | 2.08 | — |
| ‡Light Yellow No. 37 | 10.46 | 3.09 | 1.77 | — |
| Shutter Green No. 71 | 9.32 | 2.80 | 1.59 | — |
| Chestnut Brown No. 92; Dark Blue No. 158 | 7.92 | 2.45 | 1.46 | — |
| Trim White No. 82 | 8.42 | 2.59 | 1.49 | — |

‡To be discontinued when stocks are exhausted.

APPLICATION—Brush, Spray
DRYING TIME—24 hours; 48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Approx. 550 Sq. Ft. per gallon

## EUSTON WHITE LEAD

(PRICES UPON REQUEST)

## *EVERON HOUSE PAINT (White)

An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT.

| Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|
| 6.36 | 2.08 | — | — |

APPLICATION—Brush, Roller, Spray
DRYING TIME—16 hours; recoat in 48 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

* AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.



GLD026247

Glidden

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| **FARM BUILDING PAINTS** | | | | |
| For Exteriors—See: Endurance Paints, Metallite, SPRED Glide On, Nev-A-Rust, Stock Farm White | | | | |
| For Interiors —See: SPRED Products; Maintenance Finishes Section | | | | |
| **FENCE PAINTS** | | | | |
| See: Stock Farm White; Metallite; Nev-A-Rust | | | | |
| **FILLER, WOOD** | | | | |
| See: Glid-Tone Wood Filler | | | | |
| **FLOOR FINISHES** | | | | |
| See: Pli-Namel; Florenamel; Penetrex; Glid-Tone Gloss Varnish | | | | |
| **FLOOR WAX** | | | | |
| See: Glidden Paste Wax; Glid-N Floor Wax | | | | |
| ***FLORENAMEL (Alkyd)** | | | | |
| An alkyd enamel with extra durability, for use on porches, floors of wood and concrete, canvas decks, railings—inside and outside. Will not waterspot; standing pools of water do not affect it. FLORENAMEL gives concrete basement floors and walls a mirror-like enamel finish. It's scrubbable. FLORENAMEL is made to take the roughest wear and weather. May be tinted with DRAMATONE Tinting Colors. All colors | 7.46 | 2.35 | — | — |
| APPLICATION—Brush, Spray<br>DRYING TIME—12 hours<br>THINNER—Turpentine or Mineral Spirits<br>COVERAGE—500 to 600 Sq. Ft. per gallon | | | | |
| ***GLIDDENCOAT (White Enamel Undercoat)** | | | | |
| A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with colors in oil or DRAMATONE Tinting Colors | 6.77 | 2.15 | 1.29 | .87 |
| APPLICATION—Brush, Spray<br>DRYING TIME—Overnight for sanding and recoating<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—500 Sq. Ft. per gallon | | | | |
| **GLIDDEN PASTE WAX** | | | | |
| For furniture, floors and automobiles; in fact, any surface where a wax finish is desired. It polishes quicker and easier than other similar products and will retain its gloss and finish over a period of several months. It dries hard and imparts longer protection to floor surfaces even when subjected to extreme hard usage | 4 lbs.<br>3.39 | 1 lb.<br>.98 | — | — |
| APPLICATION—Cloth or Applicator | | | | |
| **GLIDDENSPAR VARNISH** | | | | |
| The finest interior-exterior spar varnish. Has extreme resistance to exposure, water and acids. Recommended for exterior surfaces such as doors, porch ceilings and those places inside the home which are subjected to water and exposure, such as window sills | 9.16 | 2.75 | 1.61 | 1.00 |
| APPLICATION—Brush<br>DRYING TIME—8 hours; 48 hours for recoating<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—650 Sq. Ft. per gallon | | | | |
| **GLIDE-ON, SPRED** | | | | |
| See: SPRED Products Section | | | | |

* AVAILABLE IN 5-GAL. CANS AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



GLD026248

Glidden

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| **GLID-N FLOOR WAX (Liquid)** | | | | |
| For use on all types of floors. Dries to a gloss finish without polishing. The hard wax film resists wear, keeps dirt on surface where it can be removed easily with a stiff brush or damp mop. Resists water. Scrubbable | 3.65 | 1.19 | — | — |
| **GLID-N LIQUID CLEANER (Detergent)** | | | | |
| An excellent degreaser as well as cleaner. Does a remarkably easy job on walls, woodwork, floors, linoleum, tile, windows, dishes, mirrors and automobiles. Dries free from streaks. Harmless to the skin. Requires only two to three teaspoonsful to a gallon of water | 4.65 | 1.39 | .89 | — |
| **GLID STRIP (Non-Flammable)** | | | | |
| **Wash Away Paint and Varnish Remover** | | | | |
| A non-flammable, water-flush paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal | 7.16 | 2.39 | 1.33 | .89 |
| ***GLID-TITE GALVANIZED IRON PRIMER** | | | | |
| A primer for all galvanized metal, plymetal, galvaneal, or treated metal surfaces. The metal requires no previous etching with acids. Excellent for use on new eave troughs and gutters. Finish coat adhesion is better if application is thin rather than heavy | 6.37 | 2.05 | — | — |
| APPLICATION—Brush<br>DRYING TIME—Overnight; 72 hours for recoating<br>THINNER—Turpentine or Mineral Spirits<br>COVERAGE—Up to 600 Sq. Ft. per gallon | | | | |
| **GLID-TONE CRYSTALACQ (Brushing Lacquer)** | | | | |
| A crystal clear, quick-drying, water- and wear-resistant lacquer finish for brush application. Easy to use. Excellent for floors, woodwork, furniture, linoleum, etc. | 7.77 | 2.39 | 1.43 | — |
| APPLICATION—Brush<br>DRYING TIME—1 to 6 hours, depending on surface<br>THINNER—Glid-Tone Crystalacq Reducer<br>COVERAGE—300 Sq. Ft. per gallon | | | | |
| **GLID-TONE CRYSTALACQ REDUCER** | | | | |
| Special Thinner for Crystalacq | — | — | 1.04 | — |

* AVAILABLE IN 5-GAL. CANS AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



GLD026249

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| **GLID-TONE GLOSS VARNISH** | | | | |
| A deluxe, general-purpose interior varnish. Phenolic ether resins give it extreme abrasion resistance, durability, and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed | 8.92 | 2.69 | 1.56 | 1.00 |
| APPLICATION—Brush<br>DRYING TIME—6 to 8 hours<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—650 Sq. Ft. per gallon | | | | |
| **GLID-TONE SATIN-SHEEN VARNISH** | | | | |
| A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains. DO NOT USE ON FLOORS | 7.77 | 2.39 | 1.43 | .92 |
| APPLICATION—Brush<br>DRYING TIME—2 hours<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—650 Sq. Ft. per gallon | | | | |
| **GLID-TONE SPAR VARNISH** | | | | |
| Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use — spars, hulls, decks, house sidings, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces | 9.62 | 2.82 | 1.63 | 1.04 |
| APPLICATION—Brush<br>DRYING TIME—8 hours; 48 hours for recoating<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—650 Sq. Ft. per gallon | | | | |
| **GLID-TONE WOOD STAIN** | | | | |
| An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors. | | | | |
| APPLICATIONS—Wiping Cloth, Brush | | | | |
| DRYING TIME—12 hours — Stains, All Colors | 5.62 | 1.85 | 1.19 | .80 |
| THINNER—Glid-Tone Stain Reducer — Glid-Tone Stain Reducer | 3.42 | 1.30 | .86 | .66 |
| **GLID-TONE WOOD BLEACH** | | | | |
| Has the amazing properties of bleaching practically any type of wood from its original color to an almost natural white and without any deposit of a salt of any kind in the pores of the wood, necessary to the production of the blond effects so popular and modern at present. | | | | |
| Available in two size units. Large unit consists of 1 gallon of No. 1 Solution and 1 quart of No. 2 Solution. Small unit consists of 1 quart of No. 1 Solution and ½ pint of No. 2 Solution | Large Unit 10.40 | Small Unit 4.10 | — | — |
| APPLICATION—Mop, Cloth, Waste<br>DRYING TIME—12 hours or more | | | | |



GLD026250

Glidden

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| **GLID-TONE WOOD FILLER** | | | | |
| For use on all open-grained wood, such as oak, chestnut, walnut and mahogany. Has pure silex base and will not shrink or break away from the pores of the wood when dry. Furnished in paste form. Must be reduced with naphtha or turpentine | 5.36 | 1.80 | — | .78 |
| APPLICATION—Brush, Cloth<br>THINNER—Turpentine, Naphtha | | | | |
| **GLOSS FINISHES** | | | | |
| See: Speed-Wall; Japalac; Ripolin; Florenamel | | | | |
| **GYMNASIUM FLOOR FINISH** | | | | |
| See: Penetrex; also See: Maintenance Finishes Section | | | | |
| **HEAT RESISTING ALUMINUM** | | | | |
| See: Metallite | | | | |
| **HOUSE PAINT** | | | | |
| See: Endurance Paints; SPRED Glide-On; Everon | | | | |
| **IRON PRIMER** | | | | |
| See: Glid-Tite Galvanized Iron Primer; Liquid Red Lead | | | | |
| **IMPERIAL ONE-COAT WHITE HOUSE PAINT (Alkyd Fortified)** | | | | |
| See: Endurance Imperial | | | | |
| **INTERIOR ALUMINUM** | | | | |
| See: Metallite Interior Chrome Finish | | | | |
| **JAPALAC SCREEN AND IRON ENAMEL** | | | | |
| Gloss black, solid-covering enamel for exterior screens, wood and metal sash, wrought iron, decorative lamps, etc. Also ideal for interior ironwork, pipes, grills, furnaces, stoves, heaters, andirons, etc. Will not clog screen mesh. Resists weather and protects metal from rusting | 4.92 | 1.65 | 1.07 | .75 |
| APPLICATION—Brush, Spray or Special Applicator<br>DRYING TIME—6 to 8 hours<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—600 Sq. Ft. per gallon | | | | |

| | Gals. | Qts. | Pts. | ½ Pts. | ¼ Pts. |
|---|---|---|---|---|---|
| **JAPALAC ENAMEL** | | | | | |
| **Quick-Drying, Alkyd Gloss** | | | | | |
| An extra-durable, alkyd enamel in brilliant colors that cover in ONE COAT. Bright hues and muted tones give new life and sparkle to old surfaces—walls, ceilings, woodwork and furniture. JAPALAC Quick-Drying Alkyd Enamel is formulated for the finest enameling inside and outdoors. It looks, wears and washes like baked enamel. Colors may be tinted with DRAMATONE Tinting Colors. | | | | | |
| Ultra White, Brilliant Black, Flat Black and Colors | 9.92 | 2.95 | 1.69 | 1.08 | .67 |
| APPLICATION—Brush, Roller, Spray<br>DRYING TIME—4 to 6 hours; 24 hours for recoating<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—Approx. 500 Sq. Ft. per gallon | | | | | |



GLD026251

Glidden

| | Gals. | Qts. | Pts. | ½ Pts. |
|---|---|---|---|---|
| **JAPALAC SPRAY ENAMEL** | | | | |
| In Ready-To-Spray Cans | | | | |
| All-purpose, interior-exterior enamel in pressurized, aerosol cans ready for immediate spraying. Extra-durable, quick-drying enamel of brilliant beauty. Gives professional appearance to porch and lawn furniture, bicycles, toys, tables, chairs, etc. Ideal for wickerwork. Colors match regular JAPALAC Alkyd Enamel colors. In addition, JAPALAC SPRAY ENAMEL is available in ready-to-spray Interior-exterior Aluminum, rich Gold, and a clear finish. | 12 Av. Oz. Cans | | | |
| White, Colors, and Clear | 1.69 | | | |
| APPLICATION—Spray<br>DRYING TIME—Ten minutes | | | | |
| **JAPALAC VARNISH STAIN** | Gals. | | | |
| Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof | 7.16 | 2.25 | 1.35 | .90 |
| APPLICATION—Brush, Spray<br>DRYING TIME—4 to 6 hours; 24 hours for recoating<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—600 Sq. Ft. per gallon | | | | |
| ***JAPAN DRIER** | | | | |
| A top quality drier for use in drying oil and linseed oil paints. It is made from hard gums. Very popular with professional painters. Two and one-half gallons are enough for fifty gallons of oil | 3.82 | 1.40 | .94 | .70 |
| **LACQUER** | | | | |
| See: Glid-Tone Crystalacq (Brushing Lacquer) | | | | |
| **LATEX PAINTS** | | | | |
| See: SPRED Products Section | | | | |
| **LINOLEUM COATING** | | | | |
| See: Glid-Tone Crystalacq | | | | |
| **LINSEED OIL** | (PRICES UPON REQUEST) | | | |
| **LIQUID CLEANER** | | | | |
| See: Glid-N Liquid Cleaner | | | | |
| ***LIQUID RED LEAD (Modified)** | | | | |
| Recommended whenever a shop coat of red lead is specified. Comes ready to apply, is extremely elastic and is an excellent rust preventative | 9.06 | 2.75 | 1.59 | 1.05 |
| APPLICATION—Brush, Spray<br>DRYING TIME—16 hours; 48 hours for recoating<br>THINNER—Mineral Spirits or Turpentine<br>COVERAGE—500 to 600 Sq. Ft. per gallon | | | | |
| **LIQUID WAX** | | | | |
| See: Glid-N Floor Wax | | | | |
| **MACHINERY ENAMEL** | | | | |
| See: Truck, Tractor and Machinery Enamel; Japalac | | | | |
| **MASONRY FINISHES** | | | | |
| See: Clear Driwall; Silicone Driwal; SPRED Glide-On | | | | |

* AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.



GLD026252