



FRICTION MATERIAL

MATCHED SETS FOR TRUCKS, Cont'd

Set No.	Application	Set No.	Application
INTERNATIONAL—Cont'd		GENERAL MOTORS TRUCK—Cont'd	
1191	1941-52; K4, K5, KB4, KB5, L160-161, 162	*653	1939-50; AC100, 150; CC100, 150, 250, EC100, 150; FC100, 150
1192	1941-52; K6, KB6, L170-171-172-175	654	1939-50; AC300, 350, 400; AF300, 350; CC250, 260, 300, 350, 400; EC300, 350; EF300, 350; FC300, 350; FCS300, 350; FCS300, 350; FF300 (Rear)
1193	1941-52; K5, K6, K7, K8F, KB5, KB6, KB7, KB8F, L170-175, L180-183, 185, LC160, 161, 162, 180, 182, LF170, 171, 172		1951-52; 280-22, 300-24, 350-24; F350-24 (Rear)
1194	1941-49; K8, KB8, KB8F	*1014A	1946-49; EC150, 250; FC150, 250, FP150
1195	1941-52; K8, KB8, L184, L190-93, LC190, 191, 192		1950-52; P150-22, 250-22
1196	1947-52; KB8, L184, L190, L193, L194, L195, L200, L202, L205	1196	1949-52; HC470-475, 600, 620, 640; HCR620, 640; HF470-475; HF-600, 620, 640; HFR620, 640
1198	1941-48; K7, KB7, KS7	1198	1949-52; HC450-455, 520; HCR520, HCS450, 456-458, HCS520; HCW620, HF450-455, 520; HFR-450, 451, 520
1227	1948-49; K1, K1M, K2, K3	1199	1949-52; HC650, 700, 720; HCR720; HF700, 720, HFR720
1228	1948; K3	*1210	1946-48; EC250; FC250
1229	1948-40; K1, K1M, K2, K3, KB1, KB2, KB3		1950-52; 250-22
1230	1950-52; L174, L180-183, L185, LC180-182, LF190-192	1234	1949-52; HC450-455, 470-475, 520, 600, 620, 640, 650; HCR520, 620, 640; HCS400, 405-407, 450, 456-458, 520; HCW400, 402-405, 620; HF450-455, 470-475, HFR-450, 451, 520
1233	1950-52; L160-165, L170-175, LC160-162, LF170-172	1239	1949-52; HC700, 720; HCR720; HF-600, 620, 640; HFR620, 640
1234	1950-52; L190-195, L200-205, LC190-192, LC200-202, LF190-192	1240	1949-52; HF700, 720; HFR720
1235	1950-52; L180-185, LC180-182	2032	1951-53; 280-22, 300-24, 350-24, F350-24
1236	1950-52; L150-153; LM150-152	2039	1953; F250-22 (Front)
GENERAL MOTORS TRUCK		*2040	1953; F150-22, FPM150-22 (F & R); F250-22 (Rear)
644	1939-50, AC300, 350, 400; AF300, 350; CC250, 260, 300, 350, 400; EC300, 350, EF300, 350; FC300, 350, FCS300, 350; FF300 (Front)		
	1951-52; 280-22, 300-24, 350-24, F350-24, (Front)		

*Bonded lining equipped. Available only in Han-Di-Pack Part No. 2040 BS, see pages 18 and 19.

*Bonded lining equipped. Drilled set can be used by drilling shoes. For undrilled sets for bonding see pages 18 and 19 covering Han-Di-Pack.

INLITE SHIM STOCK

A non-compressible, high heat resisting, high quality flexible material. Easy to use. Furnished in two thicknesses, .020" and .03125". Each carton contains approximately 100 feet.

Part Number	SIZE		Part Number	SIZE		Part Number	SIZE	
	Width	Thickness		Width	Thickness		Width	Thickness
76	1½"	.020"	85	3½"	.020"	82	2"	.03125"
77	1¾"	.020"	86	4"	.020"	83	2¼"	.03125"
78	2"	.020"	80	1½"	.03125"	87	3"	.03125"
79	2¼"	.020"	81	1¾"	.03125"	88	4"	.03125"
84	3"	.020"						

