

O'BRIEN

REGISTERED	
REGIN. No.	131400
Code No.	13550
Date	'5-8-72

"SEVENTY-FIVE" *Gloss* HOUSE PAINT

CC WHITE
Controlled Chalking

STARTS WHITE
STAYS WHITE

N21606

"SEVENTY-FIVE" GLOSS HOUSE PAINT

"Seventy-Five" Gloss House Paint is a premium quality, modified linseed oil paint for exterior use. For properly prepared wood, metal and masonry surfaces. Available in standard colors, and three types of white: Self-Cleaning White; CC (Controlled Chalking) White; and White Bases Nos. 1, 2, and 3 (for tinting only).

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand and dull glossy areas under eaves and protected areas, wash with detergent and thoroughly rinse. Clean metal by sanding or wire brushing.

Priming — Where possible tint primer toward top coat color. UNPAINTED WOOD, COMPOSITION (factory primed) BOARD: Prime with "Seventy-Five" Priming White. UNPAINTED MASONRY: Prime with alkali-resistant "A-R" Primer. UNPAINTED FERROUS METAL: Prime with Flexico Blox-Rust (alkyd or latex type). UNPAINTED GALVANIZED METAL: Prime with Flexico Blox-Rust (latex type only). PREVIOUSLY PAINTED WOOD AND METAL (INCLUDING ALUMINUM SIDING): If in good condition, no priming is required.

Tinting — Tint White Bases Nos. 1, 2, and 3 with lead-free and sun-proof Tone-All Universal Tinting Colors, observing minimum-maximum recommendations.

Application — Stir well. Apply by brush or spray over a dry surface at temperature not less than 60° F. If thinning is desired, use turpentine or mineral spirits up to one-half pint per gallon for brush application. For spray, thin with light naphtha one pint per gallon. On new work, putty and caulking should be applied after the prime coat has dried for 18-24 hours. Avoid painting in damp weather or late in the evening. Allow 48 hours good drying weather between coats.—(OWY)

CAUTION! COMBUSTIBLE!

CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surface of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

SINCE

O'BRIEN

1875

THE O'BRIEN CORPORATION • SOUTH BEND, IND. 46621

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • LOS ANGELES, CAL. • SAN FRANCISCO, CAL. • BRUNSWICK, GA.

49 TOC 001840

THE GILSON ROUND A60-XX (V) 1 2 3 4 5 6 7 8 9 10 11 12

O'BRIEN

REGISTERED

REG'N. No. 37400

Code No. 14430

Date 5-8-72

"SEVENTY-FIVE" *Gloss* HOUSE PAINT

A60-19 GOLDENROD
ENAMELIZED TRIM COLOR
NET 128 FL OZ (4 CANS)

"SEVENTY-FIVE GLOSS HOUSE PAINT — ENAMELIZED TRIM COLORS

"Seventy-Five" Gloss House Paint Enamelized Trim Colors are premium quality, alkyd modified paint colors for exterior trim use only. These colors dry faster and harder than body paint. All colors are chalk- and fade-resistant. Recommended for all wood and metal trim areas such as frames, shutters, trellis, doors, etc. **CAUTION:** Enamelized Trim Colors should not be used for body work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. For repaint work, sand and dull glossy areas under eaves and protected areas, wash with detergent and thoroughly rinse.

Priming — Do not prime with conventional house paint primers. **UNPAINTED WOOD:** Use Enamelized Trim Color as a self-primer over new wood by reducing the first coat with one pint of turpentine or mineral spirits per gallon of color. **UNPAINTED FERROUS METAL:** Prime with Flexico Blox-Rust (alkyd or latex type). **UNPAINTED GALVANIZED METAL:** Prime with Flexico Blox-Rust (latex type only), allowing 48 hours drying before recoating.

Application — Stir well. Apply by brush, roller, or spray over a dry surface at temperature not less than 60° F. On repaint work apply Enamelized Trim Colors at package consistency or thin sparingly with turpentine or mineral spirits if desired. Allow 48 hours good drying weather between all coats. — (OWY)

CAUTION! COMBUSTIBLE!

CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surface of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**

SINCE

O'BRIEN

1875

THE O'BRIEN CORPORATION • SOUTH BEND, IND. 46621

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • LOS ANGELES, CAL. • SAN FRANCISCO, CAL. • BRUNSWICK, GA.

O'BRIEN

REGISTERED	
REG'N. No.	31400
Code No.	14400
Date	5-8-72

"SEVENTY-FIVE" *Gloss* HOUSE PAINT

A60-03 EVERGREEN
ENAMELIZED TRIM COLOR
NET 128 FL. OZ. (1 GAL.)

"SEVENTY-FIVE GLOSS HOUSE PAINT — ENAMELIZED TRIM COLORS

"Seventy-Five" Gloss House Paint Enamelized Trim Colors are premium quality, alkyd modified paint colors for exterior trim use only. These colors dry faster and harder than body paint. All colors are chalk- and fade-resistant. Recommended for all wood and metal trim areas such as frames, shutters, trellis, doors, etc. **CAUTION:** Enamelized Trim Colors should not be used for body work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. For repaint work, sand and dull glossy areas under eaves and protected areas, wash with detergent and thoroughly rinse.

Priming — Do not prime with conventional house paint primers. **UNPAINTED WOOD:** Use Enamelized Trim Color as a self-primer over new wood by reducing the first coat with one pint of turpentine or mineral spirits per gallon of color. **UNPAINTED FERROUS METAL:** Prime with Flexico Blox-Rust (alkyd or latex type). **UNPAINTED GALVANIZED METAL:** Prime with Flexico Blox-Rust (latex type only), allowing 48 hours drying before recoating.

Application — Stir well. Apply by brush, roller, or spray over a dry surface at temperature not less than 60° F. On repaint work apply Enamelized Trim Colors at package consistency or thin sparingly with turpentine or mineral spirits if desired. Allow 48 hours good drying weather between all coats. — (OWY)

CAUTION! COMBUSTIBLE!

CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surface of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**

SINCE

O'BRIEN

1875

THE O'BRIEN CORPORATION • SOUTH BEND, IND. 46621

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • LOS ANGELES, CAL. • SAN FRANCISCO, CAL. • BRUNSWICK, GA.

O'BRIEN

REGISTERED

REG'N. No. 31400

Code No. 14250

Date 5-8-72

"SEVENTY-FIVE"
Gloss
HOUSE PAINT

A60-14 DARK BROWN
ENAMELIZED TRIM COLOR
NET 128 FL. OZ. (1 GAL.)

"SEVENTY-FIVE GLOSS HOUSE PAINT — ENAMELIZED TRIM COLORS

"Seventy-Five" Gloss House Paint Enamelized Trim Colors are premium quality, alkyd modified paint colors for exterior trim use only. These colors dry faster and harder than body paint. All colors are chalk- and fade-resistant. Recommended for all wood and metal trim areas such as frames, shutters, trellis, doors, etc. **CAUTION:** Enamelized Trim Colors should not be used for body work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. For repaint work, sand and dull glossy areas under eaves and protected areas, wash with detergent and thoroughly rinse.

Priming — Do not prime with conventional house paint primers. **UNPAINTED WOOD:** Use Enamelized Trim Color as a self-primer over new wood by reducing the first coat with one pint of turpentine or mineral spirits per gallon of color. **UNPAINTED FERROUS METAL:** Prime with Flexico Blox-Rust (alkyd or latex type). **UNPAINTED GALVANIZED METAL:** Prime with Flexico Blox-Rust (latex type only), allowing 48 hours drying before recoating.

Application — Stir well. Apply by brush, roller, or spray over a dry surface at temperature not less than 60° F. On repaint work apply Enamelized Trim Colors at package consistency or thin sparingly with turpentine or mineral spirits if desired. Allow 48 hours good drying weather between all coats. — (OWY)

CAUTION! COMBUSTIBLE!

CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surface of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**

SINCE

O'BRIEN

1875

THE O'BRIEN CORPORATION • SOUTH BEND, IND. 46621

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • LOS ANGELES, CAL. • SAN FRANCISCO, CAL. • BRUNSWICK, GA.

O'BRIEN

REGISTERED

REG'N. No. 37400

Code No. 14550

Date 5-8-72

"SEVENTY-FIVE" *Gloss* HOUSE PAINT

A60-20 RIPPLE GREEN
ENAMELIZED TRIM COLOR
NET 128 FL. OZ. (1 GAL.)

"SEVENTY-FIVE GLOSS HOUSE PAINT — ENAMELIZED TRIM COLORS

"Seventy-Five" Gloss House Paint Enamelized Trim Colors are premium quality, alkyd modified paint colors for exterior trim use only. These colors dry faster and harder than body paint. All colors are chalk- and fade-resistant. Recommended for all wood and metal trim areas such as frames, shutters, trellis, doors, etc. **CAUTION:** Enamelized Trim Colors should not be used for body work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. For repaint work, sand and dull glossy areas under eaves and protected areas, wash with detergent and thoroughly rinse.

Priming — Do not prime with conventional house paint primers. **UNPAINTED WOOD:** Use Enamelized Trim Color as a self-primer over new wood by reducing the first coat with one pint of turpentine or mineral spirits per gallon of color. **UNPAINTED FERROUS METAL:** Prime with Flexico Blox-Rust (alkyd or latex type). **UNPAINTED GALVANIZED METAL:** Prime with Flexico Blox-Rust (latex type only), allowing 48 hours drying before recoating.

Application — Stir well. Apply by brush, roller, or spray over a dry surface at temperature not less than 60° F. On repaint work apply Enamelized Trim Colors at package consistency or thin sparingly with turpentine or mineral spirits if desired. Allow 48 hours good drying weather between all coats. — (OWY)

CAUTION! COMBUSTIBLE!

CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surface of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**

SINCE

O'BRIEN

1875

THE O'BRIEN CORPORATION • SOUTH BEND, IND. 46621

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • LOS ANGELES, CAL. • SAN FRANCISCO, CAL. • BRUNSWICK, GA.

O'BRIEN

REGISTERED
REG'N. No. 37460
Code No. 13900
Date 5-8-72

"SEVENTY-FIVE"[®] *Gloss* HOUSE PAINT

A20-00 PRIMING WHITE

NET 128 FL. OZ. (1 GAL.)

"SEVENTY-FIVE GLOSS HOUSE PAINT — PRIMING WHITE

"Seventy-Five" House Paint Priming White is a premium quality, modified linseed oil primer. Recommended especially for use as a primer for "Seventy-Five" Low-Lustre House Paint and "Seventy-Five" Gloss House Paint. Prepares new or previously painted wood surfaces for longer-lasting finish coats. **CAUTION: Do not use as a primer for "Seventy-Five" Enamelized Trim Colors.**

NOTE: After several applications of oil type low-lustre house paints (such as "Seventy-Five" Low-Lustre) . . . a prime coat is recommended to seal and recondition the surface.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand and dull glossy areas under eaves and protected areas, **wash with detergent and thoroughly rinse.**

Tinting — Tint with **lead-free** and **sun-proof** Tone-All Universal Tinting Colors, toward the finish color. May also be tinted with Oil Colors.

Application — Stir well. Apply by brush, roller, or spray over a dry surface at temperature not less than 60° F. If thinning is desired, use turpentine or mineral spirits up to one-half pint per gallon for brush application. For spray, thin with light naphtha one pint per gallon. Allow 48 hours good drying weather between primer and top coat. Putty and caulking may be applied after 18-24 hours drying. — (OWY)

CAUTION! COMBUSTIBLE!

CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surface of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**

SINCE

O'BRIEN

1875

THE O'BRIEN CORPORATION • SOUTH BEND, IND. 46621

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • LOS ANGELES, CAL. • SAN FRANCISCO, CAL. • BRUNSWICK, GA.