

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME

Raybestos-Manhattan, Inc.

EMERGENCY TELEPHONE NO.

203/371-0101

ADDRESS (Number, Street, City, State, and ZIP Code)

100 Oakview Drive Trumbull, CT 06611

CHEMICAL NAME AND SYNONYMS

TRADE NAME AND SYNONYMS

PRODUCT TYPE

Noven Rolls

R/H CORE CODE OR MATERIAL NO.

M357 -B and M635 L

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Unit)	ALLOYS AND METALLIC COATINGS	%	TLV (Unit)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Unit)
Asbestos	40-80	2f/cc	Varnish & Plant Oils	5-50	NL
Brass	5-15%	NL			
Gilsonite	0-6%	NL			

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H ₂ O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (=1)	
SOLUBILITY IN WATER			
APPEARANCE AND ODOR	Light Tan Noven Product - Solid		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA			
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

PAGE (1)

(Continued on reverse side)

October 21, 1980

PERCAB-Rayonne, N. J.

PLAINTIFF'S
EXHIBIT

WV-021598

PLAINTIFF'S
EXHIBIT

78702.02

GEWVOCT04-011592

WV-21598

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME Raybestos-Manhattan, Inc.		EMERGENCY TELEPHONE NO. 203/371-0101
ADDRESS (Number, Street, City, State, and ZIP Code) 100 Oakview Drive Trumbull, CT 06611		
CHEMICAL NAME AND SYNONYMS		TRADE NAME AND SYNONYMS
PRODUCT TYPE Woven Rolls	R/H CODE OR MATERIAL NO. M357 -B and M635 L	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Unit)	ALLOYS AND METALLIC COATINGS	%	TLV (Unit)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Unit)
Asbestos	40-80	2f/cc
Brass	5-15%	NL
Gilsonite	0-6%	NL
Varnish & Plant Oils	5-50	NL

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H ₂ O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____=1)	
SOLUBILITY IN WATER			
APPEARANCE AND ODOR Light Tan Woven Product - Solid			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA			
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARDS			