

PRATT & LAMBERT



PRATT'S PATENT LIQUID DRYER A JAPAN DRIER

D55

DANGER!
HARMFUL OR FATAL IF SWALLOWED
COMBUSTIBLE
See Other Cautions on Back Panel, FA20

1 QUART 946ml

COMBUSTIBLE — CONTAINS NITROCEUM DISTILLATE.
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Keep away from heat and open flame. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use.
Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN. **BA20**

PRATT'S PATENT LIQUID DRYER

Invented by A.W. Pratt, Pratt's Patent Liquid Dryer is made only by Pratt & Lambert, Inc.

Pratt's Patent Liquid Dryer is uniform. It mixes easily and thoroughly with linseed oil or linseed oil combined with lead, zinc and other pigments. It never curdles, or saponifies; it stays mixed. It does not burn or harm the paint film.

Directions for Use

It is difficult to offer specific rules for using Pratt's Dryer, as the drying of paint is affected by a multitude of factors, which include temperature, humidity and film thickness. More Pratt's Dryer is needed on very damp and cool days than on dry and warm days. A slight excess of Pratt's Dryer will do no harm. In general, 1/4 pint to 1/2 pint of Pratt's Dryer is sufficient to dry one gallon of paint, varnish or enamel. 1/4 pint will dry one gallon of raw linseed oil.

RMAU

N15651



 **PRATT & LAMBERT, INC.**
BUFFALO, NEW YORK 14220

Mfg. in U.S.A. — 68

0007-PTL-001530