


A-C AND D-C RELAYS




Type SR—Thermal Overload Switch—Two Pole

WHEN ORDERING SPECIFY

- Catalog number
- Heater coil number or full load current




NEMA 1




Open Type

APPROXIMATE DIMENSIONS AND SHIPPING WEIGHTS



NEMA 1—3 Lbs.



Open Type—2½ Lbs.

Maximum Horsepower Ratings					Open Type		General Purpose NEMA 1	
A-c Single Phase		A-c Polyphase		D-c				
115V.	230-550V.	110V.	220-550V.	115-230V.	Cat. No.	Price	Cat. No.	Price
1½	3	3	5	½	10172H2	\$14.	10172H1	\$16.

Prices include two heater coils at \$1.50 each.

HEATER COILS

H.P.	Single Phase		Polyphase				Direct Current	
	110 Volts	220 Volts	110 Volts	220 Volts	440 Volts	550 Volts	120 Volts	240 Volts
1/8	9586-	9586-	9586-	9586-	9586-	9586-	9586-	9586-
1/8	---	---	---	---	---	---	---	---
1/8	H159	H152	---	---	---	---	H148	H141
1/4	H162	H155	H150	H143	H1470	H1468	H150	H143
1/4	H164	H157	H153	H145	H138	H1470	H153	H146
1/2	H167	H160	H157	H149	H142	H139	H160	H153
3/4	H171	H164	H160	H153	H146	H144	---	---
1	H172	H166	H163	H155	H149	H146	---	---
1½	H186	H168	H167	H153	H160	H150	---	---
2	---	H170	H170	H162	H155	H153	---	---
3	---	H173	H173	H166	H159	H157	---	---
5	---	---	---	H171	H164	H162	---	---

Heater coils listed are for average motors. For more accurate selections see index on page 281.


Type RP—A-c Open or Reverse Phase Relay

WHEN ORDERING SPECIFY

- Catalog number



Cover Removed





With Conduit Receptacle

THREE PHASE OR TWO PHASE, 3 OR 4 WIRE

Volts	Cycles	For Panel Mounting		With Conduit Receptacle	
		Cat. No.	Price	Cat. No.	Price
110	60	10182-H1	\$50.	10182-H13	\$58.
220	60	H2	50.	H14	58.
440	60	H3	50.	H15	58.
550	60	H4	50.	H16	58.
110	50	H5	50.	H17	58.
220	50	H6	50.	H18	58.
440	50	H7	50.	H19	58.
550	50	H8	50.	H20	58.
110	25	H9	50.	H21	58.
220	25	H10	50.	H22	58.
440	25	H11	50.	H23	58.
550	25	H12	50.	H24	58.

APPROXIMATE DIMENSIONS AND SHIPPING WEIGHTS

For Panel Mounting
12 Lbs.With Conduit Receptacle
15 Lbs.