N 3236

MASTER PAINTER'S EXTERIOR PRIMER

DIRECTIONS

NEW WORK — Thin with 2 Pints Linseed Oil and 1 Pint of Thinsol or Turpentine to each gallon of Primer.

On very resinous wood, such as yellow pine or cypress, thin with 2 Pints of Linseed Oil and 1 Pint of Benzol.

OLD PAINTED WORK — Be sure that all loose and scaling paint is removed and that surface is clean and in proper condition for painting. Thin Primer with 1 Pint of Linseed Oil and 1 Pint of Thinsol or Turpentine.

ANALYSIS 1558 WHITE	
Pigment	63.3%
Vehicle	36.7%
	100.0%

PIGMENT	
Titanium Pigments	47.6%
White Lead	4.0%
Zinc Oxide	3.9%
Magnesium Silicates	36.2%
Calcite	7.9%
Body Control Agent	.4%
	100.0%

VEHICLE	
Treated Vegetable Oil Solution	10.4%
Refined Linseed Oil	43.6%
Heat Bodied Oil	8.8%
Oleoresinous Varnish	9.8%
Oleum Spirits	23.6%
Drier	3.8%
	100.0%

(12-61) R—FORM M. P. 152

CAUTION! COMBUSTIBLE

Keep from Heat and Open Flame. CONTAINS LEAD OR OTHER COMPOUNDS HARMFUL IF EATEN. Do not apply on interior surfaces of a dwelling, or a place used for the care of children, or on window sills, toys, cribs and other furniture which might be chewed by children. Avoid breathing vapor, spray mist, or dust, if sanding, and prolonged contact with skin may cause skin irritation. Wash thoroughly after handling and before eating or smoking. Do not take internally. Keep container closed when not in use. Keep Out of the Reach of Children. Use with Adequate Ventilation. (IV-361

ONE GALLON U. S. MEASURE

Made in U.S.A

GL032753