



INTER-OFFICE CORRESPONDENCE *Mr. G. E. Coleman*  
*Pioneer*

TO Mr. G. E. Coleman  
Los Angeles

DATE August 25, 1977

FROM J. C. Schmitt - Rochelle Park

SUBJECT Pioneer Product Labels

We have reviewed all of the labels which you submitted in accordance with your June 29 letter and find a varying practice of showing warnings and safety precautions. For your guidance, we offer the following general remarks concerning warning statements on the labels and some of the practices to be observed. Following our general remarks, we will make some specific comments on groups of labels, and this will be followed by detailed recommendations on certain of the labels.

In general, the following should be observed:

1. Directions for installation and application must be separated from safety precautions and statements of product hazards. Precautions needed for proper performance of the product must be a part of this section on directions.
2. Safety precautions must be preceded by the appropriate signal word such as CAUTION, WARNING or DANGER, printed in a type size larger than any other type in the same panel. Hazardous ingredients must be identified, precautions to be observed must be described and instructions on medical treatment should be included. All of this is to be in clear print in a prominent location on the label.
3. The above two types of statements can be indicated on most labels under the headings of:

1. SAFETY PRECAUTIONS

2. APPLICATION PRECAUTIONS

These should suffice unless the nature of the product hazard is more severe than usual due to low flash point, toxic ingredients, etc.



4. Containers of five gallon capacity or greater should carry an additional label concerning the hazard of emptied containers. On cutback products, this label should read as follows:

ATTENTION!

THIS CONTAINER HAZARDOUS WHEN EMPTIED

Since Emptied Containers Retain Product Residues (Vapor, Liquid or Solid), All Labeled Hazard Precautions Must be Observed.

Do not expose to open flame.

For water based emulsion and latex products, the label should read as follows:

ATTENTION!

THIS CONTAINER HAZARDOUS WHEN EMPTIED

Since Emptied Containers Retain Product Residues (Vapor, Liquid or Solid), All Labeled Hazard Precautions Must be Observed. Dried, water-free residues may be combustible.

Do not expose to open flame.

- 5.. For most cutback products represented by your labels, the following general wording is the minimum warning recommended:

DANGER

CONTAINS PETROLEUM DISTILLATES  
SAFETY PRECAUTIONS

Avoid prolonged breathing of vapor or contact with skin. Use only in well ventilated area. If swallowed, do not induce vomiting. Call physician immediately. KEEP OUT OF THE REACH OF CHILDREN. KEEP AWAY FROM FIRE OR OPEN FLAME.

DANGER - HARMFUL OR FATAL IF SWALLOWED

6. For most water based emulsion and latex products, the minimum warning statement should be as follows:

WARNING

SAFETY PRECAUTIONS

HARMFUL IF SWALLOWED. KEEP  
OUT OF THE REACH OF CHILDREN.

7. We note several product labels carry the warning paragraph concerning the content of asbestos fiber. In this paragraph, we prefer the wording that OSHA "has stated" that repeated inhalation of asbestos fiber is a health hazard, rather than OSHA "believes" that it is a hazard. This warning statement should appear in the same panel and adjacent to all other health and safety warnings. We also prefer the use of petroleum distillates as a description of the solvents instead of mineral spirits and other terms.
8. Any other warning statements required by local regulations should be in the same panel and adjacent to the safety precautions and warnings. This would apply to the California Prohibition of spraying asbestos containing products.
9. Labels should not contain such terms as "non-toxic", if another portion of the label states that ingestion can be harmful. Avoid the use of "non-toxic" altogether.
10. There is some inconsistency in the use of the signal words "CAUTION, WARNING AND DANGER". As a general term to call attention to warning statements, the words SAFETY PRECAUTIONS is recommended. The word CAUTION is a signal word for minimum hazards such as avoiding ingestion or of combustibility, etc. The word WARNING

is a stronger word, which will apply to irritants or harmful vapors, flammables and similar hazards. The word DANGER is a still stronger term which will apply to toxic materials, petroleum distillates, and higher flammability characteristics.

11. All product use and performance claims and statements should be substantiated by factual records.
12. Flintkote has full liability for the contents of customer labels applied by Flintkote, even though the labels may be furnished by the customer. The requirements for Flintkote labels extend to private account labels. For more on liability for private labeled products see the enclosed letter of October 8, 1976 from S. Weiss to C. T. Derry. The Pioneer Division should be governed by the statements in this letter.

#### GF-8 CEMENT

One large group of labels are those used on Flintkote GF-8 Tile Cement and the various private labels for this same product. Included are the labels to be applied to the carton for one gallon cans. We suggest that all carton labels for GF-8 Cement, and other cutback products carry the following statement:

WARNING  
Contents Flammable  
Do not store near heat sources.  
Read precautions on containers  
before using.

Referring to the GF-8 label for five gallon containers, application instructions and safety instructions are intermingled. We would suggest that the safety precaution information be consolidated in one panel as follows:

G.F.P.

DANGER - FLAMMABLE MIXTURE  
DO NOT USE NEAR FIRE OR FLAME

FLASH POINT IS 25° F T.C.C

CONTAINS PETROLEUM DISTILLATE.  
HARMFUL OR FATAL if swallowed.  
Do not induce vomiting. CALL  
PHYSICIAN IMMEDIATELY. Avoid  
prolonged contact with skin and  
breathing of vapor.

USE WITH ADEQUATE VENTILATION  
DO NOT use in same room with  
open flame. Extinguish all  
pilot lights. Turn off stoves,  
heaters, electric motors and  
other sources of ignition - and  
do not smoke - during use and  
until all vapors are gone.

KEEP CAN CLOSED WHEN NOT IN USE.  
KEEP OUT OF REACH OF CHILDREN.

This particular label has the DOT red flammable liquid diamond. Is this red diamond required on five gallon pails? If so, why is it not included on the cutback cement labels for ROBERTS and WELDWOOD?

We note that some of the private label cutback labels have a small insert on the front panel reading in essence "Warning, Flammable Mixture, Do not use near fire or flame, F.D. C of A number, see precautions elsewhere on the label." This practice is highly recommended on all labels since the front panel attracts the first attention of the buyer or user.

Some private labels for the GF-8 cutback tile cement contain the information as listed in the above recommendation, but these statements need to be separated from the application instructions, and they require larger type for the signal words. This applies to labels for GAF and TCP. Some of the private labels are totally deficient, for example, American TILE-TITE, Webtex, and Kentile. The label for Roberts Adhesive 41-5014 contains all of the essential warning information in the proper style, therefore, needs no revision. The Weldwood label does not display the warning statements properly, therefore, this must be revised.

EMULSION TILE CEMENTS

The next group of labels is for FAST-SET and other emulsion tile cements. Labels for products in this category should have the following warning statement.

WARNING  
SAFETY PRECAUTIONS  
Harmful if swallowed  
KEEP OUT OF THE REACH OF CHILDREN

On the FAST-SET label, we object to the statement "non-toxic" under the description which is inconsistent with the warning that the product is harmful if swallowed. It is suggested that the words "non-toxic" be eliminated entirely.

We question another statement which appears on the FAST-SET label and on other Flintkote labels to the effect that Flintkote is the "world's largest manufacturer of flooring adhesives". Is it possible to support or substantiate this claim?

The same recommended warning statement should be added to the Roberts Brush-On adhesive label and the Weldwood Brush-On label. On both of these labels the warning statement should stand out very clearly with large type for the word WARNING.

Similar comments apply to the BONDCOTE label and the private labels for emulsion adhesive. There is no objection to the statement that the contents consist of asphalt dispersed in water.

LATEX UNDERLAYMENT

The labels for Latex Underlayment liquid should carry this same warning, repeated as follows:

WARNING  
SAFETY PRECAUTIONS  
Harmful if swallowed  
KEEP OUT OF THE REACH OF CHILDREN

This applies as well to the Roberts and the Weldwood labels in which the warning statement should be separated and preceded with the word warning in a larger type size than used elsewhere.

The labels supplied with your June 29 letter did not include those used on the Latex Underlayment powder packages. Latex Underlayment powder contains dry portland cement, therefore, the bag or container should carry the following caution statement:

CAUTION

Contains Portland Cement.  
Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water.

Portland cement dust may be an eye irritant. If any cementitious material gets into the eye, rinse immediately and repeatedly with water for 15 minutes. Get prompt medical attention.

Avoid ingesting or inhaling.

KEEP OUT OF THE REACH OF CHILDREN

ASPHALT CUTBACK PRODUCTS

The next large group of labels is for cutback asphalt products for roofing, damp proofing and water proofing, etc. Most of the labels for these cutback products can use the minimum warning statement included under general recommendation No. 5 above. This warning statement should be more prominent than on the label for Flintkote Plastic Cement 810-22. The labels for the cartons of one gallon cans should have the same warning as recommended for the GF-8 carton. The Celotex Elastigum roof coating label would be more effective if the warning on asbestos fiber content were placed adjacent to the remainder of the warning statement.

These same comments apply to the labels for the other cutback product both Flintkote and private label.

ALUMINUM ROOF COATINGS

Another large group of labels is for the series of aluminum roof coatings both fibered and non-fibered. All of these are cutback products, therefore, should carry as a minimum the statement appearing under general recommendation No. 5. Again, we note that the five gallon labels do not carry the DOT red flammable liquid diamond. Is it necessary that this be applied to all cutback products in five gallon containers? Is this red diamond required on 55 gallon drums? Is it required on cases and cartons?

The Fibrex label contains the statement that the product is an extremely flammable mixture. What property puts Fibrex in this higher category of flammability. If Fibrex Cement is more hazardous than the other cutback products due to a lower flash point or due to the nature of the solvent, some mention of this should be made in the warning statement to identify this increased hazard. In the case of the Fibrex label, we note that the five gallon label carries the DOT red flammable liquid diamond.

ASPHALT EMULSION PRODUCTS

The next major group of labels is for asphalt emulsion products. These should carry the minimum statement given under general recommendation No. 6 above. Again, this warning statement should be separated from all other instructions, and the word "warning" should be in a type size larger than any other type in the same panel.

The same recommendations pertain to Dura Shield Driveway Coating, Deco-Color "MP" and DecoTurf, all of which appear to be emulsions or latices. If these products contain other ingredients that may be toxic or hazardous, appropriate warnings should be added.

Is there a slipping hazard when these products are wet, either directly after application, or during use after drying? If so, some caution statement should call attention to this.

The Rextec-Spectra labels carry the statement that the product contains phenyl mercuric acetate. This chemical is listed in the Registry of Toxic Substances. We would suggest that you obtain some information from the supplier of this material relating to the expected toxicity in the actual concentration in the Rextec-Spectra products. You might ask the supplier to make any recommendations on the warning statements needed on a product with this concentration of phenyl mercuric acetate.

DECOSOND EPOXY

The DecoBond product is a two component epoxy compound. Epoxy materials are considered toxic and the label must identify the toxic materials by name, list the hazards, give precautionary instructions, advise on clean up of spillage and first aid measures. The extent of these warning statements will depend upon the particular ingredients used in your product, and we suggest that you contact your suppliers and obtain their recommendations. The Flooring Division supplies an epoxy flooring compound, the recommendations for which are attached hereto. These recommendations cover both the wording and the minimum type size. This warning, or a similar statement should be added to the DecoBond labels.

MONOFORM EMULSION

Flintote Monoform emulsion is presumably similar to other asphalt emulsions, therefore, would carry the minimum warning statement suggested in general recommendation No. 6. If Monoform contains any other ingredients, their hazards should be evaluated and included in the warning statement, if necessary.

The Monoform labels show only 55 gallon capacity. Presumably, it is not supplied in smaller containers. These drums as well as all other containers of five gallon capacity or greater should carry the emptied container warning label.

If Monoform emulsion is sold only to commercial applicators, and if the product or its containers does not generally enter the retail trade or be brought into a household, it might be advisable to include in the label some statement such as the following:

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Even with this statement, it is still recommended that the minimum warning given in general recommendation No. 6 be added to the label.

Returned herewith is one copy of each of the labels on which we have indicated some of these changes. We did not take the time to indicate the required changes on all of the labels since these are covered in a general way in this letter.

These remarks also apply to the lithographed cans. The TREWAL can printing contains the essential warning statement. The Plastic Cement and GF-8 can printing must be revised to make the warning statement more prominent.

The same procedures will apply to stencilled drums. In response to your question of timing on the revisions, we suggest a program of priorities, giving greatest emphasis to the Epoxy product, the flammable cutback products, and products that have a greater likelihood of being used in the home such as tile cements. High priority should be given to labels completely lacking in warning statements, or lacking essentials in part. Lowest priorities go to labels with most of the essentials but requiring more prominence. An immediate change over is not only costly, but will no doubt be physically overwhelming. If existing stocks are so extensive that the change will not occur in the foreseeable future, then the cost of disposed stock may be low in comparison to a potential claim. Naturally, all reorders will include necessary revisions.

Our review did not extend to other features of the label such as descriptive matter or application instructions. These should be checked for accuracy before printing. Many labels lack the proper limited warranty statement, which should conform to the wording on the Flintkote Plastic Cement 810-22 label.

If you have any questions concerning the above, or if we can assist you further in bringing the labels into conformance, please advise.

JCS/plb  
Enclosures

cc: Mr. W. Harvey  
Mr. J. Askins  
Mr. J. Hay  
Mr. J. Kent  
Mr. W. R. Ingram  
Mr. T. H. Parke  
Mr. S. Weiss



LABEL FOR 5 GALLON PAIL

COMPONENT A

Minimum  
Type Size

Contains Epoxy resin, diethylene triamine and toluol.

12 pt. CAPS

WARNING: The ingredients in parts A & B are toxic. In addition, the contents of part B are flammable, the vapor is harmful and if allowed to contact the skin may cause sensitization or other allergic reactions or serious dermatitis. The same hazards exist in the mixture until cured.

18 pt. CAPS

Keep away from heat, sparks and open flame.  
Use only with adequate ventilation.  
Avoid contact with eyes and skin.  
Avoid breathing of vapor  
Keep closures tight and upright to prevent leakage.  
Keep container closed when not in use.  
In case of spillage, absorb and flush with large volumes of water immediately.

10 pt. CAPS

FIRST AID: In case of skin contact wash thoroughly with soap and water; for eyes, flush immediately with plenty of water for 15 minutes and call a physician. If affected by inhalation of vapors, remove to fresh air. If swallowed, call a physician immediately. Do not induce vomiting. Remove and wash contaminated clothing immediately and wash thoroughly before reuse.

10 pt. CAPS

LABEL FOR PINT CAN

COMPONENT B

|                                                                                                                                                                                                                                                                                                                                                                                 | <u>Minimum<br/>Type Size</u> |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| Contains Diethylene triamine and toluol                                                                                                                                                                                                                                                                                                                                         | 12 pt. CAPS                  |
| DANGER: The contents are toxic, and flammable, the vapor is harmful and if allowed to contact the skin may cause skin sensitization or other allergic reactions or serious dermatitis.                                                                                                                                                                                          | 18 pt. CAPS                  |
| Keep away from heat, sparks and open flame.<br>Use only with adequate ventilation.<br>Avoid contact with eyes and skin.<br>Avoid breathing of vapor.<br>Keep closures tight and upright to prevent leakage.<br>Keep container closed when not in use.<br>In case of spillage exposure, absorb and flush with large volumes of water immediately.                                | 10 pt. CAPS                  |
| FIRST AID: In case of skin contact wash thoroughly with soap and water; for eyes, flush immediately with plenty of water for 15 minutes and call a physician. If affected by inhalation of vapors, remove to fresh air. If swallowed, call a physician immediately. Do not induce vomiting. Remove and wash contaminated clothing immediately and wash thoroughly before reuse. | 10 pt. CAPS                  |