

NEG. NO. L-14

TRADEMARK FILE INFORMATION

Trademark:	Asbestile
Trademark Owner:	H.W. Johns-Manville Company
Last Assignee:	Johns-Manville Corporation
Date of First Use in Commerce:	July, 1910
Registration No.:	118,882
Date Trademark Registered:	October 9, 1917
Size of Label in Trademark File:	10.5 x 6 inches



Receipt of Pictured Label by Patent Office:



**Asbestile[®]
Cement**

Contains Asphalt, Mineral Spirits, Selected
Asbestos Fibers, Special Mineral Stabilizers

CONTENTS: 55 GALLONS PREPARED READY FOR USE

JOHNS-MANVILLE SALES CORPORATION
NEW YORK, N. Y.

1-5237

LITHO. IN U.S.A.

JOHNS-MANVILLE ASBESTILE CEMENT

A high-strength, trowelable asphalt cement reinforced with asbestos fibers and special mineral stabilizers. Designed for use with roof flashings where maximum protection is needed against weather, water, roof stress. Formulated to adhere to vertical surfaces. Used in J-M Asbestile Flashing System for Bonded Built-Up Roofs.

DANGER! TOXIC—COMBUSTIBLE MIXTURE

CONTAINS PETROLEUM DISTILLATES

DO NOT TAKE INTERNALLY

USE WITH ADEQUATE VENTILATION

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME

KEEP CONTAINER CLOSED WHEN NOT IN USE

KEEP OUT OF REACH OF CHILDREN

HANDLING INSTRUCTIONS:

■ NOTHING SHOULD BE ADDED TO THIS PRODUCT WITHOUT CONSULTING THE MANUFACTURER ■ STIR BEFORE USING ■ AS THE TEMPERATURE FALLS, THIS MATERIAL TENDS TO THICKEN. RESTORE PROPER CONSISTENCY BY PLACING IN A WARM ROOM ■ REPLACE COVER TIGHTLY

CAUTION—COMBUSTIBLE MIXTURE

N.Y.F.D. C. OF A. NO. 2224

DIRECTIONS FOR APPLYING

Brush surfaces free of dirt and loose material. Apply in thick, uniform coating. Embed flashing felts, working out entrapped air to avoid blistering. For large areas, a plasterer's trowel may be used. A pointed trowel works best in angles or for patching cracks. Bring Asbestile Cement to a feathered edge.